

Lab Exercise 7- Create Service in Kubernetes

Name: Ankur Sharma

Sap id: 500110541

BATCH: B-2 (DevOps)

Objective:

- Understand the syntax and structure of a Kubernetes Service definition file (YAML).
- Learn to create different types of Services: ClusterIP, NodePort, and LoadBalancer.
- Comprehend how Services operate independently of specific Pods.

Prerequisites

- Kubernetes Cluster: Have a running Kubernetes cluster (locally using Minikube or kind, or a cloud-based service).
- kubectl: Install and configure kubectl to interact with your Kubernetes cluster.
- Basic Knowledge of YAML: Familiarity with YAML format will be helpful for understanding Kubernetes resource definitions.

Step-by-Step Guide

NodePort Service

To expose the Service on a port on each Node in the cluster, modify the Service type to NodePort.

Create a YAML file named nodeport-service.yaml with the following content:

```
apiVersion: v1
```

```
kind: Service
metadata:
  name: nodeport-service
spec:
  selector:
    app: my-app
  ports:
    - protocol: TCP
      port: 80
      targetPort: 80
      nodePort: 30007 # A specific port in the range 30000-32767
  type: NodePort
```

Explanation:

- The primary difference from the ClusterIP Service is the addition of nodePort, which specifies the static port on each Node.
- type: Set to NodePort, exposing the Service on a specific port across all Nodes.

Apply this YAML to create the NodePort Service:

```
kubectl apply -f nodeport-service.yaml
```

```
PS C:\Users\Dell\OneDrive\Documents\kubernetes> kubectl apply -f service.yaml
service/nodeport-service created
PS C:\Users\Dell\OneDrive\Documents\kubernetes> |
```

Verify the Service:

```
kubectl get services
```

```
PS C:\Users\Dell\OneDrive\Documents\kubernetes> kubectl get services
NAME                TYPE        CLUSTER-IP    EXTERNAL-IP  PORT(S)          AGE
kubernetes           ClusterIP   10.96.0.1     <none>       443/TCP          71m
nodeport-service     NodePort    10.103.91.189 <none>       80:30007/TCP     29s
PS C:\Users\Dell\OneDrive\Documents\kubernetes> |
```

You should see the nodeport-service listed with a NodePort and details about the port exposed.