

## Lab Exercise 03

### Executing Ad Hoc Commands

**Objective:** To demonstrate ad hoc commands for quickly executing tasks on remote servers without writing full playbooks

**Tools required:** Ansible, Ubuntu OS

**Prerequisites:** None

Steps to be followed:

1. Generate SSH key pair on the main node
2. Copy the SSH key on the other two nodes
3. Update the host file with the host IP address
4. Establish connectivity between specified hosts and the Ansible server
5. Gather System Information Using Ad-Hoc Commands

#### Step 1: Establish connectivity between specified hosts and the Ansible server

- 4.1 Run the following command to verify connectivity to all servers listed under the **webserver** group in your Ansible hosts file:

**ansible -m ping dbserver**

```
[devops@ip-172-31-8-163 ~]$ ansible -m ping dbserver
[WARNING]: Platform linux on host 172.31.15.102 is using the discovered Python
interpreter at /usr/bin/python, but future installation of another Python
interpreter could change this. See https://docs.ansible.com/ansible/2.9/reference_appendices/interpreter_discovery.html for more information.
172.31.15.102 | SUCCESS => {
  "ansible_facts": {
    "discovered_interpreter_python": "/usr/bin/python"
  },
  "changed": false,
  "ping": "pong"
}
[WARNING]: Platform linux on host 172.31.5.145 is using the discovered Python
interpreter at /usr/bin/python, but future installation of another Python
interpreter could change this. See https://docs.ansible.com/ansible/2.9/reference_appendices/interpreter_discovery.html for more information.
172.31.5.145 | SUCCESS => {
  "ansible_facts": {
    "discovered_interpreter_python": "/usr/bin/python"
  },
  "changed": false,
  "ping": "pong"
}
[devops@ip-172-31-8-163 ~]$ _
```

4.2 Use the following command to check the number of hosts in the host file:

**ansible all --list-hosts**

```
[devops@ip-172-31-8-163 ~]$ ansible all --list-hosts
hosts (2):
    172.31.15.102
    172.31.5.145
[devops@ip-172-31-8-163 ~]$ _
```

## Step 2: Gather System Information Using Ad Hoc Commands

5.1 Run the following command to obtain the uptime from all managed hosts using an ad hoc command:

**ansible all -m shell -a uptime**

```
[devops@ip-172-31-8-163 ~]$ ansible all -m shell -a uptime
[WARNING]: Platform linux on host 172.31.5.145 is using the discovered Python interpreter at /usr/bin/python, but future
installation of another Python interpreter could change this. See
https://docs.ansible.com/ansible/2.9/reference_appendices/interpreter_discovery.html for more information.
172.31.5.145 | CHANGED | rc=0 >>
    05:53:04 up 1:35,  2 users,  load average: 0.00, 0.00, 0.00
[WARNING]: Platform linux on host 172.31.15.102 is using the discovered Python interpreter at /usr/bin/python, but future
installation of another Python interpreter could change this. See
https://docs.ansible.com/ansible/2.9/reference_appendices/interpreter_discovery.html for more information.
172.31.15.102 | CHANGED | rc=0 >>
    05:53:04 up 1:35,  3 users,  load average: 0.00, 0.00, 0.00
[devops@ip-172-31-8-163 ~]$
```

5.2 Similarly, execute the below command to obtain detailed information about memory usage on all hosts:

**ansible all -m shell -a "free -m"**

```
[devops@ip-172-31-8-163 ~]$ ansible all -m shell -a "free -m"
[WARNING]: Platform linux on host 172.31.15.102 is using the discovered Python interpreter at /usr/bin/python, but future
installation of another Python interpreter could change this. See
https://docs.ansible.com/ansible/2.9/reference_appendices/interpreter_discovery.html for more information.
172.31.15.102 | CHANGED | rc=0 >>
      total        used        free      shared  buff/cache   available
Mem:    952         99        222           0         630         711
Swap:    0           0           0
[WARNING]: Platform linux on host 172.31.5.145 is using the discovered Python interpreter at /usr/bin/python, but future
installation of another Python interpreter could change this. See
https://docs.ansible.com/ansible/2.9/reference_appendices/interpreter_discovery.html for more information.
172.31.5.145 | CHANGED | rc=0 >>
      total        used        free      shared  buff/cache   available
Mem:    952         97        220           0         635         713
Swap:    0           0           0
[devops@ip-172-31-8-163 ~]$
```

You will see that Ansible logs in to each machine in turn and runs the uptime command, returning the current uptime output.

By following these steps, you have successfully demonstrated how to use ad hoc commands for quickly executing tasks on remote servers without the need for full playbooks.

