

Lab Exercise 3–Provisioning an EC2 Instance on AWS

Prerequisites: Terraform Installed: Make sure you have Terraform installed on your machine. Follow the official installation guide if needed.

AWS Credentials: Ensure you have AWS credentials (Access Key ID and Secret Access Key) configured. You can set them up using the AWS CLI or by setting environment variables.

Exercise Steps:

Step 1: Create a New Directory:

Create a new directory for your Terraform configuration:

```
mkdir aws-terraform-demo
cd aws-terraform-demo
```

Step 2: Create Terraform Configuration File (main.tf):

Create a file named main.tf with the following content:

```
terraform {
  required_providers {
    aws = {
      source = "hashicorp/aws"
      version = "5.31.0"
    }
  }
}
```

```
provider "aws" {
```

```
region    = "ap-south-1"

access_key = "your IAM access key"

secret_key = "your secret access key"

}
```

```
lab-2 > main.tf > ...
1  terraform {
2    required_providers {
3      aws = {
4        source = "hashicorp/aws"
5        version = "5.82.2"
6      }
7    }
8  }
9
10 provider "aws" {
11   region = "ap-south-1"
12   access_key = "AKIAW77ZKJH0SDP2PJKB"
13   secret_key = "h0pUQaEvhoZI2sU8yrRCcM7Nwp30NLdGrVfxoZ/W"
14 }
```

This script defines an AWS provider and provisions an EC2 instance.

Step 3: Initialize Terraform:

Run the following command to initialize your Terraform working directory:

terraform init

```
dhruvchaubey@Dhruvs-MacBook-Pro lab-2 % terraform init
Initializing the backend...
Initializing provider plugins...
- Finding hashicorp/aws versions matching "5.82.2"...
- Installing hashicorp/aws v5.82.2...
- Installed hashicorp/aws v5.82.2 (signed by HashiCorp)
Terraform has created a lock file .terraform.lock.hcl to record the provider
selections it made above. Include this file in your version control repository
so that Terraform can guarantee to make the same selections by default when
you run "terraform init" in the future.

Terraform has been successfully initialized!



You may now begin working with Terraform. Try running "terraform plan" to see
any changes that are required for your infrastructure. All Terraform commands
should now work.

If you ever set or change modules or backend configuration for Terraform,
rerun this command to reinitialize your working directory. If you forget, other
commands will detect it and remind you to do so if necessary.
```

Step 4: Create Terraform Configuration File for EC2 instance (instance.tf):

Create a file named instnace.tf with the following content:

```
resource "aws_instance" "My-instance" {  
  
    instance_type = "t2.micro"  
  
    ami = "ami-03f4878755434977f"  
  
    count = 1  
  
    tags = {  
  
        Name = "UPES-EC2-Instnace"  
  
    }  
}
```

```
lab-2 >  instance.tf >  resource "aws_instance" "My-instance"  
1  resource "aws_instance" "My-instance" {  
2  instance_type = "t2.micro"  
3  ami = "ami-053b12d3152c0cc71"  
4  count = 1  
5  tags = {  
6  Name = "dhruv-instance"}  
7  }  
8
```

Step 5: Review Plan:

Run the following command to see what Terraform will do:

terraform plan (as well as terraform validate)

```

dhruvchaubey@Dhruvs-MacBook-Pro lab-2 % terraform validate
Success! The configuration is valid.

dhruvchaubey@Dhruvs-MacBook-Pro lab-2 % terraform plan

Terraform used the selected providers to generate the following execution plan. Resource actions are indicated with the following symbols:
+ create

Terraform will perform the following actions:

# aws_instance.My-instance[0] will be created
+ resource "aws_instance" "My-instance" {
  + ami                        = "ami-053b12d3152c0cc71"
  + arn                      = (known after apply)
  + associate_public_ip_address = (known after apply)
  + availability_zone         = (known after apply)
  + cpu_core_count           = (known after apply)
  + cpu_threads_per_core     = (known after apply)
  + disable_api_stop         = (known after apply)
  + disable_api_termination   = (known after apply)
  + ebs_optimized             = (known after apply)
  + enable_primary_ipv6       = (known after apply)
  + get_password_data         = false
  + host_id                  = (known after apply)
  + host_resource_group_arn   = (known after apply)
  + iam_instance_profile      = (known after apply)
  + id                       = (known after apply)
  + instance_initiated_shutdown_behavior = (known after apply)
  + instance_lifecycle        = (known after apply)
  + instance_state            = (known after apply)
  + instance_type             = "t2.micro"
  + ipv6_address_count        = (known after apply)
  + ipv6_addresses           = (known after apply)
  + key_name                  = (known after apply)
  + monitoring                = (known after apply)
  + outpost_arn               = (known after apply)
  + password_data             = (known after apply)
  + placement_group           = (known after apply)
  + placement_partition_number = (known after apply)
  + primary_network_interface_id = (known after apply)
  + private_dns               = (known after apply)
  + private_ip                = (known after apply)
  + public_dns                = (known after apply)
  + public_ip                 = (known after apply)
  + secondary_private_ips     = (known after apply)
  + security_groups           = (known after apply)
  + source_dest_check         = true
  + spot_instance_request_id   = (known after apply)
  + subnet_id                 = (known after apply)
  + tags                      = {
    + "Name" = "dhruv-instance"
  }
  + tags_all                  = {
    + "Name" = "dhruv-instance"
  }
  + tenancy                   = (known after apply)
  + user_data                 = (known after apply)
  + user_data_base64          = (known after apply)
  + user_data_replace_on_change = false
  + vpc_security_group_ids    = (known after apply)

  + capacity_reservation_specification (known after apply)

  + cpu_options (known after apply)

  + ebs_block_device (known after apply)

  + enclave_options (known after apply)

  + ephemeral_block_device (known after apply)

  + instance_market_options (known after apply)

  + maintenance_options (known after apply)

  + metadata_options (known after apply)

  + network_interface (known after apply)

  + private_dns_name_options (known after apply)

  + root_block_device (known after apply)
}

Plan: 1 to add, 0 to change, 0 to destroy.

Note: You didn't use the -out option to save this plan, so Terraform can't guarantee to take exactly these actions if you run "terraform apply" now.
dhruvchaubey@Dhruvs-MacBook-Pro lab-2 %

```

Review the plan to ensure it aligns with your expectations.

Step 6: Apply Changes:

Apply the changes to create the AWS resources:

```
terraform apply

Do you want to perform these actions?
Terraform will perform the actions described above.
Only 'yes' will be accepted to approve.

Enter a value: yes

aws_instance.My-instance[0]: Creating...
aws_instance.My-instance[0]: Still creating... [10s elapsed]
aws_instance.My-instance[0]: Creation complete after 13s [id=i-01a8a43c05f7182e1]

Apply complete! Resources: 1 added, 0 changed, 0 destroyed.
dhruvchaubey@Dhruvs-MacBook-Pro lab-2 %
```

Type yes when prompted.

Step 7: Verify Resources:

After the terraform apply command completes, log in to your AWS Management Console and navigate to the EC2 dashboard. Verify that the EC2 instance has been created.

<input type="checkbox"/>	Name	Instance ID	Instance state	Instance type	Status check	Alarm status	Availability Zone
<input type="checkbox"/>	dhruv-instance	i-01a8a43c05f7182e1	Running	t2.micro	Initializing	View alarms +	ap-south-1b

Step 8: Cleanup Resources:

When you are done experimenting, run the following command to destroy the created resources:

```
terraform destroy
```

```
Do you really want to destroy all resources?
Terraform will destroy all your managed infrastructure, as shown above.
There is no undo. Only 'yes' will be accepted to confirm.

Enter a value: yes

aws_instance.My-instance[0]: Destroying... [id=i-01a8a43c05f7182e1]
aws_instance.My-instance[0]: Still destroying... [id=i-01a8a43c05f7182e1, 10s elapsed]
aws_instance.My-instance[0]: Still destroying... [id=i-01a8a43c05f7182e1, 20s elapsed]
aws_instance.My-instance[0]: Still destroying... [id=i-01a8a43c05f7182e1, 30s elapsed]
aws_instance.My-instance[0]: Still destroying... [id=i-01a8a43c05f7182e1, 40s elapsed]
aws_instance.My-instance[0]: Still destroying... [id=i-01a8a43c05f7182e1, 50s elapsed]
aws_instance.My-instance[0]: Still destroying... [id=i-01a8a43c05f7182e1, 1m0s elapsed]
aws_instance.My-instance[0]: Destruction complete after 1m1s

Destroy complete! Resources: 1 destroyed.
dhruvchaubey@Dhruvs-MacBook-Pro lab-2 %
```

Type yes when prompted.

Notes:

Customize the instance.tf file to provision different AWS resources.

Explore the Terraform AWS provider documentation for additional AWS resources and configuration options.

Always be cautious when running terraform destroy to avoid accidental resource deletion.

This exercise provides a basic introduction to using Terraform with the AWS provider. Feel free to explore more complex Terraform configurations and resources based on your needs.