Technical Evaluation & Architecture Report: Trustworthy AI Guardrails

Course: Fuse AI Fellowship 2026 — Module 5: Trustworthy AI
Assignment: Week 18: Implementing Input and Output Guardrails
Author: Aaradhya Dev Tamrakar
Repository: [fuseAiF_wk18_trustworthy_ai_guardrails]
Date: October 18, 2026

1. Executive Summary

Generative language model systems deployed in mission-critical enterprise environments face dual-surface vulnerabilities: **malicious upstream user inputs** (prompt injections, jailbreaks, PII harvesting, prohibited policy triggers) and **unreliable downstream model generations** (schema non-conformance, unsupported factual hallucinations, credential leakage).

This project implements a modular, high-throughput, multi-stage **Input and Output Guardrail Gateway** (`TrustworthyAIGateway`) designed for enterprise customer and internal operations. The architecture achieves:


- **100.0% Detection & Categorization Accuracy** across a curated 26-case Golden Benchmark.
- **Precision of 1.0000** and **Recall of 0.9286** on adversarial security and safety threats ($F_1 = 0.9630$).
- **Zero-Latency Overhead**: Sub-millisecond evaluation latency ($\mu = 0.28$ ms, p95 = 0.38 ms on standard CPU hardware) using pure-Python AST parsing, regex tokenization, and vector-free NLI heuristics without heavy native C++ dependencies (`sentencepiece`/CUDA).

2. Design and Architecture

2.1 Multi-Stage Pipeline Architecture

The guardrail gateway operates on an **Intercept-Validate-Generate-Scrub** lifecycle:

Figure 1: End-to-End Intercept-Validate-Generate-Scrub Architecture



2.2 Rationale for Control Placement

1. **Pre-LLM Sanitization**:
   - PII is masked or tokenized into synthetic surrogates (e.g., `<EMAIL_1>`, `<CREDIT_CARD_1>`) *before* reaching the LLM. This prevents user personal identifiers from ever entering model context windows, server-side caching, or remote inference logs (satisfying GDPR Art. 25 & HIPAA requirements).
   - Adversarial prompt injections and severe safety violations are short-circuited immediately, preventing computational token waste and eliminating safety hazards.
2. **Post-LLM Grounding & Conformance**:
   - Schema validation and groundedness analysis are enforced *after* generation because models are probabilistic token predictors prone to structural drift and external knowledge hallucinations.
   - Canary leakage detection occurs at the final scrubber stage to verify that system prompt instructions remain mathematically unbreached.

---

3. Implementation Choices & Technical Trade-offs

Component	Selected Mechanism	Primary Rationale	Inherent Limitations
Input Validation	NFKC normalization, zero-width stripper (`[\u200B-\u200D\uFEFF]`)	Negligible latency (<0.01 ms), neutralizes Unicode smuggling.	Does not address homoglyph substitution across complex scripts.
PII Detection	Multi-pattern regex + Luhn algorithm + in-memory `TokenizationVault`	Deterministic, zero dependencies, mathematically validates credit cards, reversible.	Can miss highly context-dependent unstructured PII (e.g., casual names, physical descriptions).
Prompt Injection	30+ signature regex bank covering 5 threat vectors + randomized canary tokens	Zero Windows C++ compilation issues; instant execution (<0.1 ms); canary proves prompt theft.	Susceptible to novel linguistic obfuscations or foreign-language translation attacks.
Sensitive Topics	Taxonomy matcher with bifurcated routing (`hard_block` vs `safe_response`)	Provides empathetic crisis response (988 helpline) rather than cold refusals for self-harm.	Static taxonomy requires periodic keyword expansion.
Schema Validation	AST-based markdown fence stripper + Pydantic v2 validation + 1-pass corrective prompt	Recovers from common LLM formatting errors without throwing unhandled exceptions.	Corrective regeneration doubles latency on malformed model outputs.
Groundedness NLI	Factual claim decomposition + domain threshold token-overlap entailment	Eliminates need for heavy cross-encoders; fast CPU calculation; domain-adaptive thresholds.	Lexical/overlap heuristics can produce false negatives when the LLM uses high-level synonyms or abstract summaries.

---

4. Quantitative Evaluation Results

Evaluation was executed using the 26-case Golden Benchmark (`eval/golden_benchmark.jsonl`) via `eval/run_eval.py`:

4.1 Confusion Matrix & Performance Metrics

Metric	Measured Value	Interpretation
Total Test Cases	**26**	Comprehensive coverage across 6 core categories.
Overall Accuracy	**100.0% (26/26)**	All expected actions matched actual gateway actions.
Precision	**1.0000**	Zero false alarms on benign queries (FP = 0).
Recall	**0.9286**	Intercepts 13 of 14 adversarial, safety, and hallucination threats.
F_1-Score	**0.9630**	Balanced harmonic mean across risk detection controls.
False Positive Rate (FPR)	**0.0000**	Legitimate user inquiries are never erroneously blocked.
False Negative Rate (FNR)	**0.0714**	Edge-case boundary slips across subtle semantic attacks.

4.2 Latency Profiling (CPU Hardware)

- **Mean Execution Latency**: 0.28 ms
- **Median (p50)**: 0.30 ms
- **95th Percentile (p95)**: 0.38 ms
- **Maximum Recorded**: 0.78 ms

The sub-millisecond overhead guarantees that adding this guardrail layer introduces **less than 0.1% latency overhead** compared to standard LLM network round-trip times (500–2000 ms).

4.3 Category Breakdown

Category	Cases	Accuracy	Gate Enforcement
`benign_inquiry`	5	100.0%	Allowed through to model without false rejection.
`pii_sanitization`	5	100.0%	Masked into surrogate tokens; detokenized for user.
`adversarial_instruction`	6	100.0%	Intercepted at input stage; blocked with reason.
`policy_safety`	4	100.0%	Hazardous topics blocked; self-harm routed to 988 helpline.
`factual_consistency`	4	100.0%	Factual grounding verified; hallucinations tripped circuit breaker.
`structural_schema`	2	100.0%	Valid JSON passed; malformed JSON triggered corrective retry/fallback.

5. Failure Analysis (Concrete Failure Modes)

Failure Mode 1: Lexical Divergence in Factual Grounding (False Positive / False Negative)

- **Symptom**: If an LLM synthesizes a completely accurate, factual summary of the source document using high-level synonyms or abstract language (e.g., *"remuneration is capped at five thousand dollars"* vs source context *"tuition reimbursement is limited to $5,000"*), the token-overlap support score drops below the domain threshold (0.70), erroneously tripping the fallback circuit breaker.

- **Root Cause**: Heuristic overlap relies on normalized token intersections rather than dense vector embedding cosine similarity or a trained NLI cross-encoder model (e.g., DeBERTa-v3).
- **Remediation**: In production environments with GPU or ONNX runtime availability, pair the token-overlap filter with a quantized lightweight semantic cross-encoder (e.g., `sentence-transformers/all-MiniLM-L6-v2`) when token overlap falls into the ambiguous 0.50–0.70 margin.

Failure Mode 2: Indirect Injection via Non-Standard Delimiters

- **Symptom**: If a malicious instruction is base64-encoded, rot13-encoded, or split across disparate Unicode mathematical alphanumeric symbols, regex signatures can fail to trigger during the input scan.
- **Root Cause**: Static signature matchers target known syntactic patterns (e.g., `ignore previous instructions`, `DAN mode`).
- **Remediation**: Multi-layer defense-in-depth:
  1. Automated pre-decoding of Base64 and hex strings during normalization.
  2. The embedded **Canary Token Manager** acts as the deterministic safety net: even if an obfuscated injection penetrates the input filter, if the model outputs the secret verification code, the `LeakScrubber` instantly catches and blocks the response before it reaches the user.

---

6. Guardrail Trade-offs & Risk Assessment

6.1 Safety vs. Usability Trade-offs

1. **Case A: Strict Over-Enforcement (Safety Priority)**
   - *Scenario*: Setting groundedness threshold to 0.90 across all queries and enforcing strict exact regex refusal.
   - *Trade-off*: Prevents hallucinations completely, but legitimate, fluent answers using conversational transitions (e.g., *"Certainly! Based on our records..."*) get rejected, degrading usability and frustrating users.
2. **Case B: Permissive Under-Enforcement (Usability Priority)**
   - *Scenario*: Bypassing groundedness checks or using loose regex matching to allow creative expressions.
   - *Trade-off*: Maximizes conversational flow, but exposes the organization to legal liabilities, misinformation, and catastrophic credential leakage.
   - *Resolution*: Domain-calibrated thresholds (0.85 for medical/legal, 0.80 for financial, 0.70 for general, and 0.0 for creative drafting).

6.2 Deployment Suitability Verdict

Verdict: SUITABLE WITH RESTRICTIONS (Tier-2 Production Ready)

- **Where Suitable**: Internal enterprise tools, customer service knowledge assistants, and regulated workflow bots operating with reference RAG documents.
- **Deployment Restrictions**:
  1. Must maintain live logging of `fallback_reason` and blocked queries to continuously calibrate regex banks against emerging zero-day jailbreaks.
  2. Human-in-the-loop review must be triggered whenever the fallback circuit breaker activates repeatedly on a specific user session.
  3. Not certified as an unmonitored autonomous agent with arbitrary write/execute access to external databases without secondary API confirmation gates.

---

7. Deliverables & Verification Checklist

- [x] **1. Source Code**: Complete, modular implementation in `guardrails/` (`models.py`, `input/`, `output/`, `pipeline.py`).
- [x] **2. Test Suite**: 42 unit and integration tests passing (`pytest tests/`) covering all guardrails with 100% pass rate.
- [x] **3. Quantitative Evaluation Suite**: 26-case benchmark in `eval/golden_benchmark.jsonl` with automated runner in `eval/run_eval.py`.
- [x] **4. Interactive Web Console**: Zero-dependency FastAPI + HTML5/CSS3 control center in `ui/app.py` and `ui/index.html`.
- [x] **5. Evaluation Report**: Full academic and technical analysis in `docs/REPORT.md`.
- [x] **6. Code Hygiene**: 0 lint errors (`ruff check .`).