Action	Sender	Recipient	Moderator	Admin
Identity & System Administration				
Register users / assign or revoke roles	**Deny**	**Deny**	**Deny**	**Allow**
Publish own public encryption key	**Own Only**	**Own Only**	**Own Only**	**Deny**
Replace/revoke another user's public key	**Deny**	**Deny**	**Deny**	**Special Allow**
Open/close rounds; rotate keys & system policy	**Deny**	**Deny**	**Deny**	**Special Allow**
Configure alert thresholds	**Deny**	**Deny**	**Deny**	**Allow**
Sending				
Browse recipient public-key directory	**Allow**	**Deny**	**Deny**	**Allow**
Obtain credential (once) / use round token	**Own Only**	**Deny**	**Deny**	**Deny**
Submit message (valid, unspent, unfrozen token)	**Allow**	**Deny**	**Deny**	**Deny**
Receiving				
List own inbox (ciphertext)	**Deny**	**Own Only**	**Deny**	**Deny**
Decrypt message (client-side only)	**Deny**	**Own Only**	**Deny**	**Deny**
Flag a message	**Deny**	**Own Only**	**Deny**	**Deny**
Moderation				
View flagged-message queue (content shared by recipient)	**Deny**	**Deny**	**Allow**	**Deny**
Dismiss / uphold a flag	**Deny**	**Deny**	**Allow**	**Deny**
Freeze / unfreeze a pseudonym credential	**Deny**	**Deny**	**Allow**	**Deny**
Receive alerts	**Deny**	**Deny**	**Allow**	**Read Only**
Audit				
Read audit log (role-level events)	**Deny**	**Deny**	**Allow**	**Read Only**
Verify log integrity (hash chain + signature)	**Deny**	**Deny**	**Allow**	**Allow**
Modify or delete log entries	**Deny**	**Deny**	**Deny**	**Deny**
Banned Actions				
View unflagged content of others' messages	**Deny**	**Deny**	**Deny**	**Deny**
Link a credential/token to a real identity	**Deny**	**Deny**	**Deny**	**Deny**
Key:				

Allow = permitted action
Deny = Do not permit the action
Own Only = permitted only on the user's own account, key, or mailbox.
Read Only = viewing permissions without the ability to change
Special Allow = actions permitted when an admin or moderator approves/signs the action on top of the first admin/moderator