

Polynomial Regression

Shusen Wang

Warm-up: Linear Regression


Linear Regression (Task)

Input: vectors $\mathbf{x}_1, \dots, \mathbf{x}_n \in \mathbb{R}^d$ and labels $y_1, \dots, y_n \in \mathbb{R}$

Output: a vector $\mathbf{w} \in \mathbb{R}^d$ and scalar $b \in \mathbb{R}$ such that $\mathbf{x}_i^T \mathbf{w} + b \approx y_i$.

Tasks

assume y_i is a linear function of \mathbf{x}_i .



Linear
Regression

Least Squares Regression (Method)

Input: vectors $\mathbf{x}_1, \dots, \mathbf{x}_n \in \mathbb{R}^d$ and labels $y_1, \dots, y_n \in \mathbb{R}$

1. Add one dimension to $\mathbf{x} \in \mathbb{R}^d$: $\bar{\mathbf{x}}_j = [\mathbf{x}_j; 1] \in \mathbb{R}^{d+1}$.
2. Solve least squares regression: $\min_{\mathbf{w} \in \mathbb{R}^{d+1}} \|\bar{\mathbf{X}} \mathbf{w} - \mathbf{y}\|_2^2$.

Tasks

Methods

Linear
Regression

Least Squares Regression

Least Squares Regression (Method)

Input: vectors $\mathbf{x}_1, \dots, \mathbf{x}_n \in \mathbb{R}^d$ and labels $y_1, \dots, y_n \in \mathbb{R}$

1. Add one dimension to $\mathbf{x} \in \mathbb{R}^d$: $\bar{\mathbf{x}}_j = [\mathbf{x}_j; 1] \in \mathbb{R}^{d+1}$.
2. Solve least squares regression: $\min_{\mathbf{w} \in \mathbb{R}^{d+1}} \|\bar{\mathbf{X}} \mathbf{w} - \mathbf{y}\|_2^2$.

Tasks

Linear
Regression

Methods

Least Squares Regression

Algorithms

Analytical Solution

Gradient Descent

Conjugate Gradient

Polynomial Regression

The Regression Task

Input: vectors $\mathbf{x}_1, \dots, \mathbf{x}_n \in \mathbb{R}^d$ and labels $y_1, \dots, y_n \in \mathbb{R}$.

Output: a function $f: \mathbb{R}^d \mapsto \mathbb{R}$ such that $f(\mathbf{x}) \approx y$.

Question: f is unknown! So how to learn f ?

The Regression Task

Input: vectors $\mathbf{x}_1, \dots, \mathbf{x}_n \in \mathbb{R}^d$ and labels $y_1, \dots, y_n \in \mathbb{R}$.

Output: a function $f: \mathbb{R}^d \mapsto \mathbb{R}$ such that $f(\mathbf{x}) \approx y$.

Question: f is unknown! So how to learn f ?

Answer: polynomial approximation; f is a polynomial function.

Taylor expansion:
$$f(x) = f(a) + f'(a)(a - x) + \frac{f''(a)}{2!} (a - x)^2 + \dots$$

Polynomial Regression: 1D Example

Input: scalars $x_1, \dots, x_n \in \mathbb{R}$ and labels $y_1, \dots, y_n \in \mathbb{R}$.

Output: a function $f: \mathbb{R} \mapsto \mathbb{R}$ such that $f(x) \approx y$.

One-dimensional example: $f(x) = w_0 + w_1x + w_2x^2 + \dots + w_px^p$.

Polynomial regression:

1. Define a feature map $\boldsymbol{\phi}(x) = [1, x, x^2, x^3, \dots, x^p]$.
2. For $j = 1$ to n , do the mapping $x_j \mapsto \boldsymbol{\phi}(x_j)$.
 - Let $\boldsymbol{\Phi} = [\boldsymbol{\phi}(x_1); \dots, \boldsymbol{\phi}(x_n)]^T \in \mathbb{R}^{n \times (p+1)}$
3. Solve the least squares regression $\min_{\mathbf{w} \in \mathbb{R}^{p+1}} \|\boldsymbol{\Phi} \mathbf{w} - \mathbf{y}\|_2^2$.

Polynomial Regression: 2D Example

Input: vectors $\mathbf{x}_1, \dots, \mathbf{x}_n \in \mathbb{R}^2$ and labels $y_1, \dots, y_n \in \mathbb{R}$.

Output: a function $f: \mathbb{R}^2 \mapsto \mathbb{R}$ such that $f(\mathbf{x}_i) \approx y_i$.

Two-dimensional example: how to do feature mapping?

Polynomial features:

$$\Phi(\mathbf{x}) = [1, \underbrace{x_1, x_2}_{\text{degree-1}}, \underbrace{x_1^2, x_2^2, x_1x_2}_{\text{degree-2}}, \underbrace{x_1^3, x_2^3, x_1x_2^2, x_1^2x_2}_{\text{degree-3}}].$$

degree-0 degree-1 degree-2 degree-3

Polynomial Regression

```
import numpy
X = numpy.arange(6).reshape(3, 2)
print('X = ')
print(X)
```

```
X =
[[0 1]
 [2 3]
 [4 5]]
```

```
from sklearn.preprocessing import PolynomialFeatures
poly = PolynomialFeatures(degree=3)
Phi = poly.fit_transform(X)
print('Phi = ')
print(Phi)
```

```
Phi =
[[ 1.  0.  1.  0.  0.  1.  0.  0.  0.  1.]
 [ 1.  2.  3.  4.  6.  9.  8. 12. 18. 27.]
 [ 1.  4.  5. 16. 20. 25. 64. 80. 100. 125.]]
```

degree-0 degree-1 degree-2 degree-3


Polynomial Regression

- \mathbf{x} : d -dimensional
- $\Phi(\mathbf{x})$: degree- p polynomial
- The dimension of $\Phi(\mathbf{x})$ is $O(d^p)$

Polynomial Regression

Input: vectors $\mathbf{x}_1, \dots, \mathbf{x}_n \in \mathbb{R}^d$ and labels $y_1, \dots, y_n \in \mathbb{R}$.

Output: a function $f: \mathbb{R}^d \mapsto \mathbb{R}$ such that $f(\mathbf{x}_i) \approx y_i$.



Training, Test, and Overfitting

Polynomial Regression: Training

Input: vectors $\mathbf{x}_1, \dots, \mathbf{x}_n \in \mathbb{R}^d$ and labels $y_1, \dots, y_n \in \mathbb{R}$.


Feature map: $\phi(\mathbf{x}) = \bigotimes^p \bar{\mathbf{x}}$. Its dimension is $O(d^p)$.

Least squares: $\min_{\mathbf{w}} \|\Phi \mathbf{w} - \mathbf{y}\|_2^2$.



Question: what will happen as p grows?

1. For sufficiently large p , the dimension of the feature $\phi(\mathbf{x})$ exceeds n .
2. Then you can find \mathbf{w} such that $\Phi \mathbf{w} = \mathbf{y}$. (Zero training error!)

Training and Testing



Underfitting



Overfitting

Training and Testing

Train:

Input: vectors $\mathbf{x}_1, \dots, \mathbf{x}_n \in \mathbb{R}^d$ and labels $y_1, \dots, y_n \in \mathbb{R}$.


Output: a function $f: \mathbb{R}^d \mapsto \mathbb{R}$ such that $f(\mathbf{x}_i) \approx y_i$.

Test:


Input: a *never-seen-before* feature vectors $\mathbf{x}' \in \mathbb{R}^d$.

Input: predict its label by $f(\mathbf{x}')$.


Training and Testing



BAD




GOOD



BAD


Training and Testing



Hyper-Parameter Tuning

Question: for the polynomial regression model, how to determine the degree p ?

Answer: the degree p leads to the smallest test error.



Hyper-Parameter Tuning

Training Set

Test Set

Train a degree-1 polynomial regression



Test MSE = 23.2

Train a degree-2 polynomial regression



Test MSE = 19.0

Train a degree-3 polynomial regression



Test MSE = 16.7

Train a degree-4 polynomial regression



Test MSE = 12.2

Train a degree-5 polynomial regression



Test MSE = 14.8

Train a degree-6 polynomial regression



Test MSE = 25.1

Train a degree-7 polynomial regression



Test MSE = 39.4

Train a degree-8 polynomial regression



Test MSE = 53.0

Hyper-Parameter Tuning

Training Set

Test Set

Train a degree-1 polynomial regression



Test MSE = 23.2

Train a degree-2 polynomial regression



Test MSE = 19.0

Train a degree-3 polynomial regression



Test MSE = 16.7

Train a degree-4 polynomial regression



Test MSE = 12.2

Train a degree-5 polynomial regression



Test MSE = 14.8

Train a degree-6 polynomial regression



Test MSE = 25.1

Train a degree-7 polynomial regression



Test MSE = 39.4

Train a degree-8 polynomial regression



Test MSE = 53.0

Hyper-Parameter Tuning

Training Set


Test Set

Train a degree-1 polynomial regression



Test MSE = 23.2

Train a degree-2 polynomial regression



Test MSE = 19.0

Train a degree-3 polynomial regression




Test MSE = 16.7

Train a degree-4 polynomial regression



Test MSE = 12.2

Train a degree-5 polynomial regression




Test MSE = 14.8

Train a degree-6 polynomial regression




Test MSE = 25.1

Train a degree-7 polynomial regression



Test MSE = 39.4

Train a degree-8 polynomial regression



Test MSE = 53.0


- **Wrong! The test labels are unavailable!**
- **Even if you have the test labels, never do this!**

Cross-Validation (Naïve Approach) for Hyper-Parameter Tuning

Cross-Validation (Naïve Approach)



Cross-Validation (Naïve Approach)



Cross-Validation (Naïve Approach)

Training Set

Test~~Set~~

Train a degree-1 polynomial regression



Test MSE~~X~~ = 23.2

Train a degree-2 polynomial regression



Test MSE~~X~~ = 19.0

Train a degree-3 polynomial regression



Test MSE~~X~~ = 16.7

Train a degree-4 polynomial regression



Test MSE~~X~~ = 12.2

Train a degree-5 polynomial regression



Test MSE~~X~~ = 14.8

Train a degree-6 polynomial regression



Test MSE~~X~~ = 25.1

Train a degree-7 polynomial regression



Test MSE~~X~~ = 39.4

Train a degree-8 polynomial regression



Test MSE~~X~~ = 53.0

Cross-Validation (Naïve Approach)

Training Set

Validation Set

~~Test Set~~

Train a degree-1 polynomial regression



Valid. MSE = 23.1

Train a degree-2 polynomial regression



Valid. MSE = 19.2

Train a degree-3 polynomial regression



Valid. MSE = 16.3

Train a degree-4 polynomial regression



Valid. MSE = 12.5

Train a degree-5 polynomial regression



Valid. MSE = 14.4

Train a degree-6 polynomial regression



Valid. MSE = 25.0

Train a degree-7 polynomial regression



Valid. MSE = 39.1

Train a degree-8 polynomial regression




Valid. MSE = 53.5

k -Fold Cross-Validation


k -Fold Cross-Validation

1. Propose a grid of hyper-parameters.
 - E.g. $p \in \{1, 2, 3, 4, 5\}$.
2. Randomly partition the training samples to k parts.
 - $k - 1$ parts for training.
 - One part for test.
3. Compute the averaged test errors of the k repeats.
 - The average is called the **validation error**.
4. Choose the hyper-parameter p that leads to the smallest **validation error**.



Example: 5-fold cross-validation

Example: 10-Fold Cross-Validation



Example: 10-Fold Cross-Validation

hyper-parameter	validation error
-----------------	------------------

p=1	23.19
-----	-------

p=2	21.00
-----	-------


p=3	18.54
-----	-------

p=4	24.36
-----	-------

p=5	27.96
-----	-------


Real-World Machine Learning Competition

The Available Data




The public and private are mixed;
Participants cannot distinguish them.


Train A Model



Prediction



Submission to Leaderboard



Submission to Leaderboard

Training

Public

Private

Labels:

y

unknown

unknown

Features:

X

X_{public}

X_{private}

Question: Why two leaderboards?

Answer: The score can be evilly used for hyper-parameter tuning (cheating).


y_{public}

y_{private}

Submission

Score=0.9527

Secret!



Summary

- Polynomial regression for non-linear problems.
- Polynomial regression has a hyper-parameter p .
- Tune the hyper-parameters using cross-validation.
- Make your model parameters and hyper-parameters independent of the test set!!!