

NOTE:


1. ELECTRICAL CHARACTERISTICS

- 1-1. CONTACT RESISTANCE: 50 milliohms MAX.  
1-2. INSULATION RESISTANCE: 1,000 Megohms MIN.  
1-3. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC  
FOR 1 MINUTE.

2. MECHANICAL CHARACTERISTICS

- 2-1. RETENTION FORCE: MIN.100gf/PIN  
2-2. RoHS 2002/95/EC COMPLIANT.  
3. RESISTANCE TO REFLOW SOLDERING HEAT: 260°C Max

ITEM	PAPT	NAMF	QTY	MATERIAL	FINISHING
③	Shell	1	BRASS		
②	Terminal	10	BRASS		
①	Housing	1	LCP UL 94V-0	BLACK	

							DSND		DATE		SCALE: N/A	MODEL TYPE: TF CARD CONN			
△ X						ANGLAR	±5°	DWN		DATE		VIEW: 	PART NO.:		
△ X						L ≤ 4	±0.2	CHKD		DATE		UNIT: mm	DWG NO.: XKTF-005		
△ X						4<L ≤ 16	±0.3			DATE					
△ X						16<L ≤ 63	±0.4	APPD		DATE		SIZE: A4	WEIGHT 1.0g		
MARK	DESCRIPTION			DATE	REVISED	APPROVED	L > 63		±0.5		DATE				
REVISIONS							UNSPECIFIED TOLERANCES		KXB INDUSTRIAL PRECISION CO.,LIMITED				SHEET		
www.xk-dg.cn   www.helloxkb.com   www.helloxkb.cn													1/1		
													REVISION A0		