TEHTÄVÄT OSA 1:

```
mysql> SELECT * FROM pet WHERE (species = 'dog' AND sex = 'm')
    -> ;
+--------+-------+---------+------+------------+------------+
| name   | owner | species | sex  | birth      | death      |
+--------+-------+---------+------+------------+------------+
| Fang   | Benny | dog     | m    | 1990-08-27 | NULL       |
| Bowser | Diane | dog     | m    | 1989-08-31 | 1995-07-29 |
+--------+-------+---------+------+------------+------------+
2 rows in set (0.00 sec)
```

```
mysql>  SELECT * FROM pet WHERE birth >= '1990-1-1';
+----------+--------+---------+------+------------+------------+
| name     | owner  | species | sex  | birth      | death      |
+----------+--------+---------+------+------------+------------+
| Fluffy   | Harold | cat     | f    | 1993-02-04 | NULL       |
| Claws    | Gwen   | cat     | m    | 1994-03-17 | NULL       |
| Fang     | Benny  | dog     | m    | 1990-08-27 | NULL       |
| Chirpy   | Gwen   | bird    | f    | 1998-09-11 | 2000-09-15 |
| Whistler | Gwen   | bird    | NULL | 1997-12-09 | NULL       |
| Slim     | Benny  | snake   | m    | 1996-04-29 | NULL       |
+----------+--------+---------+------+------------+------------+
6 rows in set (0.00 sec)
```

```
mysql> select * FROM pet;
+----------+--------+---------+------+------------+------------+
| name     | owner  | species | sex  | birth      | death      |
+----------+--------+---------+------+------------+------------+
| Fluffy   | Harold | cat     | f    | 1993-02-04 | NULL       |
| Claws    | Gwen   | cat     | m    | 1994-03-17 | NULL       |
| Buffy    | Harold | dog     | f    | 1989-05-13 | NULL       |
| Fang     | Benny  | dog     | m    | 1990-08-27 | NULL       |
| Bowser   | Diane  | dog     | m    | 1989-08-31 | 1995-07-29 |
| Chirpy   | Gwen   | bird    | f    | 1998-09-11 | 2000-09-15 |
| Whistler | Gwen   | bird    | NULL | 1997-12-09 | NULL       |
| Slim     | Benny  | snake   | m    | 1996-04-29 | NULL       |
+----------+--------+---------+------+------------+------------+
8 rows in set (0.00 sec)
```

```
mysql> SELECT name FROM pet WHERE (species = 'dog' );
+--------+
| name   |
+--------+
| Buffy  |
| Fang   |
| Bowser |
+--------+
3 rows in set (0.00 sec)
```

```
mysql> SELECT name, owner FROM pet WHERE (species = 'dog' );
+--------+--------+
| name   | owner  |
+--------+--------+
| Buffy  | Harold |
| Fang   | Benny  |
| Bowser | Diane  |
+--------+--------+
3 rows in set (0.00 sec)
```

TEHTÄVÄT OSA2:

```
mysql> SELECT name FROM pet ORDER BY name;
+----------+
| name     |
+----------+
| Bowser   |
| Buffy    |
| Chirpy   |
| Claws    |
| Fang     |
| Fluffy   |
| Slim     |
| Whistler |
+----------+
8 rows in set (0.00 sec)
```

```
mysql> SELECT owner,count(*) FROM pet GROUP BY owner;
+--------+----------+
| owner  | count(*) |
+--------+----------+
| Harold |        2 |
| Gwen   |        3 |
| Benny  |        2 |
| Diane  |        1 |
+--------+----------+
4 rows in set (0.00 sec)
```

```
mysql> SELECT name,count(*) FROM pet GROUP BY name;
+----------+----------+
| name     | count(*) |
+----------+----------+
| Fluffy   |        1 |
| Claws    |        1 |
| Buffy    |        1 |
| Fang     |        1 |
| Bowser   |        1 |
| Chirpy   |        1 |
| Whistler |        1 |
| Slim     |        1 |
+----------+----------+
8 rows in set (0.01 sec)
```

```
mysql> SELECT owner FROM pet WHERE owner LIKE "H%";
+--------+
| owner  |
+--------+
| Harold |
| Harold |
+--------+
2 rows in set (0.00 sec)
```

```
mysql> SELECT name FROM pet WHERE name LIKE "%ff%";
+--------+
| name   |
+--------+
| Fluffy |
| Buffy  |
+--------+
2 rows in set (0.00 sec)
```

```
mysql> SELECT name FROM pet WHERE name LIKE '____';
+------+
| name |
+------+
| Fang |
| Slim |
+------+
2 rows in set (0.00 sec)
```