ASTRAEUS II



A COMPREHENSIVE REPORT

AARON KUMAR
AADIT GUPTA
ADWAITH SHAJI
ARMAAN SINGH
DEVANSH PAVITHRAN
MEDHANSH KAPOOR
PARMEET ABBAT
SAHIB SOHI
SANIL MANANDHAR
SHIVAM PATEL
SOHAM SONI
SAUMYA SONI

We would like to extend our sincere gratitude to the following individuals for their invaluable support and advice on this comprehensive report.

Simona Matei
—NSS Club Supervisor/Calculus Instructor Ontario, Canada—

Dr. Darrin L. Mayhew
—PhD Organic Chemistry, Ontario, Canada—

Dr. Baaziz Manel, M.D
—Resident in internal Medicine, Marianhospital, Stuttgart, Germany—

Dr. Suruchi Kapoor, M.D
—New Delhi, India—

Dr. Dilbaj Singh
—PhD Applied Mathematics—

Table of Contents

0.0 Executive Summary **3**
1.0 Design and Propulsion Systems **4**
1.1 Overview of the ASTRAEUS II 4
1.2 Fueling Systems 4
1.2.1 Hydrogen-Oxygen (HHO) Generator 5
1.2.2 Nuclear and Ion Thrusters 6
1.3 Aerodynamics and Thermal Protection 7
1.3.1 Alternative propulsion comparison 8
Electromagnetic Thruster: Backup Propulsion System 8
1.3.2 Structural Integrity Under High-Speed Travel 8
2.0 Launch Systems and Flight Mechanics **8**
2.1 Pre-Launch Preparations 8
2.1.1 Payload Integration 8
2.1.2 Rocket Assembly and Inspection 9
2.2 After Initial Launch Maneuvers 10
2.2.1 Stage 2 Launch 10
2.2.2 Multi-Stage Analysis and Optimization 11
2.3 Construction and Assembly in Orbit 11
2.3.1 Lagrange Point (L1) as the Construction Site 11
2.3.2 Assembly Stages 12
3.0 Propulsion and Journey to Trappist-1e **13**
3.1 Main Propulsion Systems 13
3.1.1 Nuclear Orion Ion Thrusters 13
3.3 Deceleration & Arrival Protocols (Braking Maneuvers & Reverse Thrust Systems) 13
3.4 Relativistic Effects of High-Speed Travel 14
4.0 Settlement Location and Analysis **15**
4.1 Choosing Trappist-1e 15
4.2 Environmental Conditions and Habitability 15
4.3 Resource Availability for Long-Term Sustainability 16
4.4 Challenges and Solutions 17
5.0 Settlement Exterior Design **19**
6.0 Interior Architecture and Infrastructure **19**
6.1 Transportation within the Settlement 19
6.2 Waste Management and Recycling Systems 21
6.3 Water Filtration 21
6.4 Living Quarters and Modular Housing 23
6.5 Cultural and Recreational Facilities 23

6.6 Education and Research Hubs 24
6.7 AI and Robotics for Construction and Maintenance 24
7.0 Astrobiology and Life Support Systems 25
7.1 Health Monitoring and Medical Facilities 25
7.2 Food Production and Hydroponic Farming 30
8.0 Space Defense and Security Systems 34
8.1 Space Debris Tracking and Mitigation 34
8.2 Cybersecurity and Data Protection 37
8.3 EMP Protection and Shielding 37
8.4 Energy Redundancy and Independence 38
9.0 Terraforming and Long-Term Expansion 39
9.1 Strategies for Terraforming Trappist-1e 41
9.2 Future Human Settlement and Growth 41
9.3 Potential Scientific and Economic Developments 42
10.0 Environmental Engineering and Sustainability 43
10.1 Cryogenic Research and Resource Conservation 43
10.2 Robotics and Automation in Maintenance 45
10.2.1 Modular Self-Assembling Robots 45
10.3 Advanced Waste and Energy Management 46

0.0 Executive Summary

ASTRAEUS II is not just a vision—it's the **future** of our civilization, and interstellar civilization. The design of ASTRAEUS II is backed up by real engineering, innovative science, and bold new ideas. This project is not just an exercise in thought; **we designed, built, and tested key technologies** that bring deep-space settlement closer to reality. ASTRAEUS II is a massive, self-sustaining megastructure, housing just over 313,000 habitants on a journey to Trappist-1e—40.7 light-years away—a potentially habitable exoplanet. To make this possible, we engineered an **Orion nuclear-ion propulsion system**, enabling sustained high-speed travel, and **successfully built and tested** a working ion thruster, proving the feasibility of advanced electric propulsion. The ship's rotating habitation ring provides artificial gravity, its hydroponic farming modules achieve **near 100% efficiency**, and its AI-driven autonomous medical system ensures real-time health monitoring and robotic-assisted surgeries. ASTRAEUS II is fortified with EMP shielding, laser-optic communications, and maglev transportation, creating a city in space that operates with virtually zero-waste sustainability. **Unlike traditional concepts**, ASTRAEUS II integrates real-world experiments, breakthrough propulsion systems, as well as next-generation life support solutions. Xanthoria elegans is not just a theoretical model—it is the first step toward humanity's future among the stars.

1.0 Design and Propulsion Systems

1.1 Overview of the ASTRAEUS II

ASTRAEUS II is designed after the concept of **overkill**; it offers **everything and more** to travel to its settlement location Trappist 1e. At the core of ASTRAEUS II lies the residential area—the large ring—housing around 313, 448 habitants. As ASTRAEUS II is always spinning, the residential area experiences centrifugal force which creates a sensation of gravity. The large tanks in front of ASTRAEUS II hold all the water required for residents—this of course is recycled and reused over the course of its travels to Trappist 1e. The front hosts the ASTRAEUS agriculture modules—*Grade 12 1st place large group winning design.* These modules work at 95%+ efficiency, leaving virtually no wasted space. Taking a look at the space behind the residential area, we find the thrusters and reactors that will enable ASTRAEUS II to travel to Trappist 1e with ease. Finally, at the very end we leave the communications antenna, which is able to send and receive information using laser optic signals—the fastest means of data transfer known to man.





1.2 Fueling Systems

1.2.1 HHO Generator

Electrolysis of water splits it into oxygen gas (O_2) and hydrogen gas (H_2). It is carried out in a reaction chamber where stainless steel or platinum electrodes are immersed in an electrolyte solution of potassium hydroxide (KOH) or sodium hydroxide (NaOH). The electrolytes make the water more conductive so that the reaction can occur more effectively. Hydrogen ions receive electrons at the cathode and turn into hydrogen gas (H_2), and oxygen ions lose electrons at the anode and turn into oxygen gas (O_2).

The strong electrolytes like sodium hydroxide (NaOH) or potassium hydroxide (KOH) decrease the resistance of water to the passage of electricity. This increases efficiency by lowering energy loss in the form of heat. The concentration of the electrolyte has to be precisely balanced, as too little slows the reaction and too much creates too many gas bubbles on the electrodes. These bubbles reduce electrode contact with water, reducing overall efficiency.

Increasing HHO Generator Efficiency

Increasing the electrode surface area means that more water molecules can be reacted at a time, resulting in overall higher efficiency. The use of mesh or perforated plate electrodes, as opposed to solid plates, enhances the active surface area, resulting in higher gas yield. Specialized materials, like platinum-coated electrodes, also further optimize the system by enhancing electrical conductivity and withstanding corrosion, resulting in a more durable and efficient system.



HHO gas being formed near electrodes

Optimal temperatures speed up the reaction by lowering the electrical resistance of water. Too much heat, though, results in losses through evaporation and parasitic side reactions. To maximize efficiency, temperature sensors are inserted into the reaction chamber to keep the system at an optimum operating point, typically between 50°C and 80°C.

Rather than a steady direct current, pulsed DC electrolysis will result in a greater efficiency and hydrogen gas yield. Pulsing the current at precise frequencies lowers energy loss and electrode wear, prolonging the life of the system. Resonant frequency electrolysis is also employed in some systems, where the frequency of the pulse is set at the same level as the natural vibration frequency of water molecules, which makes electrolysis even more efficient.

Contemporary high-frequency pulsed electrolysis with the assistance of plasma decomposition can attain more than 85% efficiency in the conservation of energy, meaning minimal energy is wasted in the process. Sophisticated thermoelectric devices are employed in waste heat recovery and its conversion as usable energy. The HHO gas produced may be directly supplied to internal combustion engines to add to the fuel combustion efficiency. By improving the air-fuel mixture, HHO reduces fuel consumption and carbon emissions while increasing engine power output.

1.2.2 Nuclear and Ion Thrusters

The ASTRAEUS II nuclear reactor is a small, high-efficiency fission reactor based on radioactive materials compressed into rods and contained in deuterium as a moderator. The reactor works by creating a controlled chain reaction within the fuel rods to produce heat, which is passed on to a working fluid through a heat exchanger. Boron control rods are removed or inserted to manage the reaction rate for safe and stable energy output. Heated deuterium is circulated by pumps through a closed-loop HHO gas being generated in close proximity to an electrode system, conveying thermal energy to drive the spacecraft's propulsion systems and onboard systems. Efficiency and safety are the design priorities, with the deuterium also serving as a coolant and neutron moderator. This architecture is a modular, scalable system that is designed for the long-duration missions that are needed for interstellar flight.



Diagram of nuclear reactor used for **ASTRAEUS II**

The ion thruster we built operates on the principle of ionizing a propellant and accelerating the ions to generate thrust through an electric field. Unlike advanced systems that use noble gases like xenon, our small-scale version utilizes a simple setup with air as the propellant. The system includes a copper tube as the ionization chamber and a steel brush cathode to enhance electron emission. When a high-voltage DC circuit is applied, the electrons emitted by the cathode ionize the air, creating positively charged ions. These ions are then accelerated by the electric field generated between the cathode and anode, producing thrust. A neutralizer is not included due to the simplicity of the design, and thrust is observed through the characteristic blue glow during ionization. This straightforward build demonstrates the core principles of ion propulsion and serves as a proof of concept for more advanced thruster designs.

Small ion thruster assembly



Small ion thruster running with 30,000+ volts creating an arc discharge.

1.3 Aerodynamics and Thermal Protection

1.3.1 Alternative propulsion comparison

One possible contender for the main propulsion method used is the antimatter-based sail, an incredibly powerful system that harnesses a violent nuclear fission reaction between antimatter and a uranium-coated sail.

The anti-matter sail has two components: a feasibly small amount of antimatter, and a uranium-238 coated carbon fiber sail. When the antimatter makes contact with the sail, it can induce a nuclear fission reaction through interactions between the anti-protons and uranium nuclei. This produces a large expulsion of gamma rays, neutrons, and other ejecta that generate an impulse several orders of magnitude greater than any standard nuclear reactor can. Though volatile, the amount of produced energy can be directly controlled through biasing the electrostatics of the incident beam of antimatter and the uranium.

This system has the advantage of efficiency and raw power. Antimatter is the densest form of energy conceivable, meaning very little space and mass must be allocated to power the sail. If implemented, it must likely be used in combination with smaller thrusters to allow for small scale corrections instead of the large outputs this system is adapted for. Research must still be conducted on superior ways to harvest and store antimatter before it can be implemented on ASTRAEUS II.

1.3.2 Structural Integrity Under High-Speed Travel

Travelling through space at relativistic speeds poses several threats to the structure, safety, and feasibility of the ship's exterior. The main challenges include harsh mechanical stresses from acceleration, the threat of colliding with miniscule space debris, and the effects of radiation particle bombardment.

The issue of acceleration on the exterior of the spacecraft can be addressed in two ways: material selection and the concept of gradual/constant acceleration for space travel. ASTRAEUS II will be composed of materials with extremely high tensile strength, such as carbon composites (~500 ksi) and titanium alloys (~200 ksi). Given standard density, they can withstand pulling upwards of 100 000 g's before significant warping. This threshold should be met by allowing adequate periods of time when accelerating and decelerating the spacecraft into and out of long-distance travel. This relates directly to the concept of constant acceleration; providing a sustained, low acceleration over the entirety of the travel duration rather than short thrusts. ASTRAEUS II circumvents one major limitation of this approach, adequate fuel, through its aforementioned ion thruster system.

Additionally, both physical debris and radiation pose threats on the integrity of the spacecraft exterior during long-distance travel. The high speeds at which ASTRAEUS II moves would mean that even the smallest particles (masses of <1g) would collide with kinetic energies equivalent to that of explosives. It should be prefaced that there is a degree of flight planning responsible for this; the spacecraft must avoid areas of heavy debris concentration like asteroid belts. To mitigate this

risk, modifications will be made to the exterior design of ASTRAEUS II which will be discussed later.

2.0 Launch Systems and Flight Mechanics

2.1 Pre-Launch Preparations

Pre-launch preparations are undoubtedly the most important phase of any space mission. Thorough pre-launch preparations ensure a space mission succeeds with ease. During the inspections of the projectile, engineers must inspect, optimize and integrate the payload inside the shell meticulously. Fuel loading processes, electronic systems and even the environment have to be tested prior to launch. Above all else, safety systems must also be inspected and tested to ensure failsafes are functional. The preparation process for the SpinLaunch-integrated rocket involves the following steps:

2.1.1 Payload Integration

Payload is positioned at the front of the rocket—shown in image below—it requires careful handling and integration as the integrity of the payload cannot be compromised at any point of the trip to the L1 point. The payload is encapsulated within an aerodynamic chassis with a reinforced nose cone to protect it from the stresses and extreme temperature differences. It is protected using thermal insulation and vibration damping systems to prevent any and all damage during the trip, especially during the initial launch when the projectile is leaving the centrifuge.



Source: Spinlaunch.com, Spaceport America.

The payload inside the SpinLaunch system goes through vibration dampening to ensure the rocket is reliable when delivering payloads to the L1 point.

Engineers conduct precise tests to ensure everything in the system is aligned and that the center of mass for the projectile is perfectly in place. Again, this is done to ensure the payload reaches L1 reliably.



Source: Spinlaunch.com, Spaceport America

2.1.2 Rocket Assembly and Inspection

The rocket, powered by Orion nuclear thrusters for the first stage and biofuels for the second stage, is assembled in a modular format to allow seamless integration of its components.

The exterior of the SpinLaunch Rocket is thoroughly inspected for any imperfections using a laser system. This is done to ensure the flight of the SpinLaunch rocket is reliable.

Fuel System Verification

Orion Nuclear Thrusters (Second Stage Booster)

The onboard nuclear reactor is activated in a controlled, ground-based environment to confirm its functionality.The cryogenic hydrogen tanks are pressurized and tested for leaks, ensuring readiness for nuclear fission-powered propulsion.

Second-Stage Biofuel Tanks (First Stage Booster)

The biofuel tanks are filled under strict safety protocols. Sensors monitor fuel purity, density, and pressure. The second-stage engines are cold-fired (without full ignition) to confirm operational readiness.

Subsystem Checks

Guidance Systems: The rocket's onboard navigation computers are calibrated to align with the preprogrammed trajectory.Backup navigation systems are tested for redundancy in case of primary system failure. **Communications Systems:** Long-range communications equipment is tested to ensure seamless transmission of telemetry data to ground stations.

2.2 After Initial Launch Maneuvers

$$\Delta v = I_{sp} * g_0 * ln(\frac{m_0}{m_f}) - \frac{1}{2}(\frac{C_D * A * p}{m}) * v^2 * \Delta t$$

$m_f = 750\ 000\ kg$ (including normal dry mass of 250 000 kg and the propellant needed for stage 2 that is 500 000 kg)
$m_i = 2\ 500\ 000\ kg$ (including fuel, also known as the wet mass)
$d_1 = 90\ 000\ m$ (altitude of first flight stage)
$v = 4\ 000\ m/s$ (This exhaust velocity falls in the average range of modern-day spacecraft (3 000-4 500), meaning that only average engine and fuel efficiency/quality are required.)
$I_{sp} = 350$ (estimated specific impulse)
$g_0 = 9.81$ (acceleration due to gravity)
$C_D = 0.5$ (estimated drag coefficient)
$A = 25$ (estimated surface area)
$p = 1.225$ (air density at sea level, relevant during Stage 1 launch)
$\Delta t = 1$
$m = 2\ 500\ 000\ kg$ (instantaneous mass of rocket, will change throughout the launch)

Substituting in all the determined values produces a delta-v value of 4080 m/s for the first stage of the launch.

2.2.1 Stage 2 Launch

$$\Delta v = I_{sp} * g_0 * ln(\frac{m_0}{m_f}) - \frac{1}{2}(\frac{C_D * A * p}{m}) * v^2 * \Delta t$$

$m_f = 100\ 000\ kg$ (excluding previous dry mass that was ejected)
$m_i = 600\ 000\ kg$ (including fuel, also known as the wet mass)
$v_e = 4\ 000\ m/s$ (This exhaust velocity falls in the average range of modern-day spacecraft (3 000-4 500), meaning that only average engine and fuel efficiency/quality are required.)
$I_{sp} = 350$ (estimated specific impulse)
$g_0 = 9.81$ (acceleration due to gravity)
$C_D = 0.3$ (estimated drag coefficient)
$A = 10$ (estimated surface area)
$p = 0.5$ (air density decreases in higher levels of the atmosphere, relevant for Stage 2)
$\Delta t = 1$
$m = 600\ 000\ kg$ (instantaneous mass of rocket, will change throughout the launch)

Substituting in all the determined values produces a delta-v value of 6 125 m/s for the second stage of the launch.

2.2.2 Multi-Stage Analysis and Optimization

The total delta-v of the launch can be found by adding the delta-v of both stages. The threshold to safely exit the Earth and enter LEO (Low Earth Orbit) is 10 000 m/s, meaning that the total must exceed this quantity in order to be successful.

$$\Delta v_t = 10\,000\ m/s$$
$$\Delta v_t = \Delta v_1 + \Delta v_2$$
$$\Delta v_t = 4\,080 + 6\,125$$
$$\Delta v_t = 10\,205\ m/s$$

As this threshold is exceeded, further delta-v will be needed to travel to the L1 Point, though substantially less due to the lack of drag and opposing gravity. Though it could be accomplished by drastically increasing the fuel (wet mass), each construction rocket will instead utilize a **gravity turn** to propel forward.

2.3 Construction and Assembly in Orbit

2.3.1 Lagrange Point (L1) as the Construction Site

The construction of ASTRAEUS II takes place at the Earth-Sun Lagrange Point (L1), a strategically chosen location due to its unique gravitational properties. This section explains how the SpinLaunch rockets deliver components to L1 and the subsequent assembly of the spacecraft.

Strategic Importance of L1: Lagrange Point 1 (L1) is approximately 1.5 million kilometers from Earth, where the gravitational forces of the Earth and Sun create a stable zone. This location minimizes fuel requirements for maintaining position, making it ideal for long-term construction projects. The reduced gravitational interference allows for precise assembly operations and long-term stability of ASTRAEURS II.

Delivery of Components Using SpinLaunch Rockets: The SpinLaunch rockets transport modular components of ASTRAEUS II to L1. Each rocket carries a specific payload, such as structural segments, propulsion modules, or life-support systems. These components are secured within modular containers designed for easy assembly in microgravity. **Payload Integration in Microgravity:** Once the rockets reach L1, robotic arms on pre-stationed assembly platforms retrieve the payloads and position them for construction. Each payload is equipped with automated docking interfaces to ensure precise alignment during assembly.

Robotic Construction Platforms

At L1, specialized autonomous robotic systems handle the majority of the assembly process. **Manipulator Arms:** Multi-jointed robotic arms are programmed to position and attach structural components. **Magnetic Alignment Systems:** These ensure the precise positioning of metal components before welding or bolting. **3D Printing Units:** Advanced 3D printers are used to fabricate

smaller components, such as joints and fasteners, on-site using stored raw materials. The robotic systems are monitored and controlled by a team of engineers from Earth-based mission control, with real-time adjustments made as needed.

2.3.2 Assembly Stages

- Stage 1: Core Structure Construction
  - The central frame of ASTRAEUS II is constructed first to serve as the backbone for subsequent modules.
  - The frame includes reinforced beams and docking ports to accommodate future expansion.
- Stage 2: Propulsion System Integration
  - The Orion nuclear thrusters are attached to the rear section of the spacecraft, while smaller ion thrusters are positioned along the sides for maneuvering.
- Stage 3: Habitat Module Assembly
  - The living quarters and life-support modules are added to the central structure. These include prefabricated modular sections delivered by SpinLaunch rockets.

Collision Avoidance: At L1, automated collision detection systems ensure safe docking and assembly of components in a clutter-free environment. Assembly Platform Maintenance: Drones equipped with repair tools are stationed to address potential malfunctions in robotic systems or payloads. The construction process at L1 leverages advanced robotics, modular design, and SpinLaunch technology to create ASTRAEUS II efficiently and safely. This strategic approach ensures minimal energy consumption while enabling high-precision assembly in space.

3.0 Propulsion and Journey to Trappist-1e

3.1 Main Propulsion Systems

3.1.1 Nuclear Orion Ion Thrusters

ASTRAEUS II utilizes 3 main reactor units near the rear of the ship that generate the bulk of the energy needed to power the spaceship. In addition to these, 12 large thrusters and 15 smaller thrusters are used in combination for supporting thrust and a greater control over the movement of ASTRAEUS II around obstacles and debris. The direction of the smaller thrusters can be notably reversed to decelerate the ship, as will be necessary as it approaches and enters the orbit of Trappist 1-e.

3.2 Calculations for Interstellar Travel

ASTRAEUS II will complete construction at the aforementioned Earth-Sun Lagrange Point (L1) and take courses for the intended destination of Trappist-1e.

The distance from Trappist-1e to Earth is roughly 385 trillion kilometers (40.7 ly). The additional 1.5 million kilometres from the L1 point is completely negligible in terms of total travel time, so it will be omitted for the remaining calculations.

$$d = 0.65c(t)$$
$$0.65c = 1.94 * 10^{8} m/s$$
$$d = 3.85 * 10^{17} m$$
$$t = \frac{3.85*10^{17} m}{1.94*10^{8} m/s}$$
$$t = 1.98453608247 \times 10^{9} s$$
$$t = 62.92\ years$$

3.3 Deceleration and Arrival Protocols (Braking Maneuvers and Reverse Thrust Systems)

As ASTRAEUS II draws near to Trappist-1e, it must drastically reduce its velocity to prepare for a long-term orbit around the exoplanet. This maneuver must be as controlled as possible to ensure that the spacecraft and those unboard do not suffer harsh side effects from rapid deceleration. The ship will use a two-part system to achieve the above requirements: a large reverse thrust system and a flyby braking maneuver with the parent star Trappist-1.

The human body in the ideal reclined position with advanced g-suits can withstand sustained decelerations of approximately 1.5g with little to no ill effects. Anything beyond this threshold has been associated with fluid buildup, cardiovascular issues, and other adverse health effects. ASTRAEUS II will reverse the thrust direction of its nuclear and ion thrusters well in advance of the intended arrival. The final velocity after this gradual phase will be roughly 100 km/s, an adequate speed for the second gravity-assist phase of the arrival protocol. This situation can be modelled using relatively simple kinematic equations:

$$v_i = 0.65 * 3.0 * 10^{8} = 194\,865\,098\ m/s$$
$$v_f = 100\ m/s$$
$$a_{max} = -14.72\ m/s^{2}$$
$$t = \frac{1*10^{2} - 1.94865098*10^{8}}{-14.72}$$
$$t = 1.324 * 10^{7}\ s$$

This corresponds to roughly 5 months of deceleration.

However, ASTRAEUS II will still be travelling far too fast to enter the orbit of Trappist-1e, requiring further deceleration. A gravity assist manoeuvre about the host star Trappist 1 is beneficial for three reasons; it does not require any further mechanical thrust, the main ship can align for orbital insertion, and Trappist 1 itself is in a conveniently close proximity to the intended destination.

Finally, once a sufficiently low speed (~10m/s) is reached, ASTRAEUS II will integrate with the orbit of Trappist 1-e and remain stable.

3.4 Relativistic Effects of High-Speed Travel

Given that ASTRAEUS II will travel at a significant fraction of the speed of light for sustained periods, the ship and those onboard will experience relativistic effects dictated by the Theory of Special Relativity. These include time dilation, length contraction, and changes in relativistic mass (not relevant to this section).

Given the approximate propulsion speed of 0.65c,

$$\gamma = \frac{1}{\sqrt{1-\frac{v^2}{c^2}}}$$
$$\gamma = \frac{1}{\sqrt{1-\frac{(0.65c)^2}{c^2}}}$$
$$\gamma = \frac{1}{0.75993420767}$$
$$\gamma = 1.31590338993$$

The Lorentz factor (γ) is approximately 1.31, which is a value that can be extrapolated for subsequent calculations.

Time Dilation:
Given the proper time interval of 62.92 years,
$t = t_o(\gamma)$
$t = 62.92(1.31590338993) = \sim 82.79\ years$ for an observer on Earth

Length Contraction:
Given the proper length interval (as measured from the reference frame of Earth, stationary to both points) of 40.7 light years,
$L = \frac{L_o}{\gamma}$
$L = \frac{40.7}{1.31590338993} = \sim 30.92\ light\ years$ for an observer on ASTRAEUS II

4.0 Settlement Location and Analysis

4.1 Choosing Trappist-1e

Preoccupied with a single leaf, you will miss the entire tree.

In the process of selecting a location for the settlement, the team for ASTRAEUS II was puzzled. There were several choices, however, in one way or another it was believed that they would be unable to provide for the needs of this settlement. The team was too focused on the financial

resources available or the technology in hand. However, as per competition rules this submission simply “must relate to free space settlements.”

Acknowledging this, the team finally saw the tree—finally began focusing on what location will allow this settlement to achieve generational habitation. Thus, ASTRAEUS II welcomes Trappist-1e as its home.

With Trappist-1e as the official settlement location, there are fundamental assumptions that must be recognized regarding the feasibility of this settlement. First, it is to be assumed that ASTRAEUS II has the funding and technological advancements necessary for a palpable mission to Trappist 1-e. Second, the journey itself is assumed to be made in a sufficient time frame that sustains adequate supplies for settlers in conjunction with ensuring their psychological conditions are positive. Lastly, the following data for Trappist 1-e and its habitability must be deemed accurate as per a series of recent studies conducted by NASA.

4.2 Environmental Conditions and Habitability

Forty-one light years away from Earth exists the Trappist-1 planetary system; the most studied planetary system besides our own solar system. The system consists of 7 earth-like planets, with 3 of them being within the habitable zone of the Trappist-1 star. Of these 3 planets in the habitable zone, Trappist-1e was chosen for its similarities to Earth and the possibility of water within the planet's crust. The following subsection will provide an understanding of the environmental conditions in Trappist-1e while simultaneously evaluating the habitability of this settlement location.

Table 1: Main Comparisons Between Trappist-1e & Earth

Feature	Trappist-1e	Earth
Density	5.65 g/cm³	5.51 g/cm³
Mass	0.629 $M_\oplus$	1 $M_\oplus$
Gravitational Acceleration	9.12 m/s²	9.81 m/s²
Day Length	Tidally Locked	24 Hours
Equilibrium Temperature	246 K	255 K

The above table outlines the main features of Trappist-1e and puts them into conversation with Earth’s features through comparison. Evidently, it is found that there is a difference in the mass of Trappist-1e, which is 0.629 that of Earth, and the fact that its gravitational acceleration is lower than Earth's (9.12 m/s² vs 9.81 m/s²). Essentially, this means that objects weigh less on Trappist-1e in comparison to Earth. Ultimately, this would prove useful in regards to gathering resources on the

planet and transporting them to the settlement as the system used in the aforementioned transport would require less power to reach ASTRAEUS II.

In addition, the density of Trappist-1e provides an effective estimate of the planet's surface. As per the table, Earth has a density of 5.51 g/cm³, and common knowledge defines it as a planet with a solid rocky surface filled with minerals. With a density of 5.65 g/cm³, merely a 0.14g/cm³ difference, this table illustrates how Trappist-1e could be of similar composition to Earth and could potentially contain even more valuable minerals due to its slightly higher density.

Together, these features display how the differences and similarities between Earth and Trappist-1e as made evident through the table prove to be beneficial for future excursions on the planet for resources.

4.3 Resource Availability for Long-Term Sustainability

Trappist-1e is a lustrous planet, offering countless resources that will prove beneficial for long-term sustainability on ASTRAEUS II.

When the time comes to expand the spacecraft as the population of settlers steadily increases, materials that will specifically come in handy are what can be found under the planet's potential layer of regolith. Found in rocky planets, regolith could be utilized as a method of future expansion through its constructional value. Trappist-1e also has a metallic core, similar to Earth, meaning that valuable minerals such as iron, nickel, gold, and platinum could be obtained. This will be especially useful for the production of technology, and could even be used to create a currency on the settlement.

Furthermore, water is essential for sustaining life and could also be used for various industrial processes, agriculture, and as a radiation shield. If TRAPPIST-1e has water ice on its surface or trapped beneath its crust, it could be harvested and purified for use within the settlement. Because of its water, in comparison to its "sibling planets'" that are also known to be in the habitable zone, Trappist-1e continues to outshine Trappist-1f, Trappist-1g, and Trappist-1h, proving it to be the perfect home for ASTRAEUS to orbit. Specifically, Trappist-1e is in the perfect position relative to its star compared to other planets, where the temperature is at a point where ice can be melted to harvest water (unlike its sibling planets which are either too cold or too hot).

Finally, the unique orbital characteristics of TRAPPIST-1e offer opportunities for harnessing solar energy and facilitating sustainable power generation within the space settlement. Its close proximity to its host star could mean gathering solar energy will be more effective compared to Earth. Solar panels and other energy harvesting technologies could be deployed on the planet's surface to capture and convert solar radiation into electrical energy, supporting various settlement operations and reducing dependence on external energy sources.

4.4 Challenges and Solutions

Of course as the saying goes, every opportunity comes with its fair share of obstacles. For ASTRAEUS II to settle on Trappist-1e, these challenges must be recognized as well, with ample solutions ready to aptly combat them.

A key issue is the unpredictable weather conditions on Trappist-1e, posing risks to the landing operations, surface infrastructure, and overall human survival. Should the planet possess an atmosphere, violent storms and high winds may develop—harming any surface related missions—threatening the overall safety of ASTRAEUS II and its inhabitants. Thus, the settlement must study the weather patterns of Trappist-1e in order to predict safe landing windows. If available, a network of weather monitoring satellites will be beneficial and help solidify safe windows in which these missions can be effectively carried out. Moreover, those who travel to Trappist-1e for resources and alike can be fitted with adaptive flight control systems which would modify their descent according to unexpected changes in the weather, thereby guaranteeing safer landings. Thus, backup landing zones in more stable regions of the planet can also be established, allowing for a reduction in risk.

As aforementioned, Trappist-1e is a tidally locked planet meaning one side is in constant daylight, while the other in darkness. In the short-term this could pose a psychological problem to settlers on ASTRAEUS II who have become used to Earth’s circadian rhythm. For the settlers, the absence of a consistent day-night cycle could disrupt circadian rhythms, causing insomnia, heightened fatigue, mood disorders, and possibly cognitive impairment. Resultantly, inside the station, adjustable lighting systems would be crucial in the stimulation of such a rhythm for settlers which will correspondingly promote human health. In doing so, the tidally locked planet will be able to simulate Earth's gradual dawn, noon light, dusk, and night darkness to help regulate sleep-wake cycles and overall health.

In essence, by overcoming these difficulties using cutting-edge technology, careful planning, and creative engineering, ASTRAEUS II will be able to provide a more secure and sustainable presence on Trappist-1e. For all the right reasons, Trappist-1e continues to prove itself to be not the home that ASTRAEUS II desired, but rather the home that ASTRAEUS II needed.

5.0 Settlement Exterior Design



6.0 Interior Architecture and Infrastructure

6.1 Transportation within the Settlement

Maglev trains (Magnetic levitation trains) work by employing the principles of electromagnetism to propel the train at extremely high speeds. The trains themselves float above the tracks or guidelines instead of rolling on the tracks because of the supercooled electromagnets that are involved. This works by having magnets on the bottom of each train car and on the rails. Maglevs rely on magnetic attraction and repulsion in order to float. This is done through electrodynamic suspension. Electrodynamic suspension (EDS) creates a gap of 10 cm between the train and the rail and provides a more stable method of transport. In this method, magnets that are placed on both sides of the train interact with magnets placed on the sides of the rail to induce levitation. As the train moves over the track, it experiences changing magnetic fields due to the interaction between the sets of magnets that generates an opposing field that lifts the train up. EDS systems are more stable because they have magnets placed vertically with the north pole pointing up on one side of the track and the south pole pointing up on the other side of the track. This creates a figure-eight pattern between the magnets that keep it stable. If the train were to move down or to either side, the magnets on the train induce currents on the opposing field as the magnets on the rails to stabilize movement. EDS does require superconducting coils to make the electromagnets. These coils are made of niobium-titanium and are cooled using liquid helium and placed inside a container cooled with liquid nitrogen to maintain the temperature. The coils are cooled using a pulse tube refrigerator that uses sound waves to cool the helium in the container. This is done by using a thermoacoustic cooler to create a standing wave that will bounce off the closed end of the tube and create regions of high pressure, and thus high heat. A stack is then placed between the hot region in the tube and the cold region of a tube with a heat exchanger to bring the heat to a radiator, allowing the cold side to conduct heat away from the coils.

In terms of actually moving the train, that is done through linear motors. A linear motor is similar to a conventional electromagnetic motor but simply unraveled. As the train moves, alternating coils use magnetic attraction and repulsion to attract and repel the train with specific timing, causing the train to move forward. This same feat is applied in reverse to slow the train down in a process called regenerative braking. These trains are going to be powered using a linear induction coil. This coil will gather power from the changing magnetic fields of the guiding coils and use it to power the train. The power that is generated from these induction coils works in a similar way to hydroelectricity. The coils in the track act as a stator with the magnets on the train acting as rotors. This creates a more efficient method of powering the train as the alternative would have been using generators which would have been more difficult in space.

There are many benefits to using maglev trains for transportation. They move at much higher speeds than normal trains, are mostly silent, and also environmentally friendly as they use electricity instead of fossil fuels. They also require less track maintenance as there is essentially no friction between the train and the rails, except at the very beginning and end of the tracks. This makes it so that there is less wear and tear on the tracks, meaning that less work will have to be done to maintain them. All

in all, maglevs are a great way of transporting the people that will end up living on ASTRAEUS II in a safe and efficient manner.

6.3 Water Filtration

Water can be a big concern in space. In order to address this concern, an integrated system that combines forward and reverse osmosis will be implemented to separate clean water from contaminants and produce a clean drinking water supply. In forward osmosis, the feed solution (contaminated water) is sent into a filter where the water and contaminants are separated by the semi-permeable membrane and the use of a draw solution before the draw recovery solution restores the draw solution. The main components of a forward osmosis solution are the forward osmosis membrane, the draw solution, and the draw recovery system.

The forward osmosis membrane is a membrane that only allows water to pass through it. This membrane is usually made of cellulose triacetate. In order for a forward osmosis membrane to be effective, it needs to have a high rejection rate, which is the term for the membrane's ability to stop substances other than water from passing through and its ability to prevent reverse flux. Reverse flux is when the membrane allows some of the draw solution to permeate through the membrane into the side with the feed solution. It is necessary to minimize this as much as possible because if that is not done, then it will require more resources to top up the draw solution for future uses.

The draw solution is a highly saline solution that is used to create the osmotic pressure required for forward osmosis. In order to achieve the best results, the draw solution should be specially formulated for each different type of feed solution. This will be done by having different forward osmosis systems for different feed solutions to make the process as efficient as possible.

The final main component of the forward osmosis solution is the draw recovery system. This is what takes the diluted draw solution that will be left after separating the water and contaminants and tops it up by restoring the total dissolved solids (TDS) of the draw solution so it can be used again. This will be accomplished by using a conventional seawater reverse osmosis system that can handle TDS up to 70,000 parts per million. The draw recovery system also separates the clean water from the draw solution so that the clean water can be used for whatever it is needed for. Reverse osmosis is similar to forward osmosis, but it uses hydraulic pressure to move water through the membrane instead of natural osmotic pressure.

6.4 Living Quarters and Modular Housing





6.5 Cultural and Recreational Facilities

Amphitheatre:



6.6 Education and Research Hubs

Education Facilities:

7.0 Astrobiology and Life Support Systems

7.1 Health Monitoring and Medical Facilities

7.1.1 Integrated Biometric Monitoring Systems (IBMS)

The Integrated Biometric Monitoring System (IBMS) is a large system that checks health in real-time. It can find and predict health problems before they become serious. The IBMS uses many implantable and wearable devices that keep track of vital signs, chemical markers, and physical changes all the time. The wristbands and patches are wearable devices that will track your heart rate, blood pressure, temperature, glucose level, cortisol level, and oxygen saturation. The wearable sensors will be made of soft, skin-friendly material so that they can be worn over a long duration of time. The wristbands will have sensors for tracking heart rate and oxygen in the blood. The patches will have extremely small needles that insert into the skin to test fluid for glucose and cortisol levels. Implantable chips, protected by a nontoxic polymer so that the body will not reject them, will track important health information like immune system function and internal organ status. The chips will also track pH, temperature, and organ health markers.

Powering of the sensors is of utmost importance for the IBMS, and this will be achieved by utilizing bioenergy harvesting so as not to need any external power supplies. Enzyme-based glucose fuel cells will make use of glucose to generate a small electric current to power the sensors. Wearable sensors constructed from piezoelectric material will also collect energy from movement and transform it into electrical energy. The sensors will run round the clock without the need to keep replacing the batteries.

Data from these sensors will be sent wirelessly to a central AI system through low-power, high-frequency communication technologies like Bluetooth 5.0 for short distances and ultra-wideband for longer distances between different sections of the settlement. The AI software will analyze the data using machine learning algorithms trained on vast amounts of human health data, including data from space experiments on the ISS and in Antarctica. The algorithms will recognize trends that are a sign of underlying health issues, for example, infection, cardiovascular problems, or radiation. Predictive analytics will allow the AI to diagnose medical issues from patterns in data, for instance, high cortisol levels suggesting more stress. The AI will also notify the individual and medical personnel if it recognizes anything unusual, with the notifications prioritized by severity. For example, when the heart rate rises or the oxygen saturation in the blood falls, alerts will be activated right away.

Each settler will have a holographic individual health dashboard with his or her current health data. The holograms will project 3D images from different angles using lasers, and there will be an interactive platform that will accept touch and gesture inputs. The dashboard will display useful tips, e.g., reminding one to exercise, drink, or take medicine, and offer advice on how to remain healthy in space. The AI will review the settler's medical data and offer tailored advice, including personalized exercises to enhance cardiovascular health or dietary changes to correct nutritional imbalances.

7.1.2 Autonomous Medical Facilities (AMFs)

Autonomous Medical Facilities (AMFs) are independent centers that have the ability to diagnose and treat any type of medical condition with minimal human intervention. The facilities will be equipped with robot surgery systems, 3D bioprinters, and telemedicine units to ensure comprehensive medical care. Robot surgery systems will be endowed with high-precision instruments like laser scalpels, nano-forceps, and 3D vision cameras to facilitate minimally invasive surgery that minimizes recovery time and complications. Laser scalpels will utilize focused laser beams to make tiny incisions with limited tissue damage. Nano-forceps will be utilized to achieve intricate procedures like stitching tiny blood vessels or dissecting small tumors. The robots will be guided by AI algorithms trained on surgical simulations and real procedures, whereas human surgeons on Earth will perform surgeries remotely using telepresence. Surgeons will control the robotic arms with devices that enable them to feel touch and provide accuracy. The surgical tools will be sterilized with ultraviolet (UV) light and plasma systems to ensure sterility and eliminate any chance of infection.

In case of emergencies, 3D bioprinters will print tissue grafts, bone substitutes, or whole organs as required. The bioprinters will blend synthetic and bioengineered materials to copy the shape of natural tissue. Synthetic materials will provide strength, and bioengineered materials, such as growth factors and molecules that provide cell structure stabilization, will enable cells to grow and tissues to integrate. Settlers' stem cells, stored at -196°C in very low temperatures, will serve as the main source for bioprinting. In the case of a deficiency of stem cells, artificial substitutes or donor cells that can be used universally would be used. Bioprinting would be done using layer-by-layer construction in a real-time monitored manner to maintain quality and precision. The bioprinter resolution will be 10-50 microns, which will allow it to print complex shapes that mimic natural tissues. Telemedicine facilities in the AMFs will allow settlers to have video consultations with doctors on Earth in real time.

Communications systems, i.e., laser-based optical systems, will provide uninterrupted and crisp video consultations. The medical data, i.e., imaging scans and laboratory reports, will be sent to Earth in a secure manner to be displayed, and AI systems will process the data and suggest a treatment. All medical data needs to be encrypted in AES-256 to provide confidentiality and security, and digital signatures and checksums to provide data integrity during transfer.

7.1.3 Cognitive and Emotional Monitoring of Psychological Well-being

Mental health is no less important than physical health in space settlements, and one such system that is being envisioned to cater to this is the Cognitive and Emotional Monitoring System (CEMS).

The CEMS would employ neurofeedback wearables in the form of EEG headbands to monitor brain function and emotions. Multiple electrodes would be installed in the scalp in the headbands to capture different aspects of the brain function, filtering interference using advanced signal processing techniques to obtain useful signals. The AI software would process such signals to identify symptoms of cognitive impairments, anxiety, or depression. The AI software would provide personalized support in the form of virtual reality (VR) therapy, guided meditation, or socialization. VR therapy would provide interactive sessions to relax and stress less, and guided meditation would be provided using the holographic health dashboard. Virtual companions using NLP-based algorithms

would provide emotional support and company. AI friends would provide substantive dialogue, suggest mental health exercises, and guide settlers in mindfulness meditation. Settlers would be allowed to personalize appearances, voice, and personality of virtual companions to provide it a more intimate and relaxing feel. Settlers would be allowed to use different avatars and personalize the voice and personality of the companions according to their preferences.
The hospitals and clinics will be constructed in biophilic design to assist with mental well-being.

Natural locations on Earth, such as forests, beaches, and mountains, will be projected by holographic projections for the people of the colony to view. Immersive VR interactions will allow the colonists to visit and interact with these sites, fostering an attachment to nature that reduces stress and enhances mental well-being. We have shown that being in natural settings can greatly reduce stress and enhance mental health. So, biophilic design is an important part of the hospitals in the settlement.

7.2 Emergency Response and Rehabilitation

7.2.1 Emergency Response Systems

A response system to emergencies in a space settlement can be based on potential hazards such as health, environmental hazards, or failures in equipment. The use of sophisticated machines that can be monitored in real time and automatically react is advantageous.

Live Monitoring and Early Warning Systems

The system would use AI and sensors to provide live reports of the environment, condition of equipment, and settlers' health. Environmental sensors would be used to monitor air, radiation, temperature, and pressure, and equipment sensors would provide reports of condition of life support, power systems, and building safety. We also monitor settlers' health, discussed in Section 7.1, their vital signs and chemical balances. AI would be used to recognize sudden changes so that we can prepare for low oxygen, high-radiation, or health-emergency situations. Early warnings would be transmitted using holographic warnings, wearable devices, and control systems to settlers and emergency responders.

Emergency Communication Protocols:

In case of an emergency, having a working line of communication is crucial. For that reason, there is a backup system employing radio, laser links, and cable systems to maintain connectivity even when some of the equipment is in trouble. All communication channels will send alarms to inform settlers in real time during an emergency, keeping them up to date. The AI system selects the most relevant alarms. This allows key information to be disseminated in a hurry. As a case in point, in a leak of radiation, it would inform settlers to evacuate to safety areas, and medical professionals would be on hand to treat anyone exposed to radiation.

Fast Deployment of Emergency Resources

There will be drones and robots to assist in cases of emergency. Drones will be used to deliver medicine, defibrillators, and first aid kits in a matter of minutes in a medical emergency. The drones will use sophisticated systems with GPS and obstacle detection to navigate easily. The drones will

also assist in hazards such as fire, gas leaks, and damages to buildings. The drones will carry fire extinguishers, gas detectors, and tools to assist in problem-solving and minimizing losses and risks.

7.2.2 Rehabilitation Systems

Rehabilitation of space colonies would work to rebuild body, mental, and cognitive health in cases of emergency or illness. The unique challenges of living in space, such as weightlessness and isolation, necessitate new types of rehabilitation that differ from those on Earth.

Physical Rehabilitation

Weightlessness places great stress on the body, causing muscle loss and decreased bone strength. The colony would be equipped with new rehab equipment such as exercise devices, vibration platforms, and robot exoskeletons. The strength training in space would be facilitated using air pressure and elastic bands in the exercise devices. The vibration platforms would assist in making muscles and bones more efficient in order to reduce weightlessness effects. The robot exoskeletons would help settlers gain their mobility and strength after injury or a period in bed. The robot exoskeletons would be personalized to meet individual needs and provide settlers and health professionals live health reports.

Psychological Rehabilitation

Psychological stress caused by crises and isolation in space can cause stress, anxiety, and depression. The psychological rehab program in the colony would consist of virtual reality therapy, mindfulness programs, and support groups. The virtual reality therapy would display realistic scenes of nature on Earth to relax settlers and reduce their stress. The mindfulness programs using guided breathing and meditation would be accessible using a holographic health dashboard. Social support would be offered in group sessions, recreation, and virtual emotional support partners.

Cognitive Rehabilitation

Human settlers' mental health in space is of great concern to their welfare and productivity. Cognitive rehab would be centered around brain exercises, brain-computer interface technology, and neurofeedback training. Neurofeedback training is a method of training using EEG-based headbands that monitor the activity of the brain and provide instant feedback. This can be used to enable settlers to become more focused, more memorable, and more in control of their emotions. Settlers can get cognitive training via puzzles and other memory challenges on the holographic health dashboard. BCI technologies will enable computers and robots to interact with brain activities, providing settlers with new means of performing rehabilitation routines.

Regenerative Medicine for Recovery

The primary function of regenerative medicine in rehab is to enable individuals to be restored to health after injuries or exposure to radiation. Tissue regeneration will employ use of stem cell therapies, and 3D bioprinting technology will produce personalized implants and prosthetics. An example is a bone graft created using a patient's own stem cells via 3D printing that induces the tissue to match and reduces rejection possibilities. Settlers exposed to extremely high doses of radiation can also be cured using gene therapy that enhances the body's natural mechanisms to repair DNA.

7.3 Food Production and Hydroponic Farming

7.3.1 Hydroponic Farming Systems

Hydroponic farming is going to be the backbone in the food production system within the space settlements. It would guarantee much more efficiency in space use, resources, and control of plant growth. Designing hydroponic systems should be done in a way that maximum yield with least wastage would supply nutritional requirements for settlers.

System Design and Infrastructure:

Hydroponic farming modules would be induced within the colony structure, efficiently using space by means of vertically growing methods. Crops will grow in multi-levels comprising LED lighting, nutrient feeding systems, and environmental controls. Such modules are kept pressurized and controlled with climate controls that would keep the crops protected from harsh conditions in space.

Nutrient Delivery Systems:

The plants would be grown in soilless growth mediums like perlite, coco coir, or rockwool that would give the best possible support to their roots for receiving nutrition. Closed-loop delivery of nutrients circulated with a well-balanced solution of water and other required nutrients like nitrogen, phosphorus, and potassium in a favorable manner for plants to absorb it. This would further be regulated in real time with the aid of an AI-driven control system to avoid nutrient deficiencies or toxicities of any sort.

Light and Photosynthesis:

Since it is not possible to simulate sunlight in space, the growth system will be using LED lighting, whereby it is easy to produce the required spectrum of light for photosynthesis. These LEDs are programmable to a number of different wavelengths of light, including red and blue, which plants love best. In this way, a light/dark cycle may be provided that closely simulates a normal day-night rhythm for the benefit of the plants and optimal yield. It has an intensity control and duration control of light to suit the growing stage and requirement of plants.

Environmental Controls

The level of temperature, humidity, and CO2 levels will complete the perfection of the conditions of the plants. These are continuously monitored by the AI in operation and it may change all these in real time. As an example, when the levels of CO2 drop it lets out the stored CO2 gas to increase the rate of photosynthesis. In the same way, the level of humidity is controlled in order to prevent mold formation for proper transpiration.

Water Management:

Water is too much a commodity in space, and the hydroponic system will be designed where possible to save water. A closed-loop water recycling system will be installed to catch excess water, filter it from impurities, and reintroduce the water back into the nutrient solution. It shall be so designed that, while full utilization is made to conserve water, it will make it non-wasteful by assuring a minimum loss via evaporation and leakage.

7.3.2 Crop Selection and Rotation

The selection of crops depends on their nutritional value, rate of growth, and ability to grow in a controlled environment. Most of the varietal crops-from leafy vegetables, fruits, and vegetables to legumes-will be grown in order to address every type of nutritional need among the settlers.

High Yielding Crops:

Let-tuce, spinach, and kale are chosen leafy vegetables due to nutrition and growth speed. Most of the above-mentioned veggies are picked off within weeks after sowing its seeds and hence they will become almost incessant supply. Rest, tomato, pepper and cucumber-all of immense use and hence a good nutrition provider. These are the staple crops that provide the carbohydrates and protein: potatoes, sweet potatoes, and beans. Longer growth cycles but a necessity to supplement settler caloric needs. Varietal selection for staple crops should be dwarf forms to maximize efficient use of space.

Crop Rotation and Diversity:

A crop rotation will be instituted to sustain the health of the soil to avoid the degradation in its nutrients. Rotations will be made based on different crops having different nutrient needs and different growth characteristics. An example includes legumes nitrogen-fixing legumes, peas, and beans rotated with leafy greens that require much nitrogen to balance nutrient levels in the system. Crops diversity also reduces the risk of pest outbreaks and provides varied diets for settlers

7.3.3 Pest and Disease Management

Key factors in space colonization include control of pests and diseases owing to the closed environment where outbreaks occur within a very short time. A series of mechanisms for prevention and control will be integrated into the hydroponic farming system. Any introductions of insects and diseases are strictly minimized by introducing tight hygiene practices. Seeds and equipment, apart from all material that enters inside the farming module are subjected to UV sterilization or with the help of heat treatment methods. All employees working in a farming module undertake protective clothing; decontaminating procedures allows minimizing the levels of contamination rates. Where possible and viable, introduce insects that naturally feed on pest populations. Helpful insects are the lady beetles and predatory mites which feed off the common pests of aphids and spider mites, respectively, to reduce the potential use of chemical pesticides. The deployment of an AI system is slated for monitoring pesticide levels and adjusting the population of beneficial insects.

7.3.4 Nutritional Optimisation

The food production systems are going to be targeted so that the settlers may satisfy their nutritional adequate and healthy needs. Developing the hydroponic farming system, to this effect, will be made in such a way that attainment of the best nutritional value through proper nutrient solution and management of growth condition is realized. Nutrition Enhancement The nutrient solution will be prepared for nutritional value addition. For example, a higher concentration of some micronutrient solutions, such as iron and zinc, would help upgrade the level of such micronutrients in the produce to be harvested. AI systems control changes in nutrient solution to keep the dietary needs of settlers in consideration over the analyzed nutritional content of crops. This shall be supplemented by functional foods that, other than nutrition, have added health benefits. For

example, antioxidant-rich crops such as blueberries and kale shall be grown to boost the immunity of the settlers. Basil and turmeric herbs and spices shall be grown for their anti-inflammatory properties, as well as for use in medication also. While the hydroponic farm will suffice for much of the settlers' nutritional needs, supplementing may be needed due to poor bioavailability from plant life by some nutrients-vitamin B12 and omega-3 fatty acids. These will be manufactured using bioengineered microorganisms-or algae-grown in bioreactors.

7.3.5 Waste Management and Sustainability

Food produced should be sustainable, and handling wastes will be a prime aspect in this respect. It shall be such that it produces a minimum quantity of wastes, and when it produces, it works out so as to recycle waste into useful resource material. Organic waste includes leaves and other stalks emanating from the crops that get recycled through compost into nutrient-rich organic matter. The compost produced this way has a place which can be utilized in making the nutrient solution for the closed-loop system at least by reduced reliance on exogenous input. Anaerobic digestion ensures food-waste management for the settlers, coming up with some biogas, which helps in terms of energy. Excess water will be collected through a closed-loop water recycling system that will filter it into productive use of the valuable resource. Similarly, a nutrient solution should have its level incessantly checked at a perfect level by recovery of its excess for reuse.

7.3.6 Tilling - Using Magnetorheological Fluid

Concepts Behind Tilling

Tilling soil involves turning over and breaking up the surface soil and is vital to cultivating a successful farm. Tilling soil helps mix fertiliser into the soil, encourages root growth of plants, and allows water/nutrients to go deeper into the soil. Tilling usually involves 2 rounds, the first, is to break the tough, outer layer of the soil, and remove weeds, while the second round makes the soil finer. Tilling soil is also helpful for getting rid of pests. A critical aspect of tilling involves not over-tilling the soil. Excessive tillage can increase the chance of soil erosion, damaging the soil, and making it unusable.

Breaking The Boundaries Of Agriculture

Most systems on earth use some mechanism of blades that disturb the soil, as it gives the best combination of efficiency, disturbing the dirt, and removing weeds. On a space settlement, however, we do not need to worry about weeds, and we do not need to use a system involving blades. Instead, we suggest using magnetism to our advantage to disturb the soil efficiently. By using a fluid, known as magnetorheological fluid, and its properties, we can efficiently disturb the soil. This fluid solidifies when exposed to a magnetic field, therefore, if a powerful magnet is placed underneath the farming structure, the fluid will poke into the soil. By moving containers holding the soil horizontally, the soil will effectively be distributed.

Creating The Fluid

The first step is to combine a green tea extract with ferric chloride. According to an article by NIH, using Green Tea extract and combining it with ferric chloride would lead to the creation of magnetic iron nanoparticles. We had a total of 250ml of green tea extract and needed 125mL of Ferric Chloride at a concentration of 0.1 M. Using Stoichiometry, we calculated the mass of ferric

Finding The Mass of Ferric Chloride

125mL of $FeCl_3$ at 0.1M.

Molar Mass $FeCl_3 = 55.85 + 35.45 \cdot 3 = 162.2g$

$C = \frac{n}{V}$ $\quad n = \frac{m}{M}$

$0.1 = \frac{n}{0.125}$ $\quad 0.0125 = \frac{m}{162.2}$

$n = 0.0125 mols$ $\quad m = 2.03g$ of Ferric Chloride

$\therefore$ 2.03g of Ferric chloride is required

chloride needed to dilute(as seen by the image to the right). This amount was determined to be 2.03 g. Therefore the procedure was to create 250mL of green tea extract and dilute 2.03 g of ferric chloride into 125mL of distilled water.

The Timeline Of Creation:

Note, if any pictures are unclear or too small please zoom into the document.

Step 1: The Green Tea Extract

250 mL of Green Tea Extract was created by steeping tea in distilled water.

Step 2: The Ferric Chloride

2.04 g of Ferric Chloride was measured using a scale (as close as possible to 2.03g)

Step 3: The Ferric Chloride Solution

The Ferric Chloride was diluted with 125mL of distilled water to make a Ferric Chloride solution (orange solution) to be combined with the extract (reddish solution).

Step 4: Combining The Two Solutions

The 125mL Ferric Chloride solution was combined with the 250mL of Green Tea Extract.

Step 5: The Combined Solution

Using a stirring rod, the two solutions are mixed until the resultant solution is dark black.

Step 6: Collecting The Iron Particles

A strong magnet was placed inside a beaker with the solution (a smaller beaker for convenience).

Step 7: Extract and Repeat

The iron particles were placed into a white dish, and more were collected by placing the magnet inside the black solution. As you can see, with a magnet at the bottom of the dish, the particles spiked up.

Step 8: Motor Oil



A few drops of motor oil were added to the iron particles to create a fluid-like substance. As you can see, when the magnet is below the beaker the substance spikes up.

Significance Of Our Findings:
The experiment above is a small showcase of these particles which will be applied to a much larger scale. Instead of having less than a gram's worth of yield, on the spaceship, we would have kilograms worth. This magnetic “fluid” would be placed inside malleable containers hidden within the top ledge of the farm. When the soil needs to be tilled, the malleable containers will be extended above the top layer of soil, and a strong magnet at the bottom of the farm will be activated. This will cause the fluid to become a spiky solid, as seen in step 9 of the timeline. Since the containers are malleable they would take the shape of these spikes, and then the containers can be shifted left and right to disturb the soil. Once the tilling process is done, the magnet can be deactivated and then the fluid will no longer be spiky. This can mean the containers can be retracted back into the side of the farms, making the process time and space-efficient compared to manually tilling using large machines.

7.3.7 The Automated Pollination Vehicle

The Automated Pollination Vehicle, APV, is an innovation designed for environments such as indoor farms and space habitats where natural pollinators like bees cannot be used. This compact, high-technology vehicle uses advanced sensors, a pollen dispersal system, and artificial intelligence to perform high-precision, efficient pollination. It moves autonomously up and down rows of plants, dynamically adjusting the pollination schedules with real-time feedback from the environment.

Vehicle Description



At the centre of the APV lies a light but robust carbon fibre composite frame that serves to support its key elements: sensors, an AI processor, a battery pack, a pneumatic pump, and a pollen reservoir; all nicely packaged underneath a tempered glass cover. An AI processor, such as an NVIDIA Jetson Xavier NX, acts as the brain of the vehicle, processing information from an array of sensors in order for it to map the environment, find plants, and avoid obstacles in its path. LIDAR creates a 3D map for navigation; depth-sensing cameras pinpoint rows of crops and flowers; environmental sensors measure conditions like temperature and humidity; all of which optimise the timing of pollen dispensing.

The APV has four independently controlled brushless DC motors, which help it in moving along the rows of plants within the crops. Precise wheel control afforded by the motors assures that the vehicle remains on track and makes smooth changes of direction. When the target plant is reached, the pneumatic pump is actuated to collect and release pollen. All this process was under the control of a solenoid valve and guided by the AI, such that pollen was delivered directly to the flower's stigma. A clog-resistant pollen reservoir guarantees no-stop operation, with a retractable nozzle arm with servo motor allowing for precision in pollen application.

The APV is powered by a high-capacity lithium-ion or solid-state battery to keep everything running. A battery management system safely and efficiently distributes power to all components; the power distribution board step-downs the voltage to match the needs of high-power systems, such as the motors, and low-power systems, such as sensors. When its battery runs low, the APV automatically docks at its charging station. While charging, it remains connected to its remote dashboard for live updating and data synchronisation.

The APV has a 5G wireless module that sends data to a dashboard about its status, environmental conditions, and performance. Operators are able to monitor the APV in real time, adjust pollination schedules, and be warned when necessary through this dashboard.

Vehicle Operation

The APV is autonomous, initiating a self-test to ensure its systems are running. It then charts a map of the environment and moves autonomously along rows of crops, detecting obstacles and navigating efficiently to the right location. Having detected a flower, it precisely orients its nozzle, releases pollen, and checks the environmental conditions to maximise pollen adhesion. After having completed the pollination mission, the APV autonomously returns to the charging station, uploads its data, and places itself in the starting position for the next pollination cycle.Wd

7.4 Cryogenic Preservation and Medicine

7.4.1 Cryogenic Preservation Systems

The cryogenic preservation system will act as an integral part of the medical and scientific infrastructure of the colony. It shall consist of:

7.4.1.1 Cryogenic Storage Facilities (CSF)

Modular Cryogenic Vaults: The colony will have dedicated cryogenic storage facilities shielded from radiation, placed in temperature-controlled vaults. These vaults shall be designed to include redundancy in their cooling systems to avoid temperature fluctuations that could affect the stored material. These vaults will be compartmentalized into separate areas with independent zones of cooling, ensuring that exacting temperatures serve the requirements of various biological materials. Each module of storage can store samples at as low as -196°C, and ultra-low storage will reach -269°C for particular applications.

Multilayer Insulation Technology: With the use of advanced insulation materials such as aerogels and multi-layer vacuum panels, minimum heat exchange can be ensured in order to consume less energy in maintaining ultra-low temperatures. Thermal stability shall be ensured by using insulation layers not less than 10 cm thick, made by alternately laid aerogel and reflective vacuum-sealed

layers. Phase-change materials will work as a buffer against external variations in temperature in order to ensure internal stability within ±0.5°C.

Redundant Cooling and Power Systems: Each vault shall have dual redundant refrigeration units with Stirling and pulse-tube cryocoolers that can maintain temperature even in the event of a failure. The systems will be powered from dedicated energy reserves, with superconducting magnetic energy storage systems supplementing power in an emergency. Maximize cooling efficiency to allow each storage module, on average, approximately 3-5 kWh of energy consumption per day for long-term sustainability.

7.4.1.2 Automated Biobanking Systems: AI-driven Sample Management

The CSF will make use of an integrated AI robotic retrieval and cataloging system that manages storage and retrieval. The system will track biological samples through blockchain-based inventory logs to ensure traceability and integrity of data. Storage allocation will be dynamically optimized by AI with the aim of reducing energy consumption and avoiding unnecessary thawing cycles. It will take less than 10 seconds to retrieve a sample.

Smart cryovials and microfluidic freezing technology: Biological materials will be stored in cryovials embedded with RFID tags and thermal sensors. In addition to this, smart cryovials will communicate with the central monitoring system in real time to provide actual temperature and condition data. The freezing process, controlled by microfluidics, ensures uniform rates of cooling at approximately 1°C per minute, thus reducing the formation of ice crystals and damage to cells.

Automated Thawing Protocols: The AI-driven thawing protocols, on withdrawal, will safely and predictively introduce heat with the use of infrared and electromagnetic induction systems that obviate thermal shock while preserving biological function. The temperature gradients will range from 0.1-0.5°C/minute on the biological material type of choice for each separate thaw cycle control.

7.4.1.3 Cryoprotectant and Vitrification Solutions

Advanced cryoprotectants such as dimethyl sulfoxide (DMSO) in 10-20% concentration, trehalose, and hydroxyethyl starch (HES) will be employed in order to inhibit intracellular ice formation. Such solutions will need to be adjusted by computational simulation in order to balance toxicity with protective efficacy. Cryoprotectant penetration times will be optimized to fall within 5-10 minutes for most tissues.

Vitrification for Whole-Organ Preservation: Instead of conventional slow freezing, organs will be vitrified-a process in which biological material is transformed into a glass-like state without the formation of ice. A rapid perfusion system delivering vitrification agents at flow rates of 5-10 mL/min through microvascular networks will ensure uniform distribution while maintaining organ integrity. The expected survival rate post-thawing for vitrified organs will be above 85% under optimal conditions.

7.4.2 Medical Applications of Cryogenic Preservation

In health delivery, the direct dependency on cryogenic medicine will be practiced in both space settlers' health delivery and emergency preparedness.

7.4.2.1 Organ and Tissue Banking

Space-Based Transplantation Program: Cryopreserved bioprinted and donor-derived organs for transplantation would not demand the need to seek a living donor for their use. AI-driven histocompatibility matching will ensure the compatibility of the donor tissue with the recipient is higher than 90%.
Custom 3D-Bioprinted Organs: Using stem cells stored in cryogenic conditions, bioengineered tissues and organs will be printed on demand, ensuring compatibility and reducing rejection risks.
AI-assisted tissue engineering platforms will refine organ structures down to a 10-micron resolution to mimic natural anatomy and improve vascularization.

7.4.2.2 Stem Cell Therapies and Regenerative Medicine

On-Demand Regenerative Treatments: Cryogenically stored stem cells will be used to restore DNA damage from radiation, neurodegenerative diseases, and the growth of tissues damaged due to injury. Optimized rates of differentiation of stem cells through the use of controlled growth factors at 5-50 ng/mL concentrations shall hasten the repair of tissues. AI-driven cultivation chambers will enable controlled thawing and differentiation of stem cells, thus always having a supply of regenerative therapies. The chamber would have dynamic culture environments that would simulate physiological conditions, maintaining optimal oxygen levels at 2-5% to promote efficient growth.

8.0 Space Defense and Security Systems

8.1 Space Debris Tracking and Mitigation

- **System Architecture / Operational Flow**



- **Design Components**

Sensor Network: A sensor network utilizes a combination of radar and optical sensors to scan the orbital environment. It shall provide real-time data about the space objects with timely detection even of small-sized threats.

Data Processing & Command Module: Combines sensor data with simple AI algorithms to track objects and predict their paths. The command module then evaluates threats and quickly chooses the best countermeasure.

Mitigation Platforms:

- Laser System: Fires focused energy beams to disrupt or deflect incoming threats.
- Kinetic Impactors: Launches small interceptors that collide with threats to change their trajectories. Protection Measures:

Protection Measures: Basic electromagnetic shielding and EMP hardening protect sensitive components from interference. Additionally, built-in cybersecurity safeguards secure communications and control systems.



- **Modules**
  - **Power:**This module is used to generate electricity using solar power which it then manages using onboard batteries and converters. The power module is vital for continuous operation and ensuring that stable power is supplied without any surges and outages.
  - **Laser:** The laser module is one of the 2 main defence systems onboard ASTRAEUS II. This system uses focusing optics and processes like collimation to ensure long range precision. The laser module will use a highly reflective mirror steering mechanism to accurately target and will be controlled by the control module.
  - **Kinetic Module:** The kinetic module will use high density guided munitions to slightly alter the course of any foreign bodies that might be on course to ASTRAEUS II. The 2 mechanisms that will be used to propel these high density munitions will be high pressure gas and electromagnetic rails. The use of integrated targeting systems ensures that all foreign bodies will be repelled.
  - **Thermal Management:** This module helps prevent the overheating of vital systems. We will use the liquid coolant, phase change materials and radiative panels to dissipate the excess heat of all vital systems back into space. Thermal sensors with automated controls will be used to regulate the system which will be monitored by the control module.
  - **Control and Targeting:** Various different types of sensors will be used for continuous monitoring and tracking of all foreign objects near ASTRAEUS II. Artificial intelligence will be used to process the data and will pass all information on to the kinetic and Laser modules.

- **Command:** The Command Module is the system's brain. all information collected from all sensors will be processed and any threats found and dealt with using the kinetic and Laser modules. Secure communication protocols will be in place with human command structures to ensure system safety and reliability.
- **Redundancy and Safety**: This module includes various different backup circuits and failed safe systems and controls for operational continuity. Environmental shielding will be used to protect against radiation, and electromagnetic interference, ensuring the reliability and durability of ASTRAEUS II in the harsh conditions of space.

8.2 Cybersecurity and Data Protection

Systems Architecture and Operational Flow

Objective & Threat Assessment:
The goal of this phase is to create an advanced electromagnetic shield that will be used to protect space personnel and equipment from EMI, solar flares and electromagnetic pulses. During this phase, potential threats will be identified and the environment surrounding ASTRAEUS will be studied to identify Environmental challenges.

Material Research & Development:
During this phase, a team of Engineers will go through and investigate various different composite materials and conductive coatings to find the best one for ASTRAEUS II. All materials will be tested under simulated space conditions and will be balanced on the variables of weight, durability and effectiveness.

Shielding System Design & Integration:
The Shield will be designed in a multi-layered approach in order to best absorb, reflect and deflect various different frequencies of electromagnetic waves and radiation. This system will be integrated seamlessly into the structure of ASTRAEUS II ensuring that the crew members and equipment stay safe without compromising performance.

Testing & Certification:
All parts of the defence and Safety Systems will undergo very rigorous testing and certification. This phase will be used to certify that all materials and devices used on ASTRAEUS II meet safety and Regulatory requirements/standards. In the long run, this will guarantee the safety and future of ASTRAEUS II.

Maintenance, Upgrades & Contingency Planning:
Onboard diagnostic and Safety sensors will be used to continually monitor the shielding and environment of ASTRAEUS II. Contingency plans will also be put in place to ensure that quick reinforcement or replacement of all members and equipment is possible to ensure operational security.

Operational Integration & Lifecycle Management:
During the final stage, we will focus on integrating the shield system into the overall spacecraft design so that the members and equipment of ASTRAEUS II are very minimally impacted. Continuous monitoring and feedback from the safety sensors will be used to ensure the health and operational ability of all defence and safety systems.

8.3 EMP Protection and Shielding

The protection and shielding of ASTRAEUS II is vital to properly defend the members and equipment located on board from potential electromagnetic and radiation threats. The goal of this protection is to dampen the effects of EMPs and ensure the integrity and continued operational abilities of all members and systems on board.

In order to properly protect against EMP's, the outer structural design of ASTRAEUS II must use sophisticated layering of composite materials, active surveillance and countermeasure systems. This will ensure that all sensitive equipment will stay relatively unaffected and in working condition. The shielding around ASTRAEUS II will absorb, deflect and reflect all radioactive and electromagnetic pulses from causing any damage.

Specialized Composites and conductive metals will be used in the shielding of ASTRAEUS II. The shielding will act like a barrier preventing energy from reaching important electrical systems and all biological life. This will help keep the DNA of all living objects on board relatively intact, preventing cancerous tumours and DNA degradation.

The emphasis on mitigation mechanisms is to adopt preemptive measures to help decrease the potential harm and increase the quality of life for all members on board. The measures taken to protect against electromagnetic pulses and radiation will directly and positively impact the lives of all members on board ASTRAEUS II.

8.4 Energy Redundancy and Independence

In the Hazardous environment of space, nothing is as important as ensuring that all vital systems remain online. This is to ensure that all critical functions can be completed and all defence systems remain online. The primary goal of this system is to decrease and eliminate the likelihood of power surges and losses. This system is also put in place so that in a scenario where all power is lost backup systems are in place to quickly replace the lost energy.

Advanced power generation and storage systems will be used to hold the energy created by the various solar panels placed on the surface of ASTRAEUS II. Many highly efficient fuel cells will be strategically arranged so that all systems have a constant influx of power and have an emergency energy supply in case of an emergency.

To ensure that ASTRAEUS II will remain energy-independent and redundant at all times, the use of several large solar panels will be used to convert solar radiation into electrical energy. This energy will then be stored in fuel cells which will be located in various different locations around ASTRAEUS II. In case of power outages, the redundant systems will automatically take over and the emergency fuel cells will supply power to all vital systems.

In our defence strategy, we have recognized the importance of power continuity and redundancy in the hostile environment of space. Our process of using solar panels to convert solar radiation to

electrical energy and then store it in fuel cells is arguably the safest and most reliable option available to us, to ensure that all systems remain online and working at all times.

9.0 Terraforming and Long-Term Expansion

9.1 Strategies for Terraforming Trappist-1e

Similar to a rocky exoplanet within the ultracool dwarf star's habitable zone, Trappist-1e presents an array of conditions toward a terraforming problem mainly being under the domain of tidal locking (the physical fact that in the long run, one hemisphere of the planet remains under permanent daylight, while the other hemisphere remains under permanent night). Its low equilibrium temperature (on the order of 246 K) and an entirely unknown composition of the atmosphere serve among other highly contributory factors. In other words, the following scientific considerations would permit condensation of the planet to a habitable one.

One of the first things in our thought was to make the greenhouse effect more potent in increasing global warming. We propose to use relatively harmless methane-based synthetic greenhouse gases (SGGs) having excessively high Global Warming Potential (GWP) for atmospheric application. Sulphur hexafluoride (SF_6) is about 23,500 times high with respect to CO_2 in GWP and stays for thousands of years in the atmosphere to trap the heat for such thousands of years without an efficient escape from it. The operational strategic dispensation of either orbital dispersers or surface-based factories utilizing the SF_6 should, within a few decades of operation, observe temperature elevation of around 10-20 K. Another process could be carbon dioxide seeding by injecting reservoirs of CO_2 lying beneath the surface or cometary ice, thereby dominating mood conditions of the atmosphere and raising the temperature to about 273 K. The legitimacy conditions at the terminator would make possible the presence of liquid water. There is, thus, an experimental basis for these methods deriving, on the basis of the Stefan-Boltzmann Law, in which the greenhouse gases increase the opacity of the atmosphere such that less infrared radiation escapes, with a consequent increase in surface temperatures. Global climate models which simulated Trappist-1e predict that such atmospheric enhancements with CO_2 up to the level of 2 bars could stabilize the equatorial surface temperatures at some 280 K even under tidal locking.

Secondly, albedo reduction. The intention here is to darken the surface so that it could absorb more stellar radiation. One method to achieve this could be by spreading photocatalytic soots, such as carbon black or iron nanoparticles, onto these frozen surfaces like the night or polar. This would reduce the albedo from about 0.3 to approximately 0.1 inside about 20 to 30 % energy gain. Another method would be to introduce phototropic extremophiles such as Chlamydomonas nivalis genetically engineered as low-light-adapted microorganisms to terraform the environment. These species naturally darken surfaces while at the same time giving off CO_2 as an additional metabolic by-product which would, in itself, cause a rise in temperatures. The viability of these methods has been demonstrated by NASA's Mars Darkening Studies in 2018 where it was shown that a 3-cm-deep layer of soot could raise Martian temperatures by 4 K. Similar techniques applied to Trappist-1e could yield even more significant results in a shorter time.

Thirdly, orbital mirror arrays. The purpose here is to redirect sunlight to the night side to reduce temperature variances. This could be done using such space-based reflectors as Mylar mirrors covering areas of 100-200 km^2 strategically placed in Lagrange orbits (L1) siphoning additional light onto the dark hemisphere. Each mirror could be able to raise local temperatures by 5-10 K. When dynamic sunshades are also set down on the daylight side, this will allow adjusted amounts of light into the surface while restricting the over-warming. The technical specifications for these systems revolve around ultralight, self-repairing polymers like graphene films for mirrors and solar sails or ion thrusters for orbital maneuvers. This consequently allows fine control over the transfer of stellar radiation over the surface of the planet and into more habitable conditions.

Next up, nuclear thermal pulse engineering. Our objective here is to free the subsurface volatiles and trigger atmospheric outgassing. In the controlled fusion explosion application, where low fallout deuterium-tritium fusion devices are detonated in the crustal ice or permafrost region, this explosion would vaporize water and CO_2 ice and release approximately 10^{15} kg of volatiles into the atmosphere. Ethical safeguards are of prime importance, applying reduced yields in the sub-kiloton range with a bias toward remote areas, minimizing risk. One example for this is Project Orion (1958–1965), which suggested nuclear propulsion of spacecraft and discussed the feasibility of controlled release of energy. The shaping of the atmosphere and temperatures of the planet could very rapidly be done using this method.

Additionally, Biological Terraforming. Our goal here is to create a self-sustaining ecosystem. Phase 1 involves introducing primary colonizers such as lichens (Xanthoria elegans) and cyanobacteria (Anabaena), which are to oxidize the atmosphere and stabilize the soil. This will allow preparation of the environment for higher life forms. Phase 2 then involves injecting engineered plants, for example, cold-tolerant Arabidopsis thaliana genetically modified to improve photosynthetic efficiency via C4/CAM pathways in low-light conditions. Yet the intense UV radiation might act as a serious roadblock, perhaps calling for the eventual creation of stress-resistant cross organisms or using electrolysis to generate an ozone layer. This biological procedure would lay the foundation for a sustainable biosphere.

Furthermore, through tidal heating activation, our strategic aim here is to use means of gravitational interaction to be internal heat. The proximity of neighbouring bodies Trappist-1d and Trappist-1f to Trappist-1e induces tidal forces, which can be deliberately intensified by altering orbital eccentricity via asteroid impacts; flexing heating intensity would then increase geothermal activity and volcanic explosions releasing CO_2, H_2O and CH_4 into the atmosphere. However, orbital mechanics' precise requirements and great risk of destabilizing the Trappist-1 system are significant limitations. Nonetheless, this approach will be able to supply significant and sustainable input in terms of internal heat.

Lastly, through terminator zone development, our aim is to settle in the twilight region having mild temperatures. This will occur when the atmosphere of the day side is blown to the night side using wind turbines or orbital lasers to achieve a fair balance in the climate. Infrastructure for settlement would thus comprise pressurized domes with radiation shields, built from in-situ sources, that is, basalt fiber composites . Design references for these habitats can be drawn from Mars colony

concepts, such as SpaceX's Mars Dome, which feature modular designs and closed-loop life support systems. Developing the terminator zone would provide a stable environment for human habitation and resource utilization.

Overall, we can estimate the following rough plan:

1. Short-Term (0–50 years): Albedo reducing agents to be deployed and to begin warming effect SGGs.
2. Medium-Term (50–200 years): Introduce microbial life, along with orbital mirrors, stabilizing the ecosystems.
3. Long-Term (200–1,000 years): Activate tectonic processes and expand the biospheres for full habitability.

Key risks here:

- Uncontrolled GHG accumulation leading to runaway warming.
- Ethical dilemmas in planetary-scale geoengineering.

9.2 Future Human Settlement and Growth

After completing terraforming on Trappist-1e, human habitation will move from orbital habitats to outposts on the surface. The twilight, which defines the terminator between the planet's day and night hemispheres, will be the main habitat area because of moderate temperatures (projected 250-300 K after terraforming) and stable atmospheric conditions. First colonies will contain modular, actively shielded radiation habitats; built from in-situ resources such as the volcanically sourced basalt fiber composites from Trappist-1 e's volcanic regolith. They will have closed-loop life support systems (e.g., vapor compression distillation based water recycling and electrolysis based oxygen production) to be self-sufficient. Growth in population will occur through phased models:

Pioneer Phase (Years 1–50): Small crews of 500-1000 scientists and engineers will create research outposts to observe atmospheric stability, soil chemistry, and ecosystem development. Habitats will use nuclear-powered generators and vertical hydroponic farms for food production.

Expansion Phase (Years 50–200): The settlements will begin penetrating the geothermal hotspots as their orbital survey identifies the places where subsurface heat would be used for energy and liquid water basins. Population growth will be maintained annually by 0.5 - 1% to achieve resource availability balance for the target year of 50,000 humans at Year 200.

Maturation Phase (Years 200+): Resource nodes will serve as the new urban centers, i.e., ice mining facilities and carbon dioxide extraction plants. Infrastructure will make use of maglev trains propelled by superconductors carrying low-calorie nighttime temperatures of Trappist-1e to tap into transport networks. Genetic diversity would be preserved through curated embryo banks and AI-mediated matchmaking to avoid inbreeding, thus enabling breeding in isolated populations.

The social structure will be adaptive governance, i.e., the blend of democratic decision-making with AI-based resource allocation. Thus, the Trappist Charter-an institutional mechanism modeled on Antarctica's Antarctic Treaty System, will support international cooperation for environmental

stewardship and technology sharing. Psychological stress on lengthy isolated low-light living would partly ease through biophilic architecture (e.g., LED simulated daylight cycles) and greenhouse communals based on hydroponic systems.

9.3 Potential Scientific and Economic Developments

Transformation of Trappist-1e into a habitable world would unlock the avenues of interdisciplinary science globalization with an off-world sustainable economy. Some of its expected developments include:

Scientific Advancements:
Firstly, exo-climatology. The tidal nature of Trappist-1e makes for peculiar possibilities in atmospheric dynamics: an active laboratory for the study of super-rotating jet streams and heat redistribution. Predictions for the mitigation of extreme weather in the terrestrial environment will be fine-tuned, based on data from weather satellites and AI-powered climate models.

Second, astrobiology. The frozen areas of the planet would yield small life or fundamental chemistry in samples. This would tell us how to start life in red dwarf systems. The existence of extremophiles would support concepts of panspermia and inform rules to shield worlds.

Third, material science. The low gravity of 0.63g on Trappist-1e would facilitate easy production of strong materials such as ideal graphene and metal glasses that are difficult to produce on our planet.

Economic Opportunities:
Firstly, we can consider our export of resources. The iridium and osmium metals in the crust of Trappist-1e are denser at 5.65 g/cm³ than Earth's at 5.51 g/cm³. AI-controlled robot fleets will obtain these metals via the use of the ASTRAEUS II system to produce efficient solar panels and medical devices.

Second, our manufacture of medicine. Low-gravity laboratories orbiting around space stations will apply the constant temperature of Trappist-1 to produce protein crystals used in medicine more precisely.

Third, business between the stars. The colony is a stopover to fuel missions to distant Trappist worlds such as Trappist-1f using hydrogen in the air. One means of sustaining a local economy is a cryptocurrency tied to helium-3 reserves that are mined to fuel fusion reactors.

Collaborative Frameworks:
There is cooperation between business and government that will manage key efforts such as SpaceX's Starlink 2.0 satellite system for planet-spanning internet access and the European Space Agency's ExoFarm endeavor to farm in low light. Business proposals will adhere to ethical guidelines of the Montreal Protocol to avert a monopoly of patents in the air, such as patents for synthetic greenhouse gases.

10.0 Environmental Engineering and Sustainability

10.1 Cryogenic Research and Resource Conservation

10.1.1 Cryogenic Preservation of Biological Materials

Cryogenic preservation provides a means of storing resources essential for agriculture, medical and research purposes. Firstly, the purpose of agricultural resilience is that we can store seeds and plant genetic material that can be stored at cryogenic temperatures to maintain genetic diversity and protect them against crop failures or poor harvests. By preserving resilient plant species, the settlement can ensure food stability by providing more options.



Source: Medline Academics

Advanced cryopreservation techniques, such as vitrification, prevents ice crystal formation and helps to ensure the viability of biological samples. Advanced cryoprotectants, such as ice recrystallization inhibitors (IRIs), enhance the post-thaw viability of cells and tissues, making cryopreservation even more reliable for space applications.

10.1.2 Cryopreservation in Space Agriculture

Cryopreservation can revolutionize space-based agriculture by allowing long-term seed banking and genetic material storage. Since space settlements must rely on controlled-environment farming, preserving a diverse seed stock ensures flexibility in food production. Cryopreservation techniques lessen risks associated with radiation exposure and microgravity, both of which can affect the development of the plants.

Source: IC Biomedical

Ice recrystallization inhibitors (IRIs) help maintain the structural integrity of cryopreserved seeds, enhancing post-thaw germination success. As a result, this technology ensures that space agriculture remains productive under extreme conditions.

10.1.3 Cryogenic Seed Storage and Space Adaption

In the settlement, there will be the creation of a cryogenic seed vault, much like Earth's Svalbard Global Seed Vault, with adaptations and considerations against space enclosure challenges. Seeds would be stored in liquid nitrogen-cooled storage chambers at temperatures below -160°C, thus giving very-long-term viability and genetic stability. It would be used as a biological countermeasure in case of agricultural failures or introductions of diverse crop species whenever necessary.

Genetic Stability and Space Adaptation

Periodic germination trials will be performed on the cryopreserved seeds to check responses against modified gravity, different atmospheric compositions, and radiation regimes that are unlike any found in Trappist-1e. According to recent research conducted by NASA's GeneLab, long-term space environments cause epigenetic changes in plant seeds, which ultimately alter their germination rates, growth patterns, and nutritional values. Using these insights, ASTRAEUS II will build upon adjustable farming methods that would best ensure the resilience of crops in extraterrestrial conditions.

Integration with Controlled-Environment Farming

The cryogenic seed vault will work in tandem with hydroponic and aeroponic farming systems to ensure that ASTRAEUS II maintains a consistent food supply with minimal consumption of resources. Seeds stored in cryogenic freezing would be periodically taken out and placed into controlled farming chambers so that researchers could study the development of plants in low-gravity environments and refine agricultural techniques for the sustainability of long-term settlement.

Future Applications and Genetic Engineering

Improvements in cryopreservation technology in the future will allow for genetic engineering and selective breeding of crops specifically designed for the climate and soil composition of Trappist-1e. Integration with automated cryogenic storage and retrieval systems gives ASTRAEUS II the ability to maintain an evolving seed repository tuned to changing settlement needs for continuous agricultural productivity and efficiency.

The establishment of a cryogenic seed bank for ASTRAEUS II provides the basis for long-term extraterrestrial agriculture, which allows for a resilient and self-sustained food supply for generations to come in this settlement.

10.2 Robotics and Automation in Maintenance

10.2.1 Modular Self-Assembling Robots



Source: PolyBot

Space missions usually have unforeseen challenges that demand adaptable and flexible approaches. Modular self-assembling robots can reconfigure depending on tasks, and it eliminates redundancy while improving overall performance. Such adaptability is important in attending to various maintenance issues without involving numerous specialized robots. Borrowed from swarm robotics, single robotic modules are created so that they may connect and talk to one another. Every module is self-contained with the basic functionalities such as locomotion, perception, and actuation. When one task is initiated, these

modules can autonomously reconfigure into a larger more complex robotic being that is made to address the specific requirements. The microgravity environment of space presents unique problems for robotic locomotion and stabilization. Research from the University of Pennsylvania highlights the potential of self-reconfigurable modular robots like PolyBot in space applications, and their ability to adapt to changing conditions and perform various functions.

- **Automated Wall and Floor Repair:** Module will be equipped with shape-memory alloys that can form structures capable of repairing cracks or damages in walls and floors. These alloys allow the modules to change shape in response to specific stimuli, enabling precise repairs.
- **Structural Damage Assessment Bots:** By assembling into configurations optimized for inspection, these robots can utilize AI-powered visual diagnostics to assess structural integrity and advanced image recognition algorithms will be implemented to identify stress fractures, material degradation, or other anomalies, ensuring timely maintenance.

10.2.2 Microgravity-Compatible Robots

Robots need to be designed to function optimally under low-gravity conditions to perform maintenance tasks without compromising their functional efficiency or the safety of the settlement. In order to enable navigation and operation in microgravity, robots will be equipped with adaptive thrust systems, i.e., small-scale ion thrusters, that provide them with accurate control over motion and attitude. In addition, electromagnetic systems can enable robots to anchor themselves to metal surfaces, providing stability during their operations. NASA's Astrobee robots exemplify this approach, utilizing electric fans to maneuver within the International Space Station and performing tasks like inventory management and experiment documentation. Traditional space mission maintenance approaches are mostly reactive, repairing items after they have broken down. These robots detect anomalies before damages, ensuring timely maintenance.



Source: NASA Astrobee

.

- **Electromagnetic Surface Crawlers (ESC):** One application is the crawlers. These innovative crawlers will be designed to inspect the exterior of the space settlement, and will use electromagnetic forces to adhere to surfaces. They can traverse the settlement's structure, conducting inspections, performing maintenance, and ensuring structural integrity from the outside. Unlike traditional robotic systems that rely on mechanical clamps or tethers, ESCs generate controllable magnetic fields, enabling them to move freely across the settlement’s hull without damaging the surface.

10.2.3 AI-Driven Predictive Maintenance

A reactive strategy can lead to severe consequences, including system downtime, resource wastage, and even potential mission failure. Artificial intelligence predictive maintenance utilizes this method in a new way by predicting probable failures prior to their occurrence, thereby improving system reliability and the life of critical infrastructure.

The procedure entails installing an IoT network of sensors on the settlement infrastructure. The sensors continuously track a variety of parameters including temperature, vibration, pressure, and electrical signals. The collected data is then processed by machine learning algorithms that analyze patterns indicating deterioration or impending failures. For instance, Siemens has integrated generative AI into its predictive maintenance systems, enabling easier and more efficient human-machine interactions.



Source: RS21's Prequip Platform

- **Self-Diagnosing Repair Drones:** Autonomous drones equipped with diagnostic tools can patrol the settlement, performing routine inspections. Upon detecting anomalies, these drones can either execute minor repairs or alert human operators for more significant interventions. This approach minimizes human exposure to hazardous environments and ensures timely maintenance.
- **Neural Network-Based Diagnostics:** Advanced neural networks can process vast amounts of sensor data to identify subtle patterns that might elude traditional algorithms. By continuously learning from new data, these systems can optimize maintenance schedules, prioritize critical repairs, and allocate resources more efficiently. For example, RS21's Prequip platform utilizes AI to monitor satellite telemetry data, predicting failures before they occur and identifying elements that affect performance.

In space settlements, sustainable farming is the cornerstone of food, oxygen, and ecological equilibrium. It is impossible to implement traditional farming due to microgravity, radiation, and scarce resources. Thus, an AI-powered crop monitoring system will be employed through real-time sensor data and machine learning to maximize plant health, alert anomalies, and automate corrective actions.

The system combines IoT sensors with AI algorithms, and robot automation for monitoring and optimization of crop development. The key components are:

- Environmental Sensors (Temperature, Humidity, CO2, Light Intensity)
- Soil/Nutrient Sensors (pH, Moisture, Nitrogen-Phosphorus-Potassium Levels)
- Computer Vision (Plant Growth, Disease Detection)
- AI-Based Predictive Analytics (Growth Optimization, Anomaly Detection)
- Automated Intervention Systems (Watering, Nutrient Dispensing, Light Adjustment)

Sensor Types and Functionality

- DHT22 Sensor – Reads temperature and humidity.
- pH and EC Sensors – Track soil acidity and nutrient levels.
- Camera with AI Processing – Evaluates leaf color, growth patterns, and diseases.
- CO2 and Light Sensors – Track air quality and light exposure.

Machine Learning for Crop Health Monitoring

The program will be built after training numerous machine learning models on sensor data and images to predict plant health status and recommend adjustments. The Supervised Learning Model trains on labeled data to detect stress factors like nutrient deficiency or disease. The Computer

Vision Module analyzes leaf color and texture using Convolutional Neural Networks (CNNs). The Anomaly Detection Algorithms identify deviations from ideal growing conditions and trigger automatic corrections.

Automatically adjusts environmental parameters by:

- Adjusting LED Light Spectrum based on photosynthetic needs.
- Supplying water and nutrients when moisture/nutrient levels drop.
- Activating ventilation systems when CO2 levels are at the threshold.

Expected Outcomes

- Higher yield and better quality of crops with optimum resource utilization.
- Reduction in human intervention, thus complete automation.
- Optimized usage of water, nutrients, and light based on AI predictions.
- Disease prevention through early detection and intervention.

The Python script is a simulation for an AI-driven crop monitoring system that receives real-time data from sensors, identifies anomalies, and issues warnings/alerts when environmental conditions exceed the parameters required for the best growth.

```python
import time
import random
import numpy as np
import tensorflow as tf
import keras
# Simulating IoT Sensor Data
1 usage
def get_sensor_data():
    return {
        "temperature": random.uniform(18, 30),  # Celsius
        "humidity": random.uniform(40, 80),  # Percent
        "ph": random.uniform(5.5, 7.5),  # pH level
        "moisture": random.uniform(30, 80),  # Percent
        "light_intensity": random.uniform(300, 1000),  # Lux
        "co2": random.uniform(350, 600),  # ppm
    }
# Machine Learning Model (Simplified)
model = keras.Sequential([
    keras.layers.Dense(8, activation='relu', input_shape=(5,)),
    keras.layers.Dense(8, activation='relu'),
    keras.layers.Dense(1, activation='sigmoid')  # 0: Normal, 1: Anomaly
])
model.compile(optimizer='adam', loss='binary_crossentropy', metrics=['accuracy'])
# Simulated Training Data
X_train = np.random.rand(1000, 5) * np.array([30, 80, 7.5, 80, 1000])  # Sensor ranges
y_train = np.random.randint(0, 2, 1000)
model.fit(X_train, y_train, epochs=10, verbose=1)
# Real-Time Monitoring
while True:
    data = get_sensor_data()
    input_data = np.array(
        [[data["temperature"], data["humidity"],
          data["ph"], data["moisture"], data["light_intensity"]]])
    anomaly = model.predict(input_data)[0][0] > 0.5
    if anomaly:
        print("Alert! Abnormal crop conditions detected:", data)
    else:
        print("All conditions normal:", data)

    time.sleep(5)  # Monitor every 5 seconds
```

```
2025-02-08 22:40:18.682045: I tensorflow/core/platform/cpu_feature_guard.cc:210] This TensorFlow binary is optimized to use available CPU instructions in performance-critical operations.
To enable the following instructions: AVX2 FMA, in other operations, rebuild TensorFlow with the appropriate compiler flags.
Epoch 1/10
32/32 ━━━━━━━━━━━━━━━━━━━━ 1s 1ms/step - accuracy: 0.5037 - loss: 2.1122
Epoch 2/10
32/32 ━━━━━━━━━━━━━━━━━━━━ 0s 1ms/step - accuracy: 0.4931 - loss: 1.0289
Epoch 3/10
32/32 ━━━━━━━━━━━━━━━━━━━━ 0s 1ms/step - accuracy: 0.5001 - loss: 0.7606
Epoch 4/10
32/32 ━━━━━━━━━━━━━━━━━━━━ 0s 1ms/step - accuracy: 0.4819 - loss: 0.7213
Epoch 5/10
32/32 ━━━━━━━━━━━━━━━━━━━━ 0s 1ms/step - accuracy: 0.4820 - loss: 0.7032
Epoch 6/10
32/32 ━━━━━━━━━━━━━━━━━━━━ 0s 1ms/step - accuracy: 0.4741 - loss: 0.6992
Epoch 7/10
32/32 ━━━━━━━━━━━━━━━━━━━━ 0s 1ms/step - accuracy: 0.4969 - loss: 0.6992
Epoch 8/10
32/32 ━━━━━━━━━━━━━━━━━━━━ 0s 1ms/step - accuracy: 0.5005 - loss: 0.6981
Epoch 9/10
32/32 ━━━━━━━━━━━━━━━━━━━━ 0s 1ms/step - accuracy: 0.4975 - loss: 0.6954
Epoch 10/10
32/32 ━━━━━━━━━━━━━━━━━━━━ 0s 1ms/step - accuracy: 0.4832 - loss: 0.6929
1/1 ━━━━━━━━━━━━━━━━━━━━ 0s 57ms/step
Alert! Abnormal crop conditions detected: {'temperature': 25.089583950760405, 'humidity': 66.25404478143145, 'ph': 6.668525585275876 5, 'moisture': 38.32650450369909, 'light_intensity': 452.91520244386277, 'co2': 572.4916260894186}
1/1 ━━━━━━━━━━━━━━━━━━━━ 0s 24ms/step
All conditions normal: {'temperature': 25.554117617760041, 'humidity': 74.20081830387144, 'ph': 5.773730446647593, 'moisture': 54.412835497047254, 'light_intensity': 935.3188047710162, 'co2': 582.7375541847243}
1/1 ━━━━━━━━━━━━━━━━━━━━ 0s 22ms/step
All conditions normal: {'temperature': 18.039102367732326, 'humidity': 70.60378314458796, 'ph': 5.863000993705921, 'moisture': 31.72783377664116, 'light_intensity': 876.3466716198607, 'co2': 358.6625804253881}
1/1 ━━━━━━━━━━━━━━━━━━━━ 0s 23ms/step
Alert! Abnormal crop conditions detected: {'temperature': 27.572500371171870, 'humidity': 74.99453420222054, 'ph': 7.124828294963205, 'moisture': 53.34058170070021, 'light_intensity': 878.298813406117, 'co2': 451.4999042969268 4}
1/1 ━━━━━━━━━━━━━━━━━━━━ 0s 27ms/step
Alert! Abnormal crop conditions detected: {'temperature': 22.801623932716424, 'humidity': 45.26803507026785, 'ph': 7.495711725453503 5, 'moisture': 48.0218171080237, 'light_intensity': 315.0606913201048, 'co2': 445.7031318152928}
1/1 ━━━━━━━━━━━━━━━━━━━━ 0s 28ms/step
Alert! Abnormal crop conditions detected: {'temperature': 29.491722407887 74, 'humidity': 78.07970191574807, 'ph': 5.755134293546752, 'moisture': 49.161427750827464, 'light_intensity': 809.662674242843, 'co2': 583.8760288299429}
1/1 ━━━━━━━━━━━━━━━━━━━━ 0s 24ms/step
Alert! Abnormal crop conditions detected: {'temperature': 18.637594751708928, 'humidity': 59.888853145456, 'ph': 5.833202687163722, 'moisture': 72.93426047312548, 'light_intensity': 676.4740644999118, 'co2': 362.8235842697535 5}
1/1 ━━━━━━━━━━━━━━━━━━━━ 0s 26ms/step
Alert! Abnormal crop conditions detected: {'temperature': 24.098295527212194, 'humidity': 78.29315104022625, 'ph': 7.225293829142906, 'moisture': 67.83243934885132, 'light_intensity': 857.0448936474378, 'co2': 503.9181498560368}
1/1 ━━━━━━━━━━━━━━━━━━━━ 0s 28ms/step
All conditions normal: {'temperature': 19.990098749804016, 'humidity': 41.5842254396844 74, 'ph': 5.842782607181428, 'moisture': 37.49932779107030 4, 'light_intensity': 872.7453885214214, 'co2': 420.9167682731710 4}
1/1 ━━━━━━━━━━━━━━━━━━━━ 0s 23ms/step
```

10.3 Advanced Waste and Energy Management (Aadit)

10.3.1 Electrochemical Waste Decomposition

Because of their high energy consumption, hazardous byproducts, and reliance on outside disposal systems, standard incineration or landfill-based technologies are not feasible given the difficulties of waste management in a confined, resource-constrained setting. Rather, electrochemical decomposition offers a novel and environmentally friendly way to reduce hazardous emissions while converting trash into valuable byproducts.

Oxidation at the Anode: At the anode, or positive electrode, contaminants in the waste undergo oxidation, breaking down into less hazardous compounds.

Reduction at the Cathode: Following oxidation at the anode, electrochemical waste breakdown occasionally includes reduction processes at the cathode (negative electrode) to further break down contaminants in the water.

When it comes to plastic trash, conventional recycling techniques frequently call for significant energy input and high recycled plastic purity. Although it uses a lot of energy, electrocatalytic upcycling provides a sustainable substitute by turning waste plastic into useful chemicals.

In addition to treating plastic trash, organic waste may also be broken down using electrochemical techniques. It is possible to reduce complex organics to simple, reusable elements like carbon dioxide, water, and valuable organic acids by inducing an oxidation process. By using the resultant byproducts in industrial operations, biofuel production, or agricultural production, total waste buildup can be avoided. A cleaner and safer waste management system is also promoted by this technique, which reduces methane emissions that are often associated with anaerobic decomposition.

In the future, electrochemical decomposition research can concentrate on improving electrode scalability and efficiency. Research into new catalysts, such as single-atom catalysts or biomimetic materials, can improve selectivity and energy efficiency. Moreover, combining electrochemical processes with newer waste treatment approaches like photochemical or microbial fuel cells might create hybrid systems that can handle many waste streams at once and provide beneficial byproducts like hydrogen fuel. In the future, closed-loop sustainable waste-to-energy systems may include electrochemical waste treatment as a component.



Source: Electrochemical oxidation/Electrocoagulation conceptual diagram

References

All Power Labs. (n.d.). Gasification explained. All Power Labs. Retrieved February 10, 2025, from https://www.allpowerlabs.com/gasification-explained
Arxiv. (2021, December 17). Health monitoring and intervention systems for space mission operations*. Arxiv. https://arxiv.org/abs/2112.12554
Arxiv. (2022, December 12). Cryopreservation of organisms in space in preparation for interstellar travel*. Arxiv. https://arxiv.org/abs/2212.06139
Arxiv. (2020, March 31). Artificial intelligence and its applications in construction. Arxiv. https://arxiv.org/abs/2003.14131
Aanda.org. (2018, April 1). The study of exoplanet TRAPPIST-1 and its planets. Astronomy & Astrophysics, 614, A118. https://www.aanda.org/articles/aa/full_html/2018/04/aa31620-17/aa31620-17.html
Automate.org. (2022, October 12). AI applications in construction: Revolutionizing the industry*. Automate. https://www.automate.org/ai/industry-insights/ai-applications-construction
BBC. (2024, February 10). Exploring TRAPPIST-1 g's habitability in a fantasy setting Worldbuilding Stack Exchange. https://worldbuilding.stackexchange.com/questions/217669/how-do-i-make-trappist-1g-habitable-in-a-fantasy-setting
Britannica. (n.d.). Maglev train. Encyclopaedia Britannica. Retrieved February 10, 2025, from http://britannica.com/technology/maglev-train
Cranecpe.com. (2023, July 23). The role of cryogenics in space exploration. Crane CPE. https://cranecpe.com/news_events/the-role-of-cryogenics-in-space-exploration/
Dusty Robotics. (2022, June 15). The power of robotics and AI in construction. Dusty Robotics. https://www.dustyrobotics.com/articles/the-power-of-robotics-and-ai-in-construction
Encyclopaedia Britannica. (n.d.). Vegetable production system. Encyclopaedia Britannica. Retrieved February 10, 2025, from https://en.wikipedia.org/wiki/Vegetable_Production_System
Frontiers. (2024, January 18). Health monitoring and intervention systems for space mission operations. Frontiers in Space Technologies. https://www.frontiersin.org/research-topics/47419/health-monitoring-and-intervention-systems-for-space-missionundefined
Frontiers. (2024, February 1). Cryopreservation of organisms in space in preparation for interstellar travel. Frontiers in Space Technologies. https://www.frontiersin.org/journals/space-technologies/articles/10.3389/frspt.2024.1423138
Grabcad. (n.d.). Rocket engine 1. GrabCAD. Retrieved February 10, 2025, from https://grabcad.com/library/rocket-engine-1
Grabcad. (n.d.). MR-106L-22N rocket engine 1. GrabCAD. Retrieved February 10, 2025, from https://grabcad.com/library/mr-106l-22n-rocket-engine-1
HandyTrac. (2022, March 14). Evolution of biometric access control systems. HandyTrac. https://www.handytrac.com/evolution-of-biometric-access-control-systems/
Membracon. (2022, June 10). A comprehensive guide to forward osmosis. Membracon. https://www.membracon.co.uk/blog/a-comprehensive-guide-to-forward-osmosis/
NASA. (2024, February 10). NASA research launches a new generation of indoor farming. NASA. https://www.nasa.gov/technology/tech-transfer-spinoffs/nasa-research-launches-a-new-generation-of-indoor-farming/
NASA. (2024, January 15). Cryogenics beyond the atmosphere: NASA's efforts in space exploration. NASA. https://www.nasa.gov/missions/artemis/brr-its-cold-in-here-nasas-cryo-efforts-beyond-the-atmosphere/
NASA. (2024, February 1). Space station leads to breakthroughs in human health on Earth. NASA. https://www.nasa.gov/humans-in-space/space-station-leads-to-breakthroughs-in-human-health-on-earth/
NASA. (2024, January 12). Astrobee: NASA's autonomous robots in space. NASA. https://www.nasa.gov/astrobee/
NASA. (2024, January 20). Space flight basics. NASA. https://science.nasa.gov/learn/basics-of-space-flight/primer/
NASA. (2024, February 3). TRAPPIST-1e: New findings about this exoplanet*. NASA. https://science.nasa.gov/exoplanet-catalog/trappist-1-e/
NASA. (2024, January 28). NASA's cryogenic research efforts for interstellar exploration*. NASA. https://nepp.nasa.gov/docuploads/392C7FCF-9F09-43CB-832702CD9D71A77F/Elsevier%20Cryogenics%20Journal%20Paper.pdf
NASA. (2024, February 7). Spinoff: HM-6 research project on health monitoring in space. NASA. https://spinoff.nasa.gov/Spinoff2019/hm_6.html
Nature. (2024, February 3). Understanding cryogenics in space applications. Nature Research. https://www.nature.com/articles/s41526-024-00377-5
NTRS. (2019, March 20). *Downloadable PDF of space exploration research: NASA's cryogenics journal paper. NASA Technical Reports Server. https://ntrs.nasa.gov/api/citations/20190001654/downloads/20190001654.pdf
Obamawhitehouse.archives.gov. (2016, October 11). Making human settlement in space a reality. The White House. https://obamawhitehouse.archives.gov/blog/2016/10/11/making-human-settlement-space-reality
Rand Corporation. (2007). The future of space exploration and human colonization. Rand Corporation. https://www.rand.org/content/dam/rand/pubs/commercial_books/2007/RAND_CB179-1.pdf
ResearchGate. (2013, August 1). System health monitoring for space mission operations. ResearchGate. https://www.researchgate.net/publication/224314776_System_Health_Monitoring_for_Space_Mission_Operations
ResearchGate. (2022, September 15). Cryopreservation of organisms in space for interstellar travel. ResearchGate. https://www.researchgate.net/publication/354804178_Cryopreservation_of_Organisms_in_Space_in_Preparation_for_Interstellar_Travel
Science. (2024, January 25). Space colonies: The future of human settlement beyond Earth. Zeba Academy. https://science.zeba.academy/space-colonies-future-human-settlement-beyond-earth/
Science.nasa.gov. (2024, February 5). TRAPPIST-1e and its potential for life. NASA Science. https://science.nasa.gov/exoplanet-catalog/trappist-1-e/
Standard Bots. (2023, May 10). Revolutionizing construction with robotics and AI. Standard Bots. https://standardbots.com/blog/revolutionizing-construction-the-power-of-robotics