

Codly

codly

Configures codly. Is used in a similar way as `set` rules. You can imagine the following:

```
1 // This is a representation of the actual code.
2 // The actual code behave like a set rule that uses `state`.
3 let codly(
4   enabled: true,
5   offset: 0,
6   range: none,
7   languages: (:),
8   display-name: true,
9   display-icon: true,
10  default-color: rgb("#283593"),
11  radius: 0.32em,
12  inset: 0.32em,
13  fill: none,
14  zebra-fill: luma(240),
15  stroke: 1pt + luma(240),
16  lang-inset: 0.32em,
17  lang-outset: (x: 0.32em, y: 0pt),
18  lang-radius: 0.32em,
19  lang-stroke: (lang) => lang.color + 0.5pt,
20  lang-fill: (lang) => lang.color.lighten(80%),
21  lang-formatter: codly.default-language-block,
22  number-format: (number) => [ #number ],
23  number-align: left + horizon,
24  breakable: false,
25 ) = {}
```

Each argument is explained below.

Display style

Codly displays your code in three sections:

- The line number, if `number-format` is not `none`
- The language block, with a fill and a stroke, only appears on the first line
- The code itself with optional zebra striping

The block as a whole is surrounded by a stroke.

```
|-----|
|1 | [line, zebra]                | [lang block] |
|2 | [line, non-zebra]            |               |
|3 | [line, zebra]                |               |
|4 | [line, non-zebra]            |               |
|-----|
```

Note about arguments:

Some arguments can be a function that takes no arguments and returns the value. They are called within a `context` that provides the current location. They can be used to have more dynamic control over the value, without the need for sometimes slow state updates.

Enabled (`enabled`)

Whether codly is enabled or not. If it is disabled, the code block will be displayed as a normal code block, without any additional codly-specific formatting.

This is useful if you want to disable codly for a specific block.

You can also disable codly locally using the `no-codly()` function, or disable it and enable it again using the `codly-disable()` and `codly-enable()` functions.

- **Default:** `true`
- **Type:** `bool`
- **Can be a contextual function:** no

```
1 #codly(enabled: true)
2 *Enabled:*
3 ```
4 Hello, world!
5 ```
6
7 #codly(enabled: false)
8 *Disabled:*
9 ```
10 Hello, world!
11 ```
```

Enabled:

```
1 Hello, world!
```

Disabled:

```
Hello, world!
```

Offset (`offset`)

The offset to apply to line numbers.

Note that the offset gets reset automatically after every code block.

- **Default:** `0`
- **Type:** `int`
- **Can be a contextual function:** yes

```
1 #codly(offset: 0)
2 *No offset:*
3 ```
4 Hello, world!
5 ```
6
7 #codly(offset: 5)
8 *With offset:*
9 ```
10 Hello, world!
11 ```
```

No offset:

```
1 Hello, world!
```

With offset:

```
6 Hello, world!
```

Range (range)

The range of line numbers to display.

Note that the range gets reset automatically after every code block.

The same behavior can be achieved using the `codly-range()` function.

- **Default:** `none`
- **Type:** `(int, int)` or `none`
- **Can be a contextual function:** yes

```
1 #codly(range: (2, 4)) Typst
2 ```py
3 def fib(n):
4     if n <= 1:
5         return n
6     return fib(n - 1) + fib(n - 2)
7 fib(25)
8 ```
```

```
2     if n <= 1: py
3         return n
4     return fib(n - 1) + fib(n - 2)
```

Skips (skips)

Insert a skip at the specified line numbers, setting its offset to the length of the skip. The skip is formatted using `skip-number` and `skip-line`.

Each skip is an array with two values: the position and length of the skip.

Note that the skips gets reset automatically after every code block.

The same behavior can be achieved using the `codly-skip()` function, which appends one or more skips to the list of skips.

- **Default:** `()`
- **Type:** `array` or `none`
- **Can be a contextual function:** yes

```
1 #codly(skips: ((4, 32), )) Typst
2 ```py
3 def fib(n):
4     if n <= 1:
5         return n
6     return fib(n - 1) + fib(n - 2)
7 fib(25)
8 ```
```

```
1 def fib(n): py
2     if n <= 1:
3         return n
4     return fib(n - 1) + fib(n -
5 2)
...
37 fib(25)
```

Skip number (skip-number)

Sets the content with which the line number columns is filled when a skip is encountered. If line numbers are disabled, this has no effect.

Skip line (skip-line)

Sets the content with which the line columns is filled when a skip is encountered.

Languages (languages)

The language definitions to use for language block formatting.

It is defined as a dictionary where the keys are the language names and each value is another dictionary containing the following keys:

- **name** : the “pretty” name of the language as a content/showable value
- **color** : the color of the language, if omitted uses the default color
- **icon** : the icon of the language, if omitted no icon is shown

Alternatively, the value can be a string, in which case it is used as the name of the language. And no icon is shown and the default color is used.

If an entry is missing, and language blocks are enabled, will show the “un-prettified” language name, with the default color.

- **Default:** `(:)`
- **Type:** `dict`
- **Can be a contextual function:** no

```
1 #codly(
2     languages: (
3         py: (name: "Python", color: red,
4             icon: "🐍")
5     )
6 )
7 ```py
8 print('Hello, world!')
9 print('Goodbye, world!')
```

```
1 print('Hello, world!')
2 print('Goodbye, world!')
```

Python

Display name (`display-name`)

Whether to display the name of the language in the language block. This only applies if you’re using the default language block formatter.

- **Default:** `true`
- **Type:** `bool`
- **Can be a contextual function:** yes

```
1 #codly(display-name: false)
2 ```py
3 print('Hello, world!')
4 print('Goodbye, world!')
5 ```
```

```
1 print('Hello, world!')
2 print('Goodbye, world!')
```

Display icon (`display-icon`)

Whether to display the icon of the language in the language block. This only applies if you’re using the default language block formatter.

- **Default:** `true`
- **Type:** `bool`
- **Can be a contextual function:** yes

```
1 #codly(  
2     display-icon: false,  
3     languages: (  
4         py: (name: "Python", color: red,  
5             icon: "🐍")  
6     )  
7 ``py  
8 print('Hello, world!')  
9 print('Goodbye, world!')  
10 ``
```

```
1 print('Hello, world!')  
2 print('Goodbye, world!')
```

Default color (default-color)

The default color to use for language blocks.

This only applies if you're using the default language block formatter. Also note that it is also passed as a named argument to the language block formatter if you've defined your own.

- **Default:** `rgb("#283593")` (a shade of blue)
- **Type:** `color`
- **Can be a contextual function:** yes

```
1 #codly(default-color: orange)  
2 ``py  
3 print('Hello, world!')  
4 print('Goodbye, world!')  
5 ``
```

```
1 print('Hello, world!')  
2 print('Goodbye, world!')
```

Radius (radius)

The radius of the border of the code block.

- **Default:** `0.32em`
- **Type:** `length`
- **Can be a contextual function:** yes

```
1 #codly(radius: 0pt)  
2 ``  
3 print('Hello, world!')  
4 ``  
5 #codly(radius: 20pt)  
6 ``  
7 print('Hello, world!')  
8 ``
```

```
1 print('Hello, world!')  
  
1 print('Hello, world!')
```

Inset (inset)

The inset of the code block.

- **Default:** `0.32em`
- **Type:** `length`
- **Can be a contextual function:** yes

```
1 #codly(inset: 10pt)
2 ```
3 print('Hello, world!')
4 ```
5 #codly(inset: 0pt)
6 ```
7 print('Hello, world!')
8 ```
```

```
1 print('Hello, world!')
1print('Hello. world!')
```

Fill (fill)

The fill of the code block when not zebra-striped.

- **Default:** `none`
- **Type:** `none`, `color`, `gradient`, or `pattern`
- **Can be a contextual function:** yes

```
1 #codly(
2   fill:
3   gradient.linear(..color.map.flare),
4 )
5 ```
6 print('Hello, world!')
7 print('Goodbye, world!')
8 ```
```

```
1 print('Hello, world!')
2 print('Goodbye, world!')
```

Zebra color (zebra-fill)

The fill of the code block when zebra-striped, `none` to disable zebra-striping.

```
1 #codly(
2   zebra-fill:
3   gradient.linear(..color.map.flare),
4 )
5 ```
6 print('Hello, world!')
7 print('Goodbye, world!')
8 ```
```

```
1 print('Hello, world!')
2 print('Goodbye, world!')
```

- **Default:** `none`
- **Type:** `none`, `color`, `gradient`, or `pattern`
- **Can be a contextual function:** yes

Stroke (stroke)

The stroke of the code block.

- **Default:** `1pt + luma(240)`
- **Type:** `none` or `stroke`
- **Can be a contextual function:** yes

```

1 #codly(
2     stroke: 1pt +
3     gradient.linear(.,color.map.flare),
4 )
5 print('Hello, world!')
6 print('Goodbye, world!')
7

```

```

1 print('Hello, world!')
2 print('Goodbye, world!')

```

Language block inset (lang-inset)

The inset of the language block.

This only applies if you're using the default language block formatter.

- **Default:** 0.32em
- **Type:** length
- **Can be a contextual function:** yes

```

1 #codly(lang-inset: 5pt)
2
3 print('Hello, world!')
4 print('Goodbye, world!')
5

```

```

1 print('Hello, world!')
2 print('Goodbye, world!')

```

Language block outset (lang-outset)

The X and Y outset of the language block, applied as a dx and dy during the place operation.

This applies in every case, whether or not you're using the default language block formatter.

The default value is chosen to get rid of the inset applied to each line.

- **Default:** (x: 0.32em, y: 0pt)
- **Type:** dict
- **Can be a contextual function:** yes

```

1 #codly(lang-outset: (x: -10pt,
2 y: 5pt))
3
4 print('Hello, world!')
5 print('Goodbye, world!')
6

```

```

1 print('Hello, world!')
2 print('Goodbye, world!')

```

Language block radius (lang-radius)

The radius of the language block.

- **Default:** 0.32em
- **Type:** length
- **Can be a contextual function:** yes

```

1 #codly(lang-radius: 10pt)
2 ```
3 print('Hello, world!')
4 print('Goodbye, world!')
5 ```

```

```

1 print('Hello, world!')
2 print('Goodbye, world!')

```

Language block stroke (lang-stroke)

The stroke of the language block.

- **Default:** `none`
- **Type:** `none`, `stroke`, or a function that takes in the language dict or none

(see argument `languages`) and returns a stroke.

- **Can be a contextual function:** no

```

1 #codly(lang-stroke: 1pt +
  red)
2 ```
3 print('Hello, world!')
4 print('Goodbye, world!')
5 ```
6 #codly(lang-stroke: (lang) => 2pt +
  lang.color)
7 ```
8 print('Hello, world!')
9 print('Goodbye, world!')
10 ```

```

```

1 print('Hello, world!')
2 print('Goodbye, world!')

```

```

1 print('Hello, world!')
2 print('Goodbye, world!')

```

Language block fill (lang-fill)

The fill of the language block.

- **Default:** `none`
- **Type:** `none`, `color`, `gradient`, `pattern`, or a function that takes in

the language dict or none (see argument `languages`) and returns a fill.

- **Can be a contextual function:** no

```

1 #codly(lang-fill: red)
2 ```
3 print('Hello, world!')
4 print('Goodbye, world!')
5 ```
6 #codly(lang-fill: (lang) =>
  lang.color.lighten(40%))
7 ```
8 print('Hello, world!')
9 print('Goodbye, world!')
10 ```

```

```

1 print('Hello, world!')
2 print('Goodbye, world!')

```

```

1 print('Hello, world!')
2 print('Goodbye, world!')

```

Language block formatter (lang-formatter)

The formatter for the language block.

A value of `none` will use the default language block formatter. To disable the language block, set `display-icon` and `display-name` to `false`. Or set `lang-formatter` to `(..) => none`.

- **Default:** `codly.default-language-block`
- **Type:** `function`
- **Can be a contextual function:** `no`

```
1 #codly(lang-formatter: (..) => [ No! ]) Typst
2 ```
3 print('Hello, world!')
4 print('Goodbye, world!')
5 ```
```

```
1 print('Hello, world!') No!
2 print('Goodbye, world!')
```

Line number formatter (`number-format`)

The formatter for line numbers.

- **Default:** `(line) => str(line)`
- **Type:** `function`
- **Can be a contextual function:** `false`

```
1 #codly(number-format: (n) => numbering("I.", n)) Typst
2 ```
3 print('Hello, world!')
4 print('Goodbye, world!')
5 ```
```

```
I. print('Hello, world!') typ
II. print('Goodbye, world!')
```

Line number alignment (`number-align`)

The alignment of the line numbers.

- **Default:** `left + horizon`
- **Type:** `top`, `horizon`, or `bottom`
- **Can be a contextual function:** `yes`

```
1 #codly(number-align: right + horizon) Typst
2 ```py
3 # Iterative Fibonacci
4 # As opposed to the recursive
5 # version
6 def fib(n):
7     if n <= 1:
8         return n
9     last, current = 0, 1
10    for _ in range(2, n + 1):
11        last, current = current, last +
12        current
13    return current
14    print(fib(25))
15    ```
```

```
1 # Iterative Fibonacci py
2 # As opposed to the recursive
3 # version
4 def fib(n):
5     if n <= 1:
6         return n
7     last, current = 0, 1
8     for _ in range(2, n + 1):
9         last, current = current, last
10        + current
11    return current
12    print(fib(25))
```

Smart indentation (`smart-indent`)

Whether to use smart indentation, which will check for indentation on a line and use a bigger left side inset instead of spaces. This allows for linebreaks to continue at the same level of indentation. This is off by default since it is slower.

- **Default:** `false`
- **Type:** `bool`
- **Can be a contextual function:** no

```
1 #codly(smart-indent: true) Typst
2 ```py
3 def fib(n):
4     if n <= 1:
5         return n
6     else:
7         return (fib(n - 1) + fib(n - 2))
8     print(fib(25))
9 ```
```

```
1 def fib(n): py
2     if n <= 1:
3         return n
4     else:
5         return (fib(n - 1) + fib(n - 2))
6     print(fib(25))
```

Breakable (`breakable`)

Whether the code block is breakable.

- **Default:** `false`
- **Type:** `bool`
- **Can be a contextual function:** no

Parameters

`codly(...args)`

codly-disable

Disables codly.

```
1 *Enabled:* Typst
2 ```
3 Hello, world!
4 ```
5
6 #codly-disable()
7 *Disabled:*
8 ```
9 Hello, world!
10 ```
```

Enabled:

```
1 Hello, world! typ
```

Disabled:

```
Hello, world!
```

Parameters

`codly-disable()`

codly-enable

Enables codly.

```
1 #codly-disable()
2 *Disabled:*
3 ```
4 Hello, world!
5 ```
6
7 #codly-enable()
8 *Enabled:*
9 ```
10 Hello, world!
11 ```
```

Disabled:

Hello, world!

Enabled:

```
1 Hello. world! | tvb |
```

Parameters

`codly-enable()`

codly-init

Initializes the codly show rule.

```
1 #show: codly-init
```

Parameters

`codly-init(body)`

codly-offset

Lets you set a line number offset.

```
1 #codly-offset(offset: 25)
2 ```py
3 def fib(n):
4     if n <= 1:
5         return n
6     return fib(n - 1) + fib(n - 2)
7 fib(25)
8 ```
```

```
26 def fib(n):
27     if n <= 1:
28         return n
29     return fib(n - 1) + fib(n -
30 2)
30 fib(25)
```

Parameters

`codly-offset(offset)`

codly-range

Lets you set a range of line numbers to highlight. Similar to `codly(range: (start, end))`.

```

1 #codly-range(start: 2)
2 ```py
3 def fib(n):
4     if n <= 1:
5         return n
6     return fib(n - 1) + fib(n - 2)
7 fib(25)
8 ```

```

```

2     if n <= 1:
3         return n
4     return fib(n - 1) + fib(n - 2)
5 fib(25)

```

Parameters

```

codly-range(
    start,
    end
)

```

codly-skip

Appends a skip to the list of skips.

```

1 #codly-skip(4, 32)
2 ```
3 Hello, world!
4 Goodbye, world!
5 ```

```

```

1 Hello, world!
2 Goodbye, world!

```

Parameters

```

codly-skip(
    position,
    length
)

```

local

Allows setting codly setting locally. Anything that happens inside the block will have the settings applied only to it. The pre-existing settings will be restored after the block. This is useful if you want to apply settings to a specific block only.

```

1  *Special:*
2  #local(default-color: red)[
3    ``
4    Hello, world!
5    ``
6  ]
7
8  *Normal:*
9  ``
10 Hello, world!
11 ``

```

Special:

```
1 Hello, world!
```

Normal:

```
1 Hello, world!
```

Parameters

```

local(
  body,
  ..args
)

```

no-codly

Disabled codly locally.

```

1  *Enabled:*
2  ``
3  Hello, world!
4  ``
5
6  *Disabled:*
7  #no-codly(``
8  Hello, world!
9  ``)

```

Enabled:

```
1 Hello, world!
```

Disabled:

Hello, world!

Parameters

```
no-codly(body)
```