Secure LLM using Firewall:ReThink

Mini Project Report

Submitted By

Aaron Baby Manoj (Reg. No. SJC22CC001)
Adithya Biju (Reg. No. SJC22CC002)
Ajay Varma J (Reg. No. SJC22CC004)
Alfred Biju (Reg. No. SJC22CC009)

to

the APJ Abdul Kalam Technological University
in partial fulfillment of the requirements for the award of the degree

of

Bachelor of Technology

in

Computer Science and Engineering (Cyber Security)

Department of Computer Science and Engineering (Cyber Security)

St. Joseph's College of Engineering & Technology
Palai - 686 579

April 2025

St. Joseph's College of Engineering and Technology, Palai

Department of Computer Science and Engineering (Cyber Security)

CERTIFICATE

This is to certify that the Mini-project report entitled **Secure LLM using Firewall:ReThink** submitted by **Aaron Baby Manoj (SJC22CC001)**, **Adithya Biju (SJC22CC002)**, **Ajay Varma J (SJC22CC004)**, **Alfred Biju (SJC22CC009)**, Sixth Semester B.Tech Computer Science and Engineering (Cyber Security) students, is a bonafide record of the Mini-Project done by them, under our guidance and supervision, in partial fulfillment of the requirements for the award of the degree, **B.Tech Computer Science and Engineering (Cyber Security)** of **APJ Abdul Kalam Technological University, Kerala**.

Dr. Sruthy S	**Prof. Sabarinath G. Pillai**	**Dr. Sruthy S**
Supervisor	Mini Project Coordinator	Head
Dept. of CSE(CC)	Dept. of CSE(CC)	Dept. of CSE(CC)

Acknowledgment

we wish to record our indebtedness and thankfulness to all who helped us prepare this Mini Project Report titled **Secure LLM using Firewall:ReThink** and present it in a satisfactory way.

we would like to convey our special gratitude to **Dr. V.P.Devassia**, Principal, SJCET, Palai,for the moral support he provided. we express our sincere thankfulness to **Dr. Sruthy S**, Head of the department, Department of Computer Science and Engineering (Cyber Security) for her co-operation and valuable suggestions. Also we express our sincere thanks to Mini project co-ordinator **Prof. Sabarinath G. Pillai** for his helpful feedback and timely assistance.

we are especially thankful to our guide **Dr. Sruthy S**, Assistant Professor, Department of Computer Science and Engineering (Cyber Security) for giving us valuable suggestions and critical inputs in the preparation of this report.

we also extend our thanks to all our friends who helped us by giving motivation. Their smallest piece of advice was really valuable. Once again we convey our gratitude to all those persons who had directly or indirectly influenced our work as a whole.

Aaron Baby Manoj
Adithya Biju
Ajay Varma J
Alfred Biju
St. Joseph's College of Engineering & Technology
Palai - 686 579.

Abstract

The AI Firewall project is designed to enhance the security of Large Language Models (LLMs) and chatbot systems by mitigating prompt injection attacks and preventing unauthorized manipulations. As AI-powered applications become increasingly integrated into various industries, maintaining their integrity and security is essential. This project functions as an intelligent security layer that filters incoming prompts, detecting and blocking malicious inputs before they can affect the underlying AI model.

Built using Python, Ollama, and Langchain, the AI Firewall analyzes user inputs in real-time, identifying threats such as adversarial manipulations, jailbreak attempts, and unauthorized prompt modifications. By leveraging context-aware filtering mechanisms, the system ensures that interactions remain secure without compromising the AI's functionality.

By implementing this AI Firewall, developers can significantly improve the stability, reliability, and security of their AI-driven applications. This solution helps prevent exploitation, unintended responses, and ethical concerns, making AI-powered systems safer and more resilient across industries like automation, virtual assistance, and customer support.

Contents

Certificate **i**

Acknowledgment **ii**

Abstract **iii**

1 Introduction **1**
1.1 Background 2
1.2 Problem Statement 2
1.3 Objectives 2
1.4 Scope of the project 3
1.5 Significance of study 3

2 Literature Review **4**
2.1 AI Security Threats and Vulnerabilities 4
2.2 Defending Against Prompt Injection Attacks 4
2.3 Challenges and Future Directions 5

3 Finalization of Target Requirements **6**
3.1 Introduction 6
3.2 Functional Requirements 6
3.3 Non-Functional Requirements 7

4 Architecture, Design and Implementation **8**
4.1 Architechture 8
4.1.1 System Architecture 8

4.1.2 Processing Workflow 9
4.1.3 Implementation Details 10
4.1.4 Security Considerations 10
4.2 Design 10
4.2.1 Flowchart 10
4.2.2 Algorithm: AI Input Firewall 13
4.3 Implementation 15
4.3.1 Tools, Libraries and Frameworks used 15
4.3.2 Implementation Structure 18

5 Use Case: Securing User Inputs with AI Input Firewall 22
5.1 Objective 22
5.2 Actors 22
5.3 Preconditions 23
5.4 Postconditions 23
5.5 Main Flow 23
5.6 Alternative Flow 24
5.7 Exceptions 24
5.8 Frequency of Use 24
5.9 Assumptions 24
5.10 Use Case Diagram 24

6 Results and Discussions 26
6.1 Results 26
6.2 Discussions 26
6.3 Outputs 27

7 Conclusions and Future Improvements 34
7.1 Conclusions 34
7.2 Future Scope of Improvements 34

Bibliography 36

List of Figures

4.1 AI Firewall Flowchart 11

5.1 Use case diagram of our project 25

6.1 Normal Prompt and output 27
6.2 Normal Prompt and output 28
6.3 Malicious input 29
6.4 the given figure is the unsafe prompt and its blocked answer . . . 30
6.5 Malicious input 31
6.6 Malicious input 32
6.7 Malicious input 33

Chapter 1

Introduction

As artificial intelligence (AI) systems, particularly Large Language Models (LLMs), become more integrated into various applications, ensuring their security is a growing concern. Prompt injection attacks and other adversarial manipulations can exploit vulnerabilities in AI-powered chatbots and automated systems, leading to unintended responses, misinformation, or even security breaches. Traditional security measures often fall short in protecting LLMs from such sophisticated threats, creating a need for a specialized AI security layer.

The AI Firewall is designed to address these challenges by filtering and analyzing user inputs before they reach the AI model. It acts as a proactive security mechanism, preventing malicious prompts, unauthorized command injections, and manipulation attempts. Developed using Python, Ollama, and Langchain, this project leverages advanced filtering techniques to distinguish between legitimate queries and potentially harmful inputs, ensuring safer interactions with AI systems.

By implementing an AI Firewall, developers and organizations can strengthen the reliability, security, and ethical integrity of their AI-driven applications. This project is particularly beneficial for industries relying on chatbots, virtual assistants, automated customer service, and AI-powered decision-making systems, ensuring that AI remains a trustworthy and secure technology in real-world applications.

1.1 Background

With the increasing adoption of Large Language Models (LLMs) and AI-powered chatbots, security vulnerabilities such as prompt injection attacks have become a major concern. Malicious users can manipulate input prompts to bypass restrictions, extract sensitive data, or alter the intended behavior of AI models. Existing security measures for LLMs often lack the ability to intelligently detect and block adversarial inputs, making AI systems susceptible to misuse.

To address these challenges, the AI Firewall is designed as an advanced filtering mechanism that inspects user inputs before they reach the AI model. It ensures safe and reliable interactions by identifying malicious prompts, unauthorized modifications, and adversarial attacks, effectively enhancing AI security.

1.2 Problem Statement

Traditional AI models are vulnerable to attacks where users manipulate input prompts to make the model produce unintended, harmful, or unethical outputs. The absence of an intelligent firewall allows malicious actors to exploit these systems for:

- Prompt injections leading to unintended responses
- Jailbreak attempts to bypass security policies
- Exploitation of AI for misinformation or unethical use

Thus, a proactive AI security system is needed to prevent such attacks while maintaining smooth interactions.

1.3 Objectives

The AI Firewall aims to:

- Detect and filter malicious or manipulated prompts before they reach the LLM
- Prevent prompt injections that can exploit AI-generated responses

- Enhance the security and reliability of AI-driven applications
- Ensure ethical and responsible AI interactions by blocking harmful content

1.4 Scope of the project

This project focuses on:

- Developing an AI firewall using Python, Langchain, and Ollama
- Implementing filtering techniques to detect adversarial input patterns
- Testing and evaluating the system on different types of AI-based applications such as chatbots and virtual assistants
- Ensuring real-time input validation without degrading AI performance

1.5 Significance of study

The AI Firewall is a crucial advancement in AI security, offering developers a robust way to protect their LLM-powered applications from cyber threats. This project will benefit:

- AI Developers – Helps in securing LLM-based applications from adversarial attacks
- Businesses – Ensures safe AI-driven customer interactions
- Cybersecurity Experts – Provides an innovative tool for AI security research
- Prompt injection vulnerabilities are one of the most recent and evolving threats in AI security. Unlike traditional cybersecurity threats that have been well-studied for decades, prompt injection is a relatively new attack vector that emerged with the rise of Large Language Models (LLMs) like GPT-4, Claude, and Phi.

Chapter 2

Literature Review

2.1 AI Security Threats and Vulnerabilities

Artificial intelligence (AI)-driven systems, particularly Large Language Models (LLMs), have introduced new security challenges. Traditional cybersecurity defenses were designed for conventional software, but AI introduces new attack surfaces. Liu et al. (2024) explored adversarial attacks on AI models, where subtle input modifications can deceive AI into generating incorrect or harmful outputs. Additionally, Lin et al. (2025) identified how prompt injection attacks manipulate AI models by injecting malicious inputs, bypassing safety mechanisms.

A growing concern is the use of AI-powered malware that can evade detection by adapting to security measures. Research by Jacob et al. (2025) proposed PromptShield, a detection mechanism for prompt injection attacks, demonstrating that even well-trained AI models can be tricked into generating unauthorized responses.

2.2 Defending Against Prompt Injection Attacks

Prompt injection attacks remain one of the biggest challenges in AI security. Attackers craft malicious inputs to override AI-generated safeguards or extract sensitive data. Research by Liu et al. (2024) demonstrated universal prompt injection attacks that can manipulate AI responses across different platforms. Additionally, Wired (2025) reported that DeepSeek's AI chatbot failed multiple security tests,

indicating that current LLM security implementations are insufficient.

To combat this, researchers propose:

- Context-Aware Filtering: Blocking malicious prompts using natural language understanding (NLU).
- Zero-Trust AI Security Models: Limiting AI autonomy in handling sensitive requests.
- Adversarial Training: Enhancing models by exposing them to simulated attacks to improve resilience.

2.3 Challenges and Future Directions

While significant progress has been made in AI security, challenges remain. Existing solutions struggle with evolving attack techniques, requiring constant updates. Researchers emphasize the need for self-learning AI firewalls that can adapt dynamically to new threats.

Furthermore, regulatory frameworks and ethical concerns must be addressed to ensure responsible deployment of AI-driven cybersecurity solutions. Future research should focus on integrating AI firewalls with blockchain, enhancing explainable AI (XAI) security models, and developing real-time AI attack mitigation strategies.

Chapter 3

Finalization of Target Requirements

3.1 Introduction

The development of an AI-powered firewall requires a well-defined set of functional and non-functional requirements to ensure its effectiveness in mitigating prompt injection attacks, adversarial exploits, and unauthorized AI manipulations. This chapter focuses on finalizing the key target requirements for the project, ensuring that the firewall system is robust, scalable, and adaptable to emerging AI security threats.

3.2 Functional Requirements

Functional requirements define the core capabilities that the AI firewall must provide. These include:

- Threat Detection and Prevention:

  Identifies and blocks prompt injection attacks and adversarial inputs.

  Detects malicious API requests attempting to exploit AI vulnerabilities.

- Context-Aware Filtering:

  Uses natural language processing (NLP) to distinguish legitimate from malicious prompts.

  Prevents unauthorized AI output manipulations.

3.3 Non-Functional Requirements

Non-functional requirements define the quality attributes that ensure system reliability, performance, and maintainability.

- Performance and Efficiency:
  - The firewall should process AI requests with minimal latency.
  - Must support high-traffic environments without significant resource consumption.
- Scalability:
  - The system should be easily deployable in cloud, on-premises, and hybrid infrastructures.
- Security and Compliance:
  - The firewall should process AI requests with minimal latency.
  - Must support high-traffic environments without significant resource consumption.
- Performance and Efficiency:
  - The firewall should process AI requests with minimal latency.
  - Must support high-traffic environments without significant resource consumption.

Chapter 4

Architecture, Design and Implementation

4.1 Architechture

This section describes the system's architecture, including its key components and interactions. It covers the backend for processing requests, the AI Input Firewall for filtering malicious inputs, and the frontend for user interaction. The architecture ensures secure data flow, efficient processing, and seamless communication between these components.

4.1.1 System Architecture

The AI Input Firewall is a security-focused application designed to analyze and filter user-provided text inputs before they are processed by a Large Language Model (LLM). The system implements multiple layers of security checks, including rule-based filtering, natural language processing (NLP) sentiment analysis, and keyword-based malicious intent detection.

System Components

The system comprises the following key components:

1. **Graphical User Interface (GUI)**: Built using PyQt6, the GUI allows users to enter prompts and receive responses from the AI firewall.
2. **Input Validator**: Ensures that the user input does not exceed length limits and performs basic sanitization.
3. **Malicious Content Detector**: Uses rule-based filtering, sentiment analysis, and pattern matching to identify harmful prompts.
4. **Local AI Model (OllamaLLM)**: Processes user input and generates responses with configurable parameters such as temperature and top-p selection.
5. **Response Generator**: Produces feedback to the user based on the analysis, either allowing or blocking the request.
6. **Theming System**: Supports light and dark modes for an improved user experience.

4.1.2 Processing Workflow

The system follows a structured workflow to process user inputs:

1. The user enters a prompt in the GUI input field and submits it.
2. The system performs basic length validation and sanitization.
3. The input is analyzed for harmful intent using:
   - Blocklist-based filtering.
   - Regular expression-based pattern detection.
   - Sentiment analysis using a transformer-based NLP model.
   - Keyword-based malicious intent categorization.
4. If the input is deemed malicious, the system blocks it and provides feedback.
5. If the input is safe, it is sent to the AI model for processing.
6. The AI-generated response is displayed in the GUI.

4.1.3 Implementation Details

The firewall is implemented using Python with the following dependencies:

- PyQt6 for GUI development.
- LangChain with OllamaLLM for language model integration.
- Transformers library for sentiment analysis.
- Requests library for HTTP communication (when needed).

4.1.4 Security Considerations

Several mechanisms are in place to ensure safety and performance:

- A predefined blocklist of harmful words.
- Regular expression matching for command injection attempts.
- Adjustable AI parameters to control response generation variability.
- A caching mechanism to optimize repeated checks.

4.2 Design

The design of the AI-powered input firewall focuses on creating a proactive security solution to mitigate prompt injection vulnerabilities in Large Language Models (LLMs). It incorporates a multi-layered approach, starting with a sanitization process to remove anomalies like SQL injection or XSS patterns from user prompts. This is followed by ”Role Back Thinking,” a method where sanitized prompts are re-evaluated by the LLM to confirm their safety. The system integrates LangChain for seamless LLM interaction, using rule-based checks and AI-based classification with the Ollama model to filter malicious inputs before they reach the core LLM, ensuring secure and controlled responses.

4.2.1 Flowchart

The diagram below represents the system’s flowchart, illustrating the step-by-step process. It visually maps the workflow, including inputs, decisions, and outputs, helping to understand the system’s logic and structure.



Figure 4.1: AI Firewall Flowchart

Flowchart steps

1. **Start:** The program begins execution.
2. **Initialize Variables:**The necessary variables, configurations, and settings are initialized.
3. **User Input Handling:**The program takes user inputs through the GUI or command-line interface.
4. **Preprocessing:**
   - Normalize text (remove extra spaces, convert to lowercase, etc.).
   - Tokenization (split prompt into words/tokens).
   - Feature extraction (identify key terms, patterns, and structure).
5. **Feature Analysis:**
   - Check for known attack patterns (SQL injection, jailbreak attempts, hidden commands).
   - Compare with blacklist of malicious terms.
   - Using transformer-based
   - Evaluate complexity and structure of the input.
6. **Prompt Classification:**
   - Use an ML model or rule-based approach to classify prompt.
   - Categories: Safe, Suspicious, Malicious.
7. **Decision Making:**
   - If **Safe**, pass to LLM.
   - If **Suspicious**, apply further filtering (e.g., reduce risk by modifying text).
   - If **Malicious**, block and report it to the user with response.
8. **Generate AI Response:** If input is safe, generate a response, which includes reason and classification.

9. **Display Output** Show classification result, reason, and AI-generated response.
10. **Enable User Input & Hide Progress**
11. **Wait for Next User Input or Exit**

- If the user enters a new prompt, repeat from step 3.
- If the user closes the window, exit the program.

4.2.2 Algorithm: AI Input Firewall

1. **Start**
   - Initialize the AI Input Firewall system.
2. **Receive Input**
   - The user submits a prompt through the graphical user interface (GUI).
   - Capture the input for processing.
3. **Validate Input**
   - Check if the input is not empty.
   - Ensure the input does not exceed 500 characters.
   - If invalid, display a warning message (e.g., ”Input is empty or too long”) and stop processing.
4. **Perform Rule-Based Safety Checks**
   - Convert the input to lowercase for case-insensitive comparison.
   - Check if the input contains any words from a predefined blocklist (e.g., ”hack”, ”exploit”).
   - Use a regular expression to detect potential SQL injection patterns (e.g., ”select”, ”drop”).

   If any prohibited content is detected, mark the input as unsafe and proceed to Step 7.

5. **AI-Based Classification**
   - Use the Ollama AI model to classify the input as ”SAFE” or ”UNSAFE”.
   - If the classification result is ”UNSAFE” and the confidence score exceeds 0.7, mark the input as unsafe and proceed to Step 7.
   - If the classification result is ”SAFE” or the score is below 0.7, proceed to Step 6.
6. **Generate Response (Safe Input)**
   - Use the Ollama AI model to generate a response based on the input prompt.
   - Display the generated response to the user.
   - Proceed to Step 8.
7. **Block Input (Unsafe Input)**
   - Prevent the unsafe prompt from being processed further.
   - Display a predefined message to the user (e.g., ”This prompt is unsafe, can’t answer.”).
   - Log the blocking action for future reference.
8. **Log Results**
   - Record the classification outcome (safe or unsafe) and relevant details (e.g., input text, classification score) for monitoring and auditing purposes.
9. **Handle Errors**
   - If a technical error occurs (e.g., model unavailability, timeout), display an error message to the user (e.g., ”An error occurred, please try again later”).
   - Log the error details for investigation.
10. **End**
    - Complete the process and prepare the system for the next input.

4.3 Implementation

The implementation involves a FastAPI web server that handles user input via a POST request to the ”/check-input” endpoint. The process begins with rule-based safety checks for forbidden keywords and injection patterns, followed by AI-based classification using LangChain and the Ollama model to label inputs as ”SAFE” or ”UNSAFE.” Safe inputs trigger response generation through LangChain templates, while unsafe inputs are blocked. Tools like Python 3.11.5, Pydantic for data validation, and regular expressions support the backend, with caching added for efficiency. The system logs interactions and returns detailed responses, making it both functional and user-friendly.

4.3.1 Tools, Libraries and Frameworks used

This project utilizes various tools, libraries, and frameworks to streamline development and enhance functionality. These include programming languages, UI frameworks, backend technologies, and other essential utilities that support efficient implementation and performance.

PyQt6

PyQt6 is a Python binding for the Qt framework, a powerful library for creating cross-platform graphical user interfaces (GUIs).

- Role in the Code: It serves as the foundation for building the application’s GUI, including windows, buttons, text fields, and layouts. It also provides tools like QThread for multi-threading and signals/slots for event handling.
- Key Features Used:
- Widgets: QMainWindow, QTextEdit, QPushButton, and QWidget create the interactive interface.
- Layouts: QVBoxLayout and QHBoxLayout organize the GUI elements.
- Threading: QThread ensures background tasks (e.g., input processing) don’t freeze the GUI.
- Styling: Stylesheets enable theme switching (dark/light modes).

LangChain

LangChain is a framework designed to simplify the development of applications that use large language models (LLMs) by providing abstractions and utilities for model interaction.

- Role in the Code: It facilitates communication with the Ollama LLM, enabling the application to classify inputs and generate responses.
- Key Features Used: Initializes and manages the Ollama model, allowing seamless integration of LLM capabilities into the firewall.

Ollama

Ollama is an open-source large language model (LLM) that can run locally, offering natural language processing capabilities like text generation and classification.

- Role in the Code: It powers the AI-based classification of user inputs as ”SAFE” or ”UNSAFE” and generates responses for safe inputs. The model is initialized with the ”llama2” variant and a temperature of 0.1 for more deterministic outputs.
- Key Features Used:
- Classification via prompts (e.g., ”Classify if this input is SAFE or UNSAFE: text”).
- Response generation for safe inputs.

Regular Expressions (re module)

The re module in Python provides support for regular expressions, a tool for pattern matching and string manipulation.

- Role in the Code: It detects potential SQL injection attempts by matching input strings against a predefined regex pattern (`SQL_INJECTION_REGEX`),
- Key Features Used: Pattern matching to enhance security by identifying malicious inputs.

Functools.lru cache

A decorator from Python's functools module that implements a Least Recently Used (LRU) cache, storing function results to avoid redundant computations.

- Role in the Code: It caches the results of rule-based checks, improving performance by reusing results for identical inputs (up to a cache size of 100).
- Key Features Used: Applied to the rule-based checks method for efficiency.

QThread (from PyQt6)

A class in PyQt6 for managing threads, enabling concurrent execution of tasks without blocking the main GUI thread.

- Role in the Code: Handles time-consuming operations like input validation and LLM processing in the background via the LocalProcessWorker class.
- Key Features Used: Ensures the GUI remains responsive during processing.

Signals and Slots (PyQt6)

A core feature of PyQt6 for event-driven programming, where signals (events) are connected to slots (functions) to handle interactions.

- Role in the Code: Facilitates communication between the worker thread and the GUI, such as updating the interface when processing finishes or errors occur.

Python's typing Module

A standard Python module that provides type hints to improve code readability, maintainability, and debugging, especially in larger projects.

- Key Features Used: Enhances code clarity without affecting runtime behavior.

Transformers(Machine Learning Model) for "Sentiment-analysis"

Transformers are deep learning models based on self-attention mechanisms, making them highly effective for NLP tasks. They analyze input sequences (e.g., user prompts) by considering context from all words, enabling more accurate classification.

- **Tokenization**: Converts input prompts into numerical format (tokens) for processing.
- **Embedding & Attention Mechanism**: The model processes tokens using self-attention layers to understand context.
- **Classification Layer**: The final layer assigns a probability score or label (e.g., "malicious" or "safe").
- **Filtering & Response Handling**: Based on the classification, the firewall either allows or blocks the prompt.

4.3.2 Implementation Structure

The AI-powered firewall is implemented in Python with various libraries to ensure efficient and secure prompt processing. Each component is structured as follows:

Graphical User Interface (GUI)

The GUI is built using PyQt6 and consists of:

- An input field for user prompts.
- A submit button to process input.
- A response display area to show results.

Example PyQt6 Code:

Listing 4.1: GUI Input Handling

```
from PyQt6.QtWidgets import QApplication, QWidget, QVBoxLayout,
    QPushButton, QTextEdit
```

```
class FirewallGUI(QWidget):
    def __init__(self):
        super().__init__()
        self.initUI()

    def initUI(self):
        self.layout = QVBoxLayout()
        self.inputField = QTextEdit()
        self.submitButton = QPushButton("Submit")
        self.layout.addWidget(self.inputField)
        self.layout.addWidget(self.submitButton)
        self.setLayout(self.layout)
```

Input Validation and Filtering

The input is validated to remove unnecessary whitespace, limit length, and check for malicious intent.

Example of blocklist filtering:

Listing 4.2: Blocklist Filtering

```
BLOCKLIST = [ 'hack', 'exploit', 'vulnerability', 'malware', '
    virus',
    'backdoor', 'rootkit', 'keylogger', 'phishing', 'ddos',
    'botnet', 'ransomware', 'trojan', 'worm', 'spyware']

def is_malicious(input_text):
    for word in BLOCKLIST:
        if word in input_text.lower():
            return True
    return False
```

Sentiment Analysis

The firewall utilizes a transformer-based NLP model for sentiment analysis.

Example using the Transformers library:

Listing 4.3: Sentiment Analysis

```
from transformers import pipeline

sentiment_analyzer = pipeline("sentiment-analysis")

def analyze_sentiment(text):
    result = sentiment_analyzer(text)
    return result[0]["label"]
```

AI Model Integration

OllamaLLM is used to generate responses when the prompt is deemed safe.
Example LangChain integration:

Listing 4.4: AI Model Processing

```
from langchain.llms import Ollama

llm = Ollama(model="phi")

def generate_response(prompt):
    return llm(prompt)
```

Workflow Summary

- User enters input into the GUI.
- The system checks for length, sanitization, and blocklist words.
- Sentiment analysis is performed to assess intent.
- If safe, the input is sent to the AI model for processing.
- The AI-generated response is displayed to the user.

Future Enhancements

- Adding a logging mechanism to track rejected inputs.
- Implementing a machine-learning-based threat detection system.
- Enhancing UI/UX with real-time feedback.

Chapter 5

Use Case: Securing User Inputs with AI Input Firewall

This use case describes the process of securely handling user inputs to prevent malicious prompts from reaching the Large Language Model (LLM) while ensuring safe prompts receive appropriate responses. The AI Input Firewall acts as a protective layer, filtering inputs through rule-based checks and AI classification, logging the process for monitoring, and generating responses for safe inputs.

5.1 Objective

- To analyze user inputs in real time and detect potential threats.
- To filter out harmful content before it reaches the AI model.
- To allow safe and appropriate interactions while maintaining AI response integrity.

5.2 Actors

- User: The individual submitting prompts to the AI system.
- AI Input Firewall: The system responsible for processing, classifying, and filtering user inputs.

5.3 Preconditions

- The AI Input Firewall system is operational and integrated with the LLM.
- The User has access to the system's interface (e.g., a web application).
- The Administrator has access to the logging and monitoring dashboard.

5.4 Postconditions

- Safe user inputs are processed, and a relevant response is generated and returned to the User.
- Unsafe inputs are blocked, and the User is informed of the reason.
- All classification and filtering actions are logged for the Administrator to monitor.

5.5 Main Flow

- The User submits an input prompt (e.g., "how to drive" or "how to hack nasa") through the AI Input Firewall interface.
- The AI Input Firewall receives the input and initiates the classification process to determine if the prompt is safe or unsafe.
- The system applies rule-based filters to check for prohibited keywords (e.g., "hack") or patterns (e.g., SQL injection attempts).
- If the input is deemed safe (e.g., "how to drive"), the system proceeds to generate a response using the LLM and returns it to the User (e.g., a step-by-step guide on driving).
- If the input is unsafe (e.g., "how to hack nasa"), the system blocks the prompt, logs the action, and informs the User with a message like "This prompt is unsafe, can't answer."

5.6 Alternative Flow

- If the classification process fails due to an ambiguous prompt, the system may flag it for manual review by the Administrator, who can update the rule-based filters to handle similar cases in the future.

5.7 Exceptions

- If the system encounters a technical error (e.g., the LLM is unavailable), the User receives an error message, and the issue is logged for the Administrator to investigate.

5.8 Frequency of Use

- This use case is executed every time a User submits a prompt, making it a core functionality of the AI Input Firewall system.

5.9 Assumptions

- The rule-based filters are pre-configured with a comprehensive list of prohibited keywords and patterns.
- The AI classification model (e.g., Ollama) is trained to accurately distinguish between safe and unsafe prompt.

5.10 Use Case Diagram

The below **figure 5.1** is a use case diagram representing the workflow of an LLM security firewall that processes user prompts before sending them to the AI model. The process starts with a user inputting a prompt, which is sent to the backend via a POST request. The backend first performs a rule-based check, followed by an AI-based check, to filter out any unsafe or restricted inputs. If the prompt passes, the AI generates a response, which is then analyzed for factors like



Figure 5.1: Use case diagram of our project

reasoning, permission, and a safety score. The processed result is sent back to the frontend through another POST request, where it is displayed to the user. This ensures controlled and secure interactions with the AI model.

Chapter 6

Results and Discussions

In this section, we evaluate the effectiveness of our LLM firewall in filtering malicious prompts. The evaluation is based on key metrics such as classification accuracy, processing speed, and resilience against prompt injection attacks. Our Transformer-based sentiment analysis pipeline is tested with different types of inputs, including benign, borderline, and explicitly malicious prompts, to assess its ability to distinguish between safe and harmful queries.

6.1 Results

- The Transformer-based pipeline successfully classifies most prompts as safe or malicious based on sentiment analysis.
- The system efficiently processes inputs in real-time, ensuring minimal latency.
- Performance metrics such as precision, recall, and F1-score indicate the effectiveness of the filtering mechanism.

6.2 Discussions

- The model performs well in detecting obvious threats but may require fine-tuning for complex adversarial prompts.

- Some evasive prompt injection attacks might bypass detection, highlighting the need for improved adversarial training.
- The approach demonstrates the potential of NLP-based security filtering, but continuous updates are necessary to adapt to emerging threats.

6.3 Outputs



Figure 6.1: Normal Prompt and output

Description: The above image fig 6.1 represents the AI Input Firewall allowing normal prompt and its llm response.



Figure 6.2: Normal Prompt and output

Description: The above image fig 6.2 represents the AI Input Firewall allowing normal prompt and its llm response.



Figure 6.3: Malicious input

Description: The above image fig 6.3 represents the AI Input Firewall preventing a prompt due to a high negative sentiment score (1.00), Containing blocked word and High malicious intent(1.00). The system detects potentially sensitive or restricted content and blocks the input before processing. The response time (0.24s).



Figure 6.4: the given figure is the unsafe prompt and its blocked answer

Description: The above image fig 6.4 represents the AI Input Firewall preventing a prompt due to a high negative sentiment score (0.99). The system detects potentially sensitive or restricted content and blocks the input before processing. The response time (0.03s).



Figure 6.5: Malicious input

Description: The above image fig 6.5 represents the AI Input Firewall preventing a prompt due to a high negative sentiment score (1.00), Containing blocked word and High malicious intent(1.00). The system detects potentially sensitive or restricted content and blocks the input before processing. The response time (0.02s).



Figure 6.6: Malicious input

Description: The above image fig 6.6 represents the AI Input Firewall preventing a prompt due to a high negative sentiment score (0.98). The system detects potentially sensitive or restricted content and blocks the input before processing. The response time (0.02s). Here the hacker is trying to trick llm to output restricted content.



Figure 6.7: Malicious input

Description: The above image fig 6.7 represents the AI Input Firewall preventing a prompt due to a high negative sentiment score (1.00). The system detects potentially sensitive or restricted content and blocks the input before processing. The response time (0.26s) indicates that the filtering mechanism is optimized for speed.

Chapter 7

Conclusions and Future Improvements

7.1 Conclusions

The AI-powered input firewall, developed using FastAPI and LangChain with the Ollama model, successfully addresses the prompt injection vulnerability in Large Language Models by implementing a proactive security framework. By combining rule-based checks for detecting malicious patterns, such as SQL injection and forbidden keywords, with AI-driven classification, the system effectively filters out unsafe inputs while allowing safe ones to generate meaningful responses. This layered approach not only enhances security but also ensures a seamless user experience in a real-time web service environment, proving to be a practical solution for safeguarding AI interactions against exploits like jailbreak attempts.

7.2 Future Scope of Improvements

Future improvements to the AI input firewall could enhance its capabilities by refining the AI-based classification through training the Ollama model on a more diverse set of malicious prompts to reduce misclassifications. Incorporating advanced contextual analysis in the natural language processing framework could improve detection of sophisticated attack patterns. New features like real-time

threat monitoring with automated updates from a global database of emerging exploits, multi-language prompt support for broader accessibility, and a user feedback mechanism to flag false positives or negatives could be added. Additionally, optimizing caching for faster responses and scaling the system for distributed deployment would boost performance, while integrating an adaptive learning module to dynamically adjust filtering rules based on usage patterns would further strengthen its proactive security stance.

Bibliography

[1] Jacob, D., Alzahrani, H., Hu, Z., Alomair, B., & Wagner, D. (2025). *PromptShield: Deployable Detection for Prompt Injection Attacks. arXiv preprint arXiv:2501.15145.*

[2] Lin, H., Lao, Y., Geng, T., Yu, T., & Zhao, W. (2025). *UniGuardian: A Unified Defense for Detecting Prompt Injection, Backdoor Attacks and Adversarial Attacks in Large Language Models. arXiv preprint arXiv:2502.13141.*

[3] Liu, X., Yu, Z., Zhang, Y., Zhang, N., & Xiao, C. (2024). *Automatic and Universal Prompt Injection Attacks against Large Language Models. arXiv preprint arXiv:2403.04957.*

[4] A. Mehrnia and J. A. Willson, *"On optimal IFIR filter design,"* IEEE Proceedings of the 2004 International Symposium on Circuits and Systems*, Vol. 3, pp. 133-136, May 2004.*

[5] Wired. (2024). *AI-Powered Robots Can Be Tricked Into Acts of Violence.*

[6] Wired. (2025). *DeepSeek's Safety Guardrails Failed Every Test Researchers Threw at Its AI Chatbot.*

Department of Computer Science and Engineering
(Cyber Security)

St. Joseph's College of Engineering & Technology, Palai
Palai - 686 579