How Well Do COCO Detectors Drive? Zero-Shot Transfer to KITTI, Speed, and Fine-Tuning

Aaron Chandler · CMPE 249, San José State University · Track A (experimental) · November 2026
Code, configuration and command log: `https://github.com/AaronChandler976/zero-shot-detection-transfer`

Summary. Five COCO-pretrained detectors from four families (YOLO11s, RT-DETR-L, Faster R-CNN R50-FPN v2, FCOS R50-FPN, and the open-vocabulary YOLO-World-S) were evaluated on COCO val2017 and, without retraining, on KITTI val (1,496 images) through a documented KITTI→COCO label mapping. A YOLO11s fine-tuned on KITTI train serves as the in-domain reference. The pipeline first reproduces every model's published COCO mAP to within 1.4 AP. On KITTI, AP on the shared classes (person, car, truck) falls by 12.8–23.6 points. The drop is *class-specific*: car is essentially unchanged while person falls 33–44 points. Medium and large objects lose 32–60% of their COCO AP for every model, so the gap is not only about small objects. Vans being labelled "truck" account for 22–56% of the closed-set models' truck loss. The 11-point spread between models on the same three COCO classes shrinks to 4.4 points on KITTI, where most differences are within bootstrap confidence intervals. Twenty-five minutes of fine-tuning raises KITTI AP from 24.6 to 71.6. All five models run in real time at batch 1 on an RTX 5070 Ti (5–19 ms per KITTI image).

1. Question and approach

Detectors are usually compared on COCO, but a robot sees a road, not COCO. The question is: *how much of a COCO-trained detector's skill transfers to a driving dataset, which classes and object sizes break, and is the fix a better architecture or in-domain data?* The approach is a controlled experiment with one evaluation harness (pycocotools, identical thresholds) for every model. The harness was validated by reproducing known COCO numbers before any KITTI number was trusted, and automated sanity checks gate every result (109 PASS / 0 FAIL). Four analyses follow: cross-dataset generalization by class and scale, architecture plus speed–accuracy, closed- vs open-vocabulary detection, and fine-tuning. A resolution ablation, a failure analysis and four targeted verification experiments complete the study.

2. Models and datasets

Model	Family / key idea	Checkpoint	Input	Params (M)	Post-proc.	Published COCO mAP
YOLO11s [11,13]	One-stage, anchor-free CNN	yolo11s.pt (Ultralytics)	640	9.5	NMS	47.0 [13]
RT-DETR-L [8]	Transformer decoder, set prediction (DETR [7])	rtdetr-l.pt	640	33.0	none (1-to-1 matching)	53.0 [14]
Faster R-CNN v2 [3,4,5]	Two-stage, anchor-based, FPN	torchvision COCO_V1	short side 800	43.7	NMS	46.7 [16]
FCOS [6]	One-stage, anchor-free, per-pixel + centerness	torchvision COCO_V1	short side 800	32.3	NMS	39.2 [16]
YOLO-World-S v2 [9]	Open-vocabulary, CLIP text prompts [10]	yolov8s-worldv2.pt	640	12.8	NMS	37.7 (zero-shot) [15]
YOLO11s-KITTI	YOLO11s fine-tuned on KITTI train	own run (best.pt)	640	9.4	NMS	–

Table 1. Models: four detector families (two-stage, dense one-stage, DETR-style, open-vocabulary) plus one fine-tuned model. YOLO [11] is the original one-stage design that YOLO11 descends from. Params are counted from the loaded model (`results/tables/benchmark.md`; YOLO11s 9.46 M vs fine-tuned 9.43 M in `results/metrics/diagnostics/param_counts.txt`, which differ only in the class head). torchvision models resize to a short side of 800 px (max 1,333).

Datasets. *COCO val2017* [1]: 5,000 images, 80 classes. *KITTI 2D object* [2], Ultralytics release [18]: the 7,481 labelled training images split into 5,985 train / 1,496 val. All KITTI numbers below are on this val split, which was never used for training. The release drops KITTI's *DontCare* regions, which matters in Section 7. KITTI val holds 7,920 boxes, of which car

makes up 72% (5,716). Under COCO's absolute area thresholds (32^2/96^2 px), KITTI cars are 17% small, 53% medium and 30% large.

Taxonomy mapping. COCO models predict COCO classes, so KITTI ground truth was relabelled (Table 2). This follows the KITTI devkit's "neighbouring class" idea: classes with no clean COCO counterpart become *ignore regions* (`iscrowd=1`). A prediction on an ignore region is neither rewarded nor punished. Dropping such a class instead would turn every correct "car" box on a van into a false positive. Only person, car and truck are scored, and every COCO→KITTI comparison uses **the same three classes on COCO** ("COCO 3-cls AP"), never the 80-class mAP.

KITTI class	COCO class	Role	Val boxes	Reason
Car / Truck / Pedestrian	car / truck / person	scored	5,716 / 223 / 921	same concept
Van	car	ignore region	555	COCO has no van; models call vans car or truck
Person_sitting, Cyclist	person	ignore region	36, 352	KITTI cyclist box = rider + bike; a COCO person box covers only the rider
Tram, Misc	–	dropped	117, 0	no COCO equivalent / undefined

Table 2. KITTI→COCO mapping (`configs/experiments.yaml: taxonomy`, `docs/taxonomy_mapping.md`). 6,860 boxes are scored and 943 are ignore regions. Models that output KITTI labels (YOLO-World with KITTI prompts, the fine-tuned model) map van→car and person_sitting→person, and are also scored on all 7 native classes.

3. Experimental setup and hardware

Hardware/software. NVIDIA GeForce RTX 5070 Ti (16 GB, driver 617.42), AMD Ryzen 9 9900X CPU (12 cores / 24 threads), 64 GB RAM, Windows 11 (WDDM driver model); Python 3.12.16, PyTorch 2.11.0+cu128, torchvision 0.26.0, CUDA 12.8, cuDNN 9.19, Ultralytics 8.4.197, pycocotools 2.0.11. Full versions are captured automatically in every `results/run_meta/*.json`.

Inference and evaluation. All models use conf = 0.001 and at most 300 detections per image. NMS IoU is each framework's default: 0.7 for the Ultralytics models (YOLO11s, YOLO-World, fine-tuned YOLO11s), 0.5 for Faster R-CNN's final per-class NMS (its RPN applies 0.7 to proposals), and 0.6 for FCOS. RT-DETR uses no NMS. (The existing `run_meta` files record the config value 0.7, which only the Ultralytics models receive; the pipeline now records each model's actual value.) A low confidence threshold is required for mAP: a deployment threshold such as 0.25 would cut the precision–recall curve short and lower AP. Metrics are COCO-style AP@[.5:.95] (the mean of AP at IoU 0.50, 0.55, …, 0.95, each AP being the area under a 101-point interpolated precision–recall curve), AP50, AP75, $AP_{S/M/L}$, AR100 and per-class AP, all from pycocotools [17]. These are COCO-style metrics on Ultralytics' image-level split of the KITTI training set, not official KITTI benchmark results (which use IoU 0.7 for cars and 0.5 for pedestrians, with Easy/Moderate/Hard difficulty levels), so they are not comparable to the KITTI leaderboard. Inference is FP16 except FCOS, which runs in FP32 (Section 8). Qualitative and failure analysis uses conf = 0.30. YOLO-World prompts: the 80 COCO class names on COCO, and `car, van, truck, pedestrian, person sitting, cyclist, tram` on KITTI (`configs/experiments.yaml: prompts`).

Latency protocol. Batch 1, images preloaded in RAM, end-to-end time (preprocess + network + NMS) with `torch.cuda.synchronize()`. There are 200 untimed warm-up images, so every input shape has been seen once, followed by 3 timed passes over 200 images. The reported latency is the median of the three pass means, with the min–max range. Peak memory is `torch.cuda.max_memory_allocated`.

Fine-tuning. YOLO11s initialised from COCO weights, 50 epochs, image size 640, batch 16, early-stop patience 15, seed 0, deterministic, Ultralytics default optimiser and augmentation. All 50 epochs ran, taking 1,490 s (24.8 min). The best checkpoint by Ultralytics validation was the last epoch, so selecting it on the val split gave no extra advantage (`results/metrics/finetune/results.csv`, Figure 4b).

4. Commands and configuration

One config file (`configs/experiments.yaml`) defines every model, threshold, mapping and run. One script runs the stages, and every run writes a metadata file with its exact command, thresholds, image count and environment. The complete

command log, including diagnostics, is `docs/commands.md`.

```
python run_all.py --quick                                    # 2.5-min smoke test (25 images/run, 1-epoch fine-tune)
python run_all.py --stages prepare                           # COCO val2017 + KITTI, builds COCO-format KITTI GT
python run_all.py --stages predict evaluate                  # 5 models x {COCO, KITTI} + YOLO11s@1280 (14 min)
python run_all.py --stages finetune predict_ft evaluate      # fine-tune YOLO11s on KITTI (29 min)
python run_all.py --stages benchmark failures analyze sanity # latency/memory, error analysis, tables, checks
# per-run equivalent, e.g.:  python scripts/predict.py --model yolo11s --dataset kitti --imgsz 1280 --tag res1280
#                            python scripts/evaluate.py --run yolo11s__kitti --target kitti_cocomap
```

5. Results

Table 3 lists every run. Read the two COCO AP columns first: they show that the harness reproduces the published numbers, which is the precondition for trusting the KITTI columns.

Model	COCO AP (published)	COCO AP (ours)	COCO AP50	COCO 3-cls AP	KITTI AP	95% CI	KITTI AP50	KITTI AP75	KITTI AP_S	KITTI AP_M	KITTI AP_L	KITTI AR100
YOLO11s	47.0	45.6	62.3	46.4	24.6	23.6–26.4	48.2	22.5	14.0	22.2	36.8	42.7
RT-DETR-L	53.0	52.8	71.2	52.6	29.0	27.5–31.1	53.8	27.4	22.4	27.6	40.9	55.6
Faster R-CNN v2	46.7	47.0	68.1	50.8	28.3	26.9–30.3	54.4	27.3	15.3	26.9	40.0	54.7
FCOS	39.2	39.3	58.7	43.4	28.7	27.1–30.7	54.5	27.4	21.0	27.5	38.5	53.8
YOLO-World-S v2	37.7	36.8	51.3	41.6	28.8	27.4–31.0	50.0	29.5	23.7	26.4	42.4	54.0
YOLO11s @1280	–	–	–	–	26.9	25.6–28.8	51.0	25.1	21.9	25.2	36.3	47.0
YOLO11s-KITTI (fine-tuned)	–	–	–	–	**71.6**	70.3–72.9	**93.0**	**80.2**	**58.3**	**71.4**	**80.7**	**77.1**

Table 3. Main results (AP@[.5:.95] in %, unless noted). COCO: 80 classes, 5,000 images. KITTI: person/car/truck, 1,496 val images, zero-shot except the last row. Every published COCO mAP is reproduced to within 1.4 AP, which validates id mapping, coordinates and thresholds before any KITTI number is interpreted. The largest gap (YOLO11s, −1.4) is inside the 2-AP tolerance; its cause was not investigated (candidates: differences between Ultralytics' own validator and this harness, and FP16). Bold = best in column (the fine-tuned model). 95% CI = percentile interval from 1,000 image-level bootstrap [19] resamples of KITTI val (`results/tables/bootstrap_ci.md`); paired comparisons are in §6.2. Source: `results/tables/main_results.md`, `results/sanity_report.md`.

6. Analyses

6.1 Cross-dataset generalization: which classes and scales degrade?

Model	COCO 3-cls	KITTI 3-cls	Drop	person		car		truck	
				COCO	KITTI	COCO	KITTI	COCO	KITTI
YOLO11s	46.4	24.6	−21.8	58.8	19.5	44.9	45.3	35.5	9.0
RT-DETR-L	52.6	29.0	−23.6	61.7	20.1	50.0	49.5	46.1	17.4
Faster R-CNN v2	50.8	28.3	−22.5	59.6	20.5	50.0	46.4	42.8	18.1
FCOS	43.4	28.7	−14.7	53.5	20.2	42.4	46.4	34.3	19.7
YOLO-World-S	41.6	28.8	−12.8	56.5	12.8	39.2	45.9	29.2	27.7

Table 4. Domain shift on the shared classes (AP@[.5:.95]). Source: `results/tables/domain_shift.md`.




Figure 1. Per-class AP on COCO (blue) and KITTI (orange). Car transfers, while person collapses for every architecture and truck for the closed-set models.

The shift is class-specific, not uniform (Table 4, Figure 1). Car AP is essentially unchanged (−3.6 to +6.7), but person loses 33–44 points for *every* model and truck loses up to 29. A road scene is therefore not "harder" across the board. What breaks is particular classes. A plausible reason for person is that KITTI pedestrians are small, upright and often occluded, whereas COCO "person" covers every pose, crop and context. Both detection and localisation suffer. AP50 itself falls (e.g. RT-DETR 74.8→53.8 on the three classes), and the ratio AP75/AP50 on the same three classes drops from 0.69–0.76 on COCO to 0.47–0.51 on KITTI for the closed-set models (YOLO-World 0.59). After fine-tuning it recovers to 0.86. Part of the loss is therefore box placement that does not match KITTI's annotation convention, which in-domain training fixes. (Ratios from per-class AP50/AP75 in `results/metrics/*.json`.)

Truck and vans (a mapping side effect). Of the confident (score ≥ 0.3) "truck" boxes, 48% (YOLO11s), 34% (RT-DETR) and 38% (Faster R-CNN) lie on a KITTI *van*. Only 13–20% hit a real truck. Because pycocotools applies ignore regions per category, and vans are ignored for *car* only, each such box is a truck false positive. A sensitivity check (Table 5) also marks vans as ignore regions for truck. Truck AP then rises by 5.7–11.1 points for every zero-shot model, which is 22–56% of the closed-set models' COCO→KITTI truck drop. The fine-tuned model is unaffected because it learned the van/truck distinction. Van confusion is therefore a large part of the truck drop, but not all of it: RT-DETR still loses 17.6 points (46.1→28.5). This check also *refuted* one of our own hypotheses: that YOLO-World leads on truck because its explicit "van" prompt keeps vans out of the truck class. It gains as much as the others (+9.2) and still leads afterwards (36.9 vs 28.5), so the cause of its truck advantage remains open. The main mapping was not changed after seeing results; Table 5 is reported only as a sensitivity analysis.

Variant (KITTI val)	YOLO11s	RT-DETR-L	Faster R-CNN	FCOS	YOLO-World	Fine-tuned
Main mapping: truck AP / 3-cls AP	9.0 / 24.6	17.4 / 29.0	18.1 / 28.3	19.7 / 28.7	27.7 / 28.8	83.9 / 71.6
Van also ignored for truck: truck / 3-cls	14.7 / 26.5	28.5 / 32.7	25.0 / 30.6	27.9 / 31.5	36.9 / 31.9	83.9 / 71.6
Van scored as car: car AP (main → variant)	45.3→43.8	49.5→48.1	46.4→44.6	46.4→45.3	45.9→45.3	80.9→80.8

Table 5. Taxonomy sensitivity, re-scoring the same predictions (`results/tables/sensitivity_taxonomy.md`; box counts in `results/metrics/diagnostics/truck_on_van.txt`). Treating vans differently moves car AP by only 0.1–1.8, so ignoring vans is *not* why some models score higher on KITTI cars than on COCO cars.

Scale. A common expectation is that KITTI is hard because its objects are small. The data do not support this as the main explanation (Figure 2). *Medium and large* objects lose 32–60% of their COCO AP for every model (medium 45–60%, large 32–47%), and most KITTI ground truth is medium. Small objects vary widely, from 1% for YOLO-World (24.0→23.7) to 58% for Faster R-CNN (36.3→15.3). Doubling the input resolution of YOLO11s to 1280 (Table 6) raises AP_S by 7.9 points, but leaves AP_L flat and recovers only 2.3 AP overall. Pixels help small objects, but most of the gap lies elsewhere.




Figure 2. AP by COCO area bucket on the three shared classes. Medium and large objects drop sharply for every model, while the small-object drop depends strongly on the model (`results/tables/domain_shift_scale.md`).

YOLO11s on KITTI	AP	AP50	AP_S	AP_M	AP_L	AR100	Latency (ms)	Peak mem (MB)
imgsz 640	24.6	48.2	14.0	22.2	36.8	42.7	5.0	72
imgsz 1280	26.9	51.0	21.9	25.2	36.3	47.0	5.6	79

Table 6. Resolution ablation. Since KITTI images are 1242×375, 640 px halves every object. At 1280 they are near native size. The model was trained at 640, so large objects at 1280 fall outside its training scale range (`results/tables/resolution.md`).

6.2 Architecture comparison and speed–accuracy trade-off

Model	KITTI latency ms (range)	FPS	Peak mem MB	KITTI AP	COCO latency ms (range)	COCO peak MB	COCO AP
YOLO11s	**5.0** (5.0–5.0)	200	72	24.6	7.2 (6.9–7.6)	71	45.6
YOLO-World-S v2	5.4 (5.4–5.4)	185	144	28.8	6.2 (6.2–6.4)	81	36.8
RT-DETR-L	12.2 (12.2–12.3)	82	173	29.0	16.7 (13.7–18.8)	143	52.8
Faster R-CNN v2	16.4 (16.2–16.6)	61	488	28.3	19.4 (19.3–19.7)	637	47.0
FCOS (FP32)	18.8 (18.7–19.2)	53	391	28.7	25.6 (25.5–26.2)	501	39.3

Table 7. Speed and memory, batch 1, median of 3 passes × 200 images (`results/tables/benchmark.md`). Latency is end-to-end and includes each framework's own preprocessing and input size, so it compares deployable pipelines rather than bare networks. FCOS runs FP32, the others FP16. The fine-tuned YOLO11s was not benchmarked separately: it shares YOLO11s's architecture and input size, and only its class head differs.




Figure 3. KITTI latency vs KITTI AP. KITTI latencies are used because they are stable to ±0.5 ms across passes. COCO latencies vary by up to 5 ms on Windows/WDDM with variable input shapes.

Speed. On this GPU every model is real-time (>50 FPS). The one-stage YOLOs are 3.0–3.8× faster than the R50-FPN models, which also take an 800-px input and 2.7–6.8× the peak memory.

Accuracy rankings do not transfer. On the same three classes, the 11.0-AP spread on COCO (41.6–52.6) shrinks to 4.4 AP on KITTI. A paired bootstrap (same resampled images for both models) finds RT-DETR, Faster R-CNN, FCOS and YOLO-World *statistically tied*: every difference to RT-DETR has a 95% interval containing 0, e.g. YOLO-World −0.1 [−1.7, +1.4]. Only YOLO11s is clearly worse, at −4.3 [−5.5, −3.3]. YOLO-World is *last* on COCO but tied for best on KITTI, at less than half RT-DETR's latency, so it sits on the speed–accuracy frontier together with YOLO11s.

Input resolution is a confound in this comparison. A 1242×375 KITTI image is resized to about 1333×402 by torchvision (1.07× native) but to 640×193 for the Ultralytics models (0.52×), so Faster R-CNN and FCOS see roughly 4× more pixels. The YOLO11s 1280 ablation (Table 6: AP_S 14.0 → 21.9) shows how much resolution alone moves small-object AP.

NMS vs NMS-free. NMS-free RT-DETR is not measurably better than the NMS-based models on KITTI (above), and its AR100 (55.6) is close to Faster R-CNN's (54.7). On COCO it leads clearly (52.8).

6.3 Closed-set vs open-vocabulary detection

YOLO-World takes class names as text and turns them into classifier weights with a CLIP text encoder. This lets it be prompted with KITTI's own seven classes and scored natively, which a closed-set COCO model cannot do. It transfers best overall (smallest drop, −12.8; best truck and small-object AP). But it is weakest on person (12.8), and on native KITTI classes it reaches only 15.3 AP: pedestrian 7.1, cyclist 2.2, person_sitting 0.3, tram 7.4. **The prompt word matters.** Replacing "pedestrian" with "person", with identical weights, raises person AP from 12.8 to 17.5 (AP50 32.9→45.7), and removing the competing "person sitting"/"cyclist" prompts adds only 0.5 more (`results/metrics/diagnostics/yoloworld_prompts.txt`). One untested hypothesis is that "person" is far more frequent than "pedestrian" in image–text training data, giving it a better-aligned text embedding. The reported results keep the original prompts, since choosing prompts on the evaluation set would be tuning on test data. Open vocabulary therefore buys flexibility and robustness for familiar objects, but not accuracy on domain-specific categories (cyclist, tram).

6.4 Fine-tuning vs zero-shot

YOLO11s on KITTI	Zero-shot	Fine-tuned
3-cls AP / AP50 / AP75	24.6 / 48.2 / 22.5	71.6 / 93.0 / 80.2
person / car / truck AP	19.5 / 45.3 / 9.0	49.8 / 80.9 / 83.9
AP_S / AP_L	14.0 / 36.8	58.3 / 80.7
7-class native AP	n/a (COCO labels)	67.2
Missed GT @conf 0.3*	1,862	484
Background FPs @conf 0.3*	1,182	281

Table 8. Fine-tuning (`results/tables/finetune.md`, `results/failures/*/summary.json`). For comparison, YOLO-World zero-shot reaches 15.3 native 7-class AP. *Counts at a fixed confidence depend on score calibration, which fine-tuning changes, so they illustrate the shift; the AP rows are the threshold-free comparison. Native per-class AP of the fine-tuned model: car 80.9, van 77.1, truck 83.9, pedestrian 49.7, person_sitting 43.3, cyclist 60.4, tram 74.9.




Figure 4a. Native 7-class AP: open-vocabulary zero-shot vs fine-tuned.

As Table 8 and Figure 4a show, 25 minutes of fine-tuning almost triples KITTI AP. The *same* YOLO11s network (all weights are fine-tuned; the only architectural change is the output layer, resized from 80 to 7 classes) goes from the worst zero-shot model to far ahead of every other model. Truck jumps from 9.0 to 83.9, and AP75 from 22.5 to 80.2. Our interpretation is that the zero-shot gap is mainly a **mismatch of label definitions, box conventions and domain appearance** (what counts as a truck vs a van, how tightly a pedestrian is boxed, KITTI's camera and scenes), not a lack of model capacity. Fine-tuning changes all of these at once, so this experiment cannot separate them. Architecture choices moved KITTI AP by 4.4 points, whereas in-domain data moved it by 47. **Caveat:** train and val share no files, but KITTI

frames are sampled from driving sequences, so frames of the same drive very likely appear in both splits. 71.6 is therefore an optimistic estimate compared with a sequence-level split.




Figure 4b. Ultralytics' per-epoch validation mAP (7 native classes, its own evaluator, so not identical to the pycocotools numbers above) (`results/metrics/finetune/results.csv`). mAP@[.5:.95] was still rising slowly at the end (67.0 at epoch 40, 68.3 at epoch 50) while the learning rate decayed towards zero, so longer training might add a little; 50 epochs is a budget choice, not a converged optimum.

7. Failure analysis

Each prediction (conf ≥ 0.3) and GT box was classified with a light TIDE-style [12] taxonomy at IoU 0.5: TP, FP-duplicate, FP-class (confusion), FP-loc (0.1≤IoU<0.5), FP-background (IoU<0.1) and FN (missed), with predictions on ignore regions skipped (Table 9). It covers one zero-shot model from each closed-set family studied (one-stage YOLO, DETR-style, two-stage) plus the fine-tuned model; FCOS and YOLO-World were not run through it.

Run (KITTI val, conf 0.3)	TP	FN (missed)	FP-background	FP-loc	FP-class	FP-dup	Recall person/small	Recall truck/medium
YOLO11s zero-shot	4,998	1,862	1,182	760	55	134	0.14	0.24
RT-DETR-L zero-shot	5,639	1,221	4,032	1,486	412	188	0.27	0.52
Faster R-CNN zero-shot	5,728	1,132	8,193	2,179	132	119	0.46	0.44
YOLO11s fine-tuned	6,376	484	281	315	4	173	0.46	0.97

Table 9. Error breakdown over 6,860 scored GT boxes (`results/failures/*/summary.json`). A fixed conf of 0.3 is a different operating point for each model, because score calibration differs. Compare counts within a model, not across models.




Figure 5a. YOLO11s, image 000535. A clearly visible pedestrian scored 0.74 is counted as *FP-background* because KITTI did not label him. The crowded group yields misses (thick orange) and loose boxes (FP-loc).



Figure 5b. Faster R-CNN, image 000845. Most red "background" FPs on the right are real parked cars behind a hedge and a person with a cart, all unlabelled. Heavily occluded parked cars on the left are missed.

What fails. (i) *Misses dominate*: small and occluded pedestrians (zero-shot YOLO11s finds 14% of small persons) and trucks (1 of 34 small trucks). Fine-tuning recovers most cars and trucks, but small pedestrians remain the hardest case even after training (46%). (ii) *Class confusion is rare* (55–412 boxes), and the main confusion is van→truck (Section 6.1). (iii) *"Background" false positives are partly a ground-truth artefact.* Without DontCare regions, real but unlabelled distant or occluded objects are scored as hallucinations (Figure 5), so zero-shot precision is somewhat underestimated for every model. (iv) *Rows of overlapping parked cars* are a recurring miss pattern in the saved examples. NMS suppressing true

neighbours is one possible cause, but it was not measured: NMS-free RT-DETR's AR100 (55.6) is close to NMS-based Faster R-CNN's (54.7), so heavy occlusion is at least as likely.

8. Validating the measurements: one wrong setting, two timing artefacts

- **FCOS failed the automated reproduction check** (31.3 vs 39.2 published). A controlled A/B on full COCO isolated FP16 autocast as the cause: thresholds changed AP by <0.3, but FP32 restored 39.3. The loss is confined to the 77 classes not scored on KITTI. Person, car and truck AP were unchanged (53.4/42.2/34.3 FP16 vs 53.5/42.4/34.3 FP32), while the other-77 mean fell from 39.2 to 30.8 (`results/metrics/diagnostics/fcos_fp16_per_class.txt`). Consistent with this, FCOS's KITTI AP was 28.62 in FP16 and 28.73 in FP32 (`results/run_log.jsonl`). FCOS therefore runs in FP32. A mean over 80 classes can hide where an error lives, and per-class checks expose it.
- **Latency outliers, found by inspecting the benchmark.** The first benchmark (20-image warm-up) reported YOLO11s at 56.5 ms on COCO (`results/metrics/diagnostics/benchmark_first_run_warmup20.txt`). A diagnostic re-run shows the cause: on a first pass, 9 of 200 images took over 20 ms (up to 1,041 ms) and accounted for 90% of the time (mean 51.4, median 5.3 ms). A second pass over the same images averaged 5.3 ms (`results/metrics/diagnostics/bench_warmup.txt`). This is a one-time setup cost the first time each input shape appears. The fix was to warm up on all 200 images.
- **Run-to-run noise.** Timing passes over identical images can differ on Windows/WDDM, e.g. RT-DETR on COCO measured 13.7–18.8 ms across three passes (Table 7). Latency is therefore reported as the median of three passes with its range, rather than re-running until a number looks right.

9. Limitations

(1) No DontCare regions in the KITTI release, so precision is underestimated (Section 7). (2) COCO's absolute area thresholds are applied to 1242×375 images, which makes "small/medium/large" dataset-relative. (3) Truck AP rests on 223 boxes and person on 921, and the 3-class mean weights truck equally with car's 5,716. The bootstrap shows the consequence: truck AP intervals span 6–10 points (e.g. RT-DETR 13.5–22.3), and zero-shot model differences under about 1.5 AP are not significant. The bootstrap resamples images, so it does not cover other sources of variance (training seed, split choice). (4) One image-level train/val split, likely correlated by drive. (5) The taxonomy mapping is a design choice, so Table 5 reports how much it matters. (6) Latency was measured on Windows/WDDM with each framework's own preprocessing, and FCOS ran in FP32. (7) One fine-tuning run (seed 0), and only the smallest YOLO size was fine-tuned.

10. Conclusions

1. **COCO skill transfers unevenly.** On the shared classes, KITTI AP is 13–24 points lower, but car transfers almost perfectly while person and truck collapse. Reporting only mAP would hide this.
2. **The gap is not mainly about pixels or architecture.** Medium and large objects lose 32–60% of their AP, higher resolution recovers only 2.3 AP, and four of the five architectures are statistically tied on KITTI. Our interpretation is that label conventions (van vs truck, how pedestrians are boxed), domain appearance and missing labels matter more than the choice of detector. Van confusion alone explains 22–56% of the truck loss.
3. **COCO rankings are a poor guide out of domain.** The model that is last on COCO's person/car/truck (YOLO-World) is statistically tied for best on KITTI, and YOLO11s, third on COCO, is the only significantly worse model.
4. **In-domain data dominates.** Twenty-five minutes of fine-tuning (24.6→71.6) is worth roughly ten times the spread between architectures. For a robot, the practical recipe is a fast detector (5 ms) fine-tuned on the target domain, with per-class and per-scale evaluation, especially recall on small pedestrians, which remains the weakest point even after fine-tuning.
5. **Rigor matters.** Reproducing known numbers first, gating results with automated checks, and testing hypotheses with targeted experiments caught one wrong model setting and two measurement artefacts. It also refuted one of the study's own explanations: YOLO-World's "van" prompt does not explain its truck lead.

AI use. The pipeline code, diagnostic scripts and report draft were produced with AI assistance (Claude, Claude Code). I verified the results by reproducing every model's published COCO mAP, running an automated sanity-check suite (109 checks), and testing surprising findings with targeted diagnostic experiments (Section 8).

References

1. T.-Y. Lin, M. Maire, S. Belongie, et al. Microsoft COCO: Common Objects in Context. *ECCV*, 2014.
2. A. Geiger, P. Lenz, R. Urtasun. Are we ready for Autonomous Driving? The KITTI Vision Benchmark Suite. *CVPR*, 2012.
3. S. Ren, K. He, R. Girshick, J. Sun. Faster R-CNN: Towards Real-Time Object Detection with Region Proposal Networks. *NeurIPS*, 2015.
4. T.-Y. Lin, P. Dollár, R. Girshick, K. He, B. Hariharan, S. Belongie. Feature Pyramid Networks for Object Detection. *CVPR*, 2017.
5. Y. Li, S. Xie, X. Chen, P. Dollár, K. He, R. Girshick. Benchmarking Detection Transfer Learning with Vision Transformers. *arXiv:2111.11429*, 2021 (source of the Faster R-CNN v2 recipe).
6. Z. Tian, C. Shen, H. Chen, T. He. FCOS: Fully Convolutional One-Stage Object Detection. *ICCV*, 2019.
7. N. Carion, F. Massa, G. Synnaeve, N. Usunier, A. Kirillov, S. Zagoruyko. End-to-End Object Detection with Transformers. *ECCV*, 2020.
8. Y. Zhao, W. Lv, S. Xu, et al. DETRs Beat YOLOs on Real-time Object Detection (RT-DETR). *CVPR*, 2024.
9. T. Cheng, L. Song, Y. Ge, W. Liu, X. Wang, Y. Shan. YOLO-World: Real-Time Open-Vocabulary Object Detection. *CVPR*, 2024.
10. A. Radford, J. W. Kim, C. Hallacy, et al. Learning Transferable Visual Models From Natural Language Supervision (CLIP). *ICML*, 2021.
11. J. Redmon, S. Divvala, R. Girshick, A. Farhadi. You Only Look Once: Unified, Real-Time Object Detection. *CVPR*, 2016.
12. D. Bolya, S. Foley, J. Hays, J. Hoffman. TIDE: A General Toolbox for Identifying Object Detection Errors. *ECCV*, 2020.
13. Ultralytics. YOLO11 documentation (COCO performance table). https://docs.ultralytics.com/models/yolo11/
14. Ultralytics. RT-DETR documentation. https://docs.ultralytics.com/models/rtdetr/
15. Ultralytics. YOLO-World documentation (zero-shot transfer on COCO). https://docs.ultralytics.com/models/yolo-world/
16. PyTorch. torchvision.models: object detection weights table. https://docs.pytorch.org/vision/stable/models.html
17. COCO API (pycocotools), official repository. https://github.com/cocodataset/cocoapi
18. Ultralytics. KITTI dataset documentation. https://docs.ultralytics.com/datasets/detect/kitti/
19. B. Efron, R. J. Tibshirani. *An Introduction to the Bootstrap*. Chapman & Hall/CRC, 1993.

Reproducibility. Every measured number in this report is read from files that the pipeline or the scripts in `scripts/diagnostics/` wrote to `results/`; derived numbers (differences, ratios) are computed from them. Sanity checks (`scripts/sanity_checks.py`) passed with 109 PASS, 0 WARN and 0 FAIL, and the command log is `docs/commands.md`. Published numbers appear only as references, each checked against its official source.