Data acquisition with the AD7705 on the raspberry PI

Generated by Doxygen 1.8.17

1 Data acquisition with the AD7705 on the raspberry PI!	1
2 Class Index	3
2.1 Class List	3
3 Class Documentation	5
3.1 AD7705callback Class Reference	5
3.1.1 Detailed Description	5
3.2 AD7705Comm Class Reference	5
3.2.1 Detailed Description	6
3.2.2 Constructor & Destructor Documentation	6
3.2.2.1 AD7705Comm()	6
3.2.3 Member Function Documentation	6
3.2.3.1 setCallback()	6
3.2.3.2 start()	7
Index	9

## **Chapter 1**

# Data acquisition with the AD7705 on the raspberry PI!

The AD7705 is a two channel sigma delta converter which has differential inputs, a PGA and programmable data rates. It's perfect for slowly changing inputs such as pressure, temperature, heart rate etc.

This repo offers the class AD7705Comm which does all the low level communications with the AD7705. The user just need to register a callback handler which then returns the samples in realtime.

The class uses the DRDY of the AD7705 connected to Port 22 and waits for a falling edge on this port to read the data. This is done via interrupts / poll so that the ADC process sleeps until new data becomes available.

Github: https://github.com/berndporr/rpi\_AD7705\_daq

2	Data acquisition with the AD7705 on the raspberry PI

# Chapter 2

# **Class Index**

### 2.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

AD7705callback	
Callback for new samples which needs to be implemented by the main program	5
AD7705Comm	
This class reads data from the AD7705 in the background (separate thread) and calls a callback	
function whenever data is available	5

4 Class Index

### **Chapter 3**

### **Class Documentation**

#### 3.1 AD7705callback Class Reference

Callback for new samples which needs to be implemented by the main program.

#include <AD7705Comm.h>

#### **Public Member Functions**

virtual void hasSample (int sample)=0
 Called after a sample has arrived.

#### 3.1.1 Detailed Description

Callback for new samples which needs to be implemented by the main program.

The function has Sample needs to be overloaded in the main program.

The documentation for this class was generated from the following file:

· AD7705Comm.h

#### 3.2 AD7705Comm Class Reference

This class reads data from the AD7705 in the background (separate thread) and calls a callback function whenever data is available.

```
#include <AD7705Comm.h>
```

#### **Public Types**

• enum SamplingRate { SAMPLING\_RATE\_50HZ = 0, SAMPLING\_RATE\_60HZ = 1, SAMPLING\_RATE\_ $\leftrightarrow$  250HZ = 2, SAMPLING\_RATE\_500HZ = 3 }

Sampling rates.

6 Class Documentation

#### **Public Member Functions**

• AD7705Comm (const char \*spiDevice="/dev/spidev0.0")

Constructor with the spiDevice.

• ~AD7705Comm ()

Destructor which makes sure the data acquisition has stopped.

void setCallback (AD7705callback \*cb)

Sets the callback which is called whenever there is a sample.

void start (SamplingRate samplingRate=SAMPLING\_RATE\_50HZ)

Starts the data acquisition in the background and the callback is called with new samples.

• void stop ()

Stops the data acquistion.

#### 3.2.1 Detailed Description

This class reads data from the AD7705 in the background (separate thread) and calls a callback function whenever data is available.

#### 3.2.2 Constructor & Destructor Documentation

#### 3.2.2.1 AD7705Comm()

```
AD7705Comm::AD7705Comm (

const char * spiDevice = "/dev/spidev0.0")
```

Constructor with the spiDevice.

The default device is /dev/spidev0.0.

Parameters

```
spiDevice The raw /dev spi device.
```

#### 3.2.3 Member Function Documentation

#### 3.2.3.1 setCallback()

```
void AD7705Comm::setCallback ( {\tt AD7705callback} \ * \ cb \ )
```

Sets the callback which is called whenever there is a sample.

#### **Parameters**

cb Pointer to the callback interface.

#### 3.2.3.2 start()

Starts the data acquisition in the background and the callback is called with new samples.

#### **Parameters**

samplingRate	The sampling rate of the ADC.

The documentation for this class was generated from the following file:

• AD7705Comm.h

8 Class Documentation

# Index

```
AD7705callback, 5
AD7705Comm, 5
AD7705Comm, 6
setCallback, 6
start, 7
setCallback
AD7705Comm, 6
start
AD7705Comm, 7
```