

REMEMBERING WHERE TO LOOK: CONTINUAL HIERARCHICAL EVIDENCE SELECTION FOR WHOLE-SLIDE IMAGES

Hsi-Ren Hung [Second Author] Huei-Fang Yang*

Department of Computer Science and Engineering, National Sun Yat-sen University, Taiwan

ABSTRACT

Whole-slide image (WSI) diagnosis is an evidence-acquisition problem: a model must identify a small set of informative patches among thousands before it can predict reliably. Continual-learning methods typically preserve classifiers or representations, yet a budgeted diagnostic system can fail differently—the diagnostic pathway may remain unchanged while its selector forgets where to look. We introduce **PathSelect**, which makes the evidence-selection policy itself the object of continual learning. To isolate selector forgetting, the image encoder, text encoder, and cosine diagnostic head are frozen, and only a hierarchical group-to-patch selector is learned. Within each task, diagnostic, semantic, and counterfactual-utility supervision teaches the selector to acquire useful evidence. Across tasks, dual-level distillation, replay, and a utility-preservation hinge preserve both selection behavior and diagnostic usefulness, while task-local LoRA updates are folded into a single shared selector. Crucially, PathSelect does not require the same patches to remain selected: evidence may change as long as its diagnostic utility does not regress. On the four-cohort ConSlide benchmark, PathSelect reaches 0.854 class-incremental accuracy with 0.060 forgetting, competitive with the strongest published result (0.859), while substantially outperforming unprotected selector fine-tuning (0.452 accuracy, 0.601 forgetting). Direct selection-level measurements further show that evidence identity and evidence utility can drift differently. These results identify evidence acquisition itself as a distinct and measurable locus of catastrophic forgetting in budgeted WSI diagnosis.

Index Terms— whole-slide images, continual learning, evidence selection, computational pathology, LoRA

1. INTRODUCTION

A gigapixel whole-slide image (WSI) may contain tens of thousands of patches, yet diagnosis often depends on only a small subset. Practical systems therefore operate under an *evidence budget*: select a few patches, then decide. This makes evidence acquisition itself a potential locus of catastrophic forgetting. A model may retain its visual representation and diagnostic rule after learning new disease cohorts, yet still fail because its selector no longer retrieves the tissue that previously supported the correct decision. Conventional continual learning, which primarily measures preservation of predictions, representations, or classifier parameters, does not directly expose this failure.

We therefore ask: when diagnostic tasks arrive sequentially, does a model forget where to look, and can that ability be measured and preserved directly? PathSelect is built around this question. To isolate selector forgetting, we freeze the CONCH image and text

encoders [1] and the cosine diagnostic rule throughout training; the evidence-selection policy is the only learned continual object. This controlled setting lets us study changes in evidence acquisition directly rather than infer them only from downstream accuracy.

PathSelect uses a tissue-aware coarse-to-fine hierarchy, following the group-to-patch principle of HistoSelect [2]: a fixed tissue vocabulary first organizes patches into semantic groups, the budget is allocated across groups, and patches are then ranked within each group. Our focus is not the hierarchy itself, but what happens after a selector has learned where to look: whether that policy can remain competent as new diagnostic tasks arrive.

This leads to a deliberate separation between learning and preservation. Within a task, PathSelect must *learn where to look now*, using diagnostic, semantic, and counterfactual-utility supervision. Across tasks, it must *keep looking well*. We distinguish *behavioral continuity*—whether the selector retains its old scoring preferences—from *functional continuity*—whether the evidence it now selects remains diagnostically useful. The distinction matters because changing the selected patches is not necessarily forgetting: alternative evidence should be allowed if it is at least as useful as what was selected before. PathSelect therefore combines dual-level distillation, utility preservation, and replay, while task-local LoRA updates are folded into a single shared selector for task-free inference.

Contributions.

- We formulate continual WSI diagnosis as continual evidence selection: with the image encoder, text encoder, and diagnostic head frozen, the hard budgeted selector is the only learned, preserved, and directly evaluated continual object. This isolates a failure mode largely hidden in prior WSI continual learning—forgetting where to look even when the diagnostic pathway itself is unchanged.
- We introduce PathSelect, a fixed-cost continual selector that preserves both selection behavior and selection usefulness. Dual-level distillation stabilizes old group- and patch-level scoring, while a utility-preservation hinge allows evidence identity to change as long as diagnostic usefulness does not regress. Per-task LoRA updates are folded into one shared task-free selector, with replay driven by a compact behavioral memory that stores selector snapshots rather than image or feature tensors.
- We directly measure two complementary forms of selection drift—evidence identity with Jaccard and diagnostic function with utility retention—and show that they are not interchangeable: preserving where a selector looks does not guarantee preserving how useful what it finds remains. On the ConSlide four-cohort benchmark, PathSelect reaches 0.854 ACC, competitive with the strongest published continual result (0.859), while substantially reducing selector forgetting

*corresponding author. This work was supported in part by the National Science and Technology Council, Taiwan under Grant NSTC 112-2221-E-110-047-MY3, 114-2640-E-110-004, and 114-2634-F-006-002.

relative to unprotected sequential learning.

2. RELATED WORK

Evidence selection in WSIs. Classical MIL methods such as AB-MIL, CLAM, and TransMIL [3, 4, 5] aggregate patch features through learned attention, making evidence weighting part of the diagnostic model. HistoSelect [2] instead introduces explicit tissue-aware coarse-to-fine selection, reasoning first over tissue groups and then over patches, conditioned on a per-question query. Recent active-perception methods further learn where to inspect in a WSI [6], but do not study continual retention of the acquired policy. PathSelect adopts the group-to-patch inductive bias as its selection substrate, replaces the per-question query with a fixed task-free tissue vocabulary that provides a stable grouping reference across tasks, and learns the selector under a sequential task stream.

Continual WSI learning. Existing methods preserve diagnostic competence through rehearsal, attention or aggregation regularization, prototypes, or model adaptation. ConSlide [7] introduced rehearsal-based continual WSI analysis on a four-cohort TCGA benchmark; MICIL [8] studied class-incremental MIL; QPMIL-VL [9] used vision–language prototypes on CONCH features; Li et al. [10] distilled MIL attention with a pseudo-bag memory; CoMEL [11] applied low-rank adaptation to MIL aggregators; and MergeSlide [12] merged per-task models with prompt-based task-to-class inference. These methods primarily adapt or preserve learned diagnostic, aggregation, attention, or prototype components. PathSelect instead freezes the diagnostic pathway and makes a hard, budgeted evidence selector the sole learned continual object, measuring both evidence-identity drift and diagnostic-utility drift directly.

Parameter-efficient continual adaptation. LoRA [13] and its continual-learning variants [14, 15, 16, 17] provide parameter-efficient sequential updates through low-rank or modular adaptation. PathSelect uses task-local LoRA only as a fixed-cost consolidation mechanism: each residual is folded into one shared selector at the task boundary, and forgetting is addressed separately through replay, dual-level distillation, and utility preservation. PathSelect thus lies at the intersection of continual WSI learning and budgeted evidence acquisition, with preservation targeted at where the model looks and at how useful the acquired evidence remains.

3. METHOD

3.1. Study object: a frozen diagnostic pathway

Tasks $\tau = 1, \dots, T$ arrive sequentially. A slide is represented by frozen CONCH patch features $\{x_i\}_{i=1}^N$, $x_i \in \mathbb{R}^{512}$, from which the selector chooses an evidence set $\mathcal{P}$ of fixed size $B = 8$. Only the selected set is used for the final diagnostic prediction; during training, additional candidate evaluations serve only to construct the counterfactual supervision of Sec. 3.3. With selector scores s_i for the chosen patches, the slide representation is $z = \sum_{i \in \mathcal{P}} \text{softmax}(s)_i x_i / \|\sum_{i \in \mathcal{P}} \text{softmax}(s)_i x_i\|_2$, and the prediction is the softmax over cosine similarities between z and the frozen class-text embeddings $\{t_c\}$. The embeddings of all $C = 8$ benchmark classes are computed once and form the diagnostic logits throughout training and evaluation (Sec. 4); training uses the labels of the current task. No task identity, adapter bank, memory lookup, or trained diagnostic head is used at test time.

3.2. Hierarchical budgeted selection

Following the tissue-aware coarse-to-fine principle of HistoSelect [2], patches are assigned to groups semantically rather than clustered. Eight fixed tissue prompts are encoded once by the frozen text encoder into $\{p_k\}$; each patch joins the group G_j with $j = \arg \max_k \cos(x_i, p_k)$, and each group is summarized by its prototype $g_j = \text{mean}(x_i \in G_j)$. Two independent two-layer MLPs, the group selector F_g and the patch selector F_p , score groups and patches, respectively. F_g scores the prototypes, $r_j = F_g(g_j)$, and a largest-remainder allocation converts the softmax over the scores of the non-empty groups with remaining capacity into integer quotas $b_j \in \mathbb{N}$ with $\sum_j b_j = B$; other groups receive no quota. F_p scores the members of each group, $s_i = F_p(x_i)$, and the top b_j patches of each group form $\mathcal{P}$. The hierarchy thus answers two questions in turn: *which tissue groups deserve the budget*, and *which patches within those groups deserve the slots*.

3.3. Learning where to look: three within-task signals

The within-task objective is

$$\mathcal{L}_{\text{ev}} = \mathcal{L}_{\text{diag}} + \beta_s \mathcal{L}_{\text{sem}} + \beta_u \mathcal{L}_{\text{util}}, \quad (1)$$

whose three terms supervise the selector at different levels.

Outcome supervision: $\mathcal{L}_{\text{diag}}$. Cross-entropy on the frozen diagnostic logits asks whether the final evidence set answered correctly. It supervises the joint outcome but assigns credit weakly among the many candidate patches.

Semantic supervision: $\mathcal{L}_{\text{sem}}$. A frozen class-text prior scores how diagnostically discriminative each candidate patch appears in the CONCH embedding space: with $z_{ic} = \cos(x_i, t_c)/T$, the prior is $p_i \propto 1 - H(\text{softmax}_c(z_{ic}))/\log C$, and the selector’s score distribution over candidates is softly aligned to it with a KL term. Class-derived information thus enters training through this prior and through the frozen-head diagnostic losses used for $\mathcal{L}_{\text{diag}}$ and for the counterfactual teacher below; none of it is provided to the selector as input at inference. The prior is a weak semantic anchor, not the diagnostic target.

Counterfactual credit: $\mathcal{L}_{\text{util}}$. Let E denote the currently selected set, summarized for this purpose by the equal-weight mean of its patches (a pre-registered approximation of the head’s score-weighted pooling). For each unselected candidate i among the top-256 scored patches, the marginal counterfactual gain

$$u_i = \mathcal{L}_{\text{diag}}(E) - \mathcal{L}_{\text{diag}}(E \cup \{x_i\}) \quad (2)$$

is positive when adding the candidate would reduce the diagnostic loss; it is evaluated by a rank-one update of the pooled representation and is used only to build the teacher, never for prediction. The gains form a no-gradient teacher distribution, and $\mathcal{L}_{\text{util}} = \text{KL}(\text{softmax}(u) \parallel \text{softmax}(s))$ trains the patch selector to rank candidates by measured usefulness. The lowercase u_i is a *candidate-level* teaching signal; the value of the *whole selected set*,

$$U(\mathcal{P}) = \log C - \text{CE}(\mathcal{P}, y), \quad (3)$$

measures how much the complete set improves over a uniform diagnostic state. This distinction between candidate utility u_i and set utility U becomes central across tasks.




Fig. 1. PathSelect overview. Top (solid arrows; training and inference): frozen CONCH patch features are grouped by eight fixed tissue prompts; the group selector F_g turns group scores into integer quotas ($\sum_j b_j = B = 8$), the patch selector F_p keeps the top b_j patches within each group, and the frozen head diagnoses from the selected evidence alone by cosine with the class-text embeddings—inference ends there. Bottom (dashed; training only): each task trains fresh LoRA adapters on the same two MLPs and folds them into one shared selector at the task end; a Selection Memory of 512 behavioral snapshots (scores, indices, utilities; no images or features) drives replay, dual-level distillation, and the utility-preservation hinge.

3.4. One shared selector: LoRA consolidation

For task τ , low-rank LoRA adapters are attached to the four linear layers of F_g and F_p ; the base selector is frozen during the task and only the current adapters receive gradients. At the task boundary the residual of each adapted layer ℓ is folded into its base weight, $W_\tau^{(\ell)} = W_{\tau-1}^{(\ell)} + B_\tau^{(\ell)} A_\tau^{(\ell)}$, an exact rewrite of the effective weight used immediately before, and the adapters are reset for the next task. The parameter count therefore does not grow with T , and inference always uses one shared selector. LoRA consolidation provides a fixed-cost shared-selector parameterization; continual preservation is handled separately by the objectives of Sec. 3.5.

3.5. Keeping looking well: preserving behavior and function

After a task is learned, PathSelect stores a bounded Selection Memory $\mathcal{M}$ of at most 512 behavioral snapshots, filled by reservoir sampling. A snapshot stores an internal sample reference, the task tag, group scores r_{old} (8 values), candidate indices (≤ 256), patch scores s_{old} (≤ 256), and utilities (≤ 256); it contains no raw image or feature tensor, and the 512-entry memory occupies 3.11 MB when serialized. During later tasks, one snapshot is replayed per training step: the slide’s frozen features are reloaded from the training feature store by the sample reference and pass through the same forward path as current slides. Replay therefore assumes authorized training-time access to the pre-extracted feature records, whose storage (19.5 GB for this benchmark) is not included in the memory figure. The con-

tinual objective is

$$\mathcal{L}_{CL} = \lambda_{kd} [\text{KL}(\sigma(r_{old}) || \sigma(r_{new})) + \text{KL}(\sigma(s_{old}) || \sigma(s_{new}))] + \lambda_{eq} \max(0, U_{old} - U_{new}) + \lambda_r \mathcal{L}_{diag}^{\text{rep}}, \quad (4)$$

where σ denotes the softmax over groups and over candidates, respectively; the objective separates three complementary preservation roles.

Behavioral continuity: $\mathcal{L}_{KD}$. Dual-level distillation preserves the old *soft* selection policy—group preferences and patch-score distributions—without requiring the final hard top- B set to be identical.

Functional continuity: $\mathcal{L}_{eq}$. Selection identity may change if an alternative evidence set is at least as useful. The hinge $\max(0, U_{old} - U_{new})$ is a *floor*, not a *ceiling*: regression is penalized, improvement is free. This is the difference between remembering the same evidence and retaining the same evidence-selection competence.

Task competence: replay. Replay applies the ordinary diagnostic loss $\mathcal{L}_{diag}^{\text{rep}}$ to replayed old slides; no replay-specific loss is introduced. The task objective $\mathcal{L}_{total} = \mathcal{L}_{ev} + \mathcal{L}_{CL}$ is optimized over the current task’s LoRA adapters.

4. EXPERIMENTS

4.1. Protocol and measurements

Benchmark. We use the four-cohort TCGA benchmark introduced by ConSlide [7] in the form released by QPMIL-VL [9]: CLAM-tiled 256×256 patches at $10\times$, pre-extracted CONCH features, and ten patient-level folds. Tasks arrive in the reverse order $\text{ESCA} \rightarrow \text{RCC} \rightarrow \text{BRCA} \rightarrow \text{LUNG}$ (LUNG denotes the NSCLC subtype task; the forward order is also reported), each a binary subtype task, for a final eight-class label space. All runs use 5 epochs per task, learning rate 10^{-3} , $B = 8$ (the operating point of the preliminary budget sweep in Sec. 4.3), LoRA rank 4, $\beta_s = \beta_u = 0.1$, and unit λ 's; selector inputs are zero-padded to a common width so that all arms share one architecture and parameter count.

Two protocols. The *comparison protocol* follows the benchmark's CONCH-feature release [9]: ten folds, one run per fold with the seed equal to the fold index, and the metrics average accuracy (ACC), masked ACC (task-IL), forgetting [18], and backward transfer (BWT) [19]. The *ablation protocol* fixes fold 1 (2,273 training slides; test sizes 15/76/93/95) and varies five seeds; comparisons are paired by seed with win counts, 5/5 is called systematic and 4/5 directional, and no p -values are reported at this seed count. Ablation decisions followed two-sided criteria fixed before the corresponding runs, the existing design is retained on a split, and one pre-specified expectation that the data refuted is reported as measured. The controlled variants are sequential fine-tuning of the selector (SeqFT), LoRA with boundary merging only, replay, replay+distillation, and full PathSelect (replay+distillation+utility hinge); per-task specialists and joint offline training are references rather than deployable continual baselines.

Measurements. Across our controlled variants the eight-way class-text head is fixed at every stage, so differences arise from selector updates and incoming task data rather than from head updates. Class-IL accuracy takes the argmax of this head at every stage, so predictions may fall on classes not yet seen; restricting the argmax to the classes seen so far, as accumulating heads do, leaves final accuracy unchanged and changes forgetting by at most 0.007 in our ten-fold runs, indicating that the head convention has little effect on the reported comparison. Task-IL accuracy restricts the argmax to the task's own pair; leakage is the fraction predicted into another task's class set. Selection is measured separately: selection Jaccard, $|\mathcal{P}_{\text{own}} \cap \mathcal{P}_{\text{final}}|/|\mathcal{P}_{\text{own}} \cup \mathcal{P}_{\text{final}}|$, is the hard identity retention between the set selected immediately after learning a task and the set selected at the end (an evaluation quantity, not the distillation loss), and functional retention is $\Delta U = U_{\text{final}} - U_{\text{own}}$.

4.2. Where does PathSelect stand among published methods?

Table 1 places PathSelect in the continual WSI landscape on the ConSlide four-cohort benchmark, in the format of a landscape comparison (references, regularization, rehearsal, WSI-specific, and vision-language rows); quoting published entries follows the practice of the benchmark's own tables. PathSelect reaches 0.854 ± 0.044 ACC, 0.925 ± 0.019 masked ACC, and 0.060 ± 0.041 forgetting: the second-highest ACC among the continual methods in the table, 0.005 below the strongest published result (0.859), and above every regularization, rehearsal, ConSlide, and prompt-based row; the offline joint-training reference reaches 0.908. ConSlide reports slightly lower forgetting (0.058 vs. 0.060) at substantially lower ACC (0.499), so we do not claim the lowest forgetting. Rerunning the strongest method with its released code and the paper's settings reproduces its published results in both orders to within 0.01 (reverse

0.868 ± 0.046 , forward 0.884 ± 0.033), which cross-validates the data, folds, metric definitions, and procedure; relative to the published and reproduced reverse values, PathSelect is 0.005 and 0.014 lower in ACC, within one standard deviation of either, with comparable forgetting (0.060 vs. 0.064). We therefore describe PathSelect as competitive with the strongest published method rather than above or below it. What differs is the adaptation cost and the inference structure: PathSelect adapts 16.4k selector parameters per task, versus 0.365M learnable parameters reported for the strongest method ($22.3\times$ fewer) and 0.5–39M for the MIL-based rows—counts that refer to different adapted components and are reported as context—with no prototype pool or task-specific module at inference and a 3.1 MB behavioral memory (a 30-WSI rehearsal buffer of features would occupy about 180 MB at 6.1 MB per slide). The frozen head with mean pooling over all patches reaches 0.679 ACC, a 17.5-point gap to PathSelect relative to this no-selection reference.

4.3. Ablations

Which part matters, and does it hold in both task orders? (Table 2) Learned selection is itself meaningful: in a preliminary budget sweep with a learned flat selector (inference only; seven budgets $\times$ four tasks), learned selection beat random selection in all 28 cells and peaked at $B = 8$ (0.8797 vs. 0.6607). Table 2 then removes one part of PathSelect at a time under the comparison protocol. On the flat substrate, removing continual preservation altogether drops ACC from 0.830 to 0.452 and raises forgetting from 0.090 to 0.601, in every fold on every metric. Selector-only fine-tuning nevertheless remains above the published full-model fine-tuning reference (0.452 vs. 0.234); because the implementations are not controlled, we treat this comparison as context rather than attribution. Replay recovers most of the accuracy (0.821); distillation and the utility hinge then add 0.8 ACC points (7/10 folds) and remove 2.4 forgetting points (8/10); the hierarchy adds 2.5 ACC points (8/10) and removes 2.9 forgetting points (7/10) under the canonical reverse order. Under the forward order the chain is $0.529 \rightarrow 0.841$ (replay) $\rightarrow 0.841$ (full, flat) $\rightarrow 0.811$ (full, hierarchical): preservation is again decisive (10/10 folds on every metric), distillation and the hinge no longer add accuracy (5/10) but still reduce forgetting (−0.9 points, 8/10), and the hierarchy costs 3.0 points (9/10). Across both orders, what is robust is the preservation framework itself and the forgetting reduction from distillation and utility preservation; their accuracy increment and the substrate's benefit are order-dependent, and we report both rather than select an order. The hierarchy is retained as the pre-registered choice on the canonical order.

Do the three preservation losses do different jobs? (Table 3)

Replay is the largest single contributor ($0.447 \rightarrow 0.778$) because it restores task attribution: with distillation alone, leakage stays at 0.323, three times the full method—in one seed 59 of 76 renal slides land in the lung classes—so distillation preserves *how* the selector scores but not *which task* the evidence belongs to. The utility hinge alone reaches 0.809; its increment on top of replay and distillation is order-sensitive and is reported as such above. Under the hierarchy, removing the group level of distillation costs 3.95 task-IL and 3.71 class-IL points (5/5), so quota-level and patch-level preservation act at different resolutions. No single loss or pair matches the full set.

What does accuracy alone not show? (Table 4) Unprotected selectors retain almost none of their original evidence (Jaccard $0.0023/0.0010$) and lose old-task utility by an order of magnitude more than full PathSelect (ΔU $-220/-301$ vs. -16.8). LoRA merging alone shows no systematic difference from full fine-tuning (3/5): merging is the deployment substrate, not the preservation

Table 1. Comparison on the ConSlide four-cohort benchmark [7] (CONCH features, reverse order ESCA→RCC→BRCA→LUNG, ten-fold CV, mean±sd). Published rows are quoted from the most recent published table on this benchmark (Table 2 of [9]) and were not rerun by us; PathSelect uses the identical public split files and metric definitions, while training implementations and hyperparameters follow each method. Unlike the cited MIL baselines, PathSelect adapts only the evidence selector and keeps the diagnostic pathway frozen (a cosine head fixed to all eight class prompts from the first task), so parameter counts characterize adaptation cost rather than capacity-matched architectures. Buffer sizes in WSIs; PathSelect’s Selection Memory holds 512 behavioral snapshots (3.1 MB, excluding the feature store required for replay). Forward-order results are in Table 2. [‡]Our released-code reproduction matches the reported results within 0.01 in both orders; settings-level details (class-ensemble ordering, mini-batch, hardware) are documented in the released repository.

Type	Method	ACC↑	Forgetting↓	BWT↑	Masked ACC↑	Buffer
<i>Published methods—values quoted from [9]</i>						
Reference	JointTrain (offline reference)	0.908±.022	—	—	0.937±.022	—
Reference	FineTune (lower)	0.234±.008	0.927±.023	−0.927±.023	0.803±.060	0
Regularization	EWC [20]	0.235±.011	0.928±.020	−0.928±.020	0.833±.069	0
Regularization	LwF [21]	0.236±.016	0.908±.030	−0.908±.030	0.900±.041	0
Rehearsal	A-GEM [22]	0.536±.047	0.527±.067	−0.527±.067	0.872±.026	30
Rehearsal	ER-ACE [23]	0.703±.049	0.281±.062	−0.279±.063	0.889±.041	30
Rehearsal	DER++ [24]	0.684±.055	0.310±.069	−0.307±.072	0.910±.043	30
Rehearsal	ER [25]	0.644±.028	0.387±.050	−0.386±.049	0.901±.035	30
WSI CL	ConSlide [7]	0.499±.025	0.058±.032	−0.021±.039	0.854±.039	30
VLM	AttriCLIP [26]	0.694±.058	0.207±.063	−0.207±.063	0.861±.019	0
VLM	MI-Zero [27]	0.839±.034	—	—	0.909±.019	0
VLM WSI CL	QPMIL-VL [9]	0.859±.032	0.064±.031	−0.064±.031	0.925±.018	0
<i>Reproduction check—our run of the released code on the same folds[‡]</i>						
VLM WSI CL	QPMIL-VL (reproduced)	0.868±.046	0.064±.054	−0.064±.054	0.935±.018	0
<i>Our method—run under the same splits and metrics</i>						
Selection CL	PathSelect (ours)	0.854±.044	0.060±.041	−0.056±.038	0.925±.019	512 snap. (3.1 MB)

Table 2. Leave-out chain in both task orders (ConSlide benchmark, ten-fold CV, mean±sd). Reverse = ESCA→RCC→BRCA→LUNG; forward = the opposite. Fold-paired win counts are given in the text. Last two rows: the strongest published method, as reported in [9] and as rerun by us with its released code.

Configuration	Reverse		Forward	
	ACC↑	Forg.↓	ACC↑	Forg.↓
Selector fine-tuning (no preservation)	.452±.071	.601	.529±.077	.503
+ replay of snapshots	.821±.036	.114	.841±.019	.064
+ distillation + utility hinge (flat)	.830±.029	.090	.841±.043	.055
+ hierarchical selector (PathSelect)	.854±.044	.060	.811±.029	.061
Frozen head, mean pooling (no selection)	.679±.032	—	—	—
QPMIL-VL (reported)	.859±.032	.064	.890±.021	.027
QPMIL-VL (reproduced, released code)	.868±.046	.064	.884±.033	.038

mechanism. Distillation without the hinge retains slightly more identity (0.1752 vs. 0.1613) yet is less accurate and forgets more: preserving *where* the policy looks does not secure *how useful* what it finds is—the gap the utility hinge closes. Three further interventions raised Jaccard without improving diagnosis: warm-starting task 1 with full-parameter training, damping each fold-in to half, and composing independently trained residuals post hoc.

Are the update-protocol choices necessary? Each probe was decided by a rule fixed before the run. Warm start and damped merging showed no systematic benefit. A single adapter never reset lost 3.54 class-IL points on the flat substrate (4/5) and became a trade-off under the hierarchy (systematic task-IL edge for fresh adapters, systematically lower leakage for the single adapter); fresh adapters are retained. Post-hoc composition refuted a pre-specified expectation: independently trained residuals, summed once, beat the bare sequential substrate on every metric in every seed, consistent with strong interference in unprotected sequential updates (cf. task

Table 3. Preservation-component ablation (flat, fold 1, 5-seed means). Replay restores old-task competence, the utility-preservation hinge preserves functional utility, and distillation stabilizes selection behavior; no single term or pair matches the full set.

Replay	Distill.	Utility	Class-IL↑	Task-IL↑	Leak.↓
			.447	.811	.476
	✓		.600	.853	.323
		✓	.809	.885	.091
✓			.778	.907	.104
✓	✓		.797	.897	.117
✓	✓	✓	.824	.915	.101

arithmetic [28]), yet trailed the full method by 13.1 points (5/5) because independence excludes replay and distillation targets require an accumulated model; porting MergeSlide’s orthogonal-projection merging [12] to our selector did not close this gap (0.709±.035, no systematic difference from plain summation). With 128 memory entries PathSelect still outperformed replay with 512 (task-IL +3.06, 5/5), reported for task-IL and this range only. A task-conditioned query, a stateful multi-round selector, and a group-level semantic prior failed their pre-specified criteria and were removed.

Table 4. Selection-level metrics under the ablation protocol (flat, fold 1, mean over 5 seeds); what accuracy alone cannot show.

Method	Class-IL $\uparrow$	Sel. Jaccard $\uparrow$	Leakage $\downarrow$	$\Delta U \uparrow$
Sequential fine-tuning	0.4774	0.0023	0.4408	−220
LoRA merge only	0.4466	0.0010	0.4756	−301
+ replay	0.7778	0.0864	0.104	−21.2
+ distillation	0.7972	0.1752	0.117	−31.9
PathSelect (full)	0.8239	0.1613	0.1005	−16.8

5. DISCUSSION AND LIMITATIONS

PathSelect suggests that continual learning in budgeted perception should distinguish two failure modes that accuracy alone conflates: a policy may change *where* it looks, and the new evidence may or may not remain *functionally equivalent*. The quantities in this paper therefore play different roles and should not be collapsed into one notion. Distillation preserves a soft behavior distribution, whereas Jaccard measures hard identity after the fact; candidate utility u_i teaches which patch is useful now, whereas set utility U evaluates whether the selected evidence remains useful across time; and the utility-preservation hinge uses U as a lower bound, deliberately allowing better alternative evidence.

The study also shows what is *not* sufficient. LoRA merging alone does not protect the selector. Warm start, damped merging, and post-hoc composition each increase selection Jaccard without improving diagnosis (Sec. 4.3), so “choose the same patches” is not a complete continual-learning objective: selection stability is not sufficient for diagnostic preservation, and identity and function must be measured separately. This is why behavioral and functional preservation are treated as complementary constraints rather than redundant regularizers.

Our claims are bounded in five ways. (i) The benchmark uses four organ-separated TCGA tasks, one frozen foundation model, one main budget ($B = 8$), known task boundaries during training, and five seeds or ten folds; the tasks are highly separable (a linear probe separates them at 98.21%), so harder within-organ or mixed-task streams may yield different conclusions. (ii) The hierarchical substrate’s advantage and the accuracy increment of distillation and the utility hinge over replay are order-dependent (Table 2), while their forgetting reduction holds in 8/10 folds in both orders; all pre-specified comparisons were made on the canonical reverse order and forward-order results are reported as measured. (iii) The frozen head assumes that the full class vocabulary is available as text from the start, even though slides of future tasks are not. (iv) The memory is compact and stores no image or feature tensors, but replay requires training-time access to the feature store, and no formal privacy guarantee is claimed. (v) The fold-to-fold spread of our runs and of the reproduced baseline (sd 0.03–0.05) exceeds the gaps between the top methods, so single-split rankings on this benchmark should be read with that variance in mind. Finally, PathSelect is a one-shot evidence-acquisition policy rather than a multi-step navigation agent; its task-free shared selector can serve as a foundation for continual evidence-navigation systems, but sequential, stateful acquisition is left to future work.

6. CONCLUSION

PathSelect reframes continual WSI learning around an under-measured question: after learning new diagnostic tasks, does the model still know where to look? By freezing the diagnostic path-

way, it isolates the evidence selector as the continual-learning object; within tasks, semantic and counterfactual signals teach the selector to find useful evidence, and across tasks a single shared selector is preserved at two levels—distillation maintains selection behavior, while a utility-preservation hinge allows evidence identity to change without letting usefulness regress—with replay maintaining old-task competence. On a public four-cohort benchmark the method is competitive with the strongest published result at a fraction of the adaptation cost and with task-free inference, and direct selection-level measurements show that evidence identity and evidence utility drift differently. Continual learning for budgeted perception should therefore preserve not only what a model predicts, but also the policy by which it acquires the evidence used to predict.

Compliance with Ethical Standards

This study uses publicly available, de-identified whole-slide images from The Cancer Genome Atlas (TCGA), released under its data-use policies; no new human-subject data were collected and no additional ethical approval was required. Funding is acknowledged on the first page.

7. REFERENCES

- [1] Ming Y. Lu, Bowen Chen, Drew F. K. Williamson, Richard J. Chen, et al., “A visual-language foundation model for computational pathology,” *Nature Medicine*, 2024.
- [2] Wentao Huang, Weimin Lyu, Peiliang Lou, Qingqiao Hu, Xiaoling Hu, Shahira Abousamra, Wenchao Han, Ruifeng Guo, Jiawei Zhou, Chao Chen, and Chen Wang, “Act like a pathologist: Tissue-aware whole slide image reasoning,” in *CVPR*, 2026.
- [3] Maximilian Ilse, Jakub Tomczak, and Max Welling, “Attention-based deep multiple instance learning,” in *ICML*, 2018.
- [4] Ming Y. Lu, Drew F. K. Williamson, Tiffany Y. Chen, Richard J. Chen, Matteo Barbieri, and Faisal Mahmood, “Data-efficient and weakly supervised computational pathology on whole-slide images,” *Nature Biomedical Engineering*, 2021.
- [5] Zhuchen Shao, Hao Bian, Yang Chen, Yifeng Wang, Jian Zhang, Xiangyang Ji, and Yongbing Zhang, “Transmil: Transformer based correlated multiple instance learning for whole slide image classification,” in *NeurIPS*, 2021.
- [6] Jingyun Chen, Fengxiang Liu, Linghan Cai, Songhan Jiang, Shenjin Huang, Hongpeng Wang, Lequan Yu, and Yongbing Zhang, “Agentic visual reasoning in whole-slide pathology images via active perception,” *arXiv preprint arXiv:2608.08648*, 2026.
- [7] Yanyan Huang, Weiqin Zhao, Shujun Wang, Yu Fu, Yuming Jiang, and Lequan Yu, “Conslide: Asynchronous hierarchical interaction transformer with breakup-reorganize rehearsal for continual whole slide image analysis,” in *ICCV*, 2023, pp. 21349–21360.
- [8] Pablo Meseguer, Rocío Del Amor, and Valery Naranjo, “MICIL: Multiple-instance class-incremental learning for skin cancer whole slide images,” *Artificial Intelligence in Medicine*, vol. 152, pp. 102870, 2024.

- [9] Jiaxiang Gou, Luping Ji, Pei Liu, and Mao Ye, “Queryable prototype multiple instance learning with vision-language models for incremental whole slide image classification,” in *AAAI*, 2025, pp. 3158–3166.
- [10] Xianrui Li, Yufei Cui, Jun Li, and Antoni B. Chan, “Advancing multiple instance learning with continual learning for whole slide imaging,” in *CVPR*, 2025, pp. 20800–20809.
- [11] Byung Hyun Lee, Wongi Jeong, Woojae Han, Kyoungbun Lee, and Se Young Chun, “Continual multiple instance learning with enhanced localization for histopathological whole slide image analysis,” in *ICCV*, 2025.
- [12] Doanh C. Bui, Trinh T. L. Vuong, Yen Dang, and Jin Tae Kwak, “MergeSlide: Continual model merging and task-to-class prompt-aligned inference for lifelong learning on whole slide images,” in *WACV*, 2026, pp. 4859–4868.
- [13] Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen, “Lora: Low-rank adaptation of large language models,” in *ICLR*, 2022.
- [14] Yan-Shuo Liang and Wu-Jun Li, “Inflora: Interference-free low-rank adaptation for continual learning,” in *CVPR*, 2024.
- [15] Yichen Wu et al., “Sd-lora: Scalable decoupled low-rank adaptation for class incremental learning,” in *ICLR*, 2025.
- [16] Jiangpeng He, Zhihao Duan, and Fengqing Zhu, “Cl-lora: Continual low-rank adaptation for rehearsal-free class-incremental learning,” in *CVPR*, 2025.
- [17] Pin-Zhen Chen and Huei-Fang Yang, “Flexem: Task-free online continual learning with flexible expansion and merging,” in *ICIP*, 2026, to appear; verify final title/venue string at camera-ready.
- [18] Arslan Chaudhry, Puneet K. Dokania, Thalaiyasingam Ajanthan, and Philip H. S. Torr, “Riemannian walk for incremental learning: Understanding forgetting and intransigence,” in *ECCV*, 2018.
- [19] David Lopez-Paz and Marc’Aurelio Ranzato, “Gradient episodic memory for continual learning,” in *NeurIPS*, 2017.
- [20] James Kirkpatrick et al., “Overcoming catastrophic forgetting in neural networks,” *PNAS*, 2017.
- [21] Zhizhong Li and Derek Hoiem, “Learning without forgetting,” *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 40, no. 12, pp. 2935–2947, 2017.
- [22] Arslan Chaudhry, Marc’Aurelio Ranzato, Marcus Rohrbach, and Mohamed Elhoseiny, “Efficient lifelong learning with A-GEM,” in *ICLR*, 2019.
- [23] Lucas Caccia, Rahaf Aljundi, Nader Asadi, Tinne Tuytelaars, Joelle Pineau, and Eugene Belilovsky, “New insights on reducing abrupt representation change in online continual learning,” in *ICLR*, 2022.
- [24] Pietro Buzzega, Matteo Boschini, Angelo Porrello, Davide Abati, and Simone Calderara, “Dark experience for general continual learning: a strong, simple baseline,” in *NeurIPS*, 2020.
- [25] Arslan Chaudhry, Marcus Rohrbach, Mohamed Elhoseiny, Thalaiyasingam Ajanthan, Puneet K. Dokania, Philip H. S. Torr, and Marc’Aurelio Ranzato, “On tiny episodic memories in continual learning,” *arXiv preprint arXiv:1902.10486*, 2019.
- [26] Runqi Wang, Xiaoyue Duan, Guoliang Kang, Jianzhuang Liu, Shaohui Lin, Songcen Xu, Jinhu Lü, and Baochang Zhang, “AttriCLIP: A non-incremental learner for incremental knowledge learning,” in *CVPR*, 2023, pp. 3654–3663.
- [27] Ming Y. Lu, Bowen Chen, Andrew Zhang, Drew F. K. Williamson, Richard J. Chen, Tong Ding, Long Phi Le, Yung-Sung Chuang, and Faisal Mahmood, “Visual language pre-trained multiple instance zero-shot transfer for histopathology images,” in *CVPR*, 2023, pp. 19764–19775.
- [28] Gabriel Ilharco, Marco Tulio Ribeiro, Mitchell Wortsman, Suchin Gururangan, Ludwig Schmidt, Hannaneh Hajishirzi, and Ali Farhadi, “Editing models with task arithmetic,” in *ICLR*, 2023.