

Connect REST API Developer Guide

Q

Search

⌕

Winter '26 (API version 6...

Latest

When to Use Connect REST API

Connect REST API Architecture

Connect REST API Limits

Build the Resource URL

Send HTTP Requests

HTTP Request Flow and a Response Body

Inputs and Binary File Upload Examples

Wildcards

> Specify Response Sizes

Response Body Encoding

Status Codes and Error Responses

< OAuth and Connect REST API

Web Server OAuth Authentication Flow

User-Agent OAuth Authentication Flow

Tokens

Request Static Assets and Post Forms Directly from HTML

Connect REST API Developer Guide / Introduction / Connect REST API Architecture

Connect REST API Architecture

To use Connect REST API, understand a few characteristics of its architecture, like how to authenticate, and which data formats it supports.

Authentication

Connect REST API uses [OAuth 2.0](#).

Salesforce is accessed securely using HTTPS.

CORS (Cross-Origin Resource Scripting)

Cross-Origin Resource Sharing (CORS) allows web browsers to request resources from other origins. For example, using CORS, the JavaScript for a web application at `https://www.example.com` can request a resource from `https://www.salesforce.com`. To allow access to supported Salesforce APIs, Apex REST resources, and Lightning Out from JavaScript code in a web browser, add the requesting origin to your Salesforce CORS allowlist. See [Perform Cross-Origin Requests from Web Browsers](#).

Default HTML entity encoding

Responses are minimally HTML entity-encoded by default. Clients can request raw (unencoded) output. Set the `X-Header-Entity-Encoding` HTTP header in a request to `false`. For more information, see [Response Body Encoding](#).

JSON and XML support

The JavaScript Object Notation (JSON) format is supported with UTF-8. Date-time information is in [ISO 8601](#) format.

XML serialization is similar to SOAP API. XML requests are supported in UTF-8 and UTF-16, and XML responses are provided in UTF-8.

Responses are in JSON format by default. To specify XML, use the HTTP header `Accept: application/xml`. (To specify JSON, use `Accept: application/json`.)

You can append either `.json` or `.xml` to the URI of any resource to specify how the return is formatted. For example, `/chatter/feeds/filter/me/001/feed-elements.xml`.

Note

Not all features support XML.

Localized names and times

Connect REST API localizes both the names and datetimes to the locale setting of the user. Users set their locale in their personal information. If the user hasn't set their locale, Connect REST API uses the default locale for the organization.

Clients can use any locale available in the organization to override the default locale. To override the locale for any API request, use the `Accept-Language` HTTP header.

For orgs created in Summer '23 and later, the language specified in the `Accept-Language` HTTP header must be the same as specified in a `language` query parameter.

Note

ISO 8601 dates are always in GMT.

Salesforce ID length

Salesforce IDs in response bodies are always 18-character IDs. In request bodies, you can use either 15-character IDs or 18-character IDs.

UI Themes

Clients can use the `X-Header-Theme` HTTP header to specify a UI theme for any API request. There are two themes, each with their own set of motif icons: `Classic` and `Salesforce1`. Theme names are case-sensitive.

Method overriding

To override an HTTP method if you use an HTTP library that doesn't allow overriding or setting an arbitrary HTTP method name, use the request parameter `_HttpMethod`.

```
POST https://instance_name/services/data/v65.0/chatter/
/chatter/users/me/conversations/03MD0000000008KMAQ
?_HttpMethod=PATCH&read=true
```


Note

The `_HttpMethod` parameter is case-sensitive. Use the correct case for all values.

DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

Share your feedback



DEVELOPER CENTERS

- [Heroku](#)
- [MuleSoft](#)
- [Tableau](#)
- [Commerce Cloud](#)
- [Lightning Design System](#)
- [Einstein](#)
- [Quip](#)

POPULAR RESOURCES

- [Documentation](#)
- [Component Library](#)
- [APIs](#)
- [Trailhead](#)
- [Sample Apps](#)
- [Podcasts](#)
- [AppExchange](#)

COMMUNITY

- [Trailblazer Community](#)
- [Events and Calendar](#)
- [Partner Community](#)
- [Blog](#)
- [Salesforce Admins](#)
- [Salesforce Architects](#)