

Question 1

Correct

Marked out of 3.00

🚩 Flag question

Write a program to read two integer values and print true if both the numbers end with the same digit, otherwise print false. Example: If 698 and 768 are given, program should print true as they both end with 8. Sample Input 1 25 53 Sample Output 1 false Sample Input 2 27 77 Sample Output 2 true

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int main(){
3      int x,y;
4      scanf("%d",&x);
5      scanf("%d",&y);
6      if(x%10==y%10){
7          printf("true"); }
8      else{
9          printf("false");
10     }
11 }
12
```

	Input	Expected	Got	
✓	25 53	false	false	✓
✓	27 77	true	true	✓

Passed all tests! ✓

Question **2**

Correct

Marked out of 5.00

🚩 [Flag question](#)

Objective

In this challenge, we're getting started with conditional statements.

Task

Given an integer, ***n***, perform the following conditional actions:

- If ***n*** is odd, print **Weird**
- If ***n*** is even and in the inclusive range of **2** to **5**, print **Not Weird**
- If ***n*** is even and in the inclusive range of **6** to **20**, print **Weird**

- If n is even and greater than **20**, print **Not Weird**

Complete the stub code provided in your editor to print whether or not n is weird.

Input Format

A single line containing a positive integer, n .

Constraints

- $1 \leq n \leq 100$

Output Format

Print Weird if the number is weird; otherwise, print Not Weird.

Sample Input 0

3

Sample Output 0

Weird

Sample Case 1: $n = 24$

$n > 20$ and n is even, so it isn't weird. Thus, we print **Not Weird**.

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int main(){
3      int n;
4      scanf("%d",&n);
5      if(n%2==0) {
6          if(n>=2 && n<=5) {
7              printf("Not Weird
8          if(n>=6 && n<=20) {
9              printf("Weird"); }
10         if(n>20) {
11             printf("Not Weird
12     else {
13         printf("Weird"); }
14     return 0;
15 }
16
17
```

	Input	Expected	Got	
✓	3	Weird	Weird	✓
✓	24	Not Weird	Not Weird	✓

Passed all tests! ✓

Question 3

Correct

Marked out of 7.00

🚩 Flag question

Three numbers form a Pythagorean triple if the sum of squares of two numbers is equal to the square of the third. For example, 3, 4 and 5 form a Pythagorean triple, since $3^2 + 4^2 = 25 = 5^2$. You are given three integers, a, b, and c. They need not be given in increasing order. If they form a Pythagorean triple, then print "yes", otherwise, print "no". Please note that the output message is in small letters.

Sample Input 1 3 5 4 Sample Output 1 yes

Sample Input 2 5 8 2 Sample Output 2 no

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main() {
3     int a,b,c;
4     scanf("%d",&a);
5     scanf("%d",&b);
6     scanf("%d",&c);
7     if(a*a+b*b==c*c) {
8         printf("yes"); }
9     else if(a*a+c*c==b*b) {
10        printf("yes"); }
11    else if(b*b+c*c==a*a) {
12        printf("yes"); }
13    else {
14        printf("no");}
15    return 0;
16 }
```

	Input	Expected	Got	
✓	3 5 4	yes	yes	✓
✓	5 8 2	no	no	✓

Passed all tests! ✓