

Type text to search here...

DNS Quiz

Go to comments

Result of DNS Quiz:

Total Questions	Full Score	Passing Rate	Your Score	Correct Answer Percentage	Elapsed
4	50	80%	50	100%	00:00:30

Congratulations!

You passed this test!

If you want to retake this quiz, please press Ctrl + F5 on Windows or press CMD + R on Mac.

Your answers are shown below:

Question 1

How does a router behave when configured with the default DNS lookup settings, and a URL is entered on the CLI?

- **A. attempts to query a DNS server on the network.**
- B. prompts the user to specify the desired IP address.
- C. continuously attempts to resolve the URL until the command is cancelled.
- D. initiates a ping request to the URL.

Explanation

By default, domain lookup function is enabled on the router so it treats every unrecognized command as a hostname, attempts to make a telnet connection to that which, in turn, attempts to resolve a hostname to IP address by querying the DNS server.
Here is a typical sample.
R1#xyz
Translating “xyz”…domain server (255.255.255.255)
Translating “xyz”…domain server (255.255.255.255) (255.255.255.255)
Translating “xyz”…domain server (255.255.255.255)
% Unknown command or computer name, or unable to find computer address

Note: In order to save some time we can disable DNS lookup by the “no ip domain lookup” global command.

Question 2

What facilitates a Telnet connection between devices by entering the device name?

- A. syslog
- B. NTP
- C. SNMP
- **D. DNS lookup**

Explanation

Your router can be configured to use DNS lookups if we wish to use the ping or traceroute commands with a host name rather than an IP address. For example:

```
R1(config)#ip domain-lookup
R1(config)#ip name-server 10.10.10.1
```

Then we can Telnet or ping to it:

```
Router# ping www.cisco.com
Translating 'www.cisco.com'...domain server (10.10.10.1) [OK]
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 198.133.219.25, timeout is 2 seconds:
!!!!!
```

Reference: https://www.cisco.com/c/en/us/support/docs/ip/domain-name-system-dns/24182-reversedns.html

Note: In the above example, 10.10.10.1 is not the IP address of www.cisco.com. This IP address is just the DNS Name Server to resolve “www.cisco.com” to the public IP address “198.133.219.25”.

Note:

By default, any single word entered on an IOS device that is not recognized as a valid command is treated as a hostname to which you want to telnet. The device will try to translate that word to an IP address in a process that can last about a minute.
Consider the following example:

```
R1#test
Translating 'test'...domain server (255.255.255.255)
% Unknown command or computer name, or unable to find computer address
```

In the output above we typed an unrecognized command “test”. The router entered the DNS resolution process which lasted about a minute. This can be annoying and this is why this feature is often turned off, especially in the lab environments.
If you don’t need to have a DNS server configured for your router, you can use the “no ip domain-lookup” command to disable the DNS translation process:

```
R1(config)#no ip domain-lookup
```

Now, if I mistype a command, the router will not perform a DNS resolution process:

```
R1#test
Translating 'test'
% Unknown command or computer name, or unable to find computer address
R1#
```

Question 3

Which command must be present in a Cisco Device configuration to enable the device to resolve an FQDN?

- A. ip domain-name

- **B. ip domain-lookup**
- C. ip name-server
- D. ip host

Explanation

FQDN stands for Fully Qualified Domain Name. The FQDN represents the absolute address of the internet presence. “Fully qualified” refers to the unique identification that guarantees that all of the domain levels are specified. The FQDN contains the host name and domain, including the top level domain, and can be uniquely assigned to an IP address. For example:

R1.9tut.com.

The command “ip domain-lookup” enables DNS-based host name-to-address translation. This command is enabled by default.

Question 4

What are two roles of Domain Name Services (DNS)? (Choose two)

- A. builds a flat structure of DNS names for more efficient IP operations
- B. improves security by protecting IP addresses under Fully Qualified Domain Names (FQDNs)
- **C. allows a single host name to be shared across more than one IP address**
- **D. enables applications to identify resources by name instead of IP address**
- E. encrypts network traffic as it travels across a WAN by default

Explanation

An example of DNS is described below:

When you attempt to go to a domain name such as 9tut.com, your browser will instruct your computer to do a DNS lookup on that domain name. This DNS lookup will query a DNS resolver (for example Google at 8.8.8.8). Once the resolver responds, the computer will usually choose the first IP in the response and use that for the connection. In the case of multiple IP addresses, the DNS server will respond with multiple IP addresses and the first IP will usually be used for the request. Due to how most DNS resolvers work, the order of IP addresses usually changes for each request.

Comments (4) Comments

1. ltholt25
   April 22nd, 2021

   “Which command must be present in a Cisco Device configuration to enable the device to resolve an FQDN?”

   answer: ip domain-lookup

   I consider this farcical. You say in your own explanation that ip domain-lookup is enabled by default on routers. Therefore, why would it be present in the running configuration of the router? Realistically, you’d need ip name-server x.x.x.x in the running config to specify where to query for IP to FQDN resolutions

2. john capper
   December 14th, 2021

Chill out!!Farcical indeed….all it’s saying is lookup shouldn’t be disabled, I think.

3. Manul
   August 6th, 2022

   @Itholt25 your suggestion is correct, but even though the devices has “ip name-server x.x.x.x” in its config and if “ip domain lookup” is missing in the config the device dosnt care to look into the DNS server. Therefore IP DOMAIN LOOKUP is the correct answer.

4. PCB
   July 5th, 2024

   running the “show running-config all” command and you’ll notice that Cisco hides a bunch of hidden default configurations that don’t show up under just a “show running-config”

Add a Comment

Name

Submit Comment

Subscribe to comments feed

QoS Quiz DAI Questions

Premium Member Zone

Welcome Darène MAYISSA!

- Welcome Premium Member!
- CCNA - New Questions Part 5
- CCNA - New Questions Part 6
- CCNA - New Questions Part 7
- CCNA - New Questions Part 8
- CCNA - New Questions Part 9
- CCNA - New Questions Part 10
- CCNA - New Questions Part 11
- CCNA - New Questions Part 12
- CCNA - New Questions Part 13
- CCNA - New Questions Part 14
- CCNA - New Questions Part 15
- CCNA - New Questions Part 16
- Composite Quizzes
- === New CCNA v1.1 Lab Sims (very important) ===
- Voice VLAN Configuration Sim 2
- Voice VLAN & LLDP Sim
- Allowed, Native VLAN & LACP Sim
- Static Routing Configuration Sim 4
- IPv4 and IPv6 Connectivity Sim
- VLAN & CDP Sim 2
- IPv4 and IPv6 Assignment Sim
- VLAN CDP & LLDP Sim
- OSPF Configuration Sim 2
- OSPF Configuration Sim 3

- Trunking & LACP Sim
- VLAN Configuration Sim
- Allowed, Native VLAN & LACP Sim 2
- 802.1Q Trunking & LACP
- IPv4 and IPv6 Assignment Sim 2
- 802.1Q Trunking, Native VLAN & LACP
- Static Routing Configuration Sim 5
- Static Routing Configuration Sim 6
- PAT, NTP & DHCP Relay Sim
- OSPF DR Sim
- NACL DHCP Snooping 3
- NAT DHCP SSH Sim
- ==== Lab Sims for CCNA (although they are rather old but please learn all of them too) ====
- IP Services Sim Version 2
- OSPF Configuration Sim
- LACP Configuration Sim
- Voice VLAN Configuration Sim
- VLAN and Trunking Configuration Sim
- Named Access-list & Port Security Sim
- Named Access-list & DHCP Snooping Sim
- VLAN and CDP Sim
- IPv4 and IPv6 Deployment Sim
- Static Routing Configuration Sim 3
- VLAN & LLDP Sim
- IPv6 Static Routing Sim
- Named Access-list & DHCP Snooping Sim 2
- ISL Trunking and LACP Sim
- === Below Sims are old and retired so you do not need to learn them ===
- Static Routing Configuration Sim 2
- IP Services Sim
- Static Routing Configuration Sim

CCNA Training

- CCNA Knowledge
- CCNA Tutorials, Practice Labs & Lab Challenges
- Spine-Leaf Architecture Tutorial
- Generative AI vs Predictive AI Tutorial
- REST API Tutorial
- Network Time Protocol (NTP) Tutorial
- DHCP Snooping Tutorial
- What is SDN?
- How a router makes a forwarding decision
- Configure SSH for Remote Access on Cisco Router
- Key Security Concepts Tutorial
- Forwarding per-hop behavior (PHB) for QoS Tutorial
- Port Security Tutorial
- Puppet Tutorial
- Chef Tutorial
- Ansible Tutorial
- JSON Tutorial
- Layer 2 Threats and Security Features
- AAA TACACS+ and RADIUS Tutorial
- STP Root Port Election Tutorial
- TCP and UDP Tutorial
- WAN Tutorial
- DHCP Tutorial

- Simple Network Management Protocol SNMP Tutorial
- Syslog Tutorial
- EtherChannel Tutorial
- Hot Standby Router Protocol HSRP Tutorial
- InterVLAN Routing Tutorial
- Cisco Command Line Interface CLI
- Cisco Router Boot Sequence Tutorial
- OSI Model Tutorial
- Subnetting Tutorial – Subnetting Made Easy
- Frame Relay Tutorial
- Wireless Tutorial
- Virtual Local Area Network VLAN Tutorial
- VLAN Trunking Protocol VTP Tutorial
- IPv6 Tutorial
- Rapid Spanning Tree Protocol RSTP Tutorial
- Spanning Tree Protocol STP Tutorial
- Network Address Translation NAT Tutorial
- Access List Tutorial
- RIP Tutorial
- EIGRP Tutorial
- OSPF Tutorial
- Practice CCNA GNS3 Labs
- CCNA Lab Challenges

CCNA 200-301

- CCNA FAQs & Tips
- Basic Questions
- Topology Architecture Questions
- Cloud & Virtualization Questions
- CDP & LLDP Questions
- Switch Questions
- VLAN & Trunking Questions
- VLAN & Trunking Questions 2
- STP & VTP Questions
- EtherChannel Questions
- TCP & UDP Questions
- IP Address & Subnetting Questions
- IP Routing Questions
- IP Routing Questions 2
- OSPF Questions
- OSPF Questions 2
- EIGRP Questions
- NAT Questions
- NTP Questions
- Syslog Questions
- HSRP Questions
- Access-list Questions
- AAA Questions
- Security Questions
- Security Questions 2
- DAI Questions
- IPv6 Questions
- DNS Questions
- QoS Questions

- Port Security Questions
- Wireless Questions
- Wireless Questions 2
- SDN Questions
- DNA Center Questions
- Drag Drop Questions
- Drag Drop Questions 2
- Drag Drop Questions 3
- VPN Questions
- DHCP Questions
- Automation Questions
- Miscellaneous Questions
- Share your CCNA Experience

Network Resources

- Free Router Simulators
- CCNA Website
- ENCOR Website
- ENSDWI Website
- ENARSI Website
- DevNet Website
- CCIE R&S Website
- Security Website
- Wireless Website
- Design Website
- Data Center Website
- Service Provider Website
- Collaboration Website

Top



Copyright © 2014 - 2026 CCNA Training
Privacy Policy | Disclaimer | Contact Us