Syslog Questions

3 questions | Original English questions and source answers

Question 1

If a notice-level messaging is sent to a syslog server, which event has occurred?

Options

A. An ARP Inspection has failed

B. A network device has restarted

C. A routing instance has flapped

D. A debug operation is running

Answer

C. A routing instance has flapped

Source explanation

Usually no action is required when a route flaps so it generates the notification syslog level message (level 5).

Source: CCNA 200-301 Questions.html | Question 1

Question 2

What will happen if you configure the logging trap debug command on a router?

Options

A. It causes the router to send all messages to the syslog server

B. It causes the router to stop sending all messages to the syslog server

C. It causes the router to send all messages with the severity levels Warning, Error, Critical, and Emergency to the syslog server

D. It causes the router to send messages with lower severity levels to the syslog server

Answer

A. It causes the router to send all messages to the syslog server

Source: CCNA 200-301 Questions.html | Question 2

Question 3

What event has occurred if a router sends a notice level message to a syslog server?

Options

A. An ICMP connection has been built

B. An interface line has changed status

C. A certificate has expired

D. A TCP connection has been torn down

Answer

B. An interface line has changed status

Source explanation

If you used to configure a Cisco device then maybe you saw this notice level message:

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to down

Number 5 in the above message represents for the Notification Level (Normal, but significant, conditions exist).

Source: CCNA 200-301 Questions.html | Question 3