DAI Questions

2 questions | Original English questions and source answers

Question 1

Refer to the exhibit. What is the effect of this configuration?

```
ip arp inspection vlan 2
interface fastethernet 0/1
 switchport mode access
 switchport access vlan 2
```

Options

A. All ingress and egress traffic is dropped because the interface is untrusted

B. Egress traffic is passed only if the destination is a DHCP server.

C. The switch discard all ingress ARP traffic with invalid MAC-to-IP address bindings

D. All ARP packets are dropped by the switch

Answer

C. The switch discard all ingress ARP traffic with invalid MAC-to-IP address bindings

Source explanation

Dynamic ARP inspection is an ingress security feature; it does not perform any egress checking.

Source: CCNA 200-301 Questions.html | Question 1

Question 2

Refer to the exhibit. What is the effect of this configuration?

```
ip arp inspection vlan 2
interface fastethernet 0/1
 switchport mode access
 switchport access vlan 2
```

Options

A. Dynamic ARP inspection is disabled because the ARP ACL is missing

B. The switch port interface trust state becomes untrusted

C. The switch port remains administratively down until the interface is connected to another switch

D. The switch port remains down until it is configured to trust or untrust incoming packets

Answer

B. The switch port interface trust state becomes untrusted

Source explanation

Dynamic ARP inspection (DAI) is a security feature that validates ARP packets in a network. It intercepts, logs, and discards ARP packets with invalid IP-to-MAC address bindings. This capability protects the network from certain man-in-the-middle attacks. After enabling DAI, all ports become untrusted ports.

Source: CCNA 200-301 Questions.html | Question 2