Port Security Questions

3 questions | Original English questions and source answers

Question 1

A network administrator enabled port security on a switch interface connected to a printer. What is the next configuration action in order to allow the port to learn the MAC address of the printer and insert it into the table automatically?

Options

A. implement auto MAC address learning

B. enable dynamic MAC address learning

C. implement static MAC addressing.

D. enable sticky MAC addressing

Answer

D. enable sticky MAC addressing

Source: CCNA Training » Port Security Quiz.pdf | Question 1

Question 2

Refer to the exhibit. Which port security violation mode is configured on interface Fa0/1?

%PM-4-ERR_DISABLE: psecure-violation error detected on Fa0/1, putting Fa0/1 in err-disable state
%PORT_SECURITY-2-PSECURE_VIOLATION: Security violation occurred, caused by MAC address 00AA.1AB9.D22F on port FastEthernet0/1
%LINKPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to down
%LINK-3-UPDOWN: Interface FastEthernet0/1, changed state to down

Options

A. restrict

B. shutdown

C. shutdown VLAN

D. protect

Answer

B. shutdown

Source explanation

After the port security violation occurs, the Fa0/1 interface was shutdown so the port security is using “shutdown” mode.

Source: CCNA Training » Port Security Quiz.pdf | Question 2

Question 3

A port security violation has occurred on a switch port due to the maximum MAC address count being exceeded. Which command must be configured to increment the security-violation count and forward an SNMP trap?

Options

A. `switchport port-security violation protect`

B. `switchport port-security violation shutdown`

C. `switchport port-security violation restrict`

D. `switchport port-security violation access`

Answer

C. switchport port-security violation restrict

Source: CCNA Training » Port Security Quiz.pdf | Question 3