Wireless Questions 2

9 questions | Original English questions and source answers

Question 1

Which WPA3 enhancement protects against hackers viewing traffic on the Wi-Fi network?

Options

A. SAE encryption

B. TKIP encryption

C. AES encryption

D. Scrambled encryption key

Answer

A. SAE encryption

Source explanation

Wi-Fi Protected Access version 3 (WPA3) is a new Wi-Fi Alliance’s (WFA) security standard for personal and enterprise networks. It aims to improve overall Wi-Fi security by using modern security algorithms and stronger cipher suites. WPA3 has two parts:

+ WPA3-Personal: Uses simultaneous authentication of equals (SAE) instead of pre-shared key (PSK), providing users with stronger security protections against attacks such as offline dictionary attacks, key recovery, and message forging.
+ WPA3-Enterprise: Offers stronger authentication and link-layer encryption methods, and an optional 192-bit security mode for sensitive security environments.

Source: CCNA 200-301 Questions.html | Question 1

Question 2

What is a recommended approach to avoid co-channel congestion while installing access points that use the 2.4 GHz frequency?

Options

A. one nonoverlapping channel

B. one overlapping channel

C. different nonoverlapping channels

D. different overlapping channels

Answer

C. different nonoverlapping channels

Source explanation

In the 2.4 GHz band, 1, 6, and 11 are the only non-overlapping channels so they should be chosen while installing APs.

Source: CCNA 200-301 Questions.html | Question 2

Question 3

Using direct sequence spread spectrum, which three 2.4-GHz channels are used to limit collisions?

Options

A. 1,6,11

B. 1,2,3

C. 1,5,10

D. 5,6,7

Answer

A. 1,6,11

Source explanation

In the 2.4 GHz band, 1, 6, and 11 are the only non-overlapping channels.

Source: CCNA 200-301 Questions.html | Question 3

Question 4

Which protocol prompts the Wireless LAN Controller to generate its own local web administration SSL certificate for GUI access?

Options

A. TACACS+

B. HTTP

C. HTTPS

D. RADIUS

Answer

C. HTTPS

Source explanation

When you enable HTTPS, the controller generates its own local web administration SSL certificate and automatically applies it to the GUI.

Reference: https://www.cisco.com/c/en/us/td/docs/wireless/controller/8-0/configuration-guide/b_cg80/b_cg80_chapter_011.html

Source: CCNA 200-301 Questions.html | Question 4

Question 5

What is a difference between local AP mode and FlexConnect AP mode?

Options

A. Local AP mode causes the AP to behave as if it were an autonomous AP

B. FlexConnect AP mode fails to function if the AP loses connectivity with the WLC

C. FlexConnect AP mode bridges the traffic from the AP to the WLC when local switching is configured

D. Local AP mode creates two CAPWAP tunnels per AP to the WLC

Answer

D. Local AP mode creates two CAPWAP tunnels per AP to the WLC

Source explanation

In Central Switched (Local) mode, an AP creates two CAPWAP tunnels to the Wireless Controller. One tunnel is used for forwarding data traffic and the other is used for forwarding the management traffic.

Source: CCNA 200-301 Questions.html | Question 5

Question 6

What is a function of Wireless LAN Controller?

Options

A. use SSIDs to distinguish between wireless clients

B. register with a single access point that controls traffic between wired and wireless endpoints

C. monitor activity on wireless and wired LANs

D. send LWAPP packets to access points

Answer

D. send LWAPP packets to access points

Source: CCNA 200-301 Questions.html | Question 6

Question 7

A wireless administrator has configured a WLAN; however, the clients need access to a less congested 5-GHz network for their voice quality. What action must be taken to meet the requirement?

Options

A. enable DTIM

B. enable AAA override

C. enable Band Select

D. enable RX-SOP

Answer

C. enable Band Select

Source explanation

Band select or Band Direction is a new feature that encourages dual band clients to connect to 5 G-Hz networks. Band select is disabled by default. The Band Select function provides a better wireless experience for users.

Source: CCNA 200-301 Questions.html | Question 7

Question 8

How does CAPWAP communicate between an access point in local mode and a WLC?

Options

A. The access point must directly connect to the WLC using a copper cable

B. The access point must be connected to the same switch as the WLC

C. The access point has the ability to link to any switch in the network, assuming connectivity to the WLC

D. The access point must not be connected to the wired network, as it would create a loop

Answer

C. The access point has the ability to link to any switch in the network, assuming connectivity to the WLC

Source: CCNA 200-301 Questions.html | Question 8

Question 9

When a WPA2-PSK WLAN is configured in the Wireless LAN Controller, what is the minimum number of characters that is required for the passphrase?

Options

A. 18

B. 6

C. 8

D. 12

Answer

C. 8

Source explanation

WPA/WPA2 preshared keys must contain 8 to 63 ASCII text characters or 64 hexadecimal characters.

Source: CCNA 200-301 Questions.html | Question 9