

FORTYGUARD

Heat Intelligence Report

Heatmap Metadata

Location:	37.29630401249074, -121.83412681853328
Date and Time:	2024-10-02 12:00
Temperature:	4.85°C (40.74°F)



Table of Contents

Table of Contents	2
Map	6
Geographic Analysis	7
1. General Location	7
2. Terrain & Elevation	7
3. Proximity to Water Bodies	7
4. Green Spaces & Vegetation	7
5. Land Cover Type	8
6. Building Density & Height	8
7. Shadow Coverage	9
8. Urban Geometry & Street Canyon Effects	9
Environmental Factors Analysis	9
1. Air Quality & Atmospheric Opacity	9
Typical AQI Range & Classification	9
Primary Pollutants & Sources	9
Air Quality–Temperature Interactions	10
Seasonal & Industrial Factors	10
2. Climate Classification & Historical Weather	10
Köppen Climate Classification	10
Historical Climate Normals (October 2, San José)	10
Comparison to Provided Temperature	10
Extreme Temperature Records	11
Long-Term Climate Profile & Urban Heat Behavior	11
3. Climate Trends & Projections	11
Observed Temperature Trends	11
Urban Expansion & Land-Use Change	11
Climate Change Projections	11
Cooling Degree Days (CDD) Trends	11
4. Soil Moisture & Permeability	12
Soil Types & Permeability	12
Seasonal Soil Moisture Conditions	12
Heat Absorption & Evaporative Cooling	12
Urbanization & Soil Sealing	12
Groundwater Influence	12
5. Heat Retention Capacity of Surfaces	13
Dominant Surface Materials	13
Surface Temperature Differentials Under Peak Solar Load	13
Thermal Admittance & Albedo	13
UHI Contribution	13
Cooling Infrastructure	13
6. Humidity Levels	13
Typical Relative Humidity	14
Dew Point Temperature	14



Humidity & Perceived Temperature	14
Seasonal Humidity Patterns	14
Humidity-Driven Phenomena	14
7. Solar Radiation Intensity	14
Global Horizontal Irradiance (GHI)	14
Solar Elevation Angle	14
Peak Sunlight Hours & Thermal Lag	15
Terrain & Urban Modifications to Solar Exposure	15
Differential Surface Absorption	15
8. Nighttime Cooling Rates	15
Diurnal Temperature Range (DTR)	15
Surface Thermal Mass & Urban Geometry Effects	15
Nighttime Cooling Assessment	15
Urban vs. Rural Nighttime Differential	16
9. Thermal Comfort Index	16
Applicable Metric Selection	16
Estimated Thermal Comfort Conditions	16
Comfort Classification	16
Vulnerable Population Risks	16
Local Mitigation Measures	17
10. Seasonal Variability of Urban Heat Islands	17
UHI Intensity by Season	17
Driving Factors for Seasonal UHI Variation	17
Urban-Rural Temperature Differentials	17
Seasonal Adaptation Measures	17
Greatest Compound Heat Risk Season	18
Urban Factors Analysis	18
1. Urban Land Use Characteristics	18
Location Context	18
Dominant Land Use Composition	18
Impervious Surface Fraction	18
Heat Differentials from Land Use Patterns	19
Zoning and Planning Policies	19
2. Anthropogenic Heat Sources	19
Major Economic Activity and Waste Heat	19
Energy-Intensive Sectors	19
Vehicle Density and Transportation Heat	19
HVAC Rejection Heat	20
Impervious Commercial Surfaces	20
Sustainability Initiatives	20
3. Green Infrastructure & Urban Cooling Systems	20
Urban Vegetation Strategy	20
Cooling Mechanisms	20
Notable Cooling Infrastructure	21
Engineered Cooling	21



Seasonal Variability and Adequacy	21
Cooling Equity	21
4. Building Material Thermal Properties	21
Dominant Building Materials	21
Albedo Values	22
Thermal Mass and Nighttime Re-radiation	22
Glass Curtain Wall Effects	22
Heat Mitigation Techniques	22
Building Stock Age	22
5. Urban Expansion & Development Trends	22
Population Growth Trajectory	23
Construction Trends	23
Net Change in Impervious Surface	23
Climate-Adaptive Urban Design	23
Near-Term Heat Profile Projection (5–10 Years)	23
6. Pedestrian Infrastructure & Outdoor Thermal Comfort	24
Walkability Characterization	24
Shading Infrastructure	24
Mean Radiant Temperature (MRT) Conditions	24
Heat Exposure Risk	24
Cooling Interventions	24
Cycling Infrastructure	25
Notable Pedestrian Comfort Zones and Deficits	25
Events Analysis	25
1. Extreme Weather Events & Heat Event History	25
Heat-Related Events	25
Other Extreme Weather With Heat Relevance	26
2. Heatwave Frequency & Intensity	26
3. Public Health Impacts & Heat Vulnerability	27
Anthropogenic Factors Analysis	29
1. Heat Emissions from Vehicles & Industry	29
Temperature Context	29
Transportation Heat Footprint	29
Industrial and Commercial Waste Heat	29
Spatial Heat Concentration	29
Temporal Patterns at Given DateTime	30
Emission-Reduction Measures	30
Waste Heat Recovery Opportunities	30
2. Cooling Infrastructure & Waste Heat Feedback Loop	30
Cooling Infrastructure Prevalence	30
The AC Feedback Loop	30
Balance-Point Temperature	31
Cooling Inequality	31
District Cooling Systems	31
Innovative and Passive Cooling Strategies	31



Cooling Demand Classification	31
3. Energy System Load & Grid Stress	31
Energy Demand Profile	31
Temperature-Demand Sensitivity	32
Grid Stability and Heat-Related Risk	32
Grid Heat Vulnerability	32
Load Shedding Risk	32
Energy Resilience Measures	32
Current Grid Stress Assessment	32
4. Traffic Behavior & Vehicular Heat Contribution	33
Traffic Pattern Characterization	33
Waste Heat Concentration Zones	33
Pavement Heat Interaction	33
Public Transit Role	33
Heat-Induced Behavioral Shifts	33
Mitigation Measures	33
Assessment at Given DateTime	34
5. Seasonal Population Dynamics & Heat Demand	34
Population Variability Assessment	34
Demand Translation for Current Period	34
Current Season Assessment	34
Weekend/Weekday and Time-of-Day Demand Variation	34
Infrastructure and Policy Adjustments	35
Key Demand Drivers Beyond Seasonal Population	35



Map



Figure 1: OverviewArea



Figure 2: Tile Area



Geographic Analysis

1. General Location

- **City:** San José, California, United States
- **Geographic classification:** Inland urban core within a broad valley (Santa Clara Valley), surrounded by mountain ranges on multiple sides
- **Köppen climate zone:** Csb (Warm-summer Mediterranean) — characterized by dry, warm summers and mild, wet winters with minimal precipitation from May through October
- **Historical temperature extremes:** All-time record high of 109°F (June 2000). October records reach approximately 100–104°F. Average high for early October is approximately 78–80°F.
- **Comparison to climate normals:** The provided temperature of 40.74°C converts to **105.3°F**. This is approximately 25–27°F above the normal average high for October 2 in San José, representing an extreme heat event well above the 99th percentile for this date. This would be consistent with a significant heat wave driven by offshore (Diablo) wind events that suppress marine influence and cause rapid warming in the Santa Clara Valley.

Sources:

- Köppen climate classification system
- NOAA/NWS climate normals for San José (SJC station)
- Historical temperature records from Western Regional Climate Center

2. Terrain & Elevation

- **Elevation:** Approximately 80–100 feet above sea level in the central San José area
- **Terrain type:** Broad, flat alluvial valley floor (Santa Clara Valley) bounded by the Santa Cruz Mountains to the west/southwest (~2,000–3,800 ft) and the Diablo Range to the east (~2,000–4,000 ft)
- **Heat retention influence:** The valley configuration traps warm air, particularly during offshore wind events when subsidence warming occurs. The surrounding mountains block cooling marine air from the Pacific, especially during Diablo wind events (northeasterly flow). This creates a heat-trapping basin effect that intensifies daytime temperatures.
- **Slope orientation:** The valley floor itself is essentially flat, but the western mountain barrier blocks the prevailing westerly marine layer, reducing natural cooling. During Diablo wind events, adiabatic compression of descending air from the east further elevates temperatures.

Sources:

- USGS elevation data and topographic maps
- NWS San Francisco Bay Area meteorological analyses of Diablo wind events

3. Proximity to Water Bodies

- **San Francisco Bay (South Bay):** Approximately 6–8 miles to the north/northwest of central San José
- **Pacific Ocean:** Approximately 25–30 miles to the west, separated by the Santa Cruz Mountains
- **Guadalupe River and Coyote Creek:** Flow through the urban area but are minor waterways with negligible thermal moderation
- **Thermal moderating effect:** Under normal conditions, the South Bay provides modest cooling via afternoon sea breezes that penetrate the valley. However, during offshore wind events (as implied by this extreme temperature), marine influence is completely suppressed. The Santa Cruz Mountains act as a significant barrier to Pacific marine layer intrusion.
- **Seasonal variation:** In October, the Pacific remains relatively warm (~58–60°F surface temperature), which normally supports moderate marine layer development. However, the effectiveness of marine cooling is highly dependent on wind direction — during Diablo winds, no marine influence reaches San José.

Sources:

- NOAA coastal and bay monitoring data
- San Francisco Bay Area mesoscale meteorological studies

4. Green Spaces & Vegetation



- **Type and extent:** San José has numerous urban parks (e.g., Guadalupe River Park, Kelley Park, Alum Rock Park on the eastern foothills), scattered street trees, and some remaining agricultural land on the urban fringe. The surrounding hillsides feature oak woodland and chaparral.
- **Estimated canopy coverage:** Approximately 15–18% citywide tree canopy coverage — relatively low compared to many U.S. cities of similar size
- **Vegetation type:** Mix of evergreen (live oaks, redwoods in riparian areas) and deciduous species (valley oaks, sycamores). In early October, most deciduous trees still retain foliage, providing some shading benefit. However, many non-native landscape trees may be drought-stressed, reducing evapotranspiration effectiveness.
- **Urban greening initiatives:** San José has an Urban Forest Master Plan with goals to increase canopy coverage. The city's "Our City Forest" program has planted trees in underserved neighborhoods.
- **Cooling contribution:** Estimated 3–7°F cooler surface temperatures in well-shaded park areas compared to adjacent paved surfaces. During extreme heat events like this, evapotranspiration is reduced due to plant stomatal closure, diminishing the cooling benefit of vegetation.

Sources:

- City of San José Urban Forest Master Plan
- American Forests urban canopy assessments
- Urban heat island mitigation literature on evapotranspiration limits during extreme heat

5. Land Cover Type

- **Dominant surface materials:** Extensive asphalt roadways and parking lots (San José is notably auto-centric with large surface parking areas), concrete sidewalks, composite roofing on residential structures, and commercial/industrial roofing (often dark membrane or metal). Suburban areas feature irrigated lawns interspersed with impervious surfaces.
- **Thermal properties:** Dark asphalt surfaces (albedo ~0.05–0.15) absorb significant solar radiation and can reach surface temperatures of 150–170°F under 105°F ambient conditions. Concrete (albedo ~0.20–0.35) performs slightly better. The extensive parking infrastructure in San José's commercial corridors creates large thermal mass zones that re-radiate heat well into evening hours.
- **Cool surface programs:** San José has adopted California's Title 24 building standards requiring cool roofing on new commercial construction (minimum aged solar reflectance of 0.63 for low-slope roofs). Some cool-pavement pilot projects have been explored but are not widely deployed.

Sources:

- California Energy Commission Title 24 Building Standards
- EPA Heat Island Effect documentation
- Urban land cover classification studies for Silicon Valley

6. Building Density & Height

- **Building density characterization:** Downtown San José features a modest mid-rise core (6–20 stories) with recent high-rise residential development (up to ~25 stories). The vast majority of the city is low-rise suburban development (1–2 story single-family homes) with scattered mid-rise commercial corridors and large single-story industrial/tech campus buildings.
- **Typical building heights:** Downtown: 60–250 feet. Suburban residential: 15–25 feet. Tech campuses (North San José): 30–60 feet with large footprints and extensive surface parking.
- **UHI contribution from vertical massing:** The relatively low-rise, spread-out urban form means less canyon-effect trapping but more direct solar exposure on horizontal surfaces. The downtown core has emerging canyon effects with new development.
- **Common materials:** Residential: wood-frame with asphalt shingle roofing (dark colors common). Commercial: tilt-up concrete, steel-frame with TPO/EPDM membrane roofing. Newer construction increasingly uses lighter-colored roofing per code.
- **Anthropogenic heat sources:** High vehicle density on major freeways (I-280, US-101, I-680, SR-87) contributing waste heat. Large data centers in North San José generating significant HVAC exhaust. During extreme heat, residential and commercial AC systems create a positive feedback loop of waste heat rejection — estimated at 2–5°F additional warming in dense commercial areas.

Sources:

- City of San José General Plan and zoning data
- Typical urban morphology for sprawling Western U.S. cities
- Anthropogenic heat flux studies for technology-sector urban areas



7. Shadow Coverage

- **Shadow coverage assessment:** At solar noon on October 2, shadow coverage in San José is minimal across the predominantly low-rise suburban landscape. Downtown offers moderate shadowing from mid-rise and high-rise buildings on north-facing street sides. Suburban areas have very limited structural shading — primarily from individual trees and single-story structures.
- **Solar angle calculation:** At 37.29°N latitude on October 2, the solar elevation at solar noon is approximately 52–53° (declination ~-4°). This produces shadow lengths roughly equal to building height (shadow ratio ~1:1). For a 20-foot residential structure, the shadow extends approximately 20 feet — insufficient to shade adjacent roadways in most cases.
- **Quantitative shading impact:** Shaded surfaces are typically 20–40°F cooler than sunlit surfaces at this solar intensity. Ambient air temperature reduction in shaded zones is more modest: approximately 3–9°F compared to fully exposed areas.
- **Permanent vs. seasonal shade:** In early October, deciduous trees still provide canopy shade. However, the predominantly evergreen and semi-deciduous urban tree mix (live oaks, various palms) provides year-round shade where present. The low canopy coverage (15–18%) means most surfaces receive direct solar radiation at midday.

Sources:

- Solar position calculations based on NOAA Solar Calculator
- Urban microclimate studies on shade-temperature relationships
- EPA guidance on shade and surface temperature reduction

8. Urban Geometry & Street Canyon Effects

- **Street canyon characteristics:** Downtown San José has emerging street canyons with estimated H/W ratios of 0.5–1.5 on major streets (Santa Clara Street, 1st Street, San Fernando Street). Suburban residential streets have very low H/W ratios of 0.1–0.3, meaning minimal radiation trapping but maximum solar exposure. Wide arterials (6–8 lanes) like Stevens Creek Blvd and El Camino Real have H/W ratios below 0.2.
- **Wind corridor presence:** The grid-oriented downtown street network (aligned roughly NW-SE and NE-SW) can channel winds when present. However, during Diablo wind events, the hot northeasterly flow is not effectively cooled by passage through the urban area. Major freeway corridors act as wind channels but also as heat sources.
- **Street layout pattern:** San José features a predominantly grid pattern in the downtown and older neighborhoods, transitioning to curvilinear suburban layouts in newer developments. The grid pattern allows some ventilation but also creates consistent solar exposure on east-west oriented streets. Cul-de-sac-heavy suburban areas trap heat due to poor ventilation.
- **Sky View Factor (SVF):** Estimated SVF of 0.85–0.95 in suburban areas (very open sky), 0.50–0.70 in downtown corridors, and 0.30–0.50 in the densest new development areas. The high SVF across most of the city means efficient nocturnal radiative cooling under normal conditions, but during extreme heat events, it also means maximum daytime solar loading. The low canyon effect means San José's UHI is driven more by surface thermal mass and anthropogenic heat than by radiation trapping.

Sources:

- Urban canyon geometry studies for Western U.S. cities
- Sky View Factor estimation methods from urban climatology literature
- City of San José street design standards and typical block dimensions

Environmental Factors Analysis

1. Air Quality & Atmospheric Opacity

Typical AQI Range & Classification

- The coordinates 37.29°N, 121.83°W correspond to San José, California, situated in the Santa Clara Valley (Silicon Valley) within the San Francisco Bay Area air basin.
- In early October, the typical AQI ranges from 30–80 (Good to Moderate by EPA standards), though wildfire smoke events — common in California's fall season — can push AQI into Unhealthy for Sensitive Groups (101–150) or higher.
- Given the extreme temperature of 105.3°F (converted from 40.74°C), conditions consistent with an offshore wind event (Diablo winds) or a significant heat dome are likely, which often coincide with elevated fire risk and degraded air quality.

Primary Pollutants & Sources



- **Ozone (O₃):** The dominant pollutant of concern in the South Bay during heat events. Ground-level ozone forms photochemically from NO_x and VOCs under intense solar radiation and high temperatures. San José routinely exceeds the 8-hour ozone NAAQS during heat waves.
- **PM_{2.5}:** Elevated during wildfire season (August–November). Vehicle emissions, industrial sources, and secondary aerosol formation from photochemistry also contribute year-round.
- **PM₁₀:** Dust from construction, agriculture in surrounding areas, and road dust resuspension.
- **NO₂ and CO:** Primarily from vehicular traffic on major corridors (I-280, I-680, US-101). Generally within attainment but contribute to ozone precursor chemistry.

Air Quality–Temperature Interactions

- Particulate matter and aerosols have a dual radiative effect: scattering incoming shortwave radiation (slight cooling) while absorbing and re-emitting longwave radiation (warming), with the net effect depending on aerosol composition. Black carbon from wildfires has a net warming effect.
- Smog and haze reduce direct solar transmittance but increase diffuse radiation, which can still heat urban surfaces effectively.
- At 105.3°F, the heat-ozone feedback loop is strongly active: high temperatures accelerate VOC evaporation and NO_x-driven photochemical ozone production. Ozone levels can increase by approximately 3–5 ppb per °F above ~90°F.

Seasonal & Industrial Factors

- October marks the transition into California's fire season peak; Santa Ana/Diablo wind events bring hot, dry offshore flow that both raises temperatures and transports wildfire smoke into the Bay Area.
- The Bay Area Air Quality Management District (BAAQMD) frequently issues Spare the Air alerts during such events.
- Industrial emissions in the South Bay are relatively modest compared to the Contra Costa refinery corridor, but tech campus HVAC systems and data center cooling contribute anthropogenic heat and some emissions during extreme heat events.

Sources:

- EPA AQI standards and breakpoint tables
- BAAQMD air quality monitoring data and Spare the Air program
- EPA National Ambient Air Quality Standards (NAAQS)
- Peer-reviewed literature on ozone-temperature feedback (e.g., Jacob & Winner, 2009, general reference)

2. Climate Classification & Historical Weather

Köppen Climate Classification

- San José is classified as **Csb** — Mediterranean climate with warm, dry summers and mild, wet winters (warm-summer Mediterranean). Some lower-elevation areas near downtown approach **Csa** (hot-summer Mediterranean) due to reduced marine influence.
- This classification is characterized by virtually no precipitation from May through October, with the dry season creating low soil moisture and high fire risk by early fall.

Historical Climate Normals (October 2, San José)

- **Typical high:** ~78–82°F
- **Typical low:** ~54–58°F
- **Typical mean:** ~66–70°F
- These normals are based on the 1991–2020 climate normal period for San José (SJC station).

Comparison to Provided Temperature

- The provided average temperature of **105.3°F** (40.74°C) is approximately **35–39°F above the normal mean** and **23–27°F above the normal daily high** for early October. This represents an extraordinary departure — well beyond 3 standard deviations from the climatological mean.
- This is consistent with an extreme heat event. For context, San José's all-time record high is 109°F (set in September 2022 during a historic heat dome). October records are typically lower; the October record high for San José is approximately 100–104°F. A reading of 105.3°F would likely set or approach an all-time October record.



Extreme Temperature Records

- San José all-time record high: 109°F (September 6, 2022)
- Estimated October record high: ~103–104°F (various years)
- The September 2022 event saw widespread records broken across California, with temperatures 20–30°F above normal for multiple consecutive days.

Long-Term Climate Profile & Urban Heat Behavior

- The Mediterranean dry summer means that by October, soil moisture is at its annual minimum, vegetation is desiccated, and evapotranspiration is severely limited — all factors that amplify sensible heat flux and surface temperatures.
- The inland valley location of San José, shielded from direct Pacific marine influence by the Santa Cruz Mountains, makes it more susceptible to extreme heat than coastal Bay Area locations like San Francisco (which may be 15–25°F cooler during the same event).

Sources:

- NOAA climate normals (1991–2020) for San José, CA (Station SJC/KSJC)
- Köppen climate classification system (Peel et al., 2007 — general reference)
- NOAA/NWS extreme temperature records for the San Francisco Bay Area

3. Climate Trends & Projections

Observed Temperature Trends

- The San Francisco Bay Area has warmed approximately **1.5–2.5°F since 1970**, with inland areas like San José warming faster than coastal zones due to reduced marine layer penetration.
- Estimated warming rate for the South Bay: approximately **0.4–0.6°F per decade** since 1970, with acceleration in recent decades.
- The frequency of extreme heat days ($\geq 100^\circ\text{F}$) in San José has increased notably. Historically, San José averaged fewer than 2 days per year above 100°F; recent decades show 4–6+ such days annually.
- Heatwave frequency and duration have increased: multi-day events with temperatures exceeding 100°F are now 2–3 times more likely than in the 1960s–1980s baseline.

Urban Expansion & Land-Use Change

- San José has experienced massive urban expansion since the 1950s, growing from ~95,000 to over 1,000,000 residents. This has converted vast areas of orchards and agricultural land (the former "Valley of Heart's Delight") to impervious urban surfaces.
- The replacement of orchards with asphalt, concrete, and buildings has dramatically reduced evapotranspiration and increased thermal mass, amplifying UHI effects by an estimated 3–7°F in the urban core relative to surrounding rural/agricultural areas.
- Ongoing densification and infill development continue to increase impervious surface fraction.

Climate Change Projections

- **2030s:** Under RCP 4.5/SSP2-4.5, San José is projected to experience 1.5–3.0°F additional warming above the 2000–2020 baseline, with extreme heat days ($\geq 100^\circ\text{F}$) increasing to 8–15 per year.
- **2050s:** Under RCP 8.5/SSP5-8.5, warming of 3.5–5.5°F above baseline is projected, with extreme heat events becoming significantly more frequent and intense. Events like the one analyzed here (105°F+ in October) could shift from exceptional to occurring once every 5–10 years.
- Projected decline in marine layer frequency and fog days further reduces natural cooling for the Bay Area.

Cooling Degree Days (CDD) Trends

- CDD (base 65°F) for San José have increased by approximately 15–25% since the 1980s.
- Typical annual CDD for San José: ~800–1,100. Projected to increase to ~1,200–1,600 by mid-century under high-emission scenarios.
- This translates directly to increased HVAC energy demand, peak electricity loads, and anthropogenic heat rejection into the urban environment.



Sources:

- Cal-Adapt climate projections (California Energy Commission)
- NOAA U.S. Climate Normals and trend analyses
- Fourth National Climate Assessment (NCA4), Chapter on Southwest region
- IPCC AR6 Working Group I — regional projections for western North America

4. Soil Moisture & Permeability

Soil Types & Permeability

- The Santa Clara Valley floor consists predominantly of **alluvial soils** — a mix of clay loams, silty clay loams, and some sandy loams deposited by Coyote Creek, Guadalupe River, and other drainages from the surrounding mountains.
- The dominant soil series include **Campbell silty clay loam** and **Yolo loam** variants, which have moderate to low permeability (hydraulic conductivity typically 0.06–0.6 inches/hour).
- Clay-rich soils in the valley floor tend to crack when dry (as they would be in early October after the dry season), creating initially high infiltration that quickly drops as clays swell upon wetting.

Seasonal Soil Moisture Conditions

- By early October, soil moisture is at or near its **annual minimum**. San José typically receives no measurable precipitation from June through September; the last significant rain may have been 4–5 months prior.
- Estimated volumetric soil moisture: **5–15%** in the upper soil profile (top 12 inches) for non-irrigated areas, well below field capacity (~30–35% for these soil types).
- Irrigated landscapes (parks, residential lawns, golf courses) maintain higher moisture but represent a small fraction of total urban area.

Heat Absorption & Evaporative Cooling

- Dry soils have lower thermal conductivity (~0.3 W/m·K) than moist soils (~1.5 W/m·K), meaning heat is concentrated at the surface rather than conducted downward, increasing surface temperatures.
- Evaporative cooling is severely limited by the lack of soil moisture. The Bowen ratio (sensible to latent heat flux) shifts strongly toward sensible heating — estimated at 5:1 or higher for bare dry soil, compared to ~0.5:1 for well-watered vegetation.
- This dramatically amplifies surface and near-surface air temperatures, directly contributing to the extreme 105.3°F reading.

Urbanization & Soil Sealing

- Estimated impervious surface coverage in San José's urban core: **60–80%**. This effectively eliminates soil-atmosphere moisture exchange over the majority of the developed area.
- Soil sealing converts potential latent heat flux to sensible heat flux, contributing an estimated 2–5°F to UHI intensity.
- Stormwater infrastructure routes any precipitation rapidly to channels, further reducing infiltration and groundwater recharge.

Groundwater Influence

- The Santa Clara Valley groundwater basin has been historically over-pumped (causing subsidence in the mid-20th century) but has been managed by the Santa Clara Valley Water District (now Valley Water) with active recharge programs.
- Groundwater table depth is typically 20–50+ feet below surface in urban areas — too deep to provide meaningful surface moisture through capillary rise, especially during the dry season.

Sources:

- USDA NRCS Web Soil Survey for Santa Clara County
- USGS groundwater data for the Santa Clara Valley basin
- Peer-reviewed literature on Bowen ratio and soil moisture–temperature feedbacks
- Valley Water (Santa Clara Valley Water District) groundwater management reports



5. Heat Retention Capacity of Surfaces

Dominant Surface Materials

- **Asphalt:** Extensive coverage across roadways, parking lots, and highways (I-280, I-680, US-101, and local arterials). San José's sprawling suburban development pattern means a very high proportion of land area is dedicated to roads and parking.
- **Concrete:** Sidewalks, building foundations, commercial plazas, and some roadways.
- **Roofing materials:** Mix of dark asphalt shingles, tile roofs (common in suburban areas), and flat commercial roofs (some with cool roof coatings).
- **Vegetation:** Street trees, residential yards, parks (e.g., Guadalupe River Park, Kelley Park), and remaining riparian corridors. Vegetation is stressed and partially dormant by early October due to drought conditions.
- **Bare soil:** Limited in urban areas but present in undeveloped parcels and hillside interfaces.

Surface Temperature Differentials Under Peak Solar Load

- At an air temperature of 105.3°F with intense solar radiation:
- **Black asphalt surface:** Estimated 140–165°F (albedo ~0.05–0.10)
- **Concrete (light gray):** Estimated 120–140°F (albedo ~0.20–0.35)
- **Dark roofing:** Estimated 150–170°F (albedo ~0.05–0.15)
- **Cool/reflective roof:** Estimated 105–120°F (albedo ~0.60–0.70)
- **Irrigated grass:** Estimated 85–95°F (due to evapotranspiration)
- **Dry grass/bare soil:** Estimated 120–140°F
- The differential between asphalt and irrigated grass can exceed **60–70°F** at the surface under these conditions.

Thermal Admittance & Albedo

- **Asphalt:** Thermal admittance ~1,200–1,500 J/(m²·K·s^{1/2}); albedo 0.05–0.12. High heat storage, slow release — major UHI contributor.
- **Concrete:** Thermal admittance ~1,400–1,800 J/(m²·K·s^{1/2}); albedo 0.20–0.35. Slightly better than asphalt due to higher reflectivity.
- **Vegetation/soil:** Thermal admittance ~600–1,000 J/(m²·K·s^{1/2}); effective albedo 0.15–0.25 but with latent heat dissipation providing additional cooling.

UHI Contribution

- The combination of extensive dark impervious surfaces, high thermal mass, and limited vegetation creates a strong UHI effect. Estimated daytime UHI intensity for San José during this event: **5–10°F** above surrounding rural/agricultural areas.
- Nighttime UHI can be even more pronounced (see Section 8) due to slow heat release from thermal mass.

Cooling Infrastructure

- San José has adopted California's Title 24 building code, which includes cool roof requirements for new commercial and some residential construction (minimum aged solar reflectance of 0.63 for low-slope roofs).
- The city's urban forest plan targets increased tree canopy coverage, currently estimated at ~15–18% citywide, with a goal of reaching higher coverage in heat-vulnerable neighborhoods.
- Some cool pavement pilot projects have been explored in the Bay Area, but widespread deployment in San José is limited as of 2024.

Sources:

- EPA Heat Island Effect resources and surface temperature studies
- Lawrence Berkeley National Laboratory (LBNL) cool surfaces research
- California Title 24 Building Energy Efficiency Standards
- Peer-reviewed literature on urban surface energy balance and thermal properties of materials

6. Humidity Levels



Typical Relative Humidity

- For San José in early October at solar noon, typical relative humidity ranges from **30–50%** under normal conditions.
- However, during an extreme heat event of 105.3°F — particularly one driven by offshore (Diablo) winds — relative humidity drops dramatically. **Estimated relative humidity: 8–20%**, consistent with hot, dry continental air mass advection.
- This extremely low humidity is characteristic of offshore wind events that bring air from the Central Valley or Great Basin over the coastal ranges.

Dew Point Temperature

- Estimated dew point during this event: **30–45°F**, indicating very dry air. This is well below the dangerous heat stress threshold of 75°F dew point.
- The low dew point means that while the absolute temperature is extreme, the moisture-driven component of heat stress is relatively low compared to humid heat events (e.g., Gulf Coast or Midwest heat waves).

Humidity & Perceived Temperature

- At 105.3°F with ~15% relative humidity, the Heat Index is approximately **101–104°F** — actually slightly below the dry-bulb temperature because low humidity allows effective evaporative cooling from skin.
- However, this does not mean conditions are safe: the extreme dry-bulb temperature still poses severe heat stress risks, and the low humidity creates additional hazards including rapid dehydration, nosebleeds, and wildfire risk.

Seasonal Humidity Patterns

- San José's humidity follows a strong seasonal cycle: highest in winter (60–80% RH) when Pacific storms bring moisture, lowest in late summer/early fall (20–40% RH at midday).
- The marine layer (fog/stratus) that moderates summer temperatures along the coast occasionally penetrates to San José, raising humidity; however, during offshore wind events, this marine influence is completely suppressed.

Humidity-Driven Phenomena

- The extremely low humidity during this event actually **enhances** nocturnal radiative cooling potential (dry air is more transparent to longwave radiation) — but this benefit is partially offset by urban thermal mass.
- The dry conditions mean that the dangerous "tropical night" phenomenon (warm + humid nights preventing recovery) is less of a concern here than in humid climates, though absolute nighttime temperatures may still remain dangerously elevated (see Section 8).
- Dew point is far below the 75°F dangerous threshold, so wet-bulb temperature-based heat stress is not the primary concern; rather, direct thermal loading and dehydration are the dominant risks.

Sources:

- NOAA climate normals for humidity at San José (KSJC)
- NWS Heat Index calculation methodology
- Peer-reviewed literature on dry heat stress vs. humid heat stress
- Steadman (1979) apparent temperature tables (general reference)

7. Solar Radiation Intensity

Global Horizontal Irradiance (GHI)

- For San José at 37.29°N on October 2 at solar noon under clear skies, the expected GHI is approximately **750–850 W/m²**.
- Extreme heat events in this region are typically associated with high-pressure ridging and clear skies, so cloud attenuation is minimal. Estimated actual GHI: **800–850 W/m²**.
- If wildfire smoke is present, GHI could be reduced by 10–30%, but the direct normal irradiance (DNI) component would be more strongly affected than diffuse radiation.

Solar Elevation Angle

- At solar noon on October 2 at 37.29°N latitude, the solar declination is approximately -4.5°.



- Solar elevation angle at solar noon: approximately **48–49°** (calculated as $90^\circ - 37.29^\circ - (-4.5^\circ) \approx 57.2^\circ$ — correcting: $90^\circ - |\text{latitude} - \text{declination}| = 90^\circ - |37.29 - (-4.5)| = 90^\circ - 41.79^\circ \approx 48.2^\circ$).
- This moderately high sun angle provides strong direct beam radiation but is notably lower than summer solstice ($\sim 76^\circ$), meaning shadows are longer and some urban canyon shading occurs.

Peak Sunlight Hours & Thermal Lag

- Day length on October 2 at this latitude: approximately **11 hours 45 minutes**.
- Peak solar radiation occurs at approximately 12:45–1:00 PM PDT (solar noon). Maximum air temperature typically lags by 2–3 hours, peaking around 2:00–4:00 PM.
- At the 12:00 PM timestamp, the temperature of 105.3°F may not yet represent the daily maximum — actual peak could reach **107–110°F** later in the afternoon.

Terrain & Urban Modifications to Solar Exposure

- The Santa Clara Valley floor is relatively flat, providing unobstructed solar exposure across most of the urban area.
- The Santa Cruz Mountains to the west (peaks $\sim 2,000$ – $3,800$ feet) and the Diablo Range to the east (peaks $\sim 2,500$ – $4,200$ feet) create a valley orientation that channels and traps heat while providing minimal afternoon shading for the valley floor.
- Urban structures in downtown San José (moderate density, buildings typically 5–15 stories) create some canyon shading, but the predominantly suburban, low-rise character of most of San José means extensive solar exposure of horizontal surfaces.

Differential Surface Absorption

- Under 800+ W/m² solar load, dark asphalt absorbs ~ 88 – 95% of incoming radiation, converting most to sensible heat storage. This drives the extreme surface temperatures noted in Section 5.
- Vegetated surfaces absorb similar total radiation but partition a significant fraction to latent heat (evapotranspiration), resulting in much lower surface temperatures — though this effect is diminished when vegetation is drought-stressed.

Sources:

- NREL National Solar Radiation Database (NSRDB) for San José
- NOAA Solar Calculator for solar position
- Peer-reviewed literature on urban surface energy balance under clear-sky conditions

8. Nighttime Cooling Rates

Diurnal Temperature Range (DTR)

- Typical DTR for San José in early October: **25–35°F** under normal conditions (e.g., high of 80°F, low of 52°F).
- During extreme heat events, DTR is often compressed due to elevated nighttime minima. Estimated DTR during this event: **18–25°F**, yielding overnight lows of approximately **80–87°F** — well above the "tropical night" threshold of 68°F (20°C).

Surface Thermal Mass & Urban Geometry Effects

- The extensive thermal mass of San José's urban surfaces (asphalt, concrete, buildings) stores enormous quantities of heat during the day. At 105.3°F air temperature with surface temperatures reaching 140–165°F, the total stored energy is substantial.
- This stored heat is released as longwave radiation throughout the night, sustaining elevated air temperatures.
- Urban canyon geometry (even in San José's relatively low-density form) reduces the sky view factor, trapping outgoing longwave radiation and slowing radiative cooling. Downtown areas with taller buildings experience this effect more strongly.

Nighttime Cooling Assessment

- San José typically exhibits **moderate nighttime cooling** due to its inland valley location and relatively low humidity, which allows efficient longwave radiation loss.
- However, during this extreme event, several factors suppress cooling:
 - Massive thermal energy stored in urban surfaces



- Possible warm air advection if offshore winds persist overnight
- Anthropogenic heat from HVAC systems running at maximum capacity (estimated 5–15 W/m² in commercial areas)
- Valley topography trapping warm air if winds calm (cold air drainage from mountains is suppressed during heat dome events)
- Consecutive hot nights (minimum >75°F) prevent physiological recovery and dramatically increase heat-related mortality risk, particularly for elderly populations and those without air conditioning.

Urban vs. Rural Nighttime Differential

- Estimated nighttime UHI intensity during this event: **7–12°F**. Rural areas in the surrounding foothills and agricultural zones may cool to 70–75°F while urban San José remains at 82–87°F.
- The nighttime UHI is typically stronger than the daytime UHI in San José due to the dominance of thermal mass release over rural radiative cooling.

Sources:

- NOAA climate normals for diurnal temperature range at San José
- Oke et al., "Urban Climates" (general reference on urban energy balance and nocturnal UHI)
- Peer-reviewed literature on nighttime heat stress and thermal mass effects

9. Thermal Comfort Index

Applicable Metric Selection

- For this hot, dry environment, the **Universal Thermal Climate Index (UTCI)** is the most appropriate metric. Unlike the Heat Index (which is optimized for humid conditions and underestimates stress in dry heat), UTCI integrates air temperature, humidity, wind speed, and mean radiant temperature (MRT) to provide a comprehensive assessment across all climate types.
- The **Wet Bulb Globe Temperature (WBGT)** is also relevant for occupational heat stress assessment (outdoor workers), as it accounts for radiant heat load.

Estimated Thermal Comfort Conditions

- **Air temperature:** 105.3°F (40.74°C)
- **Estimated relative humidity:** 10–18%
- **Estimated wind speed:** 5–15 mph (offshore wind event may produce gusty conditions, but surface winds in the valley can be variable)
- **Estimated mean radiant temperature (MRT):** 140–160°F (60–70°C) in direct sun on asphalt surfaces at midday
- **Estimated UTCI:** approximately **104–113°F (40–45°C)**, corresponding to **"Very Strong Heat Stress"** (UTCI category: >38°C = very strong; >46°C = extreme).
- **Estimated WBGT:** approximately **82–88°F (28–31°C)** — in the "Extreme Caution" to "Danger" range for occupational exposure. Despite low humidity, the intense radiant heat load elevates WBGT significantly.
- **Heat Index:** approximately 101–104°F — classified as "Danger" by NWS standards (heat cramps and heat exhaustion likely; heat stroke possible with prolonged exposure).

Comfort Classification

- Overall classification: **Very Strong to Extreme Heat Stress** Prolonged outdoor exposure is dangerous for all populations.
- In direct sun on dark surfaces, conditions approach the threshold for rapid-onset heat stroke.
- Shaded areas with air movement provide meaningful relief (UTCI reduction of 10–18°F possible in well-ventilated shade).

Vulnerable Population Risks

- **Elderly (65+):** Reduced thermoregulatory capacity, higher prevalence of cardiovascular disease, and medication interactions (diuretics, beta-blockers) increase heat stroke risk. San José has a significant senior population.
- **Outdoor workers:** Agricultural workers in surrounding areas, construction workers, landscapers, and delivery drivers face occupational heat illness risk. Cal/OSHA heat illness prevention standards require shade, water, and rest breaks above 95°F, with enhanced protocols above 95°F ("high heat procedures").



- **Children:** Higher metabolic rate per body mass, less effective sweating, and dependence on caregivers for hydration.
- **Unhoused populations:** San José has a significant unhoused population (~7,000+) with limited access to cooling and hydration.

Local Mitigation Measures

- The City of San José activates **cooling centers** at community centers and libraries during extreme heat events.
- Santa Clara County issues heat advisories coordinated with NWS Excessive Heat Warnings.
- Urban tree canopy provides localized shade, though coverage is uneven (lower in lower-income neighborhoods — a recognized environmental justice concern).
- Some transit stops have shade structures; downtown areas have some shaded walkways and arcades.
- Misting stations are not widely deployed in San José (more common in desert cities like Phoenix), but splash pads and public pools provide some relief.

Sources:

- UTCI assessment scale (Bröde et al., 2012 — general reference)
- NWS Heat Index chart and warning criteria
- Cal/OSHA Heat Illness Prevention Standard (Title 8, Section 3395)
- NIOSH Criteria for a Recommended Standard: Occupational Exposure to Heat and Hot Environments

10. Seasonal Variability of Urban Heat Islands

UHI Intensity by Season

- **Summer/Early Fall (June–October):** UHI intensity is at its maximum. Estimated daytime UHI: 4–8°F; nighttime UHI: 6–12°F. Dry conditions, high solar input, minimal evapotranspiration from stressed vegetation, and peak HVAC waste heat all contribute.
- **Late Fall/Winter (November–February):** UHI intensity moderates to daytime 2–4°F and nighttime 3–6°F. Increased precipitation raises soil moisture and vegetation vigor, enhancing evaporative cooling. Shorter days reduce solar heat loading. However, heating-season energy use adds some anthropogenic heat.
- **Spring (March–May):** UHI intensity is moderate (3–6°F). Vegetation is at peak vigor with available soil moisture from winter rains, providing maximum evapotranspiration. Increasing solar radiation begins to warm urban surfaces.

Driving Factors for Seasonal UHI Variation

- **Foliage cycles:** Deciduous trees (relatively common in San José's urban forest) provide maximum shade in summer but lose leaves by November, reducing canopy cooling. Evergreen species (oaks, some ornamentals) provide year-round but less dense shade.
- **Soil moisture:** The Mediterranean precipitation pattern creates a stark seasonal contrast — saturated soils in winter vs. desiccated soils in fall. This is the single largest driver of seasonal UHI variation in this climate.
- **HVAC load:** Summer/fall cooling demand generates substantial waste heat. San José's commercial buildings and data centers (significant in Silicon Valley) reject large amounts of heat to the outdoor environment. Estimated anthropogenic heat flux in commercial areas during extreme heat: 10–25 W/m².
- **Marine layer:** Summer fog/stratus occasionally reaches San José, temporarily suppressing UHI by reducing solar input and increasing humidity. This marine influence is absent during offshore wind events like the one producing 105.3°F.

Urban-Rural Temperature Differentials

- During peak summer/fall heat events: urban San José can be **8–12°F warmer** than rural areas in the Diablo Range foothills or Santa Cruz Mountains at night.
- During winter: the differential narrows to **2–5°F**, and on foggy nights, the UHI may actually be negligible as the marine layer homogenizes temperatures.
- Microclimatic variation within the city is significant: downtown and industrial areas (North San José) are notably warmer than neighborhoods with mature tree canopy (e.g., Willow Glen, Rose Garden).

Seasonal Adaptation Measures

- San José's **Climate Smart San José** plan includes urban greening, cool roof mandates, and tree planting targets aimed at reducing UHI.



- The city's Green Stormwater Infrastructure Plan promotes permeable surfaces and bioretention, which can increase soil moisture and evaporative cooling.
- California's building code (Title 24) increasingly requires cool roofs and improved building envelope performance, reducing both indoor heat exposure and HVAC waste heat.
- Emergency heat action plans are activated seasonally, with enhanced outreach during forecast extreme heat events.

Greatest Compound Heat Risk Season

- **Late September through mid-October** poses the greatest compound heat risk for San José. This period combines:
 - Maximum soil moisture deficit (end of dry season)
 - Still-significant solar radiation (~80% of summer peak)
 - Peak wildfire risk and associated air quality degradation
 - Diablo wind events bringing extreme heat and very low humidity
 - Vegetation at maximum stress, minimizing evapotranspiration
 - Population complacency — residents may have deactivated cooling systems or be less vigilant about heat safety as the "summer" season is perceived to have ended
- The October 2, 2024 event at 105.3°F exemplifies this compound risk perfectly — an extreme temperature anomaly occurring during the season of maximum vulnerability.

Sources:

- Climate Smart San José plan (City of San José)
- EPA Urban Heat Island publications
- Peer-reviewed literature on Mediterranean climate UHI seasonality
- California Building Standards Commission, Title 24
- NWS San Francisco Bay Area forecast office — Diablo wind climatology

Urban Factors Analysis

1. Urban Land Use Characteristics

Location Context

- The coordinates (37.29°N, 121.83°W) place this location in the heart of **San José, California**, within the southern portion of the San Francisco Bay Area — specifically near the central/downtown corridor of the city.
- The average temperature of **40.74°C (105.3°F)** on October 2, 2024 represents an extreme heat event for this area, well above the typical early-October average high of ~78–82°F, indicating a significant heat wave condition.

Dominant Land Use Composition

- **Mixed-use urban core (~25%)**: Downtown San José features mid-rise office buildings, government facilities, residential towers, and ground-floor retail — a dense mixed-use environment.
- **Residential (~40%)**: Surrounding the downtown core are extensive single-family residential neighborhoods (many post-WWII ranch-style homes) and increasing multi-family developments. North San José has seen significant apartment/condo construction.
- **Commercial/Retail (~15%)**: Strip malls, big-box retail corridors, and auto-oriented commercial zones along major arterials such as Stevens Creek Boulevard and Story Road.
- **Industrial/Tech Campus (~15%)**: North San José and areas near the airport host large technology campuses, light industrial parks, and logistics facilities with extensive surface parking and low-rise, large-footprint buildings.
- **Institutional/Open Space (~5%)**: San José State University campus, civic center, and scattered neighborhood parks.

Impervious Surface Fraction

- **Estimated: 70–80% impervious** in the immediate downtown and commercial zones. San José's auto-oriented development pattern results in extensive asphalt parking, wide roadways, and concrete surfaces.
- Residential neighborhoods have somewhat lower impervious fractions (~55–65%) due to yard space, but many front yards have been converted to driveways or hardscape.
- At 105.3°F, this high impervious fraction is critically important: asphalt and concrete surfaces can reach 150–170°F, creating intense radiant heat loads and preventing evaporative cooling.



Heat Differentials from Land Use Patterns

- The concentration of impervious surfaces in commercial corridors and tech campuses creates **heat islands 8–15°F warmer** than nearby vegetated areas during peak afternoon conditions at this extreme temperature.
- Heat-mitigating zones (parks, riparian corridors) are **largely segregated** from the densest commercial/industrial zones rather than interspersed, reducing their cooling reach.
- East San José neighborhoods tend to have lower tree canopy and higher impervious fractions compared to western neighborhoods closer to the foothills, creating a **thermal equity gap** that is well-documented in local environmental justice analyses.

Zoning and Planning Policies

- San José's **General Plan (Envision San José 2040)** promotes urban village infill development, which increases density but can also increase impervious surfaces if not paired with green infrastructure requirements.
- The city has adopted a **Climate Smart San José** plan with goals for urban greening and heat resilience, though implementation has been incremental.
- Recent zoning changes encourage transit-oriented development (TOD) near BART and VTA light rail stations, which can concentrate heat-generating density but also reduce vehicle miles traveled.

Sources:

- City of San José General Plan — Envision San José 2040
- Climate Smart San José plan documentation
- USGS National Land Cover Database (NLCD) impervious surface estimates for Santa Clara County
- General knowledge of San José urban form and development patterns

2. Anthropogenic Heat Sources

Major Economic Activity and Waste Heat

- San José is the **economic center of Silicon Valley**, and the dominant economic activities — technology, data processing, corporate offices — generate substantial waste heat through building HVAC systems and computing infrastructure.
- At 105.3°F, virtually every commercial and residential building is running air conditioning at maximum capacity, creating an enormous **positive feedback loop**: cooling interiors dumps waste heat outdoors, raising ambient temperatures further and increasing cooling demand.

Energy-Intensive Sectors

- **Data centers:** San José and surrounding North San José/Santa Clara host one of the highest concentrations of data centers in the world. These facilities operate 24/7 and reject massive amounts of heat — Estimated: a large hyperscale data center can reject 20–50 MW of thermal energy continuously. Multiple such facilities exist within ~3–5 miles north and northwest of these coordinates.
- **Technology campuses:** Large corporate campuses (including well-known companies headquartered in the area) feature extensive HVAC systems for office buildings and server rooms. Typical for this area: campus-scale HVAC systems reject 5–15 MW of waste heat per major campus.
- **Norman Y. Mineta San José International Airport:** Located approximately 2.5 miles north-northwest of these coordinates. Aircraft operations, jet exhaust, extensive tarmac and runway surfaces (albedo ~0.05–0.10), and terminal HVAC all contribute to a significant thermal footprint. Runway and apron surfaces at 105.3°F can reach 155–170°F surface temperatures.

Vehicle Density and Transportation Heat

- San José is an auto-dependent city. Major freeways — **I-280, US-101, I-880, and CA-87** — converge in and around the downtown area, all within ~1–3 miles of these coordinates.
- Typical for this area: weekday traffic volumes on US-101 through San José exceed 200,000 vehicles/day. Each vehicle engine rejects ~3–5 kW of waste heat, and exhaust temperatures reach 300–600°F.
- The freeway corridors themselves are wide impervious surfaces (6–10 lanes plus shoulders) that act as linear heat islands, elevating temperatures in adjacent neighborhoods.
- CA-87 (Guadalupe Freeway) runs directly through the urban core near these coordinates, creating a heat-generating



corridor bisecting the city.

HVAC Rejection Heat

- At 105.3°F, HVAC systems are operating at reduced efficiency (COP drops significantly above 100°F outdoor temperature), meaning they reject **more heat per unit of cooling delivered**. Estimated: at this temperature, commercial HVAC systems reject approximately 1.3–1.5 units of heat for every 1 unit of cooling provided.
- Downtown San José's mid-rise and high-rise buildings concentrate rooftop condensing units, creating localized heat plumes above the building canopy layer.
- This HVAC waste heat can elevate local air temperatures by an estimated 1–3°F in dense commercial zones, exacerbating the heat island effect precisely when it is most dangerous.

Impervious Commercial Surfaces

- San José's auto-oriented retail corridors feature extensive surface parking lots. Typical for this area: parking lots comprise 30–40% of total commercial zone land area.
- Large retail and commercial zones along Tully Road, Capitol Expressway, and Stevens Creek Boulevard (~2–4 miles in various directions) feature vast unshaded asphalt expanses that store and re-radiate heat well into evening hours.
- At 105.3°F ambient temperature, dark asphalt parking surfaces reach 150–170°F, creating dangerous radiant heat conditions for pedestrians and contributing to sustained nighttime heat.

Sustainability Initiatives

- San José has a **municipal Green Building Policy** requiring LEED Silver or equivalent for new municipal buildings.
- The city has been a leader in **community solar** and rooftop solar adoption — solar panels on commercial rooftops have the co-benefit of shading roof surfaces and reducing building heat gain, though they also reduce albedo compared to cool roofs.
- San José Clean Energy (SJCE), the community choice energy provider, supplies a high proportion of renewable energy, which reduces waste heat from local power generation (though most generation occurs outside the city).
- Google's planned **Downtown West** mixed-use development (~1 mile northwest of these coordinates, near Diridon Station) incorporates district-level sustainability features including green infrastructure and energy-efficient design.

Sources:

- Caltrans traffic volume data for Bay Area freeways
- San José municipal sustainability and green building policies
- General knowledge of Silicon Valley data center concentration and technology campus distribution
- ASHRAE data on HVAC performance degradation at extreme temperatures
- San José Clean Energy program documentation

3. Green Infrastructure & Urban Cooling Systems

Urban Vegetation Strategy

- San José's citywide **tree canopy coverage is approximately 15–18%**, which is moderate for a California city but insufficient to meaningfully counteract extreme heat events like this 105.3°F day.
- The city adopted a **Community Forest Management Plan** and has a goal of planting and maintaining trees, with emphasis on increasing canopy in underserved neighborhoods.
- Our City Forest, a nonprofit partner, has been instrumental in urban tree planting, but canopy growth is slow (10–20 years to maturity) and drought conditions limit survival rates.

Cooling Mechanisms

- Mature urban trees in San José provide localized cooling of **5–10°F** beneath the canopy through shading and evapotranspiration under normal conditions. However, at 105.3°F with likely low humidity, evapotranspiration rates may be reduced if trees are drought-stressed, diminishing cooling effectiveness.
- Parks provide measurable cool islands: well-irrigated parks can be 8–15°F cooler than surrounding asphalt at peak afternoon temperatures.
- The cooling effect of green infrastructure at this extreme temperature is **inadequate on its own** — even a 10°F reduction leaves conditions at ~95°F, still well above thermal comfort thresholds.



Notable Cooling Infrastructure

- **Guadalupe River Park and Gardens:** A linear park running along the Guadalupe River, approximately 0.5–1 mile west of these coordinates. This riparian corridor provides shade and some evaporative cooling, though the river often has low flow in October.
- **St. James Park:** A historic downtown park approximately 0.3 miles north of these coordinates, providing a small green oasis in the urban core — limited in size (~7 acres) but valuable for localized cooling.
- **Plaza de César Chávez:** A central downtown park approximately 0.2 miles from these coordinates, providing shade trees and open space in the densest part of the city.
- **Kelley Park:** A larger park (~156 acres) approximately 2.5 miles southeast, which includes the Japanese Friendship Garden and Happy Hollow — a significant cooling zone but distant from the urban core.
- **Municipal Rose Garden (San José Heritage Rose Garden):** Located approximately 2 miles west-northwest, providing irrigated green space.

Engineered Cooling

- San José does not have a significant **district cooling network**. Cooling is predominantly building-by-building, which is less efficient and generates more distributed waste heat.
- Downtown fountains and water features (such as those in Plaza de César Chávez) provide minor localized cooling but have limited thermal impact radius (~50–100 feet).
- No large-scale misting systems or artificial cooling ponds are known to be deployed in the downtown area.

Seasonal Variability and Adequacy

- October in San José is typically the transition from dry season to wet season. Most deciduous trees still have full canopy, which is favorable for shading.
- However, after a long dry summer, soil moisture is depleted and many non-irrigated trees may be drought-stressed, reducing evapotranspiration capacity by an estimated 30–50%.
- At 105.3°F, the existing green infrastructure is **grossly inadequate** to bring outdoor conditions to comfortable levels. This temperature exceeds the effective cooling capacity of urban vegetation by a wide margin.

Cooling Equity

- Tree canopy distribution in San José is **inequitable**: western neighborhoods (Willow Glen, Rose Garden, parts of Cambrian) have significantly higher canopy coverage (25–35%) compared to East San José neighborhoods (~8–12%).
- East San José, which has higher proportions of low-income and minority residents, experiences disproportionate heat exposure — a well-documented environmental justice concern in Santa Clara County.
- At 105.3°F, this disparity translates to potentially 10–15°F differences in experienced outdoor temperature between well-treed and poorly-treed neighborhoods.

Sources:

- City of San José Community Forest Management Plan
- San José Parks, Recreation and Neighborhood Services Department data
- American Forests urban tree canopy assessments for California cities
- Environmental justice and urban heat island studies for Santa Clara County
- General knowledge of San José park system

4. Building Material Thermal Properties

Dominant Building Materials

- **Residential:** The majority of San José's housing stock consists of wood-frame, stucco-clad single-family homes with asphalt shingle or tile roofing. Stucco has moderate thermal mass; wood frame has relatively low thermal mass, allowing faster heat gain and loss.
- **Commercial/Office:** Downtown mid-rises and newer tech campus buildings feature concrete and steel construction with glass curtain walls. These materials have high thermal mass (concrete: specific heat ~0.88 J/g·K, density ~2,300 kg/m³) and absorb significant daytime heat.
- **Industrial/Warehouse:** Metal-clad (corrugated steel) buildings with minimal insulation are common in industrial zones. These heat up rapidly and radiate intensely — surface temperatures can exceed 160°F at 105.3°F ambient.



- **Roadways and parking:** Asphalt is the dominant pavement material, covering an enormous fraction of the urban surface area.

Albedo Values

- **Fresh asphalt:** 0.04–0.05 (extremely low reflectance — absorbs 95%+ of solar radiation)
- **Aged/weathered asphalt:** 0.10–0.15
- **Concrete sidewalks:** 0.20–0.35
- **Asphalt shingle roofing (dark):** 0.05–0.15
- **Clay/concrete tile roofing:** 0.25–0.40
- **Glass curtain walls:** 0.05–0.10 (absorb most radiation; reflect specularly, causing glare heating of adjacent surfaces)
- **Cool roof coatings (where applied):** 0.60–0.70
- At 105.3°F with intense October solar radiation (~800–900 W/m² at solar noon), low-albedo surfaces are absorbing enormous thermal energy — a dark asphalt parking lot absorbs approximately 760–855 W/m².

Thermal Mass and Nighttime Re-radiation

- Concrete and masonry buildings in the downtown core absorb heat throughout the day and re-radiate it for 4–8 hours after sunset, creating an **urban heat island that persists well into nighttime**.
- At 105.3°F daytime peak, nighttime temperatures in the urban core may remain 15–20°F warmer than rural surroundings, potentially staying above 80°F overnight — preventing physiological recovery from heat stress.
- Asphalt roadways, which have both high thermal mass and low albedo, are the single largest contributor to nighttime heat retention in San José's urban fabric.

Glass Curtain Wall Effects

- Downtown San José's newer office towers (e.g., buildings along San Fernando Street and Santa Clara Street) feature extensive glass facades that create specular reflections, redirecting solar radiation onto streets and adjacent buildings.
- This "solar glare" effect can increase pedestrian-level radiant heat loads by 50–100 W/m² in affected areas, significantly worsening thermal comfort.
- Inside these buildings, the greenhouse effect increases cooling loads, which in turn increases HVAC waste heat rejection.

Heat Mitigation Techniques

- California's **Title 24 Building Energy Efficiency Standards** (updated in 2022) require cool roofs on new commercial buildings with minimum aged solar reflectance of 0.63 for low-slope roofs. This applies to new construction in San José.
- Adoption of cool roofs on existing buildings is **voluntary and limited** — the majority of the existing building stock still has conventional dark roofing.
- Permeable pavement adoption is minimal; most parking lots and roadways use conventional impervious asphalt.
- San José does not have a standalone cool pavement ordinance, though some pilot projects have been explored.

Building Stock Age

- A large proportion of San José's residential stock was built between 1950–1980, with **poor insulation by modern standards** (R-11 walls, R-19 attic typical vs. current code R-21/R-38). These homes gain heat rapidly and require more energy to cool.
- Newer construction (post-2010) meets California's stringent Title 24 standards with significantly better thermal envelopes, but represents a minority of total building stock.
- Older commercial buildings (pre-1990) often have outdated HVAC systems operating at lower efficiency, generating more waste heat per unit of cooling.

Sources:

- California Energy Commission Title 24 Building Energy Efficiency Standards
- Lawrence Berkeley National Laboratory Heat Island Group — albedo and cool surface research
- ASHRAE Fundamentals Handbook — thermal properties of building materials
- General knowledge of San José building stock characteristics and construction eras

5. Urban Expansion & Development Trends



Population Growth Trajectory

- San José is the **10th largest city in the United States** with approximately 1.03 million residents (2023 estimate). The city has experienced steady growth of approximately 0.5–1.0% annually over the past decade.
- The broader Santa Clara County continues to attract population due to the tech economy, placing sustained pressure on housing and infrastructure development.
- Each additional resident increases energy demand, vehicle trips, and building footprint — collectively amplifying anthropogenic heat generation.

Construction Trends

- **Vertical densification downtown:** Multiple high-rise residential and mixed-use towers have been approved or are under construction in the downtown core, particularly around the Diridon Station area. This increases building mass and HVAC loads in a concentrated zone.
- **Google Downtown West:** A major mixed-use development (~80 acres) near Diridon Station, approximately 1 mile northwest, will add millions of square feet of office, residential, and retail space. This project includes sustainability commitments but will significantly increase the built mass and population density of the area.
- **North San José:** Continued development of tech campuses and high-density residential (~3–5 miles north) is converting former industrial and agricultural land to impervious urban uses.
- **Urban infill:** Accessory dwelling units (ADUs) and lot splits under California's SB 9 are incrementally increasing impervious coverage in residential neighborhoods.

Net Change in Impervious Surface

- **Increasing:** Estimated net increase of 1–2% in impervious surface area per decade across the city, driven by infill development, ADU construction, and commercial expansion.
- Some offsetting occurs through green infrastructure requirements in new developments, but the net trend is toward more impervious coverage.
- The conversion of remaining agricultural/orchard land at the city's southern and eastern edges continues, replacing permeable, vegetated surfaces with residential subdivisions.

Climate-Adaptive Urban Design

- San José's **Climate Smart San José** plan includes goals for urban cooling, but specific heat action plans with enforceable mandates are still developing.
- California's **Extreme Heat Action Plan** (2022) provides a state-level framework that influences San José's planning, including requirements for cooling centers and heat-resilient infrastructure.
- Updated building codes (Title 24, 2022 cycle) improve new building thermal performance, but the slow turnover of existing stock limits near-term impact.
- The BART extension to San José (under construction) will provide transit options that could reduce vehicle heat contributions long-term, but construction itself temporarily increases impervious surfaces and disrupts existing green infrastructure.

Near-Term Heat Profile Projection (5–10 Years)

- Downtown densification will **intensify the urban heat island** in the core by increasing building mass, HVAC loads, and reducing sky view factor.
- If green infrastructure commitments in projects like Downtown West are fully implemented, they could partially offset heat gains in the Diridon area.
- Without aggressive cool surface mandates and urban greening, the frequency and severity of extreme heat events like this 105.3°F day will become increasingly dangerous as the built environment becomes denser.
- Estimated: San José's urban heat island intensity could increase by 1–3°F over the next decade under current development trajectories, making extreme heat events even more severe.

Sources:

- U.S. Census Bureau population estimates for San José
- City of San José planning department — approved development projects
- Climate Smart San José plan
- California Governor's Office of Planning and Research — Extreme Heat Action Plan



- VTA BART Silicon Valley Extension project documentation

6. Pedestrian Infrastructure & Outdoor Thermal Comfort

Walkability Characterization

- Downtown San José has a **Walk Score of approximately 80–90** (very walkable), with a grid street network, mixed-use destinations, and pedestrian-oriented streetscapes along San Fernando Street, Santa Clara Street, and the SoFA (South First Area) district.
- Outside the downtown core, walkability drops significantly — suburban residential neighborhoods score 30–50 (car-dependent) with incomplete sidewalk networks and long block lengths.
- At 105.3°F, even the walkable downtown becomes **functionally hostile to pedestrians** without adequate shade and cooling infrastructure.

Shading Infrastructure

- **Downtown:** Moderate street tree coverage along some corridors (e.g., The Alameda, parts of Santa Clara Street), but many blocks have young or sparse trees providing insufficient canopy. Some buildings provide awnings or arcades, but coverage is inconsistent.
- **Transit stops:** VTA light rail and bus stops have variable shelter coverage — many stops have only a simple pole-mounted sign with no shade structure, exposing waiting passengers to full solar radiation.
- **Suburban areas:** Minimal pedestrian shading. Wide arterials with narrow or absent sidewalks and no street trees are common, particularly in East San José commercial corridors.
- Estimated: less than 25% of pedestrian routes in the downtown area have continuous shade coverage; in suburban areas, this drops below 10%.

Mean Radiant Temperature (MRT) Conditions

- At 105.3°F ambient temperature with clear October skies and high solar angle (still significant at ~55° elevation at solar noon in early October at this latitude), MRT in unshaded areas can reach **140–160°F**.
- Asphalt surfaces at 155–170°F radiate intensely at pedestrian level. A person standing on an unshaded sidewalk adjacent to a dark parking lot receives radiant heat from below (pavement), from the sides (building walls, parked cars), and from above (direct solar).
- Sky view factor in downtown is moderate (~0.3–0.5 in street canyons), which traps longwave radiation between buildings but also provides some building shade on east-west streets during parts of the day.
- In open suburban areas with high sky view factor (~0.7–0.9), direct solar exposure is maximized and MRT is at its highest.

Heat Exposure Risk

- At 105.3°F, outdoor conditions exceed **dangerous heat stress thresholds** for all but the most acclimatized individuals. The Wet Bulb Globe Temperature (WBGT) in unshaded areas likely exceeds 90°F, placing conditions in the "extreme danger" category for physical activity.
- Pedestrians crossing large parking lots (common in San José's auto-oriented retail zones) face the most severe exposure: no shade, high radiant heat from all directions, and distances of 200–500 feet from building shade.
- Vulnerable populations — elderly, children, outdoor workers, unhoused individuals — face acute health risks. San José has a significant unhoused population (~6,000+) with limited access to cooling resources.
- The combination of high ambient temperature, intense surface radiation, and limited shade creates conditions where **heat stroke risk is elevated within 15–30 minutes** of unprotected outdoor exposure.

Cooling Interventions

- **Cooling centers:** The City of San José activates cooling centers at libraries and community centers during extreme heat events, but these require people to travel to them — often through the very heat they're trying to escape.
- **Misting systems:** Not widely deployed in San José's public spaces. Some individual businesses may have patio misters, but no systematic public misting infrastructure exists.
- **Cool pavements:** Limited pilot applications. The vast majority of sidewalks and roads use conventional materials.
- **Passive cooling corridors:** The Guadalupe River Trail provides a partially shaded, lower-temperature pedestrian/cycling corridor through the urban core, but it serves a recreational rather than utilitarian transportation function for most users.



Cycling Infrastructure

- San José has an expanding network of bike lanes (~300+ miles of bikeways of various classes), but most are unprotected lanes on conventional asphalt roadways with **no shade or heat mitigation**.
- At 105.3°F, cycling on unshaded asphalt roadways exposes riders to extreme radiant heat from the road surface (within 3–4 feet of 160°F+ asphalt) and convective heat from hot air.
- The Guadalupe River Trail and Los Gatos Creek Trail provide somewhat cooler cycling options due to riparian vegetation and partial shade, but they don't serve all commute routes.

Notable Pedestrian Comfort Zones and Deficits

- **Comfort zones:** Plaza de César Chávez and the adjacent Paseo de San Antonio (~0.2 miles from coordinates) offer mature tree shade and some water features — among the best pedestrian microclimates downtown. San Pedro Square Market area (~0.3 miles north-northwest) has covered outdoor dining areas providing shade.
- **Comfort deficits:** The area around the SAP Center/Diridon Station (~1 mile northwest) is notably exposed — large surface parking lots, wide roadways, and minimal shade create one of the worst pedestrian heat environments in the urban core. Similarly, the intersection zones of major arterials (e.g., Santa Clara St. and 1st Street) feature wide crossings with full solar exposure.
- **Severe deficit:** East San José commercial corridors along Story Road and Tully Road (~2–3 miles east-southeast) have minimal street trees, wide asphalt roads, and strip-mall parking lots — creating some of the most thermally hostile pedestrian environments in the city, disproportionately affecting lower-income communities.

Sources:

- Walk Score data for San José neighborhoods
- City of San José Better Bike Plan and pedestrian infrastructure assessments
- NOAA/NWS heat stress indices and WBGT threshold guidelines
- Santa Clara County Public Health Department heat vulnerability assessments
- General knowledge of San José streetscape conditions and pedestrian infrastructure

Events Analysis

1. Extreme Weather Events & Heat Event History

Heat-Related Events

- **Baseline temperature conversion:** The provided average temperature of 40.74°C converts to approximately **105.3°F**. This is an extraordinarily high value for the San José, California area (coordinates 37.29°N, 121.83°W) on October 2, and would represent a significant extreme heat event if observed.
- **September 2022 Heatwave:** One of the most severe and well-documented heat events in modern California history struck the San José/Santa Clara Valley region from late August through early September 2022. Downtown San José recorded temperatures exceeding 110°F on September 6, 2022, shattering all-time records. The event lasted approximately 10 days and was driven by an exceptionally strong and persistent upper-level ridge (heat dome) over the western United States. This event resulted in a statewide grid emergency (Flex Alerts and rotating outage warnings from CAISO), multiple heat-related fatalities across California, and overwhelmed emergency services.
- **June 2021 Pacific Northwest / Western Heat Dome:** While the most extreme temperatures were recorded in Oregon and Washington, the San José area experienced temperatures well above 100°F during this late June event. The synoptic pattern — an omega block with an exceptionally amplified ridge — is a textbook example of the pattern that drives extreme heat in the South Bay.
- **July 2006 California Heatwave:** A prolonged, multi-week heat event across California in July 2006 brought sustained temperatures above 105°F to interior valleys including the Santa Clara Valley. This event is associated with an estimated 600+ excess deaths statewide (documented in California Department of Public Health analyses) and widespread power grid strain.
- **Typical synoptic precursors for extreme heat in San José:**
 - Persistent upper-level high-pressure ridge (500 mb heights ≥ 594 dam) centered over the Great Basin or directly over California
 - Offshore (northeasterly) wind patterns that bring hot, dry air from the interior over the coastal ranges and into the Santa Clara Valley, suppressing the normal marine layer and sea breeze cooling from the San Francisco Bay
 - Antecedent dry conditions and depleted soil moisture reducing evapotranspiration, which is common by late summer/early fall
 - Reduced or absent marine stratus/fog intrusion — the South Bay's primary natural cooling mechanism



- **Seasonal heat risk context for October 2:** The traditional peak heat season for San José runs from approximately **mid-June through mid-September**, with the highest risk concentrated in July and August. October falls outside the primary heat season but is within the extended risk window. Late-season heat events in late September and early October are not unprecedented — they are typically driven by strong Santa Ana-type or Diablo wind events that bring hot, dry, offshore flow. A temperature of 105.3°F on October 2 would be **highly anomalous and record-breaking** for this date. Historically typical: Normal highs for San José on October 2 are approximately 78–82°F. The observed value exceeds the normal by roughly 23–27°F.
- **Government and institutional responses:**
 - During the September 2022 event, the City of San José activated cooling centers across community centers and libraries
 - CAISO (California Independent System Operator) issued Flex Alerts urging energy conservation to prevent rolling blackouts
 - Santa Clara County issued local heat emergency declarations
 - Cal/OSHA enforced outdoor heat illness prevention standards for workers
- **Compound events:**
 - Heat + Drought: The 2012–2016 California mega-drought coincided with multiple extreme heat years, with depleted reservoirs and critically low soil moisture amplifying surface heating
 - Heat + Wildfire Smoke: The August–September 2020 period saw extreme heat co-occurring with catastrophic wildfire smoke from the SCU Lightning Complex and other fires. The combined thermal stress and severely degraded air quality (AQI > 300 for multiple days) created a compounded public health emergency in the South Bay
 - Heat + Power Strain: Multiple events have brought CAISO within margin of ordering rotating outages, with the September 2022 event being the closest to widespread blackouts since the 2020 rolling outages

Other Extreme Weather With Heat Relevance

- **Droughts:** The Santa Clara Valley is highly susceptible to drought, with major episodes in 2007–2009, 2012–2016, and 2020–2022. Drought directly amplifies heat through the soil moisture–temperature feedback: as soils dry, incoming solar energy heats the surface rather than driving evaporation, raising daytime temperatures. Estimated: During severe drought years, peak summer temperatures in San José run approximately 2–5°F above non-drought year averages due to this feedback. By early October, soil moisture is typically at or near its annual minimum regardless of drought status, meaning this feedback is already near maximum.
- **Wildfires:** The San José area is surrounded by wildland-urban interface zones (Diablo Range to the east, Santa Cruz Mountains to the west). Major fire events such as the SCU Lightning Complex (2020, ~400,000 acres) and numerous smaller fires in the Diablo Range occur during and are exacerbated by extreme heat. Wildfire smoke can have a dual thermal effect: thick smoke layers reduce peak daytime temperatures slightly by blocking solar radiation, but trap longwave radiation at night, elevating overnight minimums and reducing the critical nighttime recovery window. The combined heat + smoke exposure significantly worsens respiratory and cardiovascular health outcomes.
- **Diablo Winds:** These hot, dry, offshore wind events (analogous to Southern California's Santa Ana winds) are the primary driver of late-season (September–November) extreme heat in the San Francisco Bay Area. They develop when high pressure builds over the Great Basin and drives northeasterly flow over the coastal ranges, producing compressional (adiabatic) warming. Diablo wind events are the most likely synoptic explanation for a 105°F reading on October 2 in San José. These winds simultaneously elevate fire danger to critical levels, creating compound heat-fire risk.

Sources:

- National Weather Service (NWS) San Francisco Bay Area forecast office — historical event summaries and climate records
- California Department of Public Health — 2006 heatwave mortality analysis
- CAISO grid emergency records and Flex Alert archives
- U.S. Drought Monitor historical data for Santa Clara County
- CAL FIRE incident archives (SCU Lightning Complex, etc.)

2. Heatwave Frequency & Intensity

- **Heatwave definition for this region:** The National Weather Service (NWS) San Francisco Bay Area office issues **Excessive Heat Warnings** for the Santa Clara Valley when temperatures are forecast to reach $\geq 105^{\circ}\text{F}$, or when daytime highs $\geq 100^{\circ}\text{F}$ and overnight lows remain $\geq 75^{\circ}\text{F}$ for two or more consecutive days. **Heat Advisories** are issued at lower thresholds, typically when highs reach 95–104°F for sustained periods. These thresholds reflect the region's relatively low acclimatization to extreme heat compared to desert locations.
- **Frequency:**
 - Historically typical: San José experiences approximately 2–4 significant heat events per year (days $\geq 100^{\circ}\text{F}$), concentrated in June–September



- Full Excessive Heat Warning–level events ($\geq 105^{\circ}\text{F}$) are less common — estimated at roughly 1–2 events per decade historically, though this frequency has increased markedly since approximately 2010
- Trend: The number of days exceeding 100°F in San José has increased. Estimated: approximately 1–3 additional extreme heat days per decade since the 1980s baseline, consistent with broader western U.S. trends documented by NOAA and academic literature
- **Intensity metrics:**
 - Typical heatwave peak temperatures in San José: $100\text{--}108^{\circ}\text{F}$
 - Record peak: approximately $109\text{--}112^{\circ}\text{F}$ (recorded during the September 2022 event at downtown San José and surrounding stations)
 - Typical heatwave duration: 2–5 days, though the September 2022 event persisted for approximately 10 days
 - **Nighttime minimum behavior — critical factor:** During major heat events, overnight lows in San José often remain in the $70\text{--}80^{\circ}\text{F}$ range, well above the $\sim 75^{\circ}\text{F}$ threshold considered dangerous for physiological recovery. The urban heat island effect in the densely developed central San José area exacerbates this. During the September 2022 event, overnight lows at some stations did not drop below $78\text{--}80^{\circ}\text{F}$ for multiple consecutive nights.
- **Record-breaking events (summary):**
 - September 2022: All-time record highs broken at multiple Bay Area stations; San José peaked near $109\text{--}112^{\circ}\text{F}$; duration ~ 10 days; statewide grid emergency; documented excess mortality
 - July 2006: Sustained multi-week event; San José peaked $\sim 108\text{--}110^{\circ}\text{F}$; estimated 600+ excess deaths statewide
 - June 2021: Peak $\sim 105\text{--}107^{\circ}\text{F}$ in San José; shorter duration ($\sim 3\text{--}4$ days locally) but part of the unprecedented Pacific Northwest heat dome
- **Trend context:** Heatwaves in the San José area are increasing in frequency, intensity, duration, and exhibiting earlier seasonal onset and later seasonal persistence. The extension of heat risk into late September and early October is consistent with observed trends of a lengthening heat season across California. Attribution studies consistently link these trends to anthropogenic climate change, with the western U.S. high-pressure ridge patterns becoming more persistent.
- **Classification of the provided temperature (105.3°F on October 2):**
 - **vs. Climate normals:** Normal high for San José on October 2 is approximately $78\text{--}82^{\circ}\text{F}$. The provided value is **$\sim 23\text{--}27^{\circ}\text{F}$ above normal** — an extreme positive anomaly.
 - **vs. Heatwave trigger thresholds:** At 105.3°F , this **meets or exceeds the NWS Excessive Heat Warning threshold ($\geq 105^{\circ}\text{F}$)** for the Santa Clara Valley.
 - **vs. Health-risk temperature bands:** This temperature falls squarely in the **"Extreme Danger"** category for heat-related illness, particularly given the late-season timing when population acclimatization to heat has diminished after the cooling of September.
 - **Explicit risk classification:** **EXCEEDING HEATWAVE THRESHOLD — Extreme heat event, high pub health risk.**
- **Heat dome and blocking pattern susceptibility:** The Santa Clara Valley's inland position relative to the coastal mountains makes it highly susceptible to heat amplification when the marine layer is suppressed. The broader California Central Valley–adjacent geography means that when upper-level ridging builds over the western U.S. (a pattern that climate models project will become more frequent and persistent), San José is directly in the zone of maximum heating. The valley's topographic enclosure by the Diablo Range and Santa Cruz Mountains can trap hot air, particularly during offshore wind events. The location is among the most heat-dome-susceptible metropolitan areas on the U.S. West Coast.

Sources:

- NWS San Francisco Bay Area — heat product criteria and warning thresholds
- NOAA/NCEI climate normals (1991–2020) for San José, CA
- Western Regional Climate Center — historical temperature records
- Peer-reviewed literature on western U.S. heatwave trends and attribution (general body of knowledge; no specific fabricated citations)

3. Public Health Impacts & Heat Vulnerability

- **Known heat-related health burden:**
 - During the July 2006 California heatwave, Santa Clara County reported significant increases in heat-related emergency department visits and hospitalizations. Statewide, the event was associated with an estimated 600+ excess deaths (California Department of Public Health).
 - The September 2022 heatwave similarly produced documented spikes in heat-related illness across Santa Clara County, including heat exhaustion, heatstroke, and acute exacerbation of cardiovascular and renal conditions.
 - Historically typical: Heat-related ED visits in Santa Clara County spike sharply when temperatures exceed approximately $95\text{--}100^{\circ}\text{F}$, with a steep dose-response curve above 100°F .
- **Vulnerable populations in the San José area:**



- **Elderly (65+):** San José has a growing senior population; those living alone or without air conditioning are at highest risk. Many older homes in central San José lack AC due to the historically mild climate.
- **Outdoor workers:** The South Bay has a large agricultural workforce in adjacent areas (southern Santa Clara Valley) and significant construction and landscaping labor forces directly exposed to extreme heat.
- **Unhoused populations:** San José has one of the largest unhoused populations among U.S. cities, with significant encampments along waterways (Guadalupe River, Coyote Creek). These individuals have virtually no access to cooling and are disproportionately affected during heat events.
- **Low-income communities:** Neighborhoods in East San José (e.g., the 95116, 95122, 95127 ZIP codes) have lower rates of air conditioning, higher housing density, less tree canopy, and greater socioeconomic vulnerability.
- **Children:** School-age children engaged in outdoor activities are at risk, particularly given that early October is within the school year and outdoor sports seasons.
- **Heat-mortality relationship:**
 - Estimated: For the San José / Santa Clara County area, excess mortality begins to increase at daily maximum temperatures above approximately 95–100°F, based on California-wide epidemiological studies. The relatively mild baseline climate means the population is less acclimatized to extreme heat than residents of desert cities like Phoenix, resulting in a lower threshold for excess mortality.
 - At 105.3°F, the temperature is well above this threshold, placing the population in a high-risk mortality zone — especially if sustained over multiple days.
 - **Late-season de-acclimatization factor:** By early October, residents have begun physiological de-acclimatization from summer heat. A sudden return to 105°F after weeks of cooler fall weather would produce a disproportionately severe health impact compared to the same temperature in mid-July, when the population is more heat-adapted.
- **Consecutive hot night risk:**
 - At a daily average of 105.3°F, overnight minimum temperatures would likely remain in the 75–85°F range, well above the ~75°F threshold for dangerous nighttime heat.
 - Sustained nighttime heat prevents the body from recovering from daytime thermal stress, leading to cumulative physiological strain. This is the primary driver of heat-related mortality during multi-day events.
 - San José's urban core, with extensive impervious surfaces, retains heat and exhibits a strong urban heat island effect that further elevates nighttime minimums by an estimated 5–10°F compared to surrounding rural areas.
- **Heat advisory and warning systems:**
 - The NWS San Francisco Bay Area office issues tiered heat products **Heat Advisory** (sustained highs 95–104°F or warm overnight lows), **Excessive Heat Watch** (potential for Excessive Heat Warning conditions in 24–72 hours), and **Excessive Heat Warning** (highs ≥105°F or sustained dangerous heat).
 - At 105.3°F, an **Excessive Heat Warning** would almost certainly be in effect for the Santa Clara Valley.
 - Santa Clara County also operates an **Operational Area Emergency Operations Center** that can be activated for heat emergencies, coordinating cooling center operations and public messaging.
- **Cooling infrastructure and public health interventions:**
 - The City of San José and Santa Clara County activate **cooling centers** at libraries, community centers, and designated public facilities during heat emergencies.
 - **Cal/OSHA Heat Illness Prevention Standard (Title 8, Section 3395)** Requires employers to provide water, shade, rest breaks, and heat illness training for outdoor workers when temperatures exceed 80°F, with enhanced provisions (High Heat Procedures) above 95°F.
 - The California Public Utilities Commission (CPUC) enforces **utility shutoff moratoriums** during extreme heat events, preventing disconnection of electricity for non-payment.
 - The Bay Area Air Quality Management District issues concurrent Spare the Air alerts when heat co-occurs with poor air quality.
- **Heat vulnerability mapping:**
 - Santa Clara County has published heat vulnerability assessments as part of its Climate Adaptation Plan. These identify East San José, central downtown areas, and parts of the Alum Rock neighborhood as having the highest heat vulnerability, driven by low tree canopy, high impervious surface coverage, older housing stock without AC, and concentrated low-income and minority populations.
 - CalEPA's **CalEnviroScreen** tool identifies several census tracts in East and Central San José as scoring in the top 10–25% statewide for combined environmental and socioeconomic vulnerability, including heat-related indicators.
- **Health-system preparedness:**
 - During the September 2022 event, Bay Area hospitals reported increased ED volumes for heat-related illness. Santa Clara Valley Medical Center (the county's safety-net hospital) and regional hospitals experienced surge conditions.
 - EMS response times can degrade during extreme heat events due to increased call volume and, in some cases, vehicle/equipment heat-related issues.
 - Historically typical: Major heat events in the South Bay produce a 20–50% increase in heat-related ED visits, with



the most severe events straining hospital capacity.

- **Equity dimension:**

- Heat-related health burden in San José is disproportionately concentrated in **low-income communities of color**, particularly in East San José where Latino and Vietnamese American communities face compounding factors: lower AC prevalence, higher outdoor occupational exposure, less green space, older and more heat-retentive housing, and reduced access to healthcare.
- The unhoused population — disproportionately composed of individuals with mental health conditions and substance use disorders — faces the most acute risk with the fewest resources.
- Historically redlined neighborhoods in San José correlate strongly with present-day urban heat island intensity and heat vulnerability, reflecting the enduring legacy of discriminatory land-use planning on heat exposure.

Sources:

- California Department of Public Health — heat-related morbidity and mortality surveillance data
- Santa Clara County Public Health Department — heat emergency response plans and vulnerability assessments
- Cal/OSHA Title 8, Section 3395 — Heat Illness Prevention Standard
- CalEPA CalEnviroScreen 4.0
- NWS San Francisco Bay Area — heat product criteria
- Academic literature on heat-mortality thresholds in California (general body of knowledge)
- Santa Clara County Climate Adaptation Plan and associated heat vulnerability mapping

Anthropogenic Factors Analysis

1. Heat Emissions from Vehicles & Industry

Temperature Context

- Average temperature: $40.74^{\circ}\text{C} = 105.3^{\circ}\text{F}$ — an exceptionally high temperature for San Jose, California (coordinates 37.29°N , 121.83°W correspond to the San Jose/South Bay area of Silicon Valley)
- This temperature is well above normal October averages ($\sim 75^{\circ}\text{F}$) and indicates an extreme heat event, likely associated with an offshore wind/heat dome pattern

Transportation Heat Footprint

- San Jose and Silicon Valley are heavily car-dependent; the region has among the highest vehicle miles traveled (VMT) per capita in California
- Dominant transport mode: private automobile — estimated 75-80% mode share for commuting based on Census/ACS data for Santa Clara County
- Major heat-generating corridors: US-101, I-280, I-880, SR-87, and SR-17 carry hundreds of thousands of vehicles daily
- Vehicular waste heat sources: internal combustion engines reject approximately 60-70% of fuel energy as waste heat (exhaust at $400\text{-}900^{\circ}\text{F}$, radiator discharge, tire-road friction adding $\sim 10\text{-}15^{\circ}\text{F}$ to pavement surface temperatures)
- At 12:00 hours on a Wednesday, midday traffic is moderate — not at peak rush hour levels but significant due to commercial/delivery traffic and lunch-hour trips

Industrial and Commercial Waste Heat

- **Data centers:** Silicon Valley hosts one of the world's highest concentrations of data centers — major facilities from Equinix, Vantage, CyrusOne, and corporate campuses (Apple, Google, Meta nearby). Data centers convert nearly 100% of electrical input to heat, with facilities ranging from 5-50+ MW each
- **Semiconductor manufacturing:** Facilities in the area (historically significant, though some have relocated) generate substantial process heat from cleanroom operations and fabrication equipment
- **Commercial office campuses:** Large corporate headquarters (Adobe, Cisco, eBay, PayPal in San Jose proper) generate significant HVAC waste heat, especially under extreme heat conditions when cooling systems run at maximum
- **San Jose International Airport (SJC):** Jet engines, APU's, ground support equipment, and vast asphalt aprons create a concentrated heat zone; airport surfaces can reach $150\text{-}170^{\circ}\text{F}$ at this ambient temperature
- Estimated: Data center waste heat in Santa Clara County likely contributes 500+ MW of continuous thermal discharge to the local environment

Spatial Heat Concentration



- Highway corridors (I-880, US-101) typically run 3-7°F warmer than surrounding residential areas due to combined vehicle exhaust, pavement absorption, and lack of vegetation
- Data center clusters in North San Jose/Santa Clara create localized thermal plumes; condenser arrays can elevate immediate surrounding air temperature by 2-5°F
- Airport apron areas: documented to be 5-10°F warmer than surrounding neighborhoods due to jet exhaust and dark pavement

Temporal Patterns at Given DateTime

- Wednesday at noon: commercial and industrial activity at full capacity; data centers operating at steady-state (24/7 load with slight midday increase from business computing demand)
- Midday delivery traffic (Amazon, FedEx, UPS) concentrated in commercial zones adds localized heat pulses
- Construction activity typically active at this hour, adding equipment exhaust heat

Emission-Reduction Measures

- California leads in EV adoption; Santa Clara County has among the highest EV registration rates in the state — estimated 20-25% of new vehicle sales are electric (2024)
- VTA (Valley Transportation Authority) has committed to zero-emission bus fleet transition
- San Jose's Climate Smart plan targets carbon neutrality by 2030
- Several data centers have implemented waste heat recovery, though most still reject heat to atmosphere

Waste Heat Recovery Opportunities

- Given the mild climate, district heating demand is low, limiting traditional waste heat recovery applications
- Some data center operators are exploring waste heat use for absorption cooling or nearby building heating during winter months
- Opportunity exists for data center waste heat to power desalination or industrial processes, though implementation remains limited

Sources:

- U.S. Census Bureau American Community Survey (commute mode share data)
- California Energy Commission data center energy reports
- San Jose Climate Smart Plan documentation
- California DMV EV registration statistics
- General thermodynamic principles of internal combustion engines and data center operations

2. Cooling Infrastructure & Waste Heat Feedback Loop

Cooling Infrastructure Prevalence

- San Jose residential AC penetration: estimated 60-70% — lower than Central Valley cities (90%+) due to historically mild climate, but rapidly increasing due to intensifying heat events
- Commercial AC penetration: effectively 100% for office buildings, retail, and institutional facilities
- Many older homes (pre-1980s) in central San Jose lack central AC and rely on portable/window units or have no mechanical cooling
- Newer construction (post-2000) in South San Jose and Evergreen areas almost universally includes central AC

The AC Feedback Loop

- At 105.3°F, virtually all available cooling systems are operating at maximum capacity
- For every unit of cooling provided indoors, approximately 1.2-1.4 units of heat are rejected outdoors (cooling load + compressor work)
- In dense commercial areas (downtown San Jose, Santana Row, Valley Fair area), concentrated condenser heat rejection can elevate local ambient temperatures by an estimated 1-3°F
- Data center cooling represents a massive concentrated feedback: a 20 MW data center rejects roughly 20 MW of heat continuously through cooling towers or air-cooled condensers
- At this extreme temperature, COP (coefficient of performance) of AC systems degrades — typical residential systems drop from COP 3.5 at design conditions to COP 2.5-3.0, meaning more electricity consumed and more waste heat per



unit of cooling

Balance-Point Temperature

- Typical cooling balance-point temperature for this climate zone (ASHRAE Zone 3C/3B): approximately 65°F
- Current temperature of 105.3°F is **40.3°F above the balance point** — an extraordinary cooling load differential
- Cooling Degree Hours at this moment: approximately 40 CDH (base 65°F), indicating extreme instantaneous cooling demand

Cooling Inequality

- East San Jose and downtown neighborhoods have higher proportions of older housing stock, lower-income residents, and rental units — AC access estimated 15-25% lower than affluent neighborhoods
- Mobile home parks in the area are particularly vulnerable — poor insulation combined with limited cooling capacity
- Unhoused population (San Jose has one of the largest unhoused populations in California) has no access to cooling infrastructure
- At 105.3°F, this inequality becomes life-threatening — indoor temperatures in un-cooled units can reach 100-110°F

District Cooling Systems

- No major district cooling system operates in San Jose; cooling is predominantly distributed (individual building systems)
- Some corporate campuses (e.g., Apple Park in nearby Cupertino) use centralized chilled water plants that are more efficient than distributed systems but still reject substantial heat

Innovative and Passive Cooling Strategies

- San Jose's "cool roof" ordinance requires high-albedo roofing on new commercial construction
- Some newer developments incorporate ground-source heat pumps, though penetration remains low (~1-2% of buildings)
- Evaporative cooling is effective in this climate during dry heat events (low humidity) and some facilities use indirect evaporative cooling
- Nighttime ventilation flushing is normally effective in San Jose's climate (typical diurnal swing of 25-30°F) but may be limited during multi-day heat events when nighttime temperatures remain elevated

Cooling Demand Classification

- At 105.3°F in October (far exceeding 99th percentile conditions for this location and season): **EMERGENCY**
- This temperature exceeds typical HVAC design conditions for San Jose (design cooling temperature is approximately 95-100°F per ASHRAE data), meaning many systems cannot maintain setpoints

Sources:

- ASHRAE climate zone designations and design temperature data
- California Residential Appliance Saturation Study (RASS)
- San Jose building code requirements for cool roofs
- Published research on AC waste heat urban temperature contributions (Salamanca et al., de Munck et al.)

3. Energy System Load & Grid Stress

Energy Demand Profile

- San Jose is served primarily by PG&E (Pacific Gas & Electric) and San Jose Clean Energy (community choice aggregator)
- Estimated consumption split: Commercial/tech sector ~50-55%, Residential ~30-35%, Industrial ~15-20% — reflecting Silicon Valley's office/data center-heavy economy
- San Jose Clean Energy sources: approximately 60% carbon-free (solar, wind, hydro, nuclear); PG&E's mix is approximately 50%+ carbon-free
- Natural gas remains significant for residential heating and peaking power plants
- Solar generation is high at noon on a clear October day — likely near peak solar output, partially offsetting cooling demand



Temperature-Demand Sensitivity

- Typical for California utilities: electricity demand increases approximately 2-5% per °F above 80°F during heat events
- At 105.3°F (25°F above the 80°F threshold), this implies demand could be 50-125% above baseline — effectively at or beyond system capacity
- CDD base 65°F: current hourly contribution is approximately 40 cooling degree-hours, translating to extreme demand
- CAISO (California Independent System Operator) typically issues Flex Alerts when temperatures across the state exceed 100°F in population centers

Grid Stability and Heat-Related Risk

- California has documented history of heat-related grid emergencies: the September 2022 heat dome triggered Stage 2 and Stage 3 grid emergencies with rotating outages
- The August 2020 heat event caused rolling blackouts affecting hundreds of thousands across California, including the Bay Area
- At 105.3°F in San Jose, CAISO would almost certainly be at or near emergency conditions, particularly if this heat is regional
- PG&E transformers and distribution equipment experience thermal derating: transformer capacity decreases approximately 1% per °F above rated ambient temperature (typically 104°F for oil-filled transformers)

Grid Heat Vulnerability

- Transmission line capacity decreases at high temperatures due to thermal sag limits — estimated 5-10% derating at these temperatures
- Underground distribution cables in urban San Jose experience reduced heat dissipation when soil temperatures rise
- Substation transformers in the area are at risk of thermal overload under sustained extreme heat combined with peak demand

Load Shedding Risk

- **Active risk:** California has a documented history of rolling blackouts during extreme heat. At 105.3°F in the Bay Area (which is abnormally hot for this region), CAISO would likely be issuing Flex Alerts or higher-level emergency notices
- The risk is compounded if this heat extends across the state, reducing import capacity from neighboring regions

Energy Resilience Measures

- California has aggressively deployed battery storage: over 7 GW statewide as of 2024, with significant installations in the Bay Area
- Demand response programs: PG&E and San Jose Clean Energy offer residential and commercial demand response; at this temperature, these programs would be fully activated
- Solar generation advantage: at noon in October, solar is producing near-peak output, providing critical supply during this demand peak
- Behind-the-meter solar + storage (Tesla Powerwall, etc.) has significant penetration in this affluent area, providing some grid relief
- San Jose has multiple microgrids at critical facilities (hospitals, emergency services)

Current Grid Stress Assessment

- At 105.3°F at noon on a weekday: the energy system is at or near **peak/emergency demand levels**
- Solar production at midday provides crucial supply, but demand likely approaches or exceeds normal peak capacity
- The afternoon hours (3-7 PM) will be even more critical as solar declines while temperatures remain elevated and thermal mass continues releasing heat

Sources:

- CAISO historical grid emergency records (2020, 2022 events)
- PG&E service territory data and rate structures
- San Jose Clean Energy power content labels
- California Energy Commission demand forecasts and temperature sensitivity analyses
- ASHRAE transformer derating standards



4. Traffic Behavior & Vehicular Heat Contribution

Traffic Pattern Characterization

- San Jose is a car-dependent metro; typical weekday sees heavy congestion on US-101, I-280, I-880, and SR-87
- Peak commute hours: 7-9:30 AM and 4-7 PM; at noon (the given time), traffic is moderate — primarily commercial, delivery, and service vehicles
- Post-pandemic hybrid work has somewhat reduced peak congestion but increased midday trip distribution
- Estimated: Santa Clara County sees approximately 40-50 million VMT per day based on Caltrans data for major corridors

Waste Heat Concentration Zones

- **I-880/US-101 interchange (near SJC airport):** One of the busiest interchanges in the South Bay — concentrated vehicle idling and acceleration generates intense localized heat
- **US-101 through North San Jose:** Tech commuter corridor with high traffic density; pavement temperatures likely 140-160°F at this ambient temperature
- **Downtown San Jose surface streets:** Signal-controlled intersections cause stop-and-go patterns that maximize per-vehicle heat output
- **Freight corridors:** I-880 is a major freight route connecting Port of Oakland to logistics centers; diesel trucks generate 2-3x the waste heat per vehicle of passenger cars
- **Parking structures:** Multi-level garages (Valley Fair, Santana Row, downtown) trap vehicle exhaust heat with limited ventilation, creating thermal reservoirs
- **Drive-through clusters:** Fast food corridors along major arterials (Stevens Creek Blvd, Tully Road) concentrate idling vehicle heat

Pavement Heat Interaction

- At 105.3°F ambient, asphalt pavement surface temperatures reach 145-165°F; vehicle traffic prevents radiative cooling by blocking sky view and adding friction heat
- Tire-road friction adds approximately 10-15°F to pavement surface temperature in high-traffic zones
- Hot exhaust (300-500°F from catalytic converters) directed at pavement surface further heats road infrastructure
- Dark asphalt absorbs 85-95% of solar radiation; combined with vehicle heat, major roads become linear heat sources radiating into adjacent areas

Public Transit Role

- VTA light rail and bus system has relatively low ridership compared to the population — estimated 3-5% commute mode share for transit
- Caltrain provides rail service but primarily serves north-south peninsula commuters
- Low transit mode share means the vast majority of trips generate individual vehicle waste heat rather than being consolidated into more efficient mass transit
- Each car trip generates approximately 3-5 kWh of waste heat per hour of driving; a bus carrying 40 passengers generates roughly the same total as 3-4 cars

Heat-Induced Behavioral Shifts

- At 105.3°F, walking and cycling are effectively eliminated for most people — shifting trips to air-conditioned vehicles and increasing VMT
- Transit ridership likely decreases due to exposed waiting areas (bus stops, light rail platforms without shade reaching 120°F+ surface temperatures)
- Increased short-distance driving (e.g., driving to lunch instead of walking) adds to midday traffic and waste heat
- Some workers may leave early or shift schedules, potentially spreading peak traffic over a longer period

Mitigation Measures

- San Jose has invested in cool pavement pilots on select streets (reflective sealcoats reducing surface temperature by 10-15°F)
- VTA is deploying zero-emission electric buses, which produce significantly less waste heat than diesel (no exhaust heat, though still generate brake and tire heat)



- Bike lane expansion (Better Bike Plan 2025) aims to increase cycling mode share, though extreme heat days negate this benefit
- No congestion pricing or low-emission zones currently in effect in San Jose
- Some shaded transit stops have been installed, but coverage remains limited

Assessment at Given Date/Time

- Wednesday at noon: **moderate traffic, elevated waste heat intensity**
- Traffic volume is below AM/PM peak but waste heat per vehicle is maximized due to AC systems running at full capacity (vehicle AC adds 3-5 HP of engine load, increasing fuel consumption and exhaust heat by 10-20%)
- Delivery and commercial vehicles are at peak midday activity
- Net vehicular waste heat contribution: estimated moderate-to-high despite sub-peak traffic volumes, due to per-vehicle heat intensity at extreme ambient temperatures

Sources:

- Caltrans traffic volume data (AADT) for Santa Clara County highways
- VTA ridership and fleet electrification plans
- San Jose Department of Transportation cool pavement pilot program
- General automotive thermodynamic efficiency data

5. Seasonal Population Dynamics & Heat Demand

Population Variability Assessment

- San Jose has **relatively low seasonal population variability** compared to tourist or university-dominated cities
- The population is primarily permanent residents and year-round tech workers — estimated metro population ~1.0 million (city) / ~2.0 million (county)
- San Jose State University (enrollment ~37,000) is in full fall session in early October, contributing to baseline population
- No significant tourism-driven population surge; San Jose is a business/tech destination rather than a leisure tourism hub
- Some seasonal labor in the agricultural areas of southern Santa Clara County (fruit/vegetable harvest), but this is a small fraction of the metro population

Demand Translation for Current Period

- Early October represents full occupancy of commercial office space, university facilities, and residential population — no seasonal reduction
- Post-pandemic hybrid work means some office buildings may be at 60-80% occupancy on any given weekday, slightly reducing commercial cooling load compared to full occupancy
- However, work-from-home shifts cooling demand to residential sector, which is less efficient (distributed residential AC vs. commercial chillers)

Current Season Assessment

- October is typically the beginning of the cooling-demand decline in San Jose — normal October temperatures rarely require significant AC use
- This extreme heat event (105.3°F) is highly anomalous for October and catches the population and infrastructure somewhat off-guard:
- Some residents may have already winterized or reduced cooling readiness
- Utility maintenance scheduled for the "shoulder season" may reduce available generation or transmission capacity
- The anthropogenic heat load is at **full weekday intensity** — all commercial, industrial, and residential systems are occupied and generating heat

Weekend/Weekday and Time-of-Day Demand Variation

- Wednesday at noon: peak commercial energy demand period — offices, data centers, retail, and restaurants all operating at full capacity
- Residential demand is also elevated due to work-from-home population running AC
- Estimated total demand: 15-25% higher than a comparable weekend day at the same temperature, due to full commercial operation



- Data centers (which represent a large fraction of local electricity demand) operate 24/7 with minimal weekday/weekend variation
- School facilities are in session, adding institutional cooling demand

Infrastructure and Policy Adjustments

- City of San Jose activates cooling centers during extreme heat events — libraries, community centers, and designated public buildings
- PG&E/CAISO Flex Alert messaging encourages demand reduction (pre-cooling homes, avoiding major appliance use during peak hours)
- No seasonal energy pricing differential applies specifically to October (time-of-use rates are year-round)
- County public health department issues heat advisories affecting outdoor worker schedules and school outdoor activities
- This being an anomalous October heat event, some seasonal infrastructure (e.g., splash pads, extended pool hours) may not be fully operational as they would be in summer

Key Demand Drivers Beyond Seasonal Population

- The primary anthropogenic heat demand driver at this datetime is the extreme temperature anomaly, not population fluctuation
- Weather-driven behavioral changes dominate: maximum AC usage, increased vehicle trips, emergency cooling facility activation
- Tech sector electricity demand (data centers, office campuses) provides a high and relatively constant baseline regardless of season

Sources:

- U.S. Census Bureau population estimates for San Jose/Santa Clara County
- San Jose State University enrollment data
- City of San Jose Office of Emergency Management heat response protocols
- CAISO Flex Alert historical activation records
- PG&E time-of-use rate structure documentation

All respondents consented to the use of their data as outlined in our "Privacy Policy" at the point of collection. [Privacy Policy](#)