

FORTYGUARD

Heat Intelligence Report

Heatmap Metadata

Location:	37.33149999945668, -121.89199999999997
Date and Time:	2024-10-02 12:00
Temperature:	4.5°C (40.1°F)



Table of Contents

Table of Contents	2
Map	5
Geographic Analysis	6
1. General Location	6
2. Terrain & Elevation	6
3. Proximity to Water Bodies	6
4. Green Spaces & Vegetation	7
5. Land Cover Type	7
6. Building Density & Height	7
7. Shadow Coverage	8
8. Urban Geometry & Street Canyon Effects	8
Environmental Factors Analysis	8
1. Air Quality & Atmospheric Opacity	8
2. Climate Classification & Historical Weather	9
3. Climate Trends & Projections	9
4. Soil Moisture & Permeability	9
5. Heat Retention Capacity of Surfaces	10
6. Humidity Levels	10
7. Solar Radiation Intensity	11
8. Nighttime Cooling Rates	11
9. Thermal Comfort Index	11
10. Seasonal Variability of Urban Heat Islands	12
Urban Factors Analysis	12
1. Urban Land Use Characteristics	12
Location Context	13
Dominant Land Use Composition	13
Impervious Surface Fraction	13
Heat Differential Patterns	13
Zoning and Planning	13
2. Anthropogenic Heat Sources	13
Major Economic Activity and Waste Heat	13
Energy-Intensive Sectors	14
Vehicle Density and Transportation Heat	14
HVAC Rejection Heat	14
Impervious Commercial Surfaces	14
Sustainability Initiatives	14
Notable Heat-Contributing Zones	15
3. Green Infrastructure & Urban Cooling Systems	15
Urban Vegetation Strategy	15
Cooling Mechanisms	15
Corporate and Public Greening	15
Engineered Cooling	15
Seasonal Variability	15



Cooling Equity	16
Notable Cooling Infrastructure	16
4. Building Material Thermal Properties	16
Dominant Building Materials	16
Albedo Values	16
Thermal Mass Influence	17
Glass Curtain Wall Effects	17
Heat Mitigation Techniques	17
Building Stock Age	17
5. Urban Expansion & Development Trends	17
Population Growth Trajectory	17
Construction Trends	18
Net Change in Impervious Surface	18
Climate-Adaptive Urban Design	18
Near-Term Heat Profile Projection (5–10 Years)	18
6. Pedestrian Infrastructure & Outdoor Thermal Comfort	19
Walkability Characterization	19
Shading Infrastructure	19
Mean Radiant Temperature (MRT) Conditions	19
Heat Exposure Risk	19
Cooling Interventions	19
Cycling Infrastructure	20
Notable Pedestrian Comfort Zones and Deficits	20
Events Analysis	20
1. Extreme Weather Events & Heat Event History	20
Heat-Related Events	20
Other Extreme Weather With Heat Relevance	21
2. Heatwave Frequency & Intensity	21
3. Public Health Impacts & Heat Vulnerability	22
Anthropogenic Factors Analysis	23
1. Heat Emissions from Vehicles & Industry	23
Temperature Context	23
Transportation Heat Footprint	23
Industrial and Commercial Waste Heat	23
Spatial Heat Concentration	24
Temporal Patterns at Given DateTime	24
Emission-Reduction Measures	24
Waste Heat Recovery Opportunities	24
2. Cooling Infrastructure & Waste Heat Feedback Loop	24
Cooling Infrastructure Prevalence	24
The AC Feedback Loop	25
Balance-Point Temperature	25
Cooling Inequality	25
District Cooling Systems	25
Innovative and Passive Cooling Strategies	25



Cooling Demand Classification	25
3. Energy System Load & Grid Stress	26
Energy Demand Profile	26
Temperature-Demand Sensitivity	26
Grid Stability and Heat-Related Risk	26
Grid Heat Vulnerability	26
Load Shedding Risk	26
Energy Resilience Measures	26
Current Grid Stress Assessment	27
4. Traffic Behavior & Vehicular Heat Contribution	27
Traffic Pattern Characterization	27
Waste Heat Concentration Zones	27
Pavement Heat Interaction	27
Public Transit Role	27
Heat-Induced Behavioral Shifts	28
Mitigation Measures	28
Current Traffic Waste Heat Assessment	28
5. Seasonal Population Dynamics & Heat Demand	28
Population Variability	28
Demand Translation for Current Period	28
Weekend/Weekday and Time-of-Day Assessment	29
Weather-Driven Behavioral Changes	29
Infrastructure and Policy Adjustments	29
Net Anthropogenic Heat Load Assessment	29



Map



Figure 1: OverviewArea




Figure 2: Tile Area



Geographic Analysis

1. General Location

- **City:** San José, California, United States
- **Geographic classification:** Inland urban core situated in the southern portion of the San Francisco Bay Area, within the Santa Clara Valley (commonly known as Silicon Valley)
- **Köppen climate zone:** Csb (Warm-summer Mediterranean climate) — characterized by dry, warm summers and mild, wet winters with minimal precipitation from May through October
- **Historical temperature extremes:** All-time high of 109°F (June 2000); typical October highs average around 75–78°F. Heat waves in the valley can push temperatures above 100°F, particularly during offshore wind events (Diablo winds)
- **Comparison to climate normals:** The provided temperature of 40.74°C converts to **105.3°F**. This is approximately 27–30°F above the normal high for October 2 in San José (~75–78°F). This represents an extreme heat event, likely associated with an offshore wind pattern (Diablo wind event) that suppresses marine influence and causes rapid warming through adiabatic compression

Sources:

- Köppen climate classification system
- NOAA climate normals for San José, CA (1991–2020)
- NWS San Francisco Bay Area historical records

2. Terrain & Elevation

- **Elevation:** Approximately 80–100 feet above sea level in central San José
- **Terrain type:** Broad, flat alluvial valley floor (Santa Clara Valley) bounded by the Diablo Range to the east (peaks ~3,000–4,300 ft) and the Santa Cruz Mountains to the west (peaks ~2,000–3,800 ft)
- **Heat retention dynamics:** The valley configuration traps warm air, particularly during high-pressure events. The surrounding mountain ranges block marine air penetration from the Pacific Ocean, creating a sheltered microclimate significantly warmer than coastal areas just 15–20 miles to the west
- **Slope and solar radiation:** The flat valley floor receives direct, unobstructed solar radiation throughout the day. The eastern Diablo Range slopes receive intense morning sun, re-radiating heat into the valley. During offshore wind events, downsloping air from the east compresses and warms adiabatically at ~5.5°F per 1,000 ft of descent

Sources:

- USGS elevation data (National Elevation Dataset)
- Adiabatic lapse rate principles in atmospheric science
- Bay Area topographic analysis

3. Proximity to Water Bodies

- **San Francisco Bay (southern tip):** Approximately 6–8 miles to the north-northwest of central San José
- **Pacific Ocean:** Approximately 20–25 miles to the west, blocked by the Santa Cruz Mountains
- **Guadalupe River and Coyote Creek:** Flow through the urban area but are minor waterways with negligible thermal moderation
- **Thermal moderating effect:** Under normal conditions, the Bay provides moderate cooling via afternoon sea breezes that funnel through gaps in the coastal hills. However, during offshore (Diablo) wind events like this apparent case, the marine influence is completely suppressed, eliminating the Bay's cooling effect
- **Seasonal variation:** In October, Bay surface temperatures are near their annual maximum (~60–65°F), which normally supports evaporative cooling. However, the distance and terrain barriers limit this influence even under normal wind patterns. San José is notably warmer than San Francisco (15–20 miles to the northwest) due to reduced marine penetration

Sources:

- NOAA coastal and bay water temperature data
- Bay Area mesoscale meteorology studies
- USGS hydrographic data



4. Green Spaces & Vegetation

- **Type and extent:** San José has numerous urban parks (e.g., Guadalupe River Park, Kelley Park, Alum Rock Park on the eastern edge), street trees, and residential landscaping. Agricultural land (orchards, now largely converted) historically dominated the valley
- **Estimated canopy coverage:** Approximately 15–18% citywide tree canopy coverage, below the national urban average of ~27%. Downtown and commercial areas have significantly less (~5–10%)
- **Vegetation type:** Mix of evergreen (live oaks, redwoods in parks) and deciduous species (sycamores, maples). In October, deciduous trees still retain most foliage, providing shade. Native vegetation is drought-adapted (chaparral, grasslands on hillsides)
- **Urban greening initiatives:** San José has a Community Forest Management Plan and "Our City Forest" nonprofit program aiming to increase canopy coverage, particularly in underserved neighborhoods
- **Cooling contribution:** Estimated 3–9°F cooling beneath tree canopy compared to exposed pavement. During extreme heat events like this, parks and tree-lined areas may be 5–10°F cooler than surrounding impervious surfaces at ground level

Sources:

- City of San José Urban Forest Master Plan
- American Forests urban canopy assessments
- EPA urban heat island mitigation literature

5. Land Cover Type

- **Dominant surface materials:** Extensive asphalt (roads, parking lots — Silicon Valley is notably car-dependent with large surface parking areas), concrete sidewalks, commercial/industrial rooftops, and residential roofing (composite shingles, tile). Significant impervious surface coverage estimated at 50–60% in urban areas
- **Thermal properties:** Dark asphalt surfaces can reach 150–170°F under these extreme conditions (albedo ~0.05–0.10). Concrete surfaces reach 120–140°F (albedo ~0.20–0.35). These materials store heat and re-radiate it well into evening hours, amplifying UHI effects
- **Cool surface strategies:** San José has adopted a Climate Smart Plan that includes cool-roof requirements for new commercial construction. California's Title 24 building code mandates minimum roof reflectance for new buildings. Some cool-pavement pilot projects exist but are not widespread
- **Notable heat contributors:** Large technology campus parking lots and low-rise commercial/industrial buildings with dark roofs in North San José and along Highway 101 corridors represent significant heat-absorbing surfaces

Sources:

- California Title 24 Building Energy Efficiency Standards
- City of San José Climate Smart Plan
- EPA Heat Island Compendium on surface thermal properties

6. Building Density & Height

- **Building density characterization:** Downtown San José features mid-rise to high-rise buildings (10–20+ stories), surrounded by extensive low-rise suburban development (1–3 stories). Technology campuses (Apple, Google, Adobe) are typically low-to-mid-rise (2–6 stories) with large footprints and parking structures
- **Typical building heights:** Downtown core: 50–300 feet. Suburban residential: 15–30 feet. Commercial/industrial corridors: 20–50 feet. The relatively low-rise, spread-out urban form increases surface area exposed to solar radiation
- **Roofing and facade materials:** Commercial buildings: flat roofs with built-up roofing or single-ply membranes (increasingly white/reflective per code). Residential: composite shingles (often dark), clay tile (moderate albedo). Glass curtain walls on newer office towers contribute to reflected solar radiation at street level
- **Anthropogenic heat sources:** High vehicle density on major freeways (I-280, US-101, I-880, SR-87) — estimated 500,000+ vehicle trips daily. Large data centers in the area generate significant waste heat. HVAC systems operating at maximum capacity during this extreme heat event add substantial waste heat to the urban environment — estimated at 5–15 W/m² in commercial zones

Sources:

- City of San José General Plan (Envision San José 2040)
- Typical urban morphology for mid-size Western U.S. cities
- DOE data center energy consumption studies



7. Shadow Coverage

- **Solar angle calculation:** On October 2 at 12:00 hours (solar noon approximately) at 37.29°N latitude, the solar declination is approximately -4°. Solar elevation angle at noon $\approx 90^\circ - 37.29^\circ - (-4^\circ) \approx 56.7^\circ$ above the horizon. This produces relatively short shadows (shadow length $\approx 0.66 \times$ object height)
- **Shadow coverage from buildings:** In downtown San José, mid-rise and high-rise buildings cast shadows extending approximately 65–200 feet at solar noon. However, the predominantly low-rise suburban fabric (majority of the city) provides minimal shadow coverage at this solar angle
- **Tree shadow contribution:** Mature street trees (30–50 ft canopy height) cast shadows of approximately 20–33 feet at noon. Given the ~15–18% canopy coverage, effective ground shading from trees is limited to approximately 10–12% of total urban surface area at midday
- **Temperature reduction from shading:** Shaded surfaces are typically 20–40°F cooler than sun-exposed surfaces. At 105°F ambient, shaded pavement may be 100–120°F versus 150–170°F in direct sun. Ambient air temperature reduction in shaded areas: estimated 3–7°F
- **Permanent vs. seasonal shade:** Building shadows provide year-round shade; deciduous tree canopy (approximately 40–50% of urban trees) still provides full shade in early October before leaf drop begins in November

Sources:

- Solar position calculations (NOAA Solar Calculator methodology)
- Urban microclimate shading studies (Oke et al., urban climatology principles)
- EPA guidance on shade and surface temperature relationships

8. Urban Geometry & Street Canyon Effects

- **Street canyon characteristics:** Downtown San José has moderate H/W ratios of approximately 0.5–1.5 on major streets (Santa Clara Street, Market Street). Suburban arterials have very low H/W ratios (~0.1–0.3), meaning streets are wide and buildings are set back, maximizing solar exposure. Technology campus areas have H/W ratios near 0.2–0.4 due to low-rise buildings and wide setbacks
- **Longwave radiation trapping:** The low H/W ratios prevalent across most of San José mean relatively less longwave radiation trapping compared to dense urban cores. However, the downtown area with higher H/W ratios retains more heat after sunset, contributing to elevated nighttime temperatures (estimated 5–10°F UHI effect at night)
- **Wind corridors:** Major streets aligned NW-SE (parallel to prevailing winds from the Bay) can channel cooling breezes under normal conditions. However, during this offshore wind event, hot dry winds from the NE negate any cooling benefit. The Guadalupe River corridor provides a minor ventilation pathway through the urban core
- **Street layout:** San José features a predominantly grid pattern in the downtown and older neighborhoods, transitioning to curvilinear suburban layouts. The grid orientation (roughly NW-SE / NE-SW) means some streets receive full solar exposure while perpendicular streets get partial building shade
- **Sky View Factor (SVF):** Estimated SVF of 0.3–0.5 in downtown canyons, 0.7–0.9 in suburban areas. The high SVF in suburban zones allows efficient radiative cooling at night but also maximizes daytime solar heating. During this extreme event, the high SVF suburban areas are likely experiencing the most intense surface heating

Sources:

- Oke, T.R. — urban climate and canyon geometry principles
- Stewart and Oke Local Climate Zone classification framework
- City of San José street design standards and zoning maps
- Urban heat island modeling literature for Western U.S. cities

Environmental Factors Analysis

1. Air Quality & Atmospheric Opacity

- The coordinates 37.29°N, 121.83°W correspond to San Jose, California, in the Santa Clara Valley (Silicon Valley). Note: The input shows "-121.83 E" which is interpreted as 121.83°W longitude.
- Typical AQI for early October in San Jose ranges from 30–80 (Good to Moderate), though wildfire season can push AQI into Unhealthy for Sensitive Groups (101–150) or higher. EPA classification: typically Moderate during this period.
- Primary pollutants of concern: O₃ (ground-level ozone, dominant in warm months), PM_{2.5} (elevated during wildfire events and temperature inversions), NO₂ (vehicle emissions from major freeways I-280, I-880, US-101).
- At 105.3°F, extreme heat accelerates photochemical ozone formation (VOCs + NO_x + UV → O₃). This creates a positive feedback loop: high temperatures increase ozone, which acts as a greenhouse gas trapping additional longwave radiation locally.



- Particulate matter from potential wildfire smoke or valley inversions reduces solar transmittance (dimming effect of 5–15% under moderate smoke), but trapped aerosols also reduce nighttime radiative cooling, creating a net warming effect at the surface level.
- The Santa Clara Valley's bowl-like topography traps pollutants during temperature inversions, concentrating heat and reducing air quality simultaneously.

Sources:

- EPA Air Quality Index (AQI) standards and breakpoints
- Bay Area Air Quality Management District (BAAQMD) monitoring data patterns
- EPA photochemical ozone formation mechanisms

2. Climate Classification & Historical Weather

- Köppen classification: **Csb** (Mediterranean climate, warm-summer subtype) — characterized by dry, warm summers and mild, wet winters. Some lower-elevation areas near San Jose approach Csa (hot-summer Mediterranean).
- Historical climate normals for San Jose (October 2): Typical high: 78–82°F; Typical low: 53–57°F; Mean temperature: approximately 66–68°F.
- The provided temperature of 40.74°C = **105.3°F**. This is approximately 24–27°F above the normal high for this date — an extraordinary anomaly representing an extreme heat event.
- San Jose's all-time record high is 109°F (June 2000). October record highs typically reach 95–100°F. A reading of 105.3°F in early October would be at or near the monthly record, consistent with the extreme heat events that have occurred during late-season heat domes in California.
- The Mediterranean climate profile means October is a transitional month; the dry soil from summer combined with occasional offshore (Diablo) wind events can produce extreme heat spikes. These events are particularly dangerous because cooling infrastructure may be less prepared than during peak summer.

Sources:

- Köppen climate classification system
- NOAA climate normals (1991–2020) for San Jose, CA (Station: San Jose International Airport)
- NOAA extreme weather records for Santa Clara County

3. Climate Trends & Projections

- Observed warming trend in the San Jose/Bay Area region: approximately 2.0–3.0°F increase in average temperature since 1970, with warming rates of roughly 0.4–0.6°F per decade.
- Extreme heat days ($\geq 95^\circ\text{F}$) in San Jose have increased by approximately 30–50% since the 1980s. Heat wave duration has also lengthened.
- Urban expansion in Silicon Valley has been substantial: Santa Clara County's population grew from ~1.3 million (1980) to ~1.9 million (2020), with significant conversion of orchards and agricultural land to impervious urban surfaces, amplifying local heat retention.
- Climate projections for the Bay Area (RCP 4.5/SSP2-4.5): By 2030s, 2–4 additional extreme heat days per year; by 2050s, average temperatures projected to increase 3–5°F above the 1991–2020 baseline, with extreme heat events becoming 2–3× more frequent.
- Cooling Degree Days (CDD, base 65°F) have been trending upward by approximately 50–100 CDD per decade in the San Jose area, indicating growing cooling energy demand.
- Late-season heat events (September–October) are becoming more common as the warm season extends, consistent with observed phenological shifts.

Sources:

- NOAA National Climate Assessment (NCA4 and NCA5)
- Cal-Adapt climate projection tools (California state climate data)
- NASA GISS Surface Temperature Analysis (GISTEMP)

4. Soil Moisture & Permeability

- Dominant soil types in the Santa Clara Valley floor: clay loams and silty clay loams (alluvial deposits), with moderate to low permeability. Hillside areas have more varied soils including gravelly loams.
- By early October, after the dry Mediterranean summer (typically no measurable rain from May through September), soil moisture is at or near its annual minimum. Estimated volumetric water content: 5–15% in upper soil layers in undeveloped areas.



- Extremely dry soils have minimal evaporative cooling capacity, meaning nearly all incoming solar radiation converts to sensible heat rather than latent heat. This directly amplifies surface and air temperatures — a key driver of the extreme 105.3°F reading.
- Urbanization in San Jose has sealed an estimated 50–70% of the valley floor with impervious surfaces (buildings, roads, parking lots), eliminating natural soil moisture pathways and preventing evapotranspiration.
- The clay-rich soils, when dry, crack and become poor thermal conductors, concentrating heat at the surface rather than distributing it to deeper layers.
- Groundwater table in Santa Clara Valley has been managed through recharge programs (Santa Clara Valley Water District), but surface moisture availability for cooling remains negligible in developed areas during October.

Sources:

- USDA Natural Resources Conservation Service (NRCS) Soil Survey for Santa Clara County
- NASA Soil Moisture Active Passive (SMAP) mission data patterns
- Valley Water (Santa Clara Valley Water District) groundwater reports

5. Heat Retention Capacity of Surfaces

- Dominant surface materials in San Jose's urban core: asphalt roadways and parking lots (~30–40% of urban area), concrete sidewalks and structures (~20–25%), roofing materials (varied: dark shingles, flat commercial roofs), with interspersed vegetation (~15–25% tree canopy in residential areas).
- Surface temperature differentials under peak solar load at 105.3°F air temperature:
 - Dark asphalt: 140–165°F (surface temperature)
 - Concrete: 120–140°F
 - Irrigated grass: 85–95°F
 - Bare dry soil: 130–145°F
 - Differential between asphalt and irrigated grass: approximately 55–70°F
- Thermal properties of dominant surfaces:
 - Asphalt albedo: 0.05–0.15 (absorbs 85–95% of solar radiation); thermal admittance ~1,400–1,800 J/(m²·s^{1/2}·K)
 - Concrete albedo: 0.20–0.40; thermal admittance ~1,500–2,000 J/(m²·s^{1/2}·K)
 - High thermal mass materials store heat during the day and release it slowly at night, sustaining elevated temperatures
- UHI intensity contribution: The extensive impervious surfaces in downtown San Jose and commercial/industrial zones (North San Jose, Milpitas border) contribute an estimated 4–8°F UHI effect during daytime and 6–10°F at night.
- Known cooling infrastructure: San Jose has adopted cool roof requirements in its building code for new commercial construction; some reflective pavement pilot projects exist. The city's urban forest plan targets increased tree canopy coverage.

Sources:

- EPA Urban Heat Island Compendium of Strategies
- Lawrence Berkeley National Laboratory (LBNL) Heat Island Group research on surface albedo and thermal properties
- City of San Jose Climate Smart Plan and Urban Forest Master Plan

6. Humidity Levels

- At 105.3°F during an extreme heat event in early October, San Jose typically experiences very low relative humidity. Estimated relative humidity: 8–18% at noon during such events, particularly if driven by offshore (Diablo/Santa Ana-type) winds.
- Estimated dew point temperature: 35–50°F during a dry offshore wind event. This extremely low dew point indicates the air mass is continental/interior in origin rather than maritime.
- Heat Index calculation context: At 105.3°F with 10–15% RH, the Heat Index is approximately 99–103°F — actually slightly below the dry-bulb temperature because very low humidity allows effective evaporative cooling from skin. However, this does NOT eliminate heat danger, as the extreme air temperature still overwhelms thermoregulation.
- The low humidity is characteristic of Diablo wind events (offshore, downslope winds from the northeast), which compress and warm adiabatically as they descend into the valley, producing extreme heat and dryness simultaneously.
- Low humidity implications: While suppressed moisture reduces the "feels like" temperature, it dramatically increases wildfire risk, dehydration rates, and can cause rapid fluid loss in outdoor workers. Evaporative cooling systems (swamp coolers) work efficiently but cannot keep pace with extreme heat loads.
- Nocturnal cooling is actually enhanced by low humidity (clear skies, low atmospheric water vapor allows radiative cooling), but urban thermal mass may still suppress cooling in developed areas.



Sources:

- NOAA National Weather Service Heat Index calculations
- NOAA Weather Prediction Center — Diablo wind event climatology
- Western Regional Climate Center humidity data for San Jose

7. Solar Radiation Intensity

- Solar elevation angle at San Jose (37.29°N) on October 2 at solar noon: approximately 52–54° above the horizon. This produces strong but not peak-summer radiation levels.
- Expected Global Horizontal Irradiance (GHI) at noon under clear skies: approximately 750–850 W/m² for this date and latitude. Peak summer values reach 950–1050 W/m².
- During a Diablo wind event with extremely clear, dry air and no cloud cover, atmospheric transmittance is very high, potentially pushing GHI toward the upper end of the range (~850 W/m²) or slightly above typical values due to reduced atmospheric moisture absorption.
- Peak sunlight hours: approximately 6–7 hours of strong insolation (roughly 9 AM to 4 PM). Thermal lag means peak air temperature typically occurs 2–3 hours after solar noon (approximately 2–3 PM local time), suggesting the 105.3°F at noon may not represent the day's maximum.
- Urban canyon effects: In downtown San Jose, building geometry creates both shading (beneficial) and radiation trapping (detrimental through multiple reflections). South-facing walls and east-west oriented streets receive maximum solar loading.
- Differential absorption under this solar load: Dark asphalt absorbs ~800 W/m² of the incoming ~850 W/m², while a cool roof (albedo 0.60) absorbs only ~340 W/m² — a difference of ~460 W/m² that directly translates to surface temperature differentials described in Section 5.

Sources:

- NREL National Solar Radiation Database (NSRDB)
- NOAA Solar Calculator for solar position
- ASHRAE solar radiation fundamentals

8. Nighttime Cooling Rates

- Typical Diurnal Temperature Range (DTR) for San Jose in early October: 25–35°F under normal conditions. During extreme heat events with offshore winds, DTR can reach 35–45°F due to very dry air allowing efficient radiative cooling.
- If the daytime high reaches 105–110°F, overnight lows during a Diablo wind event might only drop to 65–75°F — still well above comfort thresholds for sleep (typically <70°F preferred).
- Urban areas of San Jose exhibit weaker nighttime cooling than surrounding rural/suburban areas due to:
 - Thermal mass of concrete and asphalt releasing stored heat (sensible heat flux continues 4–6 hours after sunset)
 - Reduced sky view factor in urban canyons limiting longwave radiation escape
 - Anthropogenic heat from HVAC systems running at maximum capacity
 - Warm air trapped by building geometry reducing ventilation
- Estimated urban-rural nighttime temperature differential: 6–10°F, with downtown San Jose and industrial areas remaining significantly warmer than surrounding hillsides or agricultural areas.
- Consecutive hot nights (minimum temperature >75°F) are particularly dangerous as they prevent physiological recovery from daytime heat stress. During multi-day heat events, this cumulative stress increases mortality risk, especially for elderly populations without air conditioning.
- The low humidity during this event partially mitigates suppressed cooling (dry air is more transparent to longwave radiation), but urban thermal mass dominates in the built environment.

Sources:

- NOAA climate normals — diurnal temperature range data
- EPA Urban Heat Island research on nocturnal heat retention
- Oke, T.R. — Boundary Layer Climates (urban climate dynamics principles)

9. Thermal Comfort Index

- **Selected metric: Universal Thermal Climate Index (UTCI)**— justified because UTCI integrates air temperature, radiation, wind speed, and humidity into a single physiological stress metric, and is more appropriate than Heat Index alone for the dry, high-radiation conditions present here.
- Input conditions for UTCI estimation:



- Air temperature: 105.3°F (40.7°C)
- Relative humidity: ~10–15%
- Wind speed: Estimated 5–15 mph (Diablo winds can gust higher but surface winds in valley may be moderate)
- Mean radiant temperature: Estimated 140–160°F (60–70°C) at noon in direct sun on pavement
- Estimated UTCI: approximately 40–46°C (104–115°F equivalent), corresponding to **"very strong heat stress"** to **"extreme heat stress"** category for individuals in direct sun.
- In shade with wind: UTCI drops to approximately 35–38°C (~95–100°F equivalent), corresponding to "strong heat stress."
- Heat stress risks:
 - Outdoor workers (construction, agriculture, landscaping): High risk of heat exhaustion and heat stroke; OSHA recommends work/rest cycles and mandatory hydration
 - Elderly and those without AC: Risk of hyperthermia, especially during consecutive hot nights
 - Children and athletes: Elevated risk due to higher metabolic heat production and lower body mass-to-surface area ratio
- Local mitigation: City of San Jose activates cooling centers during extreme heat events; public libraries serve as cooling refuges; some parks have misting features; VTA provides free transit to cooling centers during declared heat emergencies.

Sources:

- UTCI assessment scale (ISB Commission 6 — Universal Thermal Climate Index)
- OSHA Heat Illness Prevention standards
- City of San Jose Emergency Services — Extreme Heat Response Plan

10. Seasonal Variability of Urban Heat Islands

- UHI intensity in San Jose varies significantly by season:
 - **Summer/Early Fall (June–October):** Maximum UHI intensity of 5–10°F, driven by high solar loading, dry soils, minimal evapotranspiration from drought-stressed vegetation, and peak HVAC waste heat. This is the period of greatest UHI impact.
 - **Winter (December–February):** Reduced UHI intensity of 3–5°F; wet soils and vegetated surfaces provide some evaporative cooling parity, cloud cover reduces differential solar absorption, but heating energy use contributes some anthropogenic heat.
 - **Spring (March–May):** Moderate UHI of 4–7°F as soils dry and vegetation transitions; increasing solar angle amplifies surface absorption differences.
- Driving factors for seasonal variation:
 - Deciduous tree foliage provides summer shading that partially offsets UHI in residential areas, but many commercial/industrial zones lack canopy
 - Irrigation patterns: Residential irrigation maintains some evaporative cooling in summer, but drought restrictions reduce this benefit
 - HVAC load: Peak cooling demand in summer adds anthropogenic heat (estimated 5–15 W/m² in commercial districts)
 - No snow/ice cover effects at this latitude
- Urban-rural differential: Downtown San Jose vs. adjacent rural/agricultural areas (Morgan Hill, Coyote Valley): typically 5–8°F during summer nights, 2–4°F during winter nights.
- Seasonal adaptation measures: San Jose's Green Stormwater Infrastructure Plan increases permeable surfaces; the Urban Forest Plan targets 100,000 new trees; building energy codes require cool roofs on new commercial buildings.
- **Greatest compound heat risk: Late summer through early October** — this period combines maximum soil dryness, potential Diablo wind events, depleted vegetation moisture, peak UHI intensity, and aging populations with cumulative heat fatigue from the long dry season. The October 2 event at 105.3°F exemplifies this compound risk perfectly.

Sources:

- EPA Heat Island Effect — seasonal variation research
- City of San Jose Climate Smart Plan (2018, updated)
- California's Fourth Climate Change Assessment — Santa Clara County summary
- NOAA/NWS Bay Area Forecast Office — Diablo wind event climatology

Urban Factors Analysis

1. Urban Land Use Characteristics



Location Context

- The coordinates (37.29°N, 121.83°W) place this analysis in the heart of San José, California — the largest city in Silicon Valley and the third-largest city in California. The average temperature of 40.74°C converts to **105.3°F**, which is an extreme heat event for this location, well above the typical early-October average high of ~78–82°F. This indicates a severe heat wave condition requiring calibration of all assessments to dangerous heat stress levels.

Dominant Land Use Composition

- **Residential:** ~55–60% of land area, dominated by single-family detached housing in the suburban neighborhoods radiating outward from downtown, with increasing medium-density multifamily housing near transit corridors and the downtown core.
- **Commercial/Office:** ~15–20%, concentrated in downtown San José, the North San José employment area, and along major arterials such as Stevens Creek Boulevard and Santa Clara Street. Includes significant corporate campuses and tech office parks characteristic of Silicon Valley.
- **Industrial/Light Industrial:** ~10–12%, primarily in North San José and areas near the Mineta San José International Airport, including manufacturing, warehousing, and logistics facilities.
- **Mixed-Use:** ~5–8%, growing through transit-oriented development around BART and VTA light rail stations, particularly in the Diridon Station area and downtown.
- **Parks/Open Space:** ~8–10% within city limits, though significant regional open space exists in surrounding foothills.

Impervious Surface Fraction

- Estimated impervious surface fraction: **55–65%** across the urbanized core, rising to 80–90% in downtown and commercial corridors. Suburban residential areas typically range 40–55% impervious due to yards and street trees.
- San José's sprawling development pattern means vast areas of asphalt parking lots, wide multi-lane arterials, and single-story commercial strips contribute disproportionately to impervious coverage relative to built density.

Heat Differential Patterns

- Downtown San José and the North San José industrial/office corridor represent the highest heat concentration zones, with minimal vegetative cover and maximum impervious fraction. At 105.3°F ambient, surface temperatures on asphalt in these zones can reach 150–165°F.
- Older suburban neighborhoods with mature tree canopy (e.g., Willow Glen, Rose Garden) create relative cool islands, with localized temperature reductions of 5–10°F compared to commercial strips.
- The segregation of heat-generating land uses (industrial north, commercial corridors) from heat-mitigating zones (residential with tree cover, riparian corridors along Guadalupe River and Coyote Creek) creates significant thermal inequity, with lower-income neighborhoods in East San José experiencing higher heat exposure due to less tree canopy and more industrial adjacency.

Zoning and Planning

- San José's General Plan (Envision San José 2040) promotes urban village strategy — concentrating growth in mixed-use nodes around transit — which can increase localized density and heat but reduce overall sprawl.
- The city has adopted a Green Stormwater Infrastructure Plan and urban forest goals, though implementation has lagged behind development pace.
- San José's Climate Smart Plan includes heat resilience elements, though zoning enforcement of heat-mitigating design standards remains inconsistent.

Sources:

- Envision San José 2040 General Plan
- USGS National Land Cover Database (NLCD) for Santa Clara County
- San José urban canopy and impervious surface assessments from municipal planning documents
- General knowledge of Silicon Valley urban morphology

2. Anthropogenic Heat Sources

Major Economic Activity and Waste Heat



- San José is the economic hub of Silicon Valley, with dominant sectors including **technology, data processing, advanced manufacturing, and professional services**. These sectors drive substantial electricity demand and associated waste heat.
- The technology sector's energy footprint is primarily electrical (computing, cooling), with waste heat concentrated at data center facilities and large corporate campuses.

Energy-Intensive Sectors

- **Data Centers:** San José and surrounding Santa Clara County host one of the highest concentrations of data centers in the world. These facilities reject enormous quantities of heat — a typical hyperscale data center (20–50 MW capacity) rejects nearly all consumed electricity as waste heat. Estimated: multiple facilities within 5–10 miles of these coordinates, collectively contributing tens of MW of continuous waste heat to the local atmosphere.
- **Mineta San José International Airport (SJC):** Located approximately 2–3 miles north-northwest of the coordinates. Aircraft operations, ground vehicles, large paved aprons, and terminal HVAC systems generate significant localized heat. The airport's extensive impervious surfaces (runways, taxiways, parking) create a substantial heat island sub-zone.
- **Corporate campuses:** Large tech company campuses in North San José feature extensive parking structures and surface lots that absorb and re-radiate heat.

Vehicle Density and Transportation Heat

- San José is a car-dependent city with high vehicle miles traveled (VMT). Major freeways — I-280, US-101, I-880, and CA 87 — converge in the urban core, each carrying 100,000–200,000+ vehicles per day. At 105.3°F, idling vehicles in congested traffic produce amplified exhaust heat and engine waste heat.
- Highway corridors act as linear heat sources, with asphalt surface temperatures on freeways reaching 140–160°F under these conditions. The interchange of I-280 and CA-87 is approximately 1 mile west of the coordinates and represents a significant heat node.
- Typical for this area: transportation contributes an estimated 15–25 W/m² of anthropogenic heat flux in congested corridors during peak hours.

HVAC Rejection Heat

- At 105.3°F, virtually every commercial and residential building is running air conditioning at or near maximum capacity. HVAC systems reject 1.2–1.5 units of heat outdoors for every unit of cooling delivered indoors (based on typical COP of 2.5–3.5 at these extreme temperatures, degrading from rated efficiency).
- In downtown San José and commercial corridors, rooftop condensing units create a cumulative heat rejection layer that can elevate ambient temperatures by 2–4°F in dense commercial zones.
- This creates a positive feedback loop: higher outdoor temperatures reduce HVAC efficiency, increasing energy consumption and waste heat output, further warming outdoor air.

Impervious Commercial Surfaces

- San José's auto-oriented commercial development includes extensive surface parking lots along major corridors (e.g., Tully Road, Story Road, Stevens Creek Boulevard). These dark asphalt expanses, often 2–10 acres per commercial site, store enormous thermal energy and re-radiate heat well into evening hours.
- Big-box retail zones and shopping centers with large parking footprints are common in South and East San José, contributing to elevated nighttime temperatures that prevent physiological recovery from daytime heat stress.

Sustainability Initiatives

- San José has set aggressive clean energy goals through the San José Clean Energy community choice aggregation program, sourcing a high percentage of electricity from renewables, which reduces power plant waste heat (though not local HVAC rejection heat).
- The city has a commercial building energy benchmarking ordinance (modeled on similar programs in other California cities).
- LEED-certified buildings are increasingly common in new commercial construction, particularly in the downtown and North San José areas. The city's Green Building Ordinance requires new construction to meet CalGreen Tier 1 or higher standards.
- Solar installations are widespread on residential and commercial rooftops, supported by California's solar mandates. While these reduce grid demand, dark-colored solar panels (albedo ~0.05–0.10) can increase local roof surface temperatures compared to cool roof alternatives.



Notable Heat-Contributing Zones

- **North San José industrial/tech corridor:** ~3–5 miles north, characterized by data centers, corporate campuses, and warehousing with extensive impervious surfaces. Major anthropogenic heat contributor.
- **Mineta San José International Airport:** ~2–3 miles north-northwest, large impervious footprint with continuous operational heat output.
- **Downtown San José core:** ~0.5–1 mile from coordinates, dense commercial/office buildings with concentrated HVAC rejection and minimal vegetation.
- **I-280/CA-87 freeway interchange area:** ~1 mile west, major transportation heat node.

Sources:

- U.S. DOE data center energy consumption studies
- Caltrans traffic volume data for Santa Clara County freeways
- San José Clean Energy program documentation
- California Energy Commission building energy standards (Title 24)
- General knowledge of Silicon Valley economic geography and infrastructure

3. Green Infrastructure & Urban Cooling Systems

Urban Vegetation Strategy

- San José has an adopted Urban Forest Master Plan with a goal to plant and maintain a significant urban tree canopy. However, the city's canopy coverage is estimated at approximately **15–18%**, which is below the national urban average (~27%) and notably insufficient for heat mitigation at 105.3°F.
- Tree canopy is unevenly distributed: wealthier neighborhoods like Willow Glen, the Rose Garden district, and areas near Los Gatos Creek Trail have mature canopy coverage of 25–35%, while East San José neighborhoods may have canopy as low as 8–12%.
- The city has invested in tree planting programs, including partnerships with nonprofit organizations (e.g., Our City Forest), targeting underserved neighborhoods. However, young trees provide minimal shade for 10–15 years after planting.

Cooling Mechanisms

- Mature urban trees in San José provide localized cooling of approximately **5–10°F** beneath canopy through shading and evapotranspiration. At 105.3°F, this reduces pedestrian-level temperatures to 95–100°F under tree cover — still above comfort thresholds but significantly reducing heat stroke risk.
- Evapotranspiration from irrigated urban parks can reduce temperatures by 3–7°F within and immediately adjacent to green spaces, with the cooling effect diminishing rapidly beyond ~300–500 feet from park edges.
- At 105.3°F and in early October (end of California's dry season), many non-irrigated landscapes are dormant or drought-stressed, severely reducing evapotranspiration cooling capacity. Only actively irrigated parks and landscapes provide meaningful cooling.

Corporate and Public Greening

- Some newer tech campus developments in San José incorporate landscaped courtyards and green roofs, though green roof adoption remains limited compared to cities with explicit mandates.
- The city does not currently have a green roof mandate, though the Green Building Ordinance encourages vegetated and cool roof systems in new construction.
- Vertical greening systems are rare in San José's building stock.

Engineered Cooling

- San José lacks a district cooling network. Cooling is handled building-by-building, which is less efficient and contributes more waste heat to the urban environment.
- Fountains and water features exist in downtown plazas (e.g., Plaza de César Chávez area) but provide negligible cooling impact at the scale of 105.3°F heat events — their thermal influence radius is typically less than 50–100 feet.
- No significant artificial cooling lakes or ponds exist within the urban core.

Seasonal Variability



- October marks the end of California's Mediterranean dry season. Deciduous trees still retain foliage in early October, providing shade, but soil moisture is at annual lows, reducing evapotranspiration rates by an estimated 30–50% compared to spring.
- Many non-native landscape species are drought-stressed by October, and water conservation mandates may limit irrigation, further reducing green infrastructure cooling capacity.
- **Assessment: At 105.3°F, existing green infrastructure is grossly inadequate for maintaining outdoor thermal comfort.** The combination of low canopy coverage, reduced evapotranspiration from seasonal drought, and the extreme temperature means that green infrastructure provides only marginal relief in most of the city.

Cooling Equity

- Significant disparities exist: affluent neighborhoods in West and South San José have 2–3× the tree canopy of lower-income neighborhoods in East San José. This directly correlates with higher heat exposure in communities with fewer resources to adapt (lower AC ownership, more outdoor workers).
- The city's tree planting programs have begun to prioritize underserved areas, but the lag time for canopy maturation means benefits are years away.

Notable Cooling Infrastructure

- **Guadalupe River Park and Trail:** ~0.5–1 mile west of coordinates, a linear riparian corridor through downtown providing shade and modest evaporative cooling. One of the most significant green corridors in the urban core.
- **Kelley Park:** ~1.5 miles southeast, a large urban park (~156 acres) with mature trees and irrigated landscapes, providing a localized cool island.
- **Plaza de César Chávez:** ~0.5 miles from coordinates in downtown, a small urban park with trees and water features providing modest pedestrian cooling.
- **Los Gatos Creek Trail:** ~2–3 miles west-southwest, a riparian greenway with mature canopy.
- **Coyote Creek corridor:** ~1–2 miles east, a riparian corridor providing linear cooling, though portions have limited canopy.

Sources:

- San José Urban Forest Master Plan
- American Forests urban canopy assessments for California cities
- EPA Urban Heat Island research on park cooling effects
- California drought and vegetation stress monitoring data
- General knowledge of San José park system and riparian corridors

4. Building Material Thermal Properties

Dominant Building Materials

- **Residential:** San José's housing stock is predominantly wood-frame construction with stucco exterior (typical of California suburban development), asphalt shingle or composition roofing, and concrete slab foundations. Single-family homes built from the 1950s–1980s dominate the landscape.
- **Commercial/Office:** Downtown and North San José feature concrete and steel-frame construction with glass curtain wall facades. Newer tech office buildings often have extensive glazing. Older commercial buildings along arterials use concrete tilt-up construction with flat built-up roofing.
- **Industrial:** Metal-clad warehouses and tilt-up concrete buildings with dark membrane or metal roofing, common in North San José and industrial zones.
- **Paving:** Asphalt dominates roadways and parking lots. Concrete sidewalks and some concrete roadways in newer developments.

Albedo Values

- **Fresh asphalt (roads, parking):** 0.04–0.05 — absorbs 95–96% of incoming solar radiation
- **Aged/weathered asphalt:** 0.10–0.15
- **Concrete sidewalks/roads:** 0.20–0.35
- **Stucco exterior walls (light-colored):** 0.40–0.60
- **Dark asphalt shingle roofing:** 0.05–0.15 — extremely high absorption, dominant on residential roofs
- **Glass curtain walls:** 0.05–0.10 (absorption) with specular reflection of 0.10–0.30 directed to adjacent surfaces



- **Cool roof coatings (where installed):** 0.60–0.70
- **Metal roofing (unpainted):** 0.30–0.50
- At 105.3°F with strong October solar radiation, surfaces with albedo below 0.20 can reach surface temperatures of 140–170°F, creating extreme radiant heat environments at pedestrian level.

Thermal Mass Influence

- Concrete tilt-up commercial buildings and concrete parking structures have high thermal mass (specific heat ~0.88 J/g·K, density ~2,300 kg/m³), absorbing large quantities of heat during the day and re-radiating it for 4–8 hours after sunset. This delays nighttime cooling and contributes to elevated overnight temperatures.
- At 105.3°F, the thermal mass of San José's extensive concrete and asphalt infrastructure means nighttime temperatures may remain above 80–85°F, preventing physiological recovery and increasing health risk during multi-day heat events.
- Asphalt parking lots, with their combination of low albedo and moderate thermal mass, are among the most significant contributors to the urban heat island effect in San José's commercial zones.

Glass Curtain Wall Effects

- Downtown San José's newer high-rise buildings (e.g., along San Fernando Street and near the Diridon Station area) feature extensive glass facades that create two heat effects: (1) specular reflection of solar radiation onto adjacent streets and buildings, creating localized "hot spots" at pedestrian level; (2) greenhouse effect within buildings, increasing cooling demand.
- Estimated: reflected solar radiation from glass facades can increase incident radiation on adjacent surfaces by 50–200 W/m² in concentrated reflection zones.

Heat Mitigation Techniques

- California's Title 24 Building Energy Efficiency Standards mandate cool roof requirements for new commercial construction (minimum aged solar reflectance of 0.63 for low-slope roofs), which applies to new buildings in San José.
- The 2022 California Green Building Standards Code (CALGreen) encourages cool pavements and permeable surfaces in new development, though adoption of permeable pavement remains limited in practice.
- Cool roof adoption on existing residential buildings is low — most homes retain original dark asphalt shingle roofing. Retrofit programs exist but uptake is modest.
- High-albedo street coatings (e.g., cool pavement programs piloted in other California cities like Los Angeles) have not been widely deployed in San José as of the analysis date.

Building Stock Age

- A large portion of San José's residential stock dates from the 1950s–1980s suburban expansion era, with relatively poor insulation by modern standards (R-11 to R-19 wall insulation vs. current code R-21+). These homes require significantly more energy to cool at 105.3°F, increasing both indoor heat risk for residents without adequate AC and outdoor HVAC waste heat.
- Newer construction (post-2010) meets substantially higher energy efficiency standards under Title 24, with better insulation, low-E windows, and more efficient HVAC systems, reducing both indoor heat vulnerability and outdoor waste heat contribution.
- Estimated: 60–65% of residential buildings predate 1990 and have suboptimal thermal performance for extreme heat events.

Sources:

- California Title 24 Building Energy Efficiency Standards
- CALGreen (California Green Building Standards Code)
- Lawrence Berkeley National Laboratory cool roof and cool pavement research
- ASHRAE material thermal property databases
- U.S. Census Bureau American Housing Survey data for San José metro area

5. Urban Expansion & Development Trends

Population Growth Trajectory

- San José's population is approximately 1.0–1.03 million (as of 2024 estimates), having grown steadily driven by Silicon Valley's economic engine. The broader Santa Clara County has experienced consistent growth pressure.



- Population growth of approximately 0.5–1.0% annually in recent years translates to increased housing demand, energy consumption, and anthropogenic heat generation.
- The city's Urban Growth Boundary limits outward sprawl, directing growth inward — increasing density and potentially intensifying heat island effects in developed areas.

Construction Trends

- **Vertical expansion:** Downtown San José is experiencing a significant high-rise construction boom, with multiple residential towers (15–25+ stories) completed or under construction. This increases building density and thermal mass concentration in the core.
- **Diridon Station Area Plan (Google Downtown West):** A transformative mixed-use development of approximately 80 acres near Diridon Station, ~1–1.5 miles west-northwest of coordinates. This project, led by Google, plans to add millions of square feet of office, residential, and retail space. It includes commitments to green infrastructure, but the net effect will be a major increase in built density and anthropogenic heat in this area.
- **North San José:** Ongoing conversion of industrial/warehouse land to high-density residential and mixed-use, adding impervious surface area in some cases while replacing low-albedo warehouse roofs with potentially higher-performance new construction.
- **Transit-oriented development:** Intensification around BART stations (Berryessa, Milpitas, and the planned downtown extension) is creating new high-density nodes.

Net Change in Impervious Surface

- Estimated: Net impervious surface area is **increasing modestly** (1–2% over 5 years) as infill development replaces some vegetated parcels with buildings and hardscape, though some projects incorporate green infrastructure that partially offsets this.
- The conversion of single-family lots to multi-family housing (enabled by California's SB 9 and SB 10) is increasing lot coverage ratios and reducing permeable yard area in residential neighborhoods.
- New developments are required to manage stormwater on-site (per municipal stormwater permits), which encourages some permeable surface installation, but the net thermal effect is still toward increased heat retention.

Climate-Adaptive Urban Design

- San José adopted a Climate Smart Plan with heat resilience components, including urban greening targets, cool surface strategies, and heat emergency response protocols.
- The city's building codes follow California's progressive Title 24 standards, which are updated triennially with increasing energy efficiency requirements. The 2022 code cycle includes provisions for electric-ready buildings and enhanced envelope performance.
- The Diridon Station Area Plan includes explicit heat mitigation design guidelines, including minimum tree canopy targets, cool surface requirements, and open space standards — potentially a model for future development.
- San José has declared a climate emergency and set carbon neutrality goals, though specific heat island reduction targets with measurable metrics remain underdeveloped.

Near-Term Heat Profile Projection (5–10 Years)

- Current development trajectories will **increase urban heat intensity** in the downtown core and North San José corridor due to densification, increased thermal mass, and higher anthropogenic heat output from more buildings, residents, and commercial activity.
- Partially offsetting factors include: higher-performance building envelopes in new construction, mandated cool roofs, increased tree planting, and potential cool pavement adoption.
- Net assessment: Urban heat island intensity is projected to increase by an estimated 1–3°F in the most intensively developing areas over the next decade, unless aggressive cool surface and green infrastructure programs are scaled significantly.
- Climate change projections for the South Bay indicate increasing frequency and intensity of extreme heat events like the one producing 105.3°F, compounding the urban heat island effect.

Sources:

- San José General Plan Annual Review and housing pipeline reports
- Google Downtown West (Diridon Station Area) development plan documents
- California Department of Finance population estimates
- California Senate Bills SB 9 and SB 10 housing density provisions



- Cal-Adapt climate projection tools for Santa Clara County

6. Pedestrian Infrastructure & Outdoor Thermal Comfort

Walkability Characterization

- Downtown San José has moderate walkability (Walk Score typically 70–85 for the core), with a connected street grid, sidewalks on most streets, and pedestrian-oriented development along San Carlos Street, Santa Clara Street, and the SoFA (South First Area) district.
- Outside downtown, San José is predominantly auto-oriented suburban development with wide arterials, long blocks, and limited pedestrian infrastructure. Walk Scores in suburban areas drop to 30–50.
- Sidewalk coverage is generally present on both sides of streets in the urban core but may be narrow (4–5 feet), lack shade, and be directly adjacent to high-temperature asphalt roadways.

Shading Infrastructure

- Downtown San José has limited systematic shading infrastructure. Some blocks along major streets have street trees (typically at 30–50 foot spacing), but many stretches of sidewalk are fully exposed to direct solar radiation.
- Covered walkways and arcades are rare — San José's commercial architecture does not typically feature the colonnades or deep overhangs found in some historically hot-climate cities.
- Awnings are present on some retail frontages in the SoFA district and along San Pedro Street but are inconsistent and do not form continuous shade corridors.
- At 105.3°F, the absence of continuous shade means pedestrians experience dangerous radiant heat loads on most walking routes.

Mean Radiant Temperature (MRT) Conditions

- At 105.3°F ambient temperature with clear October skies (typical for this heat event), MRT in unshaded areas can reach **140–160°F**, driven by re-radiation from asphalt surfaces (surface temp 150–165°F), building facades, and direct solar radiation (~800–900 W/m² at midday in early October at this latitude).
- Sky view factor in downtown San José is moderate (0.3–0.5 in the core, 0.6–0.8 in suburban areas), meaning less longwave radiation trapping than in deep urban canyons but also less building shade on sidewalks.
- The combination of high MRT, extreme air temperature, and low wind speeds typical of inland South Bay creates conditions where the Universal Thermal Climate Index (UTCI) would classify outdoor exposure as **"extreme heat stress" (>46°C / >115°F UTCI)** — dangerous for any prolonged outdoor activity.
- Reflected radiation from glass-facade buildings in downtown amplifies pedestrian-level radiant loads on adjacent sidewalks.

Heat Exposure Risk

- At 105.3°F, pedestrians face **severe heat stroke risk** within 15–30 minutes of unshaded exposure, particularly vulnerable populations (elderly, children, outdoor workers, unhoused individuals).
- San José has a significant unhoused population (~6,000–7,000 individuals in Santa Clara County), many of whom lack access to cooling and are exposed to these extreme conditions along creek corridors and in encampments with no shade infrastructure.
- Outdoor workers in landscaping, construction, and agriculture (in peri-urban areas) face occupational heat illness risk that is extreme at this temperature, governed by Cal/OSHA heat illness prevention standards requiring shade access and water above 80°F.
- VTA light rail and bus stops frequently lack adequate shade structures — many stops have only a pole-mounted sign with no shelter, exposing transit riders to full solar radiation during wait times.

Cooling Interventions

- Misting systems: Not widely deployed in San José's public spaces. Some private restaurants and businesses may have patio misting, but no systematic public misting infrastructure exists.
- The city activates cooling centers during extreme heat events (libraries, community centers), but these are indoor facilities, not outdoor pedestrian comfort interventions.
- Heat-reflective pavements: Not yet deployed at scale in San José, though pilot programs have been discussed.
- Passive cooling corridors: The Guadalupe River Park trail provides a partially shaded, lower-temperature walking route through downtown, but it is not designed as a comprehensive cooling corridor.



- The Diridon Station Area development plans include shaded pedestrian pathways and climate-responsive street design, which could serve as a future model.

Cycling Infrastructure

- San José has an expanding network of bike lanes (~300+ miles of bikeways of various classes), but most are unprotected painted lanes on asphalt roadways with no shade.
- At 105.3°F, cycling on exposed asphalt lanes subjects riders to radiant heat from the road surface (150°F+) in addition to ambient heat and physical exertion, creating dangerous conditions. Practical cycling is severely limited during extreme heat events.
- Trail systems (Guadalupe River Trail, Coyote Creek Trail, Los Gatos Creek Trail) offer partially shaded alternatives but are primarily recreational rather than commute-oriented.

Notable Pedestrian Comfort Zones and Deficits

- **Comfort zones:** Guadalupe River Park (~0.5–1 mile west) provides the best pedestrian thermal comfort in the urban core, with riparian tree canopy and proximity to water. Plaza de César Chávez (~0.5 miles from coordinates) offers a small shaded respite. The San Pedro Square area has some building shade and tree cover.
- **Major deficits:** Santa Clara Street and San Carlos Street corridors through downtown have long stretches of exposed sidewalk with minimal shade. East San José arterials (Story Road, Tully Road, King Road) are particularly hostile to pedestrians — wide, exposed, with minimal tree canopy and high-speed traffic generating additional radiant heat.
- **Transit exposure:** Many VTA light rail platforms (particularly at-grade stations) lack adequate shade structures, creating dangerous wait conditions at 105.3°F.
- Overall assessment: **San José's pedestrian infrastructure is critically inadequate for thermal comfort at 105.3°F.** The city was designed primarily for automobile use, and retrofitting shade and cooling infrastructure for pedestrians remains a major gap in heat resilience.

Sources:

- Walk Score data for San José neighborhoods
- San José Better Bike Plan 2025
- Cal/OSHA Heat Illness Prevention Standard (Title 8, Section 3395)
- Santa Clara County Homeless Census and Survey
- ASHRAE and ISO 7730 thermal comfort standards
- Research on Mean Radiant Temperature and UTCI in urban environments (e.g., studies from Arizona State University and Technical University of Munich)

Events Analysis

1. Extreme Weather Events & Heat Event History

Heat-Related Events

- **Baseline temperature conversion:** The provided average temperature of 40.74°C converts to approximately **105.3°F**. This is an exceptionally high temperature for San Jose, California (Santa Clara Valley) on October 2nd.
- **September 2022 Heatwave:** One of the most significant heat events in California history struck the San Jose/Bay Area region in late August through early September 2022. Temperatures in San Jose reached approximately 109-112°F in surrounding inland valleys, with San Jose proper recording highs near 105-109°F. The event lasted roughly 10 days and was associated with a persistent upper-level ridge. Multiple heat-related deaths were documented across California, and the state's electrical grid was pushed to emergency levels (Flex Alerts issued by CAISO).
- **June 2021 Pacific Northwest Heat Dome:** While the most extreme impacts were in Oregon and Washington, San Jose experienced temperatures exceeding 100°F during this event. The dome was driven by an exceptionally strong omega block pattern.
- **September 2020 Heat Event:** Coinciding with historic wildfire activity, San Jose recorded temperatures above 100°F while simultaneously experiencing hazardous air quality from wildfire smoke. This compound event created a dual health crisis — extreme heat plus inability to ventilate homes due to smoke.
- **July 2006 California Heatwave:** A prolonged, record-breaking event lasting approximately two weeks. San Jose and the Santa Clara Valley experienced sustained temperatures above 100°F. Statewide, this event was associated with an estimated 600+ excess deaths (documented in epidemiological studies). Power infrastructure was severely strained, with rolling outages and transformer failures.
- **Typical synoptic precursors:** Extreme heat in San Jose is driven by: (1) persistent upper-level high-pressure ridges



building over the Great Basin and extending westward, (2) offshore (northeasterly) wind patterns that bring hot, dry air from the interior valleys over the coastal ranges and suppress the marine layer, (3) prolonged dry antecedent conditions reducing soil moisture and evapotranspiration, (4) absence of the typical afternoon sea breeze that normally moderates South Bay temperatures.

- **Seasonal heat risk window:** The primary extreme heat season for San Jose typically runs from **mid-June through mid-October**, with peak risk concentrated in July-September. October heat events are less common but not unprecedented — "Indian summer" or late-season ridge events can produce temperatures exceeding 100°F into early-to-mid October. The date of October 2nd falls within the tail end of the heat risk season.
- **Government/institutional responses:** During the September 2022 event, California declared a grid emergency, Governor Newsom issued an emergency proclamation, cooling centers were activated across Santa Clara County, and CAISO issued unprecedented Flex Alert requests for conservation. The City of San Jose activated its Emergency Operations Center protocols for extreme heat.
- **Compound events:** The Santa Clara Valley is particularly susceptible to heat + wildfire smoke compounding (as in 2020), heat + drought (persistent during 2012-2016 and 2020-2022 droughts), and heat + power grid strain. The combination of extreme heat and poor air quality from wildfires creates a particularly dangerous scenario where residents cannot open windows for ventilation and may lack air conditioning.

Other Extreme Weather With Heat Relevance

- **Droughts:** The Santa Clara Valley experienced severe-to-exceptional drought conditions during 2012-2016 and 2020-2022. Drought amplifies heat through the soil moisture-temperature feedback: depleted soil moisture reduces latent heat flux (evapotranspiration), converting more solar energy into sensible heat. During drought years, peak temperatures in San Jose tend to run 2-5°F above already-warm normals. The region's Mediterranean climate means summers are inherently dry, but multi-year drought intensifies this baseline aridity.
- **Wildfires:** Major fires affecting the San Jose area include the SCU Lightning Complex (2020, ~400,000 acres), which burned in the Diablo Range east of San Jose. Wildfire smoke creates a complex thermal effect: dense smoke can temporarily reduce daytime highs by blocking insolation, but smoke layers can also trap longwave radiation at night, elevating overnight minimum temperatures and reducing nighttime recovery. The primary health concern is the combined thermal + air quality stress on cardiovascular and respiratory systems.

Sources:

- National Weather Service San Francisco Bay Area office historical records
- California Department of Public Health heat-related mortality reports
- CAISO grid emergency documentation
- Published epidemiological studies on the July 2006 California heatwave (e.g., Knowlton et al., Environmental Health Perspectives)
- U.S. Drought Monitor historical records

2. Heatwave Frequency & Intensity

- **Heatwave definition for this region:** The National Weather Service (NWS) San Francisco Bay Area office issues Excessive Heat Warnings for the Santa Clara Valley when temperatures are forecast to reach $\geq 105^{\circ}\text{F}$ for any duration, or sustained temperatures $\geq 100^{\circ}\text{F}$ for two or more consecutive days. Heat Advisories are issued for daytime highs of 100-104°F sustained over multiple days. The NWS also considers nighttime temperatures remaining above 68-70°F as an aggravating factor.
- **Frequency:** San Jose historically experiences approximately 3-6 days per year exceeding 100°F, though this has been increasing. Historically typical: full Excessive Heat Warning-level events ($\geq 105^{\circ}\text{F}$) occur roughly once every 2-4 years. In recent decades (2000s-2020s), the frequency of 100°F+ days has increased measurably compared to the 1970s-1990s baseline.
- **Trend direction:** Estimated: San Jose has gained approximately 3-5 additional days per decade above 95°F since the 1980s baseline. Heatwave events are becoming more frequent, longer in duration, and are extending later into the fall season (September-October events becoming less anomalous).
- **Intensity metrics:** Typical heatwave peak temperatures in San Jose range from 100-108°F. The all-time record high for San Jose is approximately 109°F. During major events, nighttime lows may remain in the 70-80°F range, which is critically important — the normal summer overnight low for San Jose is approximately 57-62°F, so heatwave nights can be 15-20°F above normal.
- **Record-breaking events:** The September 2022 event and July 2006 event represent the most significant documented heatwaves. Both featured multiple consecutive days above 105°F in the broader Santa Clara Valley, durations exceeding one week, and documented public health and infrastructure impacts.
- **Classification of provided temperature (105.3°F on October 2):**
 - **Climate normal for October 2 in San Jose:** Historically typical high temperature is approximately 78-82°F. The



provided temperature of 105.3°F is approximately **23-27°F above the climatological normal**.

- **Heatwave threshold:** This temperature **exceeds the Excessive Heat Warning threshold** ($\geq 105^{\circ}\text{F}$).
- **Health-risk classification:** This falls in the "**Extreme Danger**" category — well above the threshold where heat-related illness and mortality risk escalate sharply. For an October date, this is especially dangerous because populations have begun de-acclimatizing from summer heat.
- **Explicit classification: EXCEEDING HEATWAVE THRESHOLD — extreme anomaly for date.**
- **Heat dome and blocking pattern susceptibility:** The Santa Clara Valley's position on the west side of the Pacific Basin makes it susceptible to amplified ridging patterns. When upper-level ridges build over the eastern Pacific or Great Basin and extend westward, the typical marine influence is suppressed. The valley's topographic enclosure (bounded by the Santa Cruz Mountains to the west and Diablo Range to the east) traps hot air and limits ventilation when the sea breeze is absent. This geography makes the region prone to rapid temperature escalation during blocking events.
- **Late-season context:** A 105°F reading in early October would represent a historically rare event — likely in the top 1-2% of October temperature observations. However, climate trends suggest such late-season extremes are becoming less improbable. The de-acclimatization factor makes this particularly dangerous from a health perspective.

Sources:

- National Weather Service San Francisco Bay Area heat product criteria
- NOAA/NWS Climate Normals (1991-2020) for San Jose, CA (Station KSJC)
- Climate trend analyses from peer-reviewed literature on Bay Area heat extremes
- California's Fourth Climate Change Assessment, San Francisco Bay Area regional report

3. Public Health Impacts & Heat Vulnerability

- **Known heat-related health burden:** During the July 2006 heatwave, California documented over 600 excess deaths statewide, with significant impacts in the Bay Area including Santa Clara County. Emergency department visits for heat-related illness surged by several hundred percent during that event. Heat exhaustion, heatstroke, acute renal failure, and cardiovascular events (heart attacks, arrhythmias) are the primary acute presentations. Respiratory exacerbation occurs especially during compound heat + smoke events.
- **Vulnerable populations in San Jose/Santa Clara County:**
 - **Elderly (65+):** Significant population in San Jose; reduced thermoregulatory capacity and higher prevalence of chronic conditions.
 - **Outdoor workers:** Large agricultural workforce in the southern Santa Clara Valley; construction workers throughout the metro area. California's Cal/OSHA heat illness prevention standard applies.
 - **Unhoused population:** San Jose has one of the largest unhoused populations in the U.S. (estimated 6,000-10,000 individuals in Santa Clara County), with extreme heat exposure and limited access to cooling.
 - **Low-income communities:** Neighborhoods in East San Jose, parts of downtown, and the Alum Rock area have lower air conditioning prevalence, older housing stock with poor insulation, and less tree canopy.
 - **Children:** Particularly vulnerable during school activities and outdoor play.
- **Heat-mortality threshold:** Estimated: For the San Jose/Bay Area population, excess mortality begins to increase measurably when daily maximum temperatures exceed approximately 95-100°F. This threshold is relatively high compared to coastal California cities (e.g., San Francisco, where excess mortality begins at lower temperatures due to less acclimatization) but lower than Central Valley cities. At 105°F, the mortality risk is substantially elevated. Critically, in October, the effective threshold may be lower because populations have partially de-acclimatized from summer.
- **Consecutive hot night risk:** At 105.3°F average (which likely implies nighttime temperatures well above 75°F), the risk of sustained nighttime heat preventing physiological recovery is very high. When overnight lows remain above 75°F, the body cannot adequately cool through normal thermoregulatory processes during sleep, leading to cumulative heat stress. Multi-day events with warm nights are disproportionately deadly compared to single-day spikes. The provided temperature strongly suggests dangerous nighttime conditions.
- **Heat advisory and warning systems:**
 - NWS issues tiered products: Heat Advisory (100-104°F sustained), Excessive Heat Warning ($\geq 105^{\circ}\text{F}$ or sustained dangerous conditions).
 - Santa Clara County has a heat emergency response plan with activation tiers.
 - At 105.3°F, an Excessive Heat Warning would almost certainly be in effect.
- **Cooling infrastructure and interventions:**
 - Santa Clara County operates cooling centers during heat events (libraries, community centers, senior centers).
 - California's Cal/OSHA Heat Illness Prevention Standard (Title 8, Section 3395) mandates water, shade, rest, and high-heat procedures (above 95°F) for outdoor workers.
 - California has utility shutoff moratorium protections during extreme heat events (CPUC regulations).
 - San Jose has public splash pads, extended pool hours, and park access during heat events.
 - 2-1-1 Santa Clara County provides heat resource information.



- **Heat vulnerability mapping:** Santa Clara County and the City of San Jose have participated in heat vulnerability assessments. These consistently identify East San Jose, downtown areas, and neighborhoods with lower tree canopy, higher impervious surface coverage, and lower median income as highest-risk zones. The Bay Area Regional Health Inequities Initiative (BARHII) and CalEPA's CalEnviroScreen tool both provide vulnerability indicators for census tracts in this area.
- **Health-system preparedness:** During past major heat events, Santa Clara Valley Medical Center and regional hospitals have experienced surge conditions. EMS call volumes increase significantly (estimated 20-50% above baseline) during multi-day heat events. The county's Emergency Medical Services Agency has heat-specific protocols for field treatment of heat illness.
- **Equity dimension:** Heat health burden in San Jose is disproportionately concentrated in:
 - Low-income neighborhoods with lower air conditioning penetration (estimated that 30-40% of homes in some older San Jose neighborhoods lack AC, compared to near-universal AC in newer suburban developments).
 - Communities of color, particularly Latino/a communities in East San Jose who also have higher rates of outdoor occupational exposure.
 - The unhoused population, which faces direct exposure with minimal mitigation options.
 - Mobile home communities, which heat rapidly and have limited insulation.

Sources:

- California Department of Public Health heat surveillance data
- Santa Clara County Public Health Department heat emergency plans
- Cal/OSHA Heat Illness Prevention Standard (Title 8, CCR §3395)
- CalEnviroScreen 4.0 (CalEPA/OEHHA)
- Published epidemiological analyses of 2006 California heatwave mortality
- Santa Clara County Point-in-Time Homeless Census data
- Bay Area Regional Health Inequities Initiative (BARHII) reports

Anthropogenic Factors Analysis

1. Heat Emissions from Vehicles & Industry

Temperature Context

- Average temperature: 40.74°C = **105.3°F** — an extreme heat event for San Jose, California (coordinates correspond to the San Jose metropolitan area)
- This temperature is approximately 25–30°F above the typical October average high for San Jose (~75°F), indicating a severe late-season heat wave

Transportation Heat Footprint

- San Jose and the broader Silicon Valley region are heavily car-dependent; the dominant commute mode is single-occupancy vehicles, with an estimated 75–80% drive-alone mode share based on Census ACS data
- Major arterials contributing vehicular waste heat: US-101, I-280, I-680, CA-87, and CA-85 — these corridors carry hundreds of thousands of vehicles daily
- Vehicular waste heat sources: internal combustion engines reject approximately 60–70% of fuel energy as waste heat (radiator, exhaust, and drivetrain losses), tire-road friction adds surface heating, and brake systems release kinetic energy as thermal energy during deceleration
- At 105.3°F, vehicle cooling systems (radiators, AC compressors) work harder, increasing waste heat rejection to the ambient environment — estimated 10–15% increase in per-vehicle waste heat output compared to mild conditions
- Estimated: Highway corridors in the San Jose area likely run 3–7°F warmer than surrounding residential areas due to concentrated exhaust heat, dark pavement absorption, and reduced vegetation

Industrial and Commercial Waste Heat

- **Data centers:** Silicon Valley hosts one of the highest concentrations of data centers in the world. Major facilities operated by companies including Equinix, CyrusOne, and enterprise campuses (Apple, Google, Meta nearby) generate substantial continuous waste heat. A typical 20 MW data center rejects approximately 60–70 million BTU/hour of waste heat
- **Semiconductor manufacturing:** Facilities in the San Jose/Santa Clara area (historically including facilities from Intel, AMD legacy operations, and various fab support operations) generate process heat from cleanroom HVAC and manufacturing equipment



- **Commercial office campuses:** Large corporate headquarters with extensive HVAC systems contribute to localized heat islands, particularly through rooftop condenser units
- **San Jose International Airport (SJC):** Aircraft operations, jet exhaust, APU usage on tarmac, and extensive paved apron areas create a concentrated heat zone. Airport surfaces can reach 150–170°F at this ambient temperature
- Typical for cities of this type: Industrial/commercial waste heat contributes an estimated 2–4 W/m² of anthropogenic heat flux in commercial/industrial zones, rising to 10–20 W/m² near data center clusters

Spatial Heat Concentration

- North San Jose (data center corridor along US-101 near Cisco/Milpitas): concentrated thermal output from server farms creates measurable warming — estimated 2–4°F above surrounding residential neighborhoods
- I-880/US-101 interchange area: combined freight, commuter, and industrial traffic creates persistent heat island
- Downtown San Jose: commercial HVAC rejection, traffic congestion, and reduced sky view factor concentrate anthropogenic heat

Temporal Patterns at Given Date/Time

- October 2, 2024, 12:00 hours (noon) on a Wednesday: this is a weekday midday period
- Traffic is between morning and evening peaks but still substantial; commercial/office HVAC systems are at full cooling capacity
- Data centers operate 24/7 with consistent heat output regardless of time
- Industrial operations are at full daytime capacity
- The combination of peak solar radiation and near-peak anthropogenic activity makes this close to the daily maximum for combined heat loading

Emission-Reduction Measures

- California's Advanced Clean Cars II regulation mandates 100% zero-emission vehicle sales by 2035; current EV adoption in Santa Clara County is among the highest in the nation — estimated 20–25% of new vehicle registrations are BEVs/PHEVs
- VTA (Valley Transportation Authority) has committed to fleet electrification for buses
- San Jose's Climate Smart plan targets carbon neutrality by 2030 for municipal operations
- Data center operators increasingly use free cooling, liquid cooling, and waste heat recovery — though waste heat reuse for district heating is minimal due to mild winter climate and low heating demand

Waste Heat Recovery Opportunities

- Limited district heating demand in San Jose's mild climate reduces the economic case for waste heat capture from data centers
- Potential applications: absorption cooling (using waste heat to drive cooling), preheating domestic hot water, and agricultural/industrial process heat — largely untapped in this region

Sources:

- U.S. Census Bureau American Community Survey (commute mode data)
- California Energy Commission data center energy reports
- California Air Resources Board Advanced Clean Cars II regulation
- City of San Jose Climate Smart Plan
- General thermodynamic principles of internal combustion engine efficiency

2. Cooling Infrastructure & Waste Heat Feedback Loop

Cooling Infrastructure Prevalence

- San Jose has historically had lower residential AC penetration than inland California cities due to its typically mild Mediterranean climate — estimated 55–65% of homes have central AC, with many older homes (pre-1990) relying on natural ventilation or evaporative cooling
- This is below the California statewide average of approximately 75% and well below Central Valley cities (90%+)
- Commercial buildings: near-universal AC penetration (95%+) in office, retail, and institutional buildings
- Newer residential construction (post-2000) in South and East San Jose typically includes central AC as standard



The AC Feedback Loop

- At 105.3°F, virtually every available cooling system in the region is operating at or near maximum capacity
- For every unit of cooling delivered indoors, approximately 1.2–1.4 units of heat are rejected outdoors (cooling load + compressor work), based on typical COP of 2.5–3.5 at these extreme temperatures
- COP degrades significantly at extreme ambient temperatures — at 105°F, typical residential AC COP drops to 2.0–2.5 (from 3.5–4.0 at design conditions), meaning more waste heat per unit of cooling
- Estimated: In dense commercial areas of San Jose (downtown, Santana Row, Valley Fair area), concentrated AC waste heat can add 1.5–3°F to local ambient temperatures during extreme heat events
- The feedback is self-reinforcing: higher ambient temperatures → lower AC efficiency → more electricity consumed → more waste heat rejected → higher ambient temperatures

Balance-Point Temperature

- Typical cooling balance-point temperature for this climate zone (ASHRAE Climate Zone 3C/4): approximately 65°F for residential, 55–60°F for commercial (due to internal gains)
- At 105.3°F, the temperature is **40°F above the residential balance point** — this represents an extreme cooling load condition
- Cooling degree hours at this temperature are approximately 40 CDH (base 65°F) for this single hour — an extraordinary value

Cooling Inequality

- East San Jose (predominantly lower-income, older housing stock from 1950s–1970s) has significantly lower AC penetration and higher vulnerability to extreme heat
- Many rental units, particularly in older apartment complexes, lack central AC; window units may be unaffordable to operate at sustained extreme temperatures
- Mobile home parks (scattered in South San Jose) have poor insulation and inadequate cooling capacity
- The City of San Jose activates cooling centers during extreme heat events, but access requires transportation — a barrier for car-less residents

District Cooling Systems

- No significant district cooling system operates in San Jose; cooling is overwhelmingly distributed (individual building systems)
- Some large corporate campuses (e.g., Adobe headquarters downtown) operate centralized chilled water plants that are more efficient than distributed units but still reject substantial waste heat

Innovative and Passive Cooling Strategies

- San Jose's Green Building Ordinance requires cool roofs on new commercial construction (solar reflectance index ≥ 78)
- Some newer developments incorporate ground-source heat pumps, though penetration remains low
- Google's planned Downtown West development includes passive cooling design elements and district-scale thermal systems
- Nighttime ventilation flushing is normally effective in San Jose's Mediterranean climate (cool nights), but during heat waves like this, nighttime temperatures remain elevated, eliminating this strategy's effectiveness

Cooling Demand Classification

- At 105.3°F in October in San Jose: **EMERGENCY** — this temperature is approximately 10–15°F above the local design-day temperature for cooling systems (typically 95–100°F for San Jose), meaning many systems cannot maintain setpoints, and the event is historically anomalous for the date

Sources:

- U.S. Energy Information Administration Residential Energy Consumption Survey (RECS)
- ASHRAE climate zone classifications and design-day data
- City of San Jose Green Building Ordinance
- Published research on AC waste heat urban temperature contributions (Salamanca et al., de Munck et al.)
- PG&E service territory climate zone data



3. Energy System Load & Grid Stress

Energy Demand Profile

- San Jose is served primarily by Pacific Gas & Electric (PG&E) and San Jose Clean Energy (SJCE, the community choice aggregator)
- Estimated consumption split: Commercial/industrial ~60–65% (driven by tech campuses and data centers), Residential ~30–35%, other ~5%
- SJCE sources: approximately 60% carbon-free energy (solar, wind, hydro, nuclear from the broader CAISO grid); PG&E's mix is approximately 50% renewable/carbon-free
- Natural gas remains significant for peaking power plants that activate during extreme demand events like this

Temperature-Demand Sensitivity

- CAISO (California Independent System Operator) data shows that statewide demand increases approximately 500–800 MW per °F above ~85°F threshold
- Typical for this region: Cooling degree day baseline is 65°F; at 105.3°F, the system is experiencing approximately 40 cooling degree-hours in a single hour
- At this temperature, the San Jose area's demand is likely 40–60% above baseline (non-cooling) levels, driven almost entirely by air conditioning load
- Data centers add a relatively temperature-insensitive baseload but their cooling systems draw additional power at extreme temperatures (estimated 5–10% increase in total facility power at 105°F vs. 75°F)

Grid Stability and Heat-Related Risk

- California experienced a severe grid emergency during the September 2022 heat wave, with CAISO issuing Flex Alerts and coming within minutes of Stage 3 rolling blackouts (actual Stage 2 emergency declared September 6, 2022)
- At 105.3°F in the Bay Area in October, CAISO would almost certainly issue a Flex Alert and potentially escalate to grid emergency stages
- This temperature in October is particularly dangerous because: (1) solar generation declines in fall (shorter days, lower sun angle), (2) hydroelectric capacity is typically depleted by October, (3) some generation units may be in scheduled maintenance assuming mild fall weather
- PG&E's transmission infrastructure in the South Bay is aging; transformer capacity derates at high ambient temperatures (approximately 1% capacity loss per °F above rated temperature)

Grid Heat Vulnerability

- Underground distribution cables in older San Jose neighborhoods are susceptible to thermal overload during sustained extreme heat — soil temperatures rise, reducing cable ampacity
- Overhead transmission lines sag at high temperatures, reducing clearances and requiring derating
- Substation transformers lose approximately 0.5–1% of rated capacity per °F above their nameplate ambient rating (typically 104°F/40°C) — at 105.3°F, transformers are at or slightly above their rated ambient limit

Load Shedding Risk

- **Relevant for this location:** California has a documented history of rolling blackouts (August 2020 actual blackouts, September 2022 near-miss) during extreme heat events
- At 105.3°F across the Bay Area in October, the risk of rotating outages is **elevated to high**, particularly in late afternoon (4–9 PM) when solar generation drops while cooling demand remains extreme
- The "net demand peak" (demand minus solar) typically occurs around 7–8 PM in California — this is the highest-risk period for load shedding

Energy Resilience Measures

- California has aggressively deployed utility-scale battery storage: approximately 7,000+ MW as of mid-2024, specifically to address the evening net-demand peak
- San Jose Clean Energy offers demand response programs and time-of-use rates to incentivize load shifting
- Residential battery storage (Tesla Powerwall, Enphase) adoption is high in Santa Clara County relative to national averages



- Virtual power plant programs are active, aggregating residential batteries and EV chargers for grid support
- PG&E's Enhanced Powerline Safety Settings (EPSS) for wildfire prevention can reduce grid capacity during concurrent fire weather — a potential compounding factor in October

Current Grid Stress Assessment

- At 105.3°F at noon on a Wednesday in October, the energy system is at or approaching **historically documented stress points**
- Noon timing means solar generation is near daily peak, providing some relief — the critical period will be 5–9 PM as solar drops
- CAISO would likely be operating under a Flex Alert with potential escalation to emergency conditions by evening
- Natural gas peaker plants throughout the Bay Area would be dispatched, adding their own waste heat and emissions to the urban environment

Sources:

- CAISO grid operations data and emergency declarations (2020, 2022 events)
- PG&E integrated resource planning documents
- San Jose Clean Energy program information
- California Energy Commission demand forecasting reports
- IEEE standards on transformer derating with temperature

4. Traffic Behavior & Vehicular Heat Contribution

Traffic Pattern Characterization

- San Jose is a car-dependent metropolitan area; the freeway network (US-101, I-280, I-680, I-880, CA-85, CA-87, CA-17) forms the primary commute infrastructure
- Typical weekday traffic: morning peak 7–9:30 AM, midday moderate, evening peak 4–7 PM
- At noon on a Wednesday, traffic is in the **midday moderate** period — lower than peak but still substantial, with commercial vehicles, delivery traffic, and midday trips
- Estimated: Major San Jose freeways carry 150,000–250,000 vehicles per day on key segments (US-101 through central San Jose)

Waste Heat Concentration Zones

- **US-101/I-880 interchange (Milpitas/North San Jose):** One of the most congested interchanges in the Bay Area; concentrated stop-and-go traffic maximizes per-vehicle waste heat output
- **I-280/CA-87 interchange (downtown):** Urban freeway corridor with limited ventilation due to surrounding development
- **Stevens Creek Boulevard corridor:** Dense commercial strip with high traffic volumes, frequent stops, and extensive parking lots
- **San Jose International Airport approach roads:** Concentrated taxi/rideshare queuing, rental car operations, and passenger drop-off/pickup create localized heat
- **Freight corridors:** I-880 serves as a major freight route connecting the Port of Oakland to warehousing/distribution in South Bay — heavy diesel trucks generate 3–5x the waste heat of passenger vehicles
- Large parking structures (Valley Fair, Santana Row, downtown garages): concentrated vehicle heat in poorly ventilated multi-story structures

Pavement Heat Interaction

- At 105.3°F ambient, asphalt pavement surface temperatures likely reach 145–165°F — well above the threshold for skin burns and contributing to radiant heat loading on pedestrians and vehicles
- Vehicle traffic prevents pavement cooling by: (1) adding exhaust heat directly to surface, (2) tire friction generating additional heat, (3) vehicle bodies blocking nighttime radiative cooling, (4) displacing air that might otherwise provide convective cooling
- Estimated: Heavily trafficked roads remain 5–10°F warmer than adjacent low-traffic residential streets during evening hours due to accumulated thermal mass and reduced cooling opportunity

Public Transit Role



- VTA (Valley Transportation Authority) operates light rail and bus service; mode share for transit is low — estimated 3–5% of commute trips
- Caltrain provides rail service along the Peninsula corridor; ridership has partially recovered post-pandemic
- Low transit mode share means the vast majority of person-trips generate individual vehicle waste heat rather than shared/efficient transit heat
- A fully loaded VTA light rail car displaces approximately 50–100 individual vehicle trips, reducing per-passenger waste heat by roughly 80–90%

Heat-Induced Behavioral Shifts

- At 105.3°F, walking and cycling become dangerous (heat stroke risk); this drives mode shift toward air-conditioned vehicles, increasing traffic and waste heat
- Transit ridership may decline as waiting at exposed bus stops/light rail platforms becomes intolerable — VTA stops have limited shade infrastructure
- Increased driving to indoor destinations (malls, movie theaters) for cooling refuge adds discretionary vehicle trips
- Delivery services (food delivery, e-commerce) likely surge as people avoid going outdoors, adding commercial vehicle traffic

Mitigation Measures

- San Jose has no congestion pricing or low-emission zones currently in effect
- VTA is transitioning to battery-electric buses (zero tailpipe emissions, reduced waste heat)
- City of San Jose has implemented some cool pavement pilot projects (higher-albedo surface treatments)
- Protected bike lanes have been expanded but are largely unused during extreme heat events
- BART extension to San Jose (under construction) will eventually provide high-capacity transit reducing vehicle trips on the US-101 corridor

Current Traffic Waste Heat Assessment

- At noon on Wednesday, October 2: **moderate traffic volume** (between peaks), but per-vehicle waste heat output is elevated due to extreme ambient temperature forcing maximum AC operation in all vehicles
- Estimated net vehicular waste heat contribution: moderate-to-elevated, with the evening peak (4–7 PM) expected to produce the day's maximum traffic-related heat loading

Sources:

- Caltrans traffic volume data (AADT counts)
- VTA ridership and fleet electrification plans
- City of San Jose Department of Transportation
- Metropolitan Transportation Commission (MTC) travel surveys
- Published research on pavement surface temperatures and vehicular waste heat

5. Seasonal Population Dynamics & Heat Demand

Population Variability

- San Jose does not experience dramatic seasonal population swings comparable to tourist-dependent or university-dominated cities
- The population is relatively stable year-round (~1.0 million residents in the city, ~2.0 million in Santa Clara County)
- Moderate seasonal factors: San Jose State University (enrollment ~37,000) is in full fall session in early October, adding to daytime population; tech workers have partially returned to offices post-pandemic but hybrid work remains prevalent
- No significant tourism-driven population surge in October (unlike summer or holiday periods)

Demand Translation for Current Period

- Early October typically represents a **moderate demand period** transitioning from summer cooling to mild fall — but this extreme temperature event creates summer-peak-like demand in what should be a shoulder season
- The mismatch between expected seasonal demand and actual demand is particularly dangerous: utilities may have scheduled maintenance, reduced staffing, or lower reserve margins assuming mild October weather
- University in session means campus buildings are fully occupied and cooled, adding to institutional energy demand



Weekend/Weekday and Time-of-Day Assessment

- Wednesday at noon: full weekday commercial operations
- Office buildings, retail, restaurants, and institutional facilities are all operating at full capacity
- Commercial energy demand is at its weekday daytime peak; residential demand is moderate (many residents at work) but will spike in evening as people return home and run AC
- The combination of commercial + residential cooling demand in evening hours (5–9 PM) will create the day's maximum anthropogenic heat load
- Estimated: Weekday daytime commercial energy use in San Jose is approximately 30–40% higher than weekend levels; at this temperature, the differential narrows as residential cooling dominates regardless of day

Weather-Driven Behavioral Changes

- At 105.3°F, outdoor activities effectively cease — parks, outdoor dining, and recreational facilities see minimal use
- Indoor commercial spaces (shopping centers, restaurants, gyms) see increased occupancy as people seek cooling
- This concentrates human metabolic heat and associated cooling loads in commercial buildings rather than dispersing it outdoors
- Schools may cancel outdoor activities or dismiss early, changing afternoon traffic patterns
- Construction and outdoor labor may be curtailed under Cal/OSHA heat illness prevention requirements (mandatory rest periods, shade access at 95°F+; enhanced requirements at 105°F+)

Infrastructure and Policy Adjustments

- City of San Jose activates its Extreme Heat Response Plan: cooling centers open at community centers and libraries
- PG&E/CAISO issue Flex Alerts requesting voluntary conservation (thermostat adjustments, avoiding major appliance use during 4–9 PM)
- VTA may deploy additional service to cooling centers
- No seasonal energy pricing differential specifically for October — this event falls outside the typical summer peak pricing period (June–September), potentially meaning demand response incentives are less robust
- Cal/OSHA outdoor heat regulations require employers to provide water, shade, and rest breaks — reducing outdoor work productivity but protecting worker health

Net Anthropogenic Heat Load Assessment

- Despite stable population, the extreme temperature creates **peak-season-equivalent anthropogenic heat loading** in what is normally a shoulder season
- The combination of full weekday commercial activity + emergency-level cooling demand + moderate traffic generates an estimated anthropogenic heat flux of 20–50 W/m² in commercial/industrial zones and 5–15 W/m² in residential areas
- This is comparable to or exceeding typical August peak conditions due to the extreme temperature anomaly

Sources:

- U.S. Census Bureau population estimates for San Jose/Santa Clara County
- San Jose State University enrollment data
- Cal/OSHA Heat Illness Prevention Standard (Title 8, Section 3395)
- City of San Jose Emergency Management — Extreme Heat Response protocols
- CAISO Flex Alert historical issuance data
- Published research on anthropogenic heat flux in mid-latitude cities (Sailor & Lu, Ichinose et al.)

All respondents consented to the use of their data as outlined in our "Privacy Policy" at the point of collection. [Privacy Policy](#)