Optimization algorithms illustrated using Matlab

Carl Tape, Qinya Liu, Albert Tarantola June 1, 2006 (California Institute of Technology)

> Last compiled: March 23, 2014 Contact: carltape@gi.alaska.edu

Contents

1	The	forward problem	3
2	Set- 2.1 2.2 2.3 2.4 2.5 2.6 2.7 2.8 2.9	Generating Gaussian random vectors	3 3 3 4 4 5 5 5 6
3	Opt 3.1 3.2 3.3 3.4	imization methods quasi-Newton	7 8
4	Con	vergence results for each method	9
5	Run 5.1 5.2 5.3 5.4 5.5	Example 1: One run, one method (steepest descent)	13 14 14
	A.1 A.2 A.3	First derivatives of $g(\mathbf{m})$	17 18
R	efere	nces	19
$\mathbf{L}^{:}$	ist c	of Figures	
	1 2 3 4	Gaussian distributions	19 20 21 22

5	Example 1: Samples of the data covariance matrix, II	23
6	Example 1: Convergence curve for steepest descent	24
7	Example 1: Samples of the posterior	25
8	Example 2:	26
9	Example 2:	27
10	Example 3a: Convergence curves for steepest descent	28
11	Example 3a: Posterior distributions for steepest descent	29
12	Example 3a: Posterior models for steepest descent	30
13	Example 3b: Convergence curves for steepest descent (no errors)	31
14	Example 3b: Posterior models for steepest descent (no errors)	32
15	Example 4: Convergence for five optimization methods, I	33
16	Example 4: Convergence for five optimization methods, II	34
17	Example 4: Convergence for five optimization methods, III	35

Note

This set of notes complements the Matlab code optimization.m, which is based on the optimization algorithms presented in *Tarantola* (2005, Section 6.22). The purpose of these notes and associated code is to gain some familiarity with several standard optimization algorithms in the context of generalized least squares (e.g., *Tarantola and Valette*, 1982).

These algorithms are using a simple ray-based traveltime measurements at stations for an earthquake described by its epicenter (x_s, y_s) and origin time (t_s) within a homogeneous medium with velocity v. The problem is outlined in Tarantola (2009, Section 4.4.2), where it is illustrated using Mathematica and a single inverse approach; here we use Matlab and several different inverse approaches.

1 The forward problem

The unknown model vector comprises information describing the epicenter (x_s, y_s) , the origin time t_s , and the velocity of the homogeneous medium. The data are travel times computed assuming straight line ray paths. In Appendix A we list the Matlab codes for the forward problems.

2 Set-up for the inverse problem

The fundamental dimensions in the problem are the M=4 (Cartesian) model parameters and the N=12 observations. This means that the matrices of interest — the design matrix, matrix of partial derivatives, covariance matrices — are easily computable and invertible.

2.1 Generating Gaussian random vectors

We will need Gaussian random vectors to sample covariance matrices: the prior model, the data, and the posterior model. Figure 2 shows a set of 1000 Gaussian random vectors, generated using the Matlab command randn.

2.2 Generating samples from a covariance matrix

As described in Tarantola (2005, p. 117), a sample from a prescribed covraiance matrix, \mathbf{C} can be generated assuming its matrix-square-root, \mathbf{L} , can be obtained ¹:

$$\mathbf{C} = \mathbf{L}\mathbf{L}^t. \tag{1}$$

Let w represent a Gaussian vector with zero mean and unit covariance ($\mathbf{C}_{w} = \mathbf{I}$), easily computed in Matlab (Section 2.1). Then a random realization of \mathbf{C} is computed by

$$\mathbf{x} = \mathbf{L}\mathbf{w}.\tag{2}$$

Each new \mathbf{w} therefore leads to a new \mathbf{x} .

2.3 Specifying the prior model covariance

The the prior model distribution is given by a mean and its covariance.

We specify a prior model ("mean") as

$$\mathbf{m} = \begin{bmatrix} x_s \\ y_s \\ t_s \\ v \end{bmatrix} = \begin{bmatrix} 35.0 \text{ km} \\ 45.0 \text{ km} \\ 16.0 \text{ s} \\ 1.61 \end{bmatrix}, \tag{3}$$

where $v = \ln(V/V_0)$ is the logarithmic velocity (Appendix A).

We specify the prior model covariance as

$$\mathbf{C}_{\text{prior}} = \begin{bmatrix} (10.0)^2 & 0 & 0 & 0\\ 0 & (10.0)^2 & 0 & 0\\ 0 & 0 & (0.5)^2 & 0\\ 0 & 0 & 0 & (0.2)^2 \end{bmatrix}. \tag{4}$$

¹Typically a Cholesky decomposition would be used to the matrix composition. However, in *many* cases, especially for large-dimension matrixes, numerical instabilities arise.

2.4 Sampling the prior model to obtain a target model

In Figure 3 we show 1000 samples of the prior model distribution, generated via the approach in Section 2.2. We randomly pick one to be the target model, $\mathbf{m}_{\text{target}}$.

The Matlab code is given by

```
% prior model covariance matrix (assumed to be diagonal)
sigma_prior = [10 10 0.5 0.2];
                            % standard deviations
       = diag( sigma_prior.^2 );  % diagonal covariance matrix
if inormalization==1
   Cmfac = nparm;
else
   Cmfac = 1;
end
       = Cmfac * cprior0;
cprior
                                  % WITH NORMALIZATION FACTOR
                                  % WITH NORMALIZATION FACTOR
icprior = inv(cprior);
icprior0 = inv(cprior0);
% sample the prior model distribution using the square-root UNNORMALIZED covariance matrix
for ii=1:nsamples, randn_vecs_m(:,ii) = randn(nparm,1); end
cov_samples_m = Lprior * randn_vecs_m;
mprior_samples = repmat(mprior,1,nsamples) + cov_samples_m;
```

where randn_vecs_m is a set of Gaussian random vectors, and chol is the Matlab function that performs a Cholesky decomposition of the prior model covariance matrix.

2.5 Specifying the data covariance

Similar to Section 2.3, the data are described in terms of the "target data" and the data covariance. We specify a data covariance matrix of

The exact "target data" are simply computed from the target model, that is

$$\mathbf{d}_{\text{target}} = \mathbf{g} \left(\mathbf{m}_{\text{target}} \right), \tag{6}$$

where $\mathbf{g}(\cdot)$ denotes the forward model. For each inversion, we add data errors associated with \mathbf{C}_{D} to the exact target data, i.e.,

$$\mathbf{d}_{\mathrm{obs}} = \mathbf{d}_{\mathrm{target}} + \boldsymbol{\epsilon},$$
 (7)

where ϵ represents a Gaussian random sample of C_D (Eq. 5).

2.6 Sampling the data covariance to obtain errors for the target data

Similar to Section 2.4, we now sample the data covariance to obtain the "data". This process is shown in Figures 4 and 5, and the pertinent Matlab code is

```
% data covariance matrix (assumed to be diagonal)
tsigma = 0.5;
                                    % uncertainty in arrival time measurement, seconds
sigma_obs = tsigma * ones(ndata,1); % standard deviations
         = diag( sigma_obs.^2 ); % diagonal covariance matrix
if inormalization==1
    Cdfac = ndata;
else
    Cdfac = 1;
end
      = Cdfac * cobs0;
                                    % WITH NORMALIZATION FACTOR
cobs
                                    % WITH NORMALIZATION FACTOR
icobs = inv(cobs);
icobs0 = inv(cobs0);
Lcobs = chol(cobs0, 'lower')';
                                    % square-root (lower triangular)
% sample the data distribution using the square-root UNNORMALIZED covariance matrix
for ii=1:nsamples, randn_vecs_d(:,ii) = randn(ndata,1); end
cov_samples_d = Lcobs * randn_vecs_d;
dobs_samples = repmat(dtarget,1,nsamples) + cov_samples_d;
```

Note that the samples are generated using the matrix described cobs0, not using the normalized version cobs; this distinction is discussed next.

2.7 Normalization factors for C_M and C_D

In many problems, there are different classes of model or data parameters which one may wish to weight differently in computing a single value of the misfit function. Such weights provide have the effect of "balancing" the different parts of the misfit function. In the simplest case, one typically would like the norm operation of a vector (\mathbf{m} or \mathbf{d}) to be approximately one, e.g., $\mathbf{d}^t \mathbf{C}_D^{-1} \mathbf{d} \approx 1$. To achieve this, one simply incorporates the number of data as a factor in \mathbf{C}_D^{-1} , as shown in the code excerpt in Section 2.6. Thus, we write the weighted version of the data covariance as

$$\mathbf{C}_{\mathrm{D}}' = N\mathbf{C}_{\mathrm{D}},\tag{8}$$

where N is the total number of measurements, i.e., the number of entries in vector \mathbf{d} .

2.8 The misfit function and its gradient

The misfit function, $S(\mathbf{m})$, will depend on the choice of norm for the data space and for the model space. The nonlinear least-squares misfit function employs an L_2 -norm in both data space and model space, and it is defined by (Tarantola, 2005, Eq. 6.251)

$$2 S(\mathbf{m}) = \|\mathbf{g}(\mathbf{m}) - \mathbf{d}_{obs}\|_{D}^{2} + \|\mathbf{m} - \mathbf{m}_{prior}\|_{M}^{2}$$
$$= (\mathbf{g}(\mathbf{m}) - \mathbf{d}_{obs})^{t} \mathbf{C}_{D}^{-1} (\mathbf{g}(\mathbf{m}) - \mathbf{d}_{obs}) + (\mathbf{m} - \mathbf{m}_{prior})^{t} \mathbf{C}_{prior}^{-1} (\mathbf{m} - \mathbf{m}_{prior})$$
(9)

Here are two equivalent ways to implement the misfit function:

2.9 The posterior model and covariance matrix

```
% posterior covariance matrix (e.g., Tarantola Eq. 3.53)
% note: cpost0 does not include normalization factors Cdfac and Cmfac
Gpost = G(mpost);
cpost0 = inv(Gpost'*icobs0*Gpost + icprior0);
```

3 Optimization methods

3.1 quasi-Newton

```
for ii = 1:niter
   disp([' iteration ' num2str(ii) ' out of ' num2str(niter) ]);
         = mnew;
   delta = d(m);
         = G(m);
   % update the model: Tarantola (2005), Eq 6.319
   \% (the line-search parameter is assumed to be nu = 1)
   Hhat = icprior + Ga'*icobs*Ga;
                                                              % approximate Hessian
   ghat = Ga'*icobs*(delta - dobs) + icprior*(m - mprior); % gradient
    if 1==1
       %mnew = m - inv(Hhat)*ghat;
             = -Hhat\ghat;
       mnew = m + dm;
    else
        % equivalent formula: see Tarantola and Valette (1982), Eq. 23-35
       mutemp = (Ga*cprior*Ga' + cobs) \ (dobs-delta + Ga*(m - mprior));
       mnew = mprior + cprior*Ga'*mutemp;
    end
   % misfit function for new model
   % note: book-keeping only -- not used within the algorithm above
   Sd_vec(ii+1) = Sd(mnew,dobs,icobs);
   Sm_vec(ii+1) = Sm(mnew,mprior,icprior);
   S_vec(ii+1) = S(mnew,dobs,mprior,icobs,icprior);
    disp([num2str(ii) '/' num2str(niter) ' : prior, current, target:']);
    disp([mprior mnew mtarget]);
end
```

3.2 steepest descent

% NOTE: Use Eq. 6.315 as a preconditioner to convert the

```
preconditioned steepest descent to the quasi-Newton method.
F = F0; % identity
for ii = 1:niter
   disp([' iteration ' num2str(ii) ' out of ' num2str(niter) ]);
   m = mnew;
   % steepest ascent vector (Eq. 6.307 or 6.312)
   delta = d(m);
         = G(m);
         = cprior*Ga'*icobs*(delta - dobs) + (m - mprior);
   % search direction (preconditioned by F) (Eq. 6.311)
   p = F*g;
   % update the model
        = Ga*p;
   mu = g'*icprior*p / (p'*icprior*p + b'*icobs*b); % Eq. 6.314 (Eq. 6.309 if F = I)
   mnew = m - mu*p; % Eq 6.297
   disp(sprintf('%i/%i : prior, current, target:',ii,niter));
   disp([mprior mnew mtarget]);
   Sd_vec(ii+1) = Sd(mnew,dobs,icobs);
   Sm_vec(ii+1) = Sm(mnew,mprior,icprior);
   S_vec(ii+1) = S(mnew,dobs,mprior,icobs,icprior);
end
3.3 conjugate gradient
for ii = 1:niter
   disp([' iteration ' num2str(ii) ' out of ' num2str(niter) ]);
   % steepest ascent vector (Tarantola, 2005, Eq. 6.312)
   delta = d(m);
   Ga
         = G(m);
          = cprior*Ga'*icobs*(delta - dobs) + (m - mprior);
   % search direction (Tarantola, 2005, Eq. 6.329)
   1 = F0*g;
   if ii == 1
       alpha = 0; p = g;
      alpha = (g-gold)'*icprior*l / (gold'*icprior*lold);  % Eq. 6.331-2
      p = 1 + alpha*pold;
   end
   % update model
   b = Ga*p;
   mu = g'*icprior*p / (p'*icprior*p + b'*icobs*b); % Eq. 6.333
   mnew = m - mu*p;
   gold = g;
   pold = p;
   lold = 1;
   disp(sprintf('%i/%i : prior, current, target:',ii,niter));
   disp([mprior mnew mtarget]);
   Sd_vec(ii+1) = Sd(mnew,dobs,icobs);
```

```
Sm_vec(ii+1) = Sm(mnew,mprior,icprior);
S_vec(ii+1) = S(mnew,dobs,mprior,icobs,icprior);
end
```

3.3.1 conjugate gradient (polynomial line search)

Here, instead of using the line search suggested by *Tarantola* (2005, Eq. 6.333), we use the line search outlined in *Tape et al.* (2007). The main idea is that you compute the misfit function one more time (per iteration), which allows you to pick a better step length. The code for this line search is as follows:

```
% test model using quadratic extrapolation: Tape-Liu-Tromp (2007)
mu_test = -2*Sval / sum( g'*icprior*p );
        = m + mu_test*p;
{\tt m\_test}
Sval_test = S(m_test,dobs,mprior,icobs,icprior);
\% end iteration if the test model is unrealistic
if ~isreal(Sval_test)
   disp(' polynomial step is TOO FAR');
   S_vec(ii+1:end) = S_vec(ii);
    break;
end
% determine coefficients of quadratic polynomial (ax^2 + bx + c),
% using the two points and one slope
x1 = 0;
x2 = mu_test;
y1 = Sval;
y2 = Sval_test;
g1 = sum( g'*icprior*p );
Pa = ((y2 - y1) - g1*(x2 - x1)) / (x2^2 - x1^2);
Pb = g1;
Pc = y1 - Pa*x1^2 - Pb*x1;
% get the analytical minimum of the parabola
if Pa ~= 0, mu = -Pb / (2*Pa); else error('check the input polynomial'); end
3.4 variable metric (matrix version)
F = F0;
for ii = 1:niter
   disp([' iteration ' num2str(ii) ' out of ' num2str(niter) ]);
   m = mnew;
   % steepest ascent vector
   delta = d(m);
   Ga
          = cprior*Ga'*icobs*(delta - dobs) + (m - mprior);
   % update the preconditioner F
    if ii > 1
       dg = g - gold;
                                                  % Eq. 6.341
        v = F*dg;
                                                  % Eq. 6.355
       u = dm - v;
                                                  % Eq. 6.341
        F = F + u*u*icprior / (u*icprior*dg); % Eq. 6.356
    end
```

```
% preconditioning search direction (Eq. 6.355)
   p = F*g;
   % update the model
                                                         % Eq. 6.333
         = Ga*p;
         = g'*icprior*p / (p'*icprior*p + b'*icobs*b);
                                                        % Eq. 6.333
                                                         % Eq. 6.355
        = -mu*p;
   mnew = m + dm;
   gold = g;
   disp(sprintf('%i/%i : prior, current, target:',ii,niter));
   disp([mprior mnew mtarget]);
   Sd_vec(ii+1) = Sd(mnew,dobs,icobs);
   Sm_vec(ii+1) = Sm(mnew,mprior,icprior);
   S_vec(ii+1) = S(mnew,dobs,mprior,icobs,icprior);
end
% estimated posterior covariance matrix from F_hat, Eq. 6.362
% compare with cpost = inv(Gpost'*icobs*Gpost + icprior)
Fhat = F * cprior
```

4 Convergence results for each method

Using the misfit function in Equation (9), we can plot $S_k = S(\mathbf{m}_k)$ for a particular method. Each point represents the misfit function for the mean model. We also have the option of choosing dozens of different target models from the prior model, and then comparing the convergence curves. The "mean curve" — simply the mean of all the convergence curves — gives some idea of the general shape of the convergence. This reduces the chance that the shape of the convergence curve has characteristics that result from a particular (randomly sampled) choice of the target model.

The epicenter problem is fast, and we can compare all methods for hundreds of sets of "observations" generated from different target models (with appropriate errors added). Figures 15 and 16 show a collection of convergence curves for five different methods. The "plateau" that typically appears in the variable metric method between iterations 2 and 4 may be related to an improper choice of line search.

5 Running the code

Figure 2

5.1 Example 1: One run, one method (steepest descent)

To execute the code, type optimization in the Matlab command window. This should lead to the following prompt:

```
TYPE A NUMBER AFTER EACH PROMPT AND HIT ENTER:

Optimization problem set-up:

Forward problem (1 = epicenter; 2 = epicenter-cresent): 1

Select the number of samples for the distributions (1000): 1000

Type 1 for random initial model or 0 for fixed: 0

Type 1 for random target model or 0 for fixed: 0

Data errors (0 = none, 1 = random, 2 = fixed): 2

Type 1 to plot figures or 0 to not: 1
```

Here we have entered options for 1000 samples of the distributions, a fixed initial model, a fixed target model, and fixed errors added to the target data. The user is encouraged to examine the subsequent figures before proceeding. Figure 3 shows two representations of the 1000 4-parameter samples, in addition to the initial model (\mathbf{m}_{00}) and target model ($\mathbf{m}_{\text{target}}$) for this example. Figures 4 and 5 show samples of the data for all 1000 models.

Next, the user is faced with the following prompt:

```
Optimization methods:
```

```
0 : none (stop here)
1 : Newton (full Hessian)
2 : quasi-Newton
3 : steepest descent
4 : conjugate gradient
5 : conjugate gradient (polynomial line search)
6 : variable metric (matrix version)

TYPE A NUMBER AFTER EACH PROMPT AND HIT ENTER:
    IF YOU WANT MULTIPLE METHODS, LIST THE NUMBERS IN BRACKETS (e.g., [1 4 5])
    IF YOU WANT ALL METHODS, USE [1:6]

Select your optimization method(s) (0-6): 3
Select the number of iterations (10): 10
```

Here we have entered options for the steepest descent method with 10 iterations (for one run). The code outputs the following:

```
Initial model 1 out of 1
_____
Running steepest descent...
______
iteration 0 out of 10
0/10 : prior, current, target:
  35.0000 46.5236
                 21.2922
  45.0000 40.1182
                 46.2974
  16.0000 15.3890
                16.1314
  1.6094
         1.7748
                 2.0903
iteration 1 out of 10
1/10 : prior, current, target:
  35.0000 32.5197
                 21.2922
  45.0000 46.0045
                46.2974
  16.0000 15.3494
                16.1314
  1.6094
        1.9069
                2.0903
```

```
iteration 2 out of 10
2/10 : prior, current, target:
  35.0000 26.4517
                     21.2922
  45.0000 45.1591
                    46.2974
  16.0000 15.4300 16.1314
   1.6094
           1.8444
                      2.0903
 iteration 3 out of 10
3/10 : prior, current, target:
  35.0000
          25.1558 21.2922
  45.0000 46.5218 46.2974
  16.0000 15.3991
                     16.1314
   1.6094
           1.9042
                      2.0903
iteration 4 out of 10
4/10 : prior, current, target:
  35.0000 23.2082 21.2922
  45.0000 46.1433 46.2974
  16.0000 15.4238 16.1314
   1.6094
            1.8949
                      2.0903
iteration 5 out of 10
5/10 : prior, current, target:
  35.0000
          22.8829
                     21.2922
  45.0000 46.3288
                    46.2974
  16.0000 15.4184
                     16.1314
   1.6094 1.9225
                      2.0903
 iteration 6 out of 10
6/10 : prior, current, target:
  35.0000 21.9929
                     21.2922
  45.0000 46.0784
                     46.2974
  16.0000 15.4378
                     16.1314
   1.6094 1.9194
                      2.0903
iteration 7 out of 10
7/10 : prior, current, target:
  35.0000 21.9021 21.2922
  45.0000 46.1236 46.2974
  16.0000 15.4418 16.1314
   1.6094
           1.9349
                      2.0903
 iteration 8 out of 10
8/10 : prior, current, target:
  35.0000 21.4170 21.2922
  45.0000 45.9621
                     46.2974
  16.0000 15.4597
                     16.1314
   1.6094
            1.9331
                      2.0903
 iteration 9 out of 10
9/10 : prior, current, target:
  35.0000 21.4273
                     21.2922
  45.0000 45.9958 46.2974
  16.0000 15.4671 16.1314
   1.6094
           1.9435
                      2.0903
iteration 10 out of 10
10/10 : prior, current, target:
  35.0000
          21.1243
                    21.2922
  45.0000 45.8870
                     46.2974
  16.0000 15.4839
                     16.1314
   1.6094
          1.9418
                      2.0903
iteration 0 out of 10
0/10 : prior, current, target:
  35.0000 21.1243
                     21.2922
```

```
45.0000 45.8870 46.2974
16.0000 15.4839 16.1314
1.6094 1.9418 2.0903
```

The convergence curve is shown in Figure 6.

Because the problem is small, we can compute C_{post} no matter what optimization method is selected. By taking the square root of C_{post} , we can generate samples of the posterior distribution, as shown in Figure 7. Note that a gradient-based optimization does *not*, in general, provide C_{post} . The following output summarizes the iterative inversion:

```
cpost0 =
    4.0852
               0.5191
                        -0.0868
                                   -0.0589
    0.5191
               2.2696
                        -0.0128
                                   -0.0169
   -0.0868
             -0.0128
                         0.0868
                                    0.0129
   -0.0589
             -0.0169
                         0.0129
                                    0.0029
rho_post =
    1.0000
              0.1705
                        -0.1457
                                   -0.5367
    0.1705
               1.0000
                        -0.0287
                                   -0.2073
              -0.0287
                         1.0000
                                    0.8058
   -0.1457
   -0.5367
              -0.2073
                         0.8058
                                    1.0000
model summary (10 iterations):
    prior
              initial
                       posterior
                                    target
   35.0000
              46.5236
                        21.1243
                                   21.2922
   45.0000
              40.1182
                        45.8870
                                   46.2974
   16.0000
              15.3890
                        15.4839
                                   16.1314
    1.6094
               1.7748
                         1.9418
                                    2.0903
data summary (12 observations):
    prior
              initial
                        posterior
                                     target
                                               actual
   23.0711
              22.4575
                        19.5256
                                   19.6702
                                              18.8013
   21.3852
             22.0746
                                   17.8942
                                              17.4276
                        17.5467
   26.2956
              25.8692
                        22.0098
                                   21.7127
                                              21.6611
              19.4670
                                   19.7077
                                              19.9488
   21.0111
                        19.5895
             18.7600
                        17.6693
                                   17.9684
                                              18.2509
   18.0276
   25.0062
             24.1355
                        22.0496
                                   21.7366
                                              21.5065
   22.6165
             19.2083
                        21.7912
                                   21.5817
                                              21.7794
   20.7726
             18.4420
                        20.7472
                                   20.6359
                                              20.9650
   25.9889
             24.0179
                        23.6100
                                   23.0836
                                              24.0899
   26.2956
             22.0098
                        24.7096
                                   24.0856
                                              24.6530
              21.5993
                        24.0299
                                   23.4699
                                              23.6047
   25.2195
   28.7279
             25.5726
                        26.0369
                                   25.1811
                                              25.6414
 Compare model uncertainties :
             model parameter :
                                             XS
                                                           ys
                                                                         ts
                                                                                        V
                        units:
                                             km
                                                           km
                                                                          s
                                                                                    none
                                      10.00000
                  sigma_prior =
                                                     10.00000
                                                                   0.50000
                                                                                 0.20000
                   sigma_post =
                                       2.02118
                                                      1.50652
                                                                    0.29469
                                                                                 0.05428
   std( 1000 mpost_samples) =
                                       2.00323
                                                      1.50464
                                                                    0.29708
                                                                                 0.05420
    sigma_post / sigma_prior =
                                       0.20212
                                                                    0.58937
                                                                                 0.27139
                                                     0.15065
    iter
                       Sd
                                        Sm
                                                S = Sm + Sd
                                              14.4792276931
       0
            14.0113335953
                              0.4678940978
       1
            3.1088570163
                              0.4971076295
                                               3.6059646457
       2
                              0.4263691881
            1.3534389282
                                               1.7798081163
       3
            0.7835111960
                              0.5760238099
                                               1.3595350059
       4
            0.6091460104
                              0.5960049914
                                               1.2051510018
       5
            0.4791315017
                              0.6610991518
                                               1.1402306535
       6
            0.4353347434
                              0.6712274803
                                               1.1065622237
       7
            0.3847483631
                              0.7029226432
                                               1.0876710063
```

```
8 0.3702321343 0.7051689856 1.0754011199
9 0.3445445947 0.7222710148 1.0668156095
10 0.3401552891 0.7200477216 1.0602030107
```

5.2 Example 2: One run, all methods

Figure 8, Figure 9

We now run all of the optimization algorithms for the same run as in Example 1. For this example, the user should enter the following options:

```
TYPE A NUMBER AFTER EACH PROMPT AND HIT ENTER:
Optimization problem set-up:
 Forward problem (1 = epicenter; 2 = epicenter-cresent): 1
 Select the number of samples for the distributions (1000): 1000
 Type 1 for random initial model or 0 for fixed: 0
 Type 1 for random target model or 0 for fixed: 0
 Data errors (0 = none, 1 = random, 2 = fixed): 2
Type 1 to plot figures or 0 to not: 1
Optimization methods:
   0 : none (stop here)
   1 : Newton (full Hessian)
   2 : quasi-Newton
   3 : steepest descent
   4 : conjugate gradient
   5 : conjugate gradient (polynomial line search)
   6 : variable metric (matrix version)
TYPE A NUMBER AFTER EACH PROMPT AND HIT ENTER:
   IF YOU WANT MULTIPLE METHODS, LIST THE NUMBERS IN BRACKETS (e.g., [1 4 5])
   IF YOU WANT ALL METHODS, USE [1:6]
Select your optimization method(s) (0-6): [1:6]
Select the number of iterations (10): 10
```

5.3 Example 3a: 10 different runs, 1 method (steepest descent)

We now consider 10 different runs, with each run characterized by a randomly selected initial model but with a fixed target model (from the previous two examples). Furthermore, for each run we add a different set errors to the target data to generate the actual data. For this example, the user should enter the following options:

```
TYPE A NUMBER AFTER EACH PROMPT AND HIT ENTER:
Optimization problem set-up:
 Forward problem (1 = epicenter; 2 = epicenter-cresent): 1
 Select the number of samples for the distributions (1000): 1000
Type 1 for random initial model or 0 for fixed: 1
Type 1 for random target model or 0 for fixed: 0
Data errors (0 = none, 1 = random, 2 = fixed): 1
 Type 1 to plot figures or 0 to not: 1
Optimization methods:
   0 : none (stop here)
   1 : Newton (full Hessian)
   2 : quasi-Newton
   3 : steepest descent
   4 : conjugate gradient
    5 : conjugate gradient (polynomial line search)
   6 : variable metric (matrix version)
TYPE A NUMBER AFTER EACH PROMPT AND HIT ENTER:
   IF YOU WANT MULTIPLE METHODS, LIST THE NUMBERS IN BRACKETS (e.g., [1 4 5])
   IF YOU WANT ALL METHODS, USE [1:6]
Select your optimization method(s) (0-6): 3
Select the number of iterations (10): 10
Select the number of different runs for each inversion method (1 <= nmodel <= 1000): 10
Figure 10, Figure 11, Figure 12
```

5.4 Example 3b: 10 different runs, 1 method (steepest descent)

We now consider 10 different runs, with each run characterized by a randomly selected initial model but with a fixed target model (from the previous two examples). Furthermore, for each run we add a different set errors to the target data to generate the actual data. For this example, the user should enter the same options as in Section 5.3, but with one difference

```
Data errors (0 = none, 1 = random, 2 = fixed): 0
```

Figure 13, Figure 14

5.5 Example 4: 100 different runs, all methods

For this example, the user should enter the following options:

```
TYPE A NUMBER AFTER EACH PROMPT AND HIT ENTER:
Optimization problem set-up:
Forward problem (1 = epicenter; 2 = epicenter-cresent): 1
Select the number of samples for the distributions (1000): 1000
Type 1 for random initial model or 0 for fixed: 1
Type 1 for random target model or 0 for fixed: 1
 Data errors (0 = none, 1 = random, 2 = fixed): 1
Type 1 to plot figures or 0 to not: 0
Optimization methods:
   0 : none (stop here)
   1 : Newton (full Hessian)
   2 : quasi-Newton
   3 : steepest descent
   4 : conjugate gradient
   5 : conjugate gradient (polynomial line search)
   6 : variable metric (matrix version)
TYPE A NUMBER AFTER EACH PROMPT AND HIT ENTER:
  IF YOU WANT MULTIPLE METHODS, LIST THE NUMBERS IN BRACKETS (e.g., [1 4 5])
   IF YOU WANT ALL METHODS, USE [1:6]
Select your optimization method(s) (0-6): [1:6]
Select the number of iterations (10): 10
Select the number of different runs for each inversion method (1 <= nmodel <= 1000): 100
```

Figure 15, Figure 16, Figure 17

A Forward model functions (forward_epicenter.m)

The forward model requires the following:

- Source location (x_s, y_s) .
- Source origin time t_s .
- \bullet Homogeneous velocity of the medium V.
- Receiver location (x_r, y_r) .

We define a logarithmic velocity, v, which is a Cartesian parameter. Transforming between v and V is given by

$$v = \ln\left(V/V_0\right) \tag{10}$$

$$V = V_0 \exp(v) \tag{11}$$

where V_0 is a scaling velocity (we use $V_0 = 1 \text{ km/s}$).

The arrival time at the receiver is computed by integrating the slowness (1/V) along the ray path between source and receiver:

$$t_r = t_s + \int_{\text{ray}} \frac{1}{V(x,y)} ds. \tag{12}$$

Assuming a spatially homogeneous velocity, V(x,y) = V, the ray paths are straight lines, and thus we obtain

$$t_r = t_s + \frac{\sqrt{(x_r - x_s)^2 + (y_r - y_s)^2}}{V},$$
(13)

which can be written as

$$g(\mathbf{m}) = g(t_s, x_s, y_s, v) = t_s + \frac{\sqrt{(x_r - x_s)^2 + (y_r - y_s)^2}}{V_0 \exp(v)},$$
(14)

where $g(\cdot)$ represents the forward model, **m** is the input model (Eq. 3), and the receiver locations are assumed to be known and fixed.

A.1 First derivatives of $q(\mathbf{m})$

The partial derivatives of the arrival-time function (Eq. 14) are

$$\frac{\partial g}{\partial t_n} = 1 \tag{15}$$

$$\frac{\partial g}{\partial x_s} = -\left[(x_r - x_s)^2 + (y_r - y_s)^2 \right]^{-1/2} (x_r - x_s) \ V_0^{-1} \exp(-v)$$
 (16)

$$\frac{\partial g}{\partial y_s} = -\left[(x_r - x_s)^2 + (y_r - y_s)^2 \right]^{-1/2} (y_r - y_s) \ V_0^{-1} \ \exp(-v)$$
 (17)

$$\frac{\partial g}{\partial v} = -\left[(x_r - x_s)^2 + (y_r - y_s)^2 \right]^{1/2} V_0^{-1} \exp(-v)$$
(18)

We now discretize the problem. There are N arrival-time measurements in the data vector \mathbf{d} . We assume a single event with N receivers, and we use index i to denote the measurement

index, which in our case is also the receiver index. Then the $N \times M$ matrix of partial derivatives is given by

$$\mathbf{G} = \begin{bmatrix} \frac{\partial g_1}{\partial t_s} & \frac{\partial g_1}{\partial x_s} & \frac{\partial g_1}{\partial y_s} & \frac{\partial g_1}{\partial V} \\ \dots & \dots & \dots & \dots \\ \dots & \dots & \dots & \dots \\ \frac{\partial g_i}{\partial t_s} & \frac{\partial g_i}{\partial x_s} & \frac{\partial g_i}{\partial y_s} & \frac{\partial g_i}{\partial V} \\ \dots & \dots & \dots & \dots \\ \dots & \dots & \dots & \dots \\ \frac{\partial g_N}{\partial t_s} & \frac{\partial g_N}{\partial x_s} & \frac{\partial g_N}{\partial y_s} & \frac{\partial g_N}{\partial V} \end{bmatrix}.$$

$$(19)$$

The subscript for g_i indicates that each prediction of the arrival time will depend on the location of the i receiver.

The Matlab code for these commands can be found in forward_epicenter.m.

A.2 Second derivatives of g(m)

The 16 second derivatives of the arrival time function (Eq. 14) are then

$$\frac{\partial^2 g}{\partial t_s \partial t_s} = 0 \tag{20}$$

$$\frac{\partial^2 g}{\partial x_s \partial t_s} = 0 \tag{21}$$

$$\frac{\partial^2 g}{\partial y_s \partial t_s} = 0 ag{22}$$

$$\frac{\partial^2 g}{\partial v \partial t_s} = 0 \tag{23}$$

$$\frac{\partial^2 g}{\partial t_s \partial x_s} = \frac{\partial^2 g}{\partial x_s \partial t_s} = 0 \tag{24}$$

$$\frac{\partial^2 g}{\partial x_s \partial x_s} = \left[(x_r - x_s)^2 + (y_r - y_s)^2 \right]^{-3/2} (y_r - y_s)^2 V_0^{-1} \exp(-v)$$
 (25)

$$\frac{\partial^2 g}{\partial y_s \partial x_s} = -\left[(x_r - x_s)^2 + (y_r - y_s)^2 \right]^{-3/2} (x_r - x_s) (y_r - y_s) V_0^{-1} \exp(-v)$$
 (26)

$$\frac{\partial^2 g}{\partial v \partial x_s} = \left[(x_r - x_s)^2 + (y_r - y_s)^2 \right]^{-1/2} (x_r - x_s) V_0^{-1} \exp(-v)$$
 (27)

$$\frac{\partial^2 g}{\partial t_s \partial y_s} = \frac{\partial^2 g}{\partial y_s \partial t_s} = 0 \tag{28}$$

$$\frac{\partial^2 g}{\partial x_s \partial y_s} = \frac{\partial^2 g}{\partial y_s \partial x_s} \tag{29}$$

$$\frac{\partial^2 g}{\partial y_s \partial y_s} = \left[(x_r - x_s)^2 + (y_r - y_s)^2 \right]^{-3/2} (x_r - x_s)^2 V_0^{-1} \exp(-v)$$
 (30)

$$\frac{\partial^2 g}{\partial v \partial u_s} = \left[(x_r - x_s)^2 + (y_r - y_s)^2 \right]^{-1/2} (y_r - y_s) V_0^{-1} \exp(-v)$$
(31)

$$\frac{\partial^2 g}{\partial t_s \partial v} = 0 \tag{32}$$

$$\frac{\partial^2 g}{\partial t_s \partial v} = 0$$

$$\frac{\partial^2 g}{\partial x_s \partial v} = \frac{\partial^2 g}{\partial v \partial x_s}$$
(32)

$$\frac{\partial^2 g}{\partial y_s \partial v} = \frac{\partial^2 g}{\partial v \partial y_s} \tag{34}$$

$$\frac{\partial^2 g}{\partial v \partial v} = \left[(x_r - x_s)^2 + (y_r - y_s)^2 \right]^{1/2} V_0^{-1} \exp(-v)$$
 (35)

The matrix of second derivatives is given by

$$\frac{\partial^2 g}{\partial \mathbf{m}^2} = \begin{bmatrix}
\frac{\partial^2 g}{\partial t_s \partial t_s} & \frac{\partial^2 g}{\partial x_s \partial t_s} & \frac{\partial^2 g}{\partial y_s \partial t_s} & \frac{\partial^2 g}{\partial v \partial t_s} \\
\frac{\partial^2 g}{\partial t_s \partial x_s} & \frac{\partial^2 g}{\partial x_s \partial x_s} & \frac{\partial^2 g}{\partial y_s \partial x_s} & \frac{\partial^2 g}{\partial v \partial x_s} \\
\frac{\partial^2 g}{\partial t_s \partial y_s} & \frac{\partial^2 g}{\partial x_s \partial y_s} & \frac{\partial^2 g}{\partial y_s \partial y_s} & \frac{\partial^2 g}{\partial v \partial y_s} \\
\frac{\partial^2 g}{\partial t_s \partial v} & \frac{\partial^2 g}{\partial x_s \partial v} & \frac{\partial^2 g}{\partial y_s \partial v} & \frac{\partial^2 g}{\partial v \partial v}
\end{bmatrix}.$$
(36)

or, expanded:

$$\frac{\partial^{2} g}{\partial \mathbf{m}^{2}} = \begin{bmatrix}
0 & 0 & 0 & 0 \\
0 & d^{-3} (y_{r} - y_{s})^{2} / V & -d^{-3} (x_{r} - x_{s}) (y_{r} - y_{s}) / V & d^{-1} (x_{r} - x_{s}) / V \\
0 & -d^{-3} (x_{r} - x_{s}) (y_{r} - y_{s}) / V & d^{-3} (x_{r} - x_{s})^{2} / V & d^{-1} (y_{r} - y_{s}) / V \\
0 & d^{-1} (x_{r} - x_{s}) / V & d^{-1} (y_{r} - y_{s}) / V & d / V
\end{bmatrix} . (37)$$

where $d^2 = (x_r - x_s)^2 + (y_r - y_s)^2$ and $V = V_0 \exp(v)$ (Eq. 11)). Note that, for this example, this matrix is symmetric.

Second derivatives of $S(\mathbf{m})$ **A.3**

The second derivatives of the misfit function are collected within the Hessian matrix. These derivatives involve second derivatives of the forward operator $q(\mathbf{m})$. The entries of the Hessian of the misfit function, $\hat{\mathbf{H}}$, are defined by (Tarantola, 2005, Eq. 6.256, 6.299)

$$\hat{H}_{\alpha\beta}(\mathbf{m}) = \frac{\partial \hat{\gamma}_{\alpha}}{\partial m^{\beta}}(\mathbf{m}) = \frac{\partial^2 S}{\partial m^{\alpha} \partial m^{\beta}}(\mathbf{m}) . \tag{38}$$

In practice, the second-derivative terms are dropped in the approximation for the Hessian, e.g., Tarantola (2005, Eq. 6.257). This approximation distinguishes the Gauss-Newton method from the quasi-Newton method.

References

Tape, C., Q. Liu, and J. Tromp (2007), Finite-frequency tomography using adjoint methods—Methodology and examples using membrane surface waves, *Geophys. J. Int.*, 168, 1105–1129.

Tarantola, A. (2005), Inverse Problem Theory and Methods for Model Parameter Estimation, SIAM, Philadelphia, Penn., USA.

Tarantola, A. (2009), Mapping of Probabilities: Theory for the Interpretation of Uncertain Physical Measurements, incomplete manuscript available on-line at http://www.ipgp.fr/~tarantola/.

Tarantola, A., and B. Valette (1982), Generalized nonlinear inverse problems solved using the least squares criterion, Rev. Geophys. Space. Phys., 20(2), 219–232.




Figure 1: Source–receiver geometry for the epicenter problem. See Section 5.1.




Figure 2: Two plotting representations of 1000 samples of 4-parameter Gaussian vectors. The top shows the distributions for each parameter (mean $\bar{x}=0$; standard deviation $\sigma=1$); the bottom shows all 1000 samples.




Figure 3: 1000 samples, each a vector having 4 entries, of the prior model covariance matrix (Eq. 4). (Top) Distributions for each model parameter. (Bottom) Physical representation of the two epicenter parameters (x_s, y_s) for all 1000 samples. Also shown is the initial model, \mathbf{m}_{00} , and the target model, $\mathbf{m}_{\text{target}}$, for a single inversion run. See Section 5.1.




Figure 4: 1000 samples, each a vector having 12 entries, of the data covariance matrix (Eq. 5), plotted showing the distributions for each data index. See Section 5.1.




Figure 5: Data vectors. We pick one of 1000 models (Figure 3) to be the target model, $\mathbf{m}_{\text{target}}$, from which we compute the target data, shown as a dashed red line. The "real" data, shown as a solid red line, are computed by adding a randomly selected sample of the data covariance matrix to the target data. The data for the prior model is shown in black. See Section 5.1.




Figure 6: Convergence curve using the steepest descent algorithm. See Section 5.1.




Figure 7: 1000 samples, each a vector having 4 entries, of the posterior model covariance matrix. (Top) Distributions for each model parameter. Note the ranges on the x-axes in comparison with those in Figure 3. (Bottom) Posterior samples (cyan) superimposed on the prior samples (blue), and also showing the initial model, the posterior (final) model (\mathbf{m}_{10}), the prior model (\mathbf{m}_{prior}), and the target model (\mathbf{m}_{target}). The samples of \mathbf{C}_{post} are generated via Equation (2), i.e., they are not produced from the steepest descent algorithm. See Section 5.1.




Figure 8: Four representations of posterior distributions of the epicenter parameters (x_s, y_s) for the methods listed in Figure 9; the steepest descent distribution is shown in Figure 6. Note that all methods produce comparable results for \mathbf{m}_{post} . For each case, the samples of \mathbf{C}_{post} are generated via Equation (2). See Section 5.2.




Figure 9: Convergence curves for five different algorithms for a single run. The steepest descent curve is shown in Figure 6. See Section 5.2.




Figure 10: Convergence curves for steepest descent algorithm for 10 different initial models using the same fixed target model but with different errors added for each run. See Section 5.3.




Figure 11: Posterior distributions for 6 of the 10 runs in Example 3 (Section 5.3). Each run starts with a different initial model (black circle) and has a different posterior distribution (cyan dots). The samples of \mathbf{C}_{post} are generated via Equation (2), i.e., they are not produced from the steepest descent algorithm.




Figure 12: Posterior models for all 10 runs in Example 3 (Section 5.3). The segments connect the initial models with the posterior ("final") models. The posterior distributions for each run are not shown here (see Figure 11).




Figure 13: Same as Figure 10 but with no target errors. The 10 initial models (and target errors added) are randomly selected and are different from the 10 runs in Figure 10. Note that the convergence curves $S_{\rm D}(\mathbf{m})$ and $S(\mathbf{m})$ reaches lower values in the case here. See Section 5.4.




Figure 14: Same as Figure 12 but with no target errors. Because the target errors are the same (zero) for each run, the posterior (final) models are more tightly clustered (than in Figure 12). See Section 5.4.




Figure 15: Convergence for five optimization methods for 100 runs. Each run is characterized by a randomly selected initial model, target model, and data errors. The red curve is the mean of all 100 curves in each plot. See Figure 16 and Section 5.5.




Figure 16: Superposition of the five mean curves in Figure 15. See Section 5.5.




Figure 17: Same as Figure 16 but with 1000 different runs instead of 100. See Section 5.5.