

Term Project

Airlines On-Time Performance, Delays, Cancellations and Diversions

MILESTONE 1 - Data selection and EDA

Introduction: Airline cancellations or delays are one of the major causes of passenger inconvenience. With publicly available dataset, using data science, I am hoping to gain meaningful insights into the best-performing airlines and understand the causes of delays, diversions and cancellations across different airline carriers.

For the final project, I would like to analyze airline data to identify different factors and their effects on a carrier's performance. Using the available performance measures I would like to be able to predict the chances of a flight being on-time/delayed/cancelled.

Data Source: Excel files from BTS. The Excel data has airline performance factors such as cancelled, diverted, delayed and on-time data. The downloaded raw data has up to 34 columns.

https://www.transtats.bts.gov/OT_Delay/OT_DelayCause1.asp?20=E (Download Raw Data link for data).

Problem statement addressed:

This study will benefit Customers as it will help predict a flights performance. Customers can lookup the chances of their flight reaching on-time during their booking or even before heading to the airport. Airlines can also benefit by comparing airline performances and predicting possibilities of delay based on aircraft/origin/destination and apply corrective measures to reduce cancellations and delays and improve on-time performance.

Data Transformation

In the data transformation step, I will be modifying the following:

1. Cancellation reason in the flight dataset is represented as A, B, C and D. I will be updating the cancellation code as follows:

A Carrier

B Weather

C National Air System

D Security

1. I will be adding a new column 'Status' with the status of a flight such as, On-Time, Delayed, Cancelled, Diverted.

2. Diverted column is of binary value which can be modified to a Yes/No

```
import pandas as pd
import numpy as np
import plotly.express as px
import seaborn as sns
import matplotlib.pyplot as plt
```

```
In [2]: #Read flight data from "https://www.transtats.bts.gov/OT_Delay/OT_DelayCause1.asp?20=E"

flight_data_df = pd.read_csv('T_ONTIME_MARKETING_May.csv')
flight_data_df.head()
```

```
Out[2]:
```

	YEAR	QUARTER	MONTH	DAY_OF_MONTH	DAY_OF_WEEK	FL_DATE	MKT_UNIQUE_CARRIER	OP_UNIQUE_CAI
0	2022	2	5	1	7	5/1/2022 12:00:00 AM	AA	
1	2022	2	5	1	7	5/1/2022 12:00:00 AM	AA	
2	2022	2	5	1	7	5/1/2022 12:00:00 AM	AA	
3	2022	2	5	1	7	5/1/2022 12:00:00 AM	AA	
4	2022	2	5	1	7	5/1/2022 12:00:00 AM	AA	

5 rows × 39 columns

1. DROP DUPLICATES

Duplicates cause inconsistent results when dealing with statistics. Hence dropping duplicate rows.

```
In [3]: print('Dataframe before dropping duplicates :', flight_data_df.shape)
flight_data_df = flight_data_df.drop_duplicates() # 1,389 rows dropped
print('Dataframe after dropping duplicates :', flight_data_df.shape)
```

Dataframe before dropping duplicates : (602950, 39)

Dataframe after dropping duplicates : (601561, 39)

2. Update Null values and Drop null rows, if any

Drop null rows, if any and update null values to 0 for delays

```
In [4]: #Drop null values
print('Dataframe before dropping null rows :', flight_data_df.shape)
flight_data_df.dropna()
print('Dataframe after dropping null rows :', flight_data_df.shape)
#Update null values to 0
flight_data_df.DISTANCE = flight_data_df.DISTANCE.fillna(0)
flight_data_df.DEP_DELAY = flight_data_df.DEP_DELAY.fillna(0)
flight_data_df.ARR_DELAY = flight_data_df.ARR_DELAY.fillna(0)
flight_data_df.CARRIER_DELAY = flight_data_df.CARRIER_DELAY.fillna(0)
flight_data_df.WEATHER_DELAY = flight_data_df.WEATHER_DELAY.fillna(0)
flight_data_df.NAS_DELAY = flight_data_df.NAS_DELAY.fillna(0)
flight_data_df.SECURITY_DELAY = flight_data_df.SECURITY_DELAY.fillna(0)
flight_data_df.LATE_AIRCRAFT_DELAY = flight_data_df.LATE_AIRCRAFT_DELAY.fillna(0)
```

Dataframe before dropping null rows : (601561, 39)
Dataframe after dropping null rows : (601561, 39)

```
In [5]: flight_data_df.loc[pd.isna(flight_data_df.CANCELLATION_CODE), 'CANCELLATION_CODE']='Z'
```

3. Add new features

Cancellation code is represented as A, B, C and D, which is not very informative. The BTS website provided details on this code as follows:

```
In [6]: flight_data_df['CANCELLATION_REASON'] = ''
flight_data_df.CANCELLATION_REASON = np.where(flight_data_df.CANCELLATION_CODE=='A', 'Ca
        np.where(flight_data_df.CANCELLATION_CODE=='B', 'Weathe
        np.where(flight_data_df.CANCELLATION_CODE=='C'
        np.where(flight_data_df.CANCELLATION
        np.where(flight_data_df.CAN

flight_data_df.groupby(['CANCELLATION_REASON'])['CANCELLATION_REASON'].count().sort_inde
```

```
Out[6]: CANCELLATION_REASON
Carrier                4902
National Air System    1394
Not Cancelled          590957
Security                1
Weather                4307
Name: CANCELLATION_REASON, dtype: int64
```

Adding a new column 'STATUS' that tells the status of a flight

```
In [7]: flight_data_df['STATUS'] = ''

flight_data_df.STATUS = np.where(flight_data_df.CANCELLED==1, 'Cancelled',
        np.where(flight_data_df.DIVERTED==1, 'Diverted',
        np.where(flight_data_df.ARR_DELAY<=15, 'On-Tim
        np.where(flight_data_df.ARR_DELAY>15,
flight_data_df.groupby(['STATUS'])['STATUS'].count().sort_index()
```

```
Out[7]: STATUS
Cancelled      10604
Delayed       119624
Diverted        1581
On-Time       469752
Name: STATUS, dtype: int64
```

Creating a new column 'ARR_DELAYED'. A flag that represents if a flight was delayed. Similar to CANCELLED and DIVERTED As a step to data reduction, I will be considering flights arriving 15 minutes or later as delayed

```
In [8]: flight_data_df.loc[(flight_data_df['ARR_DELAY']>15), 'ARR_DELAYED'] = True
flight_data_df.loc[(flight_data_df['ARR_DELAY']<=15), 'ARR_DELAYED'] = False

flight_data_df.groupby(['ARR_DELAYED'])['ARR_DELAYED'].count().sort_index()
```

```
Out[8]: ARR_DELAYED
False    481937
True     119624
Name: ARR_DELAYED, dtype: int64
```

Adding a new column 'DELAY_REASON' that tells the reason for a flight getting delayed

```
In [9]: flight_data_df['DELAY_REASON'] = np.where(flight_data_df.CARRIER_DELAY != 0, 'Carrier',
        np.where(flight_data_df.LATE_AIRCRAFT_DELAY !=
        np.where(flight_data_df.WEATHER_DELAY
```

```

np.where(flight_data_df.NAS_
np.where(flight_dat

flight_data_df.groupby(['DELAY_REASON'])['DELAY_REASON'].count().sort_index()

```

```

Out[9]: DELAY_REASON
          477611
Carrier      74794
LateAircraft 26097
NAS          18695
Security      142
Weather      4222
Name: DELAY_REASON, dtype: int64

```

Data Visualization:

Implementing arithmetic functions for statistical analysis

Creating a new dataframe with total number of flights per operating carrier to calculate the %

```

In [10]: flight_totals = flight_data_df.value_counts(subset=['OP_UNIQUE_CARRIER']).reset_index()
flight_totals_df = pd.DataFrame(flight_totals)
flight_totals_df.columns = ['OP_UNIQUE_CARRIER', 'TOTAL']
flight_totals_df['PERCENTAGE'] = round(flight_totals_df.TOTAL/flight_totals_df.TOTAL.sum

flight_totals_df = flight_totals_df.sort_values('PERCENTAGE', ascending=False)
flight_totals_df.head(5)

```

```

Out[10]:
   OP_UNIQUE_CARRIER  TOTAL  PERCENTAGE
0                WN  107950         17.94
1                DL   76021         12.64
2                AA   71471         11.88
3                OO   66615         11.07
4                UA   53535          8.90

```

Calculate percentage by carrier and flight status

```

In [11]: flight_status = flight_data_df.value_counts(subset=['OP_UNIQUE_CARRIER', 'STATUS']).reset
flight_status_df = pd.DataFrame(flight_status) #create a dataframe
flight_status_df.columns = ['OP_UNIQUE_CARRIER', 'STATUS', 'COUNT'] #Add column names
flight_status_df = flight_status_df.sort_values('OP_UNIQUE_CARRIER') #Sort by operating

flight_status_df['PERCENTAGE'] = ''

for index, row in flight_status_df.iterrows():
    tot = flight_totals.loc[flight_totals.OP_UNIQUE_CARRIER==row.OP_UNIQUE_CARRIER].TOTA
    val = (row.COUNT/tot * 100)
    flight_status_df.at[index, 'PERCENTAGE'] = round(val[0].astype(float),2) #Calculate t

flight_status_df.head(10)

```

```

Out[11]:
   OP_UNIQUE_CARRIER  STATUS  COUNT  PERCENTAGE
33                9E  Delayed   3113         15.33
48                9E  Cancelled   542          2.67
74                9E  Diverted    35          0.17


```

8	9E	On-Time	16613	81.83
41	AA	Cancelled	973	1.36
56	AA	Diverted	215	0.3
3	AA	On-Time	55403	77.52
11	AA	Delayed	14880	20.82
47	AS	Cancelled	608	3.12
10	AS	On-Time	15502	79.49

Bar chart for carier performance in May 2022

```
In [12]: fig = px.bar(flight_status_df, x="OP_UNIQUE_CARRIER", y="PERCENTAGE", title="Carrier Per
            color="STATUS", text="STATUS",
            labels={"OP_UNIQUE_CARRIER": "Operating Carrier",
                    "PERCENTAGE": "Percentage (%)"})
fig.update_layout(autosize=False,width=900, height=600)
fig.show()
```

Carrier Performance in May 2022




Hawaian airlines had the best on-time performance in May'22 followed by Air Wisconsin(ZW). Frontier airlines(F9) had the most number of delays at 32.9% GoJet had the most cancellations at 7%

Pie chart for Overall Carrier performance in May'22

```
In [13]: fig = px.pie(flight_totals_df, values='PERCENTAGE', names='OP_UNIQUE_CARRIER',
                    title='Overall Operating Carrier Performance (May'22)')
fig.update_traces(textposition='inside', textinfo='percent+label')
fig.show()
```

Overall Operating Carrier Performance (May22)




We can see southwest carrier (WN) had the most number of flights in May 2022.


Bar plot for Airline with best on-time performance

```
In [14]: airline_on_time_performance = flight_status_df[flight_status_df.STATUS == 'On-Time'].sort_values(
    by='PERCENTAGE', ascending=False)

fig=px.bar(airline_on_time_performance,
            x=airline_on_time_performance.OP_UNIQUE_CARRIER,
            y=airline_on_time_performance.PERCENTAGE, title="Airline On-Time Performance",
            text=airline_on_time_performance.PERCENTAGE.apply(lambda x: '{0:1.2f}%'.format(x)),
            labels=dict(OP_UNIQUE_CARRIER="Airline Carrier", PERCENTAGE="Percentage (%)"))
fig.update_xaxes(tickangle=45)
fig.update_layout(autosize=False,width=900, height=700)
```

Airline On-Time Performance





Hawaiian airline was the best performing airline in May'22 with 87.33% on time performance and Go-Jet is the least performing airline with 64.6% on-time performance.

```
In [15]: #Load csv file with airport names for origin and destination
airport_data_df = pd.read_csv('L_AIRPORT.csv')
airport_data_df.head()
```

```
Out[15]:
```

	Code	Description
0	01A	Afognak Lake, AK: Afognak Lake Airport
1	03A	Granite Mountain, AK: Bear Creek Mining Strip
2	04A	Lik, AK: Lik Mining Camp
3	05A	Little Squaw, AK: Little Squaw Airport
4	06A	Kizhuyak, AK: Kizhuyak Bay

```
In [16]: #Create a new dataframe with the percentage by origin airport and status
flight_origin_totals = flight_data_df.value_counts(subset=['ORIGIN']).reset_index() #get
flight_origin_totals_df = pd.DataFrame(flight_origin_totals) #create a dataframe
flight_origin_totals_df.columns = ['ORIGIN', 'TOTAL'] #Add column names
#Calculate the percentage by origin airport
flight_origin_totals_df['PERCENTAGE'] = round(flight_origin_totals_df.TOTAL/flight_origi

origin_airport_delays = flight_data_df.value_counts(subset=['ORIGIN', 'STATUS']).reset_in
origin_airport_df = pd.DataFrame(origin_airport_delays) #create a dataframe
origin_airport_df.columns = ['ORIGIN', 'STATUS', 'COUNT'] #add column names
```

```

origin_airport_df = origin_airport_df.sort_values('ORIGIN') #sort by origin
origin_airport_df['PERCENTAGE'] = ''

for index, row in origin_airport_df.iterrows():
    tot = flight_origin_totals.loc[flight_origin_totals.ORIGIN==row.ORIGIN].TOTAL.values
    val = (row.COUNT/tot * 100)
    origin_airport_df.at[index, 'PERCENTAGE'] = round(val[0].astype(float),2) #calculate

origin_airport_df.head(10)
origin_airport_df = origin_airport_df.sort_values('PERCENTAGE', ascending=False) #sort by

#Add the airport name from the airport_data_df and add as a new column to the origin_air
origin_airport_df=pd.merge(origin_airport_df, airport_data_df, how='left', left_on='ORIG
origin_airport_df.rename(columns={'Description':'ORIGIN_AIRPORT_NAME'}, inplace=True)
del origin_airport_df['Code']

new = origin_airport_df.ORIGIN_AIRPORT_NAME.str.split(":", n = 1, expand = True)
origin_airport_df["ORIGIN_AIRPORT_NAME"] = new[1]
origin_airport_df.head()

```

Out[16]:

	ORIGIN	STATUS	COUNT	PERCENTAGE	ORIGIN_AIRPORT_NAME
0	GST	On-Time	12	100.0	Gustavus Airport
1	STC	On-Time	1	100.0	St. Cloud Regional
2	LWS	On-Time	95	96.94	Lewiston Nez Perce County
3	BGM	On-Time	30	96.77	Greater Binghamton/Edwin A. Link Field
4	DRT	On-Time	60	96.77	Del Rio International

Bar chart for Origin airport with most delays


In [17]:

```

fig = px.bar(origin_airport_df[origin_airport_df.STATUS=="Delayed"], x="ORIGIN_AIRPORT_N
            title="Origin Airport with most Delays",
            text=origin_airport_df[origin_airport_df.STATUS=="Delayed"].PERCENTAGE.appl
            labels=dict(ORIGIN_AIRPORT_NAME="Origin Airport", PERCENTAGE="Percentage (%)
fig.update_xaxes(tickangle=80)
fig.update_layout(autosize=False,width=900, height=700)
fig.show()

```

Origin Airport with most Delays



Ogdensburg International
Corpus Christi International
Palm Springs International
Golden Triangle Regional
San Luis County Regional
Southwest Georgia Regional
Billings Logan International
Great Falls International/Ryan Field
Baton Rouge Metropolitan
North Central West Virginia
General Mitchell International
Bemidji Regional
Blue Grass
Burlington International
Albert J Ellis
The Eastern Iowa
McAllen Miller International
Joslin Field - Magic Valley Regional
South Bend International
Pittsburgh International
Tulsa International
Bangor International
Charlotteville Albemarle
Tallahassee International
Tri Cities
Bethel Airport
Manchester-Boston Regional
Manchester-Shuttlesworth International
Birmingham-Carl T Jones Field
Huntsville International
Sheppard AFB/Wichita Falls Municipal
Sheppard Regional
Stillwater Regional
Waterloo Regional
Cincinnati/Northern New Orleans International
Louis Armstrong International
Memphis Douglas International
Charlotte Douglas International
Washington Dulles International
Sarasota/Bradenton Capital
Abraham Lincoln Toledo Express
Eugene F Kranz Toledo Express
New York Stewart International
Rickenbacker International
Presque Isle International
Pago Pago International

Origin Airport

It appears Tri Cities has multiple entries for different origin airports. Identify and update the airport name.

```
In [18]: origin_airport_df[origin_airport_df.ORIGIN_AIRPORT_NAME.str.contains('Tri Cities')]
```

	ORIGIN	STATUS	COUNT	PERCENTAGE	ORIGIN_AIRPORT_NAME
29	PSC	On-Time	451	90.56	Tri Cities
207	TRI	On-Time	302	81.4	Tri Cities
506	TRI	Delayed	66	17.79	Tri Cities
708	PSC	Delayed	44	8.84	Tri Cities
1018	TRI	Cancelled	3	0.81	Tri Cities
1093	PSC	Diverted	2	0.4	Tri Cities
1178	PSC	Cancelled	1	0.2	Tri Cities

Updating the airport name for PSC

```
In [19]: origin_airport_df.loc[origin_airport_df["ORIGIN"] == "PSC", "ORIGIN_AIRPORT_NAME"] = 'Tri Cities(PSC)'
```

```
In [20]: origin_airport_df[origin_airport_df.ORIGIN_AIRPORT_NAME.str.contains('Tri Cities')]
```

	ORIGIN	STATUS	COUNT	PERCENTAGE	ORIGIN_AIRPORT_NAME
29	PSC	On-Time	451	90.56	Tri Cities(PSC)
207	TRI	On-Time	302	81.4	Tri Cities
506	TRI	Delayed	66	17.79	Tri Cities
708	PSC	Delayed	44	8.84	Tri Cities(PSC)
1018	TRI	Cancelled	3	0.81	Tri Cities
1093	PSC	Diverted	2	0.4	Tri Cities(PSC)
1178	PSC	Cancelled	1	0.2	Tri Cities(PSC)

Since the chart has many airports to fit, filtering the list to get the top 10 origin airports with most delays


```
In [21]: top_10_origin_delay_airports = origin_airport_df[origin_airport_df.STATUS=="Delayed"].he
top_10_origin_delay_airports
```

Out[21]:

	ORIGIN	STATUS	COUNT	PERCENTAGE	ORIGIN_AIRPORT_NAME
344	PPG	Delayed	2	66.67	Pago Pago International
361	IAG	Delayed	22	57.89	Niagara Falls International
368	SCK	Delayed	22	46.81	Stockton Metro
370	HGR	Delayed	9	45.0	Hagerstown Regional-Richard A. Henson Field
371	RFD	Delayed	22	42.31	Chicago/Rockford International
373	BLV	Delayed	45	42.06	Scott AFB MidAmerica St Louis
374	PSE	Delayed	39	41.94	Mercedita
375	PQI	Delayed	22	41.51	Presque Isle International
376	USA	Delayed	30	40.54	Concord Padgett Regional
378	RIW	Delayed	14	40.0	Central Wyoming Regional

```
In [22]: fig = px.bar(top_10_origin_delay_airports[top_10_origin_delay_airports.STATUS=="Delayed"],
                    title="Top 10 Origin Airport with most Delays",
                    text=top_10_origin_delay_airports[top_10_origin_delay_airports.STATUS=="Del
                    labels=dict(ORIGIN_AIRPORT_NAME="Origin Airport", PERCENTAGE="Percentage (%)
fig.update_xaxes(tickangle=80)
fig.update_layout(autosize=False,width=900, height=700)
fig.show()
```

Top 10 Origin Airport with most Delays



Origin Airport

Flights originating from Pago Pago International are delayed 66.67%

DESTINATION

```
In [23]: #Create a new dataframe with the percentage by origin airport and status
flight_dest_totals = flight_data_df.value_counts(subset=['DEST']).reset_index() #get the
flight_dest_totals_df = pd.DataFrame(flight_dest_totals) #create a dataframe
flight_dest_totals_df.columns = ['DEST', 'TOTAL'] #Add column names
#Calculate the percentage by destination airport
flight_dest_totals_df['PERCENTAGE'] = round(flight_dest_totals_df.TOTAL/flight_dest_tota

dest_airport_delays = flight_data_df.value_counts(subset=['DEST', 'STATUS']).reset_index(
dest_airport_df = pd.DataFrame(dest_airport_delays) #create a dataframe
dest_airport_df.columns = ['DEST', 'STATUS', 'COUNT'] #add column names
dest_airport_df = dest_airport_df.sort_values('DEST') #sort by destination
dest_airport_df['PERCENTAGE'] = ''

for index, row in dest_airport_df.iterrows():
    tot = flight_dest_totals.loc[flight_dest_totals.DEST==row.DEST].TOTAL.values #get t
    val = (row.COUNT/tot * 100)
    dest_airport_df.at[index, 'PERCENTAGE'] = round(val[0].astype(float),2) #calulate the

dest_airport_df.head(10)
dest_airport_df = dest_airport_df.sort_values('PERCENTAGE', ascending=False) #sort by perc

#Add the airport name from the airport_data_df and add as a new column to the dest_airpo
dest_airport_df=pd.merge(dest_airport_df, airport_data_df, how='left', left_on='DEST', r
dest_airport_df.rename(columns={'Description':'DEST_AIRPORT_NAME'}, inplace=True)
del dest_airport_df['Code']

new = dest_airport_df.DEST_AIRPORT_NAME.str.split(":", n = 1, expand = True)
dest_airport_df["DEST_AIRPORT_NAME"] = new[1]
dest_airport_df.head()
```

```
Out[23]:
```


	DEST	STATUS	COUNT	PERCENTAGE	DEST_AIRPORT_NAME
0	GST	On-Time	12	100.0	Gustavus Airport
1	STC	On-Time	1	100.0	St. Cloud Regional
2	PPG	Delayed	3	100.0	Pago Pago International
3	TWF	On-Time	31	96.88	Joslin Field - Magic Valley Regional
4	PIH	On-Time	30	96.77	Pocatello Regional

Bar chart for Destination Airports with most delays

```
In [24]: fig = px.bar(dest_airport_df[dest_airport_df.STATUS=="Delayed"], x="DEST_AIRPORT_NAME",
                    title="Destination Airport with most Delays",
                    text=dest_airport_df[dest_airport_df.STATUS=="Delayed"].PERCENTAGE.apply(la
                    labels=dict(DEST_AIRPORT_NAME="Destination Airport", PERCENTAGE="Percentage
fig.update_xaxes(tickangle=80)
```

```
fig.update_layout(autosize=False,width=900, height=700)
fig.show()
```

Destination Airport with most Delays



Updating Destination name for PSC

```
In [25]: dest_airport_df[dest_airport_df.DEST_AIRPORT_NAME.str.contains('Tri Cities')]
dest_airport_df.loc[dest_airport_df["DEST"] == "PSC", "DEST_AIRPORT_NAME"] = 'Tri Cities'
dest_airport_df[dest_airport_df.DEST_AIRPORT_NAME.str.contains('Tri Cities')]
```

	DEST	STATUS	COUNT	PERCENTAGE	DEST_AIRPORT_NAME
40	PSC	On-Time	439	88.15	Tri Cities(PSC)
125	TRI	On-Time	310	83.56	Tri Cities
610	TRI	Delayed	57	15.36	Tri Cities
680	PSC	Delayed	59	11.85	Tri Cities(PSC)
985	TRI	Cancelled	4	1.08	Tri Cities

Since the chart has many airports to fit, filtering the list to get the top 10 destination airports with most delays

```
In [26]: top_10_dest_delay_airports = dest_airport_df[dest_airport_df.STATUS=='Delayed'].head(10)
top_10_dest_delay_airports
```


Out[26]:

	DEST	STATUS	COUNT	PERCENTAGE	DEST_AIRPORT_NAME	
	2	PPG	Delayed	3	100.0	Pago Pago International
368	PGD	Delayed	212	46.9		Punta Gorda Airport
369	PSE	Delayed	42	45.16		Mercedita
372	SMX	Delayed	4	40.0	Santa Maria Public/Capt. G. Allan Hancock Field	
373	PQI	Delayed	20	40.0		Presque Isle International
374	PSM	Delayed	10	38.46		Portsmouth International at Pease
375	EWR	Delayed	5097	37.31		Newark Liberty International
376	BKG	Delayed	3	33.33		Branson Airport
377	SCK	Delayed	15	32.61		Stockton Metro
378	USA	Delayed	24	32.43		Concord Padgett Regional

Bar chart for Destination Airprot with most delays

```
In [27]: fig = px.bar(top_10_dest_delay_airports[top_10_dest_delay_airports.STATUS=="Delayed"], x
              title="Top 10 Destination Airport with most Delays",
              text=top_10_dest_delay_airports[top_10_dest_delay_airports.STATUS=="Delayed",
              labels=dict(DEST_AIRPORT_NAME="Destination Airport", PERCENTAGE="Percentage")
fig.update_xaxes(tickangle=80)
fig.update_layout(autosize=False,width=900, height=700)
fig.show()
```

Top 10 Destination Airport with most Delays






All flights flying into Pago Pago Internation airport hasare delayed.

Histogram for Overall cancellations by cancellation reason

```
In [28]: #Using CANCELLED==1 to filter the dataframe for only cancelled rows.
fig = px.histogram(flight_data_df[flight_data_df.CANCELLED==1], x="CANCELLATION_REASON",
                  title="Number of Cancellation by Reasons",
                  labels=dict(CANCELLATION_REASON="Cancellation Reason"))
fig.show()
```

Number of Cancellation by Reasons



From the chart, we can see that most cancellations in May'22 were due to carriers followed by weather

MILESTONE 2 - Data Preparation

Dataframe at this time has most of the required features.

```
In [29]: flight_data_df.columns
```

```
Out[29]: Index(['YEAR', 'QUARTER', 'MONTH', 'DAY_OF_MONTH', 'DAY_OF_WEEK', 'FL_DATE',  
          'MKT_UNIQUE_CARRIER', 'OP_UNIQUE_CARRIER', 'ORIGIN_AIRPORT_ID',  
          'ORIGIN', 'ORIGIN_CITY_NAME', 'ORIGIN_STATE_ABR', 'ORIGIN_STATE_NM',  
          'ORIGIN_WAC', 'DEST_AIRPORT_ID', 'DEST', 'DEST_CITY_NAME',  
          'DEST_STATE_ABR', 'DEST_STATE_NM', 'DEST_WAC', 'DEP_DELAY',  
          'DEP_DELAY_NEW', 'TAXI_OUT', 'TAXI_IN', 'ARR_TIME', 'ARR_DELAY',  
          'ARR_DELAY_NEW', 'CANCELLED', 'CANCELLATION_CODE', 'DIVERTED',  
          'ACTUAL_ELAPSED_TIME', 'AIR_TIME', 'FLIGHTS', 'DISTANCE',  
          'CARRIER_DELAY', 'WEATHER_DELAY', 'NAS_DELAY', 'SECURITY_DELAY',  
          'LATE_AIRCRAFT_DELAY', 'CANCELLATION_REASON', 'STATUS', 'ARR_DELAYED',  
          'DELAY_REASON'],  
          dtype='object')
```

1. Drop any features that are not useful for your model building and explain why they are not useful.

Dropping null rows was performed in Milestone 1 - Data Transformation (Step 1). Some additional features that can be dropped are as follows.

i. Dropping the year, month, day, day of month as these details are in the FL_DATE feature which is in a DateTime format.

```
In [30]: flight_data_df.drop(['YEAR', 'QUARTER', 'MONTH'], axis=1, inplace=True)
```

```
In [31]: flight_data_df.head(5)
```

```
Out[31]:
```

	DAY_OF_MONTH	DAY_OF_WEEK	FL_DATE	MKT_UNIQUE_CARRIER	OP_UNIQUE_CARRIER	ORIGIN_AIRPORT_ID
0	1	7	5/1/2022 12:00:00 AM	AA	AA	10140
1	1	7	5/1/2022 12:00:00 AM	AA	AA	10140
2	1	7	5/1/2022 12:00:00 AM	AA	AA	10140
3	1	7	5/1/2022 12:00:00 AM	AA	AA	10140
4	1	7	5/1/2022 12:00:00 AM	AA	AA	10140

5 rows × 40 columns

ii. Dropping Origin Airport ID, Destination Airport ID, Origin_WAC, DEST_WAC as these are not significant for this project.

```
In [32]: flight_data_df.drop(['ORIGIN_WAC', 'DEST_WAC', 'ORIGIN_AIRPORT_ID', 'DEST_AIRPORT_ID'],
```

```
In [33]: flight_data_df.columns
```

```
Out[33]: Index(['DAY_OF_MONTH', 'DAY_OF_WEEK', 'FL_DATE', 'MKT_UNIQUE_CARRIER',  
        'OP_UNIQUE_CARRIER', 'ORIGIN', 'ORIGIN_CITY_NAME', 'ORIGIN_STATE_ABR',  
        'ORIGIN_STATE_NM', 'DEST', 'DEST_CITY_NAME', 'DEST_STATE_ABR',  
        'DEST_STATE_NM', 'DEP_DELAY', 'DEP_DELAY_NEW', 'TAXI_OUT', 'TAXI_IN',  
        'ARR_TIME', 'ARR_DELAY', 'ARR_DELAY_NEW', 'CANCELLED',  
        'CANCELLATION_CODE', 'DIVERTED', 'ACTUAL_ELAPSED_TIME', 'AIR_TIME',  
        'FLIGHTS', 'DISTANCE', 'CARRIER_DELAY', 'WEATHER_DELAY', 'NAS_DELAY',  
        'SECURITY_DELAY', 'LATE_AIRCRAFT_DELAY', 'CANCELLATION_REASON',  
        'STATUS', 'ARR_DELAYED', 'DELAY_REASON'],  
        dtype='object')
```

2. Perform any data extraction/selection steps.

Most of the data extraction and selection steps are already performed in Milestone 1 before plotting. I will update this section should there be any additional extraction/selection steps required.

3. Transform features if necessary.

i. Replacing values in a column

Day of week is mentioned as numbers, updating numbers to days of week.

```
In [34]: flight_data_df.DAY_OF_WEEK = np.where(flight_data_df.DAY_OF_WEEK==1, 'Sunday',  
        np.where(flight_data_df.DAY_OF_WEEK==2, 'Monday',  
        np.where(flight_data_df.DAY_OF_WEEK==3, 'Tuesd  
        np.where(flight_data_df.DAY_OF_WEEK==  
        np.where(flight_data_df.DAY_  
        np.where(flight_dat  
        np.where(f  
flight_data_df.groupby(['DAY_OF_WEEK'])['DAY_OF_WEEK'].count().sort_index()
```

```
Out[34]: DAY_OF_WEEK  
Friday      68726  
Monday      94514  
Sunday     101013  
Thursday    80976  
Tuesday     76567  
Wednesday  179765  
Name: DAY_OF_WEEK, dtype: int64
```

Arrival and departure delays in the '*_New' column for flights departing/arriving earlier than schedule are updated to 0. For this project we are considering flights arriving 15 minutes or later as delayed. Updating arr_delay to 0 for 15 minutes or less.

```
In [35]: flight_data_df.loc[flight_data_df.ARR_DELAY<=15, 'ARR_DELAY'] = 0  
flight_data_df.ARR_DELAY.unique()
```

```
Out[35]: array([  0.,  17.,  20., ..., 1830.,  658.,  651.])
```

4. Engineer new useful features.

Features such as DELAY_REASON, ARR_DELAYED, CANCELLATION_REASON and STATUS were engineered and created in Milestone 1, data transformation section. These features were required for plotting.

5. Deal with missing data (do not just drop rows or columns without justifying this).

```
In [36]: flight_data_df_null = flight_data_df.isnull().sum() / len(flight_data_df) #Calculate % o
```



```

flight_data_df_null
Out[36]: DAY_OF_MONTH      0.000000
          DAY_OF_WEEK      0.000000
          FL_DATE          0.000000
          MKT_UNIQUE_CARRIER 0.000000
          OP_UNIQUE_CARRIER 0.000000
          ORIGIN           0.000000
          ORIGIN_CITY_NAME 0.000000
          ORIGIN_STATE_ABR 0.000000
          ORIGIN_STATE_NM  0.000000
          DEST            0.000000
          DEST_CITY_NAME  0.000000
          DEST_STATE_ABR  0.000000
          DEST_STATE_NM   0.000000
          DEP_DELAY        0.000000
          DEP_DELAY_NEW    0.016958
          TAXI_OUT         0.017551
          TAXI_IN          0.017902
          ARR_TIME         0.017902
          ARR_DELAY        0.000000
          ARR_DELAY_NEW    0.020256
          CANCELLED        0.000000
          CANCELLATION_CODE 0.000000
          DIVERTED         0.000000
          ACTUAL_ELAPSED_TIME 0.020256
          AIR_TIME         0.020256
          FLIGHTS          0.000000
          DISTANCE         0.000000
          CARRIER_DELAY   0.000000
          WEATHER_DELAY    0.000000
          NAS_DELAY        0.000000
          SECURITY_DELAY   0.000000
          LATE_AIRCRAFT_DELAY 0.000000
          CANCELLATION_REASON 0.000000
          STATUS           0.000000
          ARR_DELAYED      0.000000
          DELAY_REASON      0.000000
          dtype: float64

```

```

In [37]: #Look for any features with over 40% missing data
missing_features = flight_data_df_null[flight_data_df_null > 0.40].index #Identify column
missing_features

```

```

Out[37]: Index([], dtype='object')

```

There are no features with missing data over 40%.

6. Create dummy variables if necessary.

At this point, I don't believe I need dummy variables. Will revisit this section based on outcomes from Model creations.

Conclusion

It appears we have enough information at this time to apply different models on the dataframe to be able to predict a flights performance. From the different charts, we can also see the best performing carriers, airports with most delays for arrivals and departures and reasons for cancellations.

On further analysis, it appears we do not need any external data at this time for the model prediction. I target on predicting which airline and/or airport are more likely to be delayed based on the arrival delay feature.

