

Assignment: ASSIGNMENT 1

Name: Ramani, Aarti

Date: 2022-12-10

```
## Create a numeric vector with the values of 3, 2, 1 using the `c()` function
## Assign the value to a variable named `num_vector`
## Print the vector
num_vector <- c(3,2,1)
num_vector
```

```
## [1] 3 2 1
```

```
## Create a character vector with the values of "three", "two", "one" "using the `c()` function
## Assign the value to a variable named `char_vector`
## Print the vector
char_vector <- c("three", "two", "one")
char_vector
```

```
## [1] "three" "two"    "one"
```

```
## Create a vector called `week1_sleep` representing how many hours slept each night of the week
## Use the values 6.1, 8.8, 7.7, 6.4, 6.2, 6.9, 6.6
week1_sleep <- c(6.1, 8.8, 7.7, 6.4, 6.2, 6.9, 6.6)

## Display the amount of sleep on Tuesday of week 1 by selecting the variable index
week1_sleep[3]
```

```
## [1] 7.7
```

```
## Create a vector called `week1_sleep_weekdays`
## Assign the weekday values using indice slicing
week1_sleep_weekdays <- week1_sleep[2:6]
```

```
## Add the total hours slept in week one using the `sum` function
## Assign the value to variable `total_sleep_week1`
total_sleep_week1 <- sum(week1_sleep)
```

```
## Create a vector called `week2_sleep` representing how many hours slept each night of the week
## Use the values 7.1, 7.4, 7.9, 6.5, 8.1, 8.2, 8.9
week2_sleep <- c(7.1, 7.4, 7.9, 6.5, 8.1, 8.2, 8.9)
```

```
## Add the total hours slept in week two using the sum function
## Assign the value to variable `total_sleep_week2`
total_sleep_week2 <- sum(week2_sleep)
```

```
## Determine if the total sleep in week 1 is less than week 2 by using the < operator
total_sleep_week1 < total_sleep_week2
```

```
## [1] TRUE
```

```
## Calculate the mean hours slept in week 1 using the `mean()` function
mean(week1_sleep)
```

```
## [1] 6.957143
```

```
## Create a vector called `days` containing the days of the week.
```

```
## Start with Sunday and end with Saturday
```

```
days <- c("Sunday", "Monday", "Tuesday", "Wednesday", "Thursday", "Friday", "Saturday")
```

```
## Assign the names of each day to `week1_sleep` and `week2_sleep` using the `names` function and `days`
```

```
names(week1_sleep) <- days
```

```
names(week2_sleep) <- days
```

```
## Display the amount of sleep on Tuesday of week 1 by selecting the variable name
week1_sleep["Tuesday"]
```

```
## Tuesday
```

```
##      7.7
```

```
## Create vector called weekdays from the days vector
```

```
weekdays <- days[2:6]
```

```
## Create vector called weekends containing Sunday and Saturday
```

```
weekends <- days[c(1,7)]
```

```
## Calculate the mean about sleep on weekdays for each week
```

```
## Assign the values to weekdays1_mean and weekdays2_mean
```

```
weekdays1_mean <- mean(week1_sleep[weekdays])
```

```
weekdays2_mean <- mean(week2_sleep[weekdays])
```

```
## Using the weekdays1_mean and weekdays2_mean variables,
```

```
## see if weekdays1_mean is greater than weekdays2_mean using the `>` operator
```

```
weekdays1_mean > weekdays2_mean
```

```
## [1] FALSE
```

```
## Determine how many days in week 1 had over 8 hours of sleep using the `>` operator
```

```
days_over_8 = paste('Number of days with over 8 hours of sleep = ',length(week1_sleep[week1_sleep > 8]))
days_over_8
```

```
## [1] "Number of days with over 8 hours of sleep = 1"
```

```
week1_sleep > 8
```

```
##      Sunday      Monday      Tuesday      Wednesday      Thursday      Friday      Saturday
```

```
##      FALSE       TRUE       FALSE       FALSE       FALSE       FALSE       FALSE
```

```
## Create a matrix from the following three vectors
student01 <- c(100.0, 87.1)
student02 <- c(77.2, 88.9)
student03 <- c(66.3, 87.9)

students_combined <- c(student01, student02, student03)
grades <- matrix(students_combined, byrow = TRUE, nrow = 3)

## Add a new student row with `rbind()`
student04 <- c(95.2, 94.1)
grades <- rbind(grades, student04)

## Add a new assignment column with `cbind()`
assignment04 <- c(92.1, 84.3, 75.1, 97.8)
grades <- cbind(grades, assignment04)

## Add the following names to columns and rows using `rownames()` and `colnames()`
assignments <- c("Assignment 1", "Assignment 2", "Assignment 3")
students <- c("Florinda Baird", "Jinny Foss", "Lou Purvis", "Nola Maloney")

rownames(grades) <- students
colnames(grades) <- assignments

## Total points for each assignment using `colSums()`
colSums(grades)
```

```
## Assignment 1 Assignment 2 Assignment 3
##          338.7          358.0          349.3
```

```
## Total points for each student using `rowSums()`
rowSums(grades)
```

```
## Florinda Baird      Jinny Foss      Lou Purvis      Nola Maloney
##          279.2          250.4          229.3          287.1
```

```
## Matrix with 10% and add it to grades
weighted_grades <- grades * 0.1 + grades

## Create a factor of book genres using the genres_vector
## Assign the factor vector to factor_genre_vector
genres_vector <- c("Fantasy", "Sci-Fi", "Sci-Fi", "Mystery", "Sci-Fi", "Fantasy")
factor_genre_vector <- factor(genres_vector)

## Use the `summary()` function to print a summary of `factor_genre_vector`
summary(factor_genre_vector)
```

```
## Fantasy Mystery Sci-Fi
##          2          1          3
```

```
## Create ordered factor of book recommendations using the recommendations_vector
## `no` is the lowest and `yes` is the highest
recommendations_vector <- c("neutral", "no", "no", "neutral", "yes")
factor_recommendations_vector <- factor(
  recommendations_vector,
  ordered = TRUE,
  levels = c("no", "neutral", "yes")
)
factor_recommendations_vector
```

```
## [1] neutral no      no      neutral yes
## Levels: no < neutral < yes
```

```
## Use the `summary()` function to print a summary of `factor_recommendations_vector`
summary(factor_recommendations_vector)
```

```
##      no neutral      yes
##      2       2       1
```

```
## Using the built-in `mtcars` dataset, view the first few rows using the `head()` function
head(mtcars)
```

```
##      mpg cyl disp  hp drat   wt  qsec vs am gear carb
## Mazda RX4      21.0   6  160 110 3.90 2.620 16.46  0  1    4    4
## Mazda RX4 Wag  21.0   6  160 110 3.90 2.875 17.02  0  1    4    4
## Datsun 710     22.8   4  108  93 3.85 2.320 18.61  1  1    4    1
## Hornet 4 Drive  21.4   6  258 110 3.08 3.215 19.44  1  0    3    1
## Hornet Sportabout 18.7   8  360 175 3.15 3.440 17.02  0  0    3    2
## Valiant        18.1   6  225 105 2.76 3.460 20.22  1  0    3    1
```

```
## Using the built-in mtcars dataset, view the last few rows using the `tail()` function
tail(mtcars)
```

```
##      mpg cyl disp  hp drat   wt  qsec vs am gear carb
## Porsche 914-2  26.0   4 120.3  91 4.43 2.140 16.7  0  1    5    2
## Lotus Europa   30.4   4  95.1 113 3.77 1.513 16.9  1  1    5    2
## Ford Pantera L 15.8   8 351.0 264 4.22 3.170 14.5  0  1    5    4
## Ferrari Dino   19.7   6 145.0 175 3.62 2.770 15.5  0  1    5    6
## Maserati Bora   15.0   8 301.0 335 3.54 3.570 14.6  0  1    5    8
## Volvo 142E     21.4   4 121.0 109 4.11 2.780 18.6  1  1    4    2
```

```
## Create a dataframe called characters_df using the following information from LOTR
name <- c("Aragon", "Bilbo", "Frodo", "Galadriel", "Sam", "Gandalf", "Legolas", "Sauron", "Gollum")
race <- c("Men", "Hobbit", "Hobbit", "Elf", "Hobbit", "Maia", "Elf", "Maia", "Hobbit")
in_fellowship <- c(TRUE, FALSE, TRUE, FALSE, TRUE, TRUE, TRUE, FALSE, FALSE)
ring_bearer <- c(FALSE, TRUE, TRUE, FALSE, TRUE, TRUE, FALSE, TRUE, TRUE)
age <- c(88, 129, 51, 7000, 36, 2019, 2931, 7052, 589)

characters_df <- data.frame(name, race, in_fellowship, ring_bearer, age)
```

```
## Sorting the characters_df by age using the order function and assign the result to the sorted_charac
```

```
sorted_characters_df <- characters_df[order(age),]
```

```
## Use `head()` to output the first few rows of `sorted_characters_df`  
head(sorted_characters_df)
```

```
##      name  race in_fellowship ring_bearer  age  
## 5    Sam Hobbit          TRUE          TRUE   36  
## 3  Frodo Hobbit          TRUE          TRUE   51  
## 1  Aragon   Men          TRUE         FALSE   88  
## 2   Bilbo Hobbit        FALSE          TRUE  129  
## 9   Gollum Hobbit        FALSE          TRUE  589  
## 6 Gandalf  Maia          TRUE          TRUE 2019
```

```
## Select all of the ring bearers from the dataframe and assign it to ringbearers_df  
ringbearers_df <- characters_df[characters_df$ring_bearer == 1,]
```

```
## Use `head()` to output the first few rows of `ringbearers_df`  
head(ringbearers_df)
```

```
##      name  race in_fellowship ring_bearer  age  
## 2   Bilbo Hobbit        FALSE          TRUE  129  
## 3  Frodo Hobbit          TRUE          TRUE   51  
## 5    Sam Hobbit          TRUE          TRUE   36  
## 6 Gandalf  Maia          TRUE          TRUE 2019  
## 8   Sauron  Maia        FALSE          TRUE 7052  
## 9   Gollum Hobbit        FALSE          TRUE  589
```