

4.2.9

EE25BTECH11006 - ADUDOTLA SRIVIDYA

september 12,2025

Question

Find the coordinates of the point which divides the line segment joining $A(1, -2, 3)$, $B(3, 4, -5)$ in the ratio

- ☐ 2 : 3 internally
- ☐ 2 : 3 externally

Given Information

Given vector **A**:

$$\begin{bmatrix} 1 \\ -2 \\ 3 \end{bmatrix} \quad (1)$$

Given vector **B**:

$$\begin{bmatrix} 3 \\ 4 \\ -5 \end{bmatrix} \quad (2)$$

Required Formulae

Internal division:

$$P = \frac{m\mathbf{B} + n\mathbf{A}}{m + n} \quad (3)$$

External division:

$$Q = \frac{m\mathbf{B} - n\mathbf{A}}{m - n} \quad (4)$$

$$P = \frac{2 \begin{bmatrix} 3 \\ 4 \\ -5 \end{bmatrix} + 3 \begin{bmatrix} 1 \\ -2 \\ 3 \end{bmatrix}}{5} = \frac{\begin{bmatrix} 6 + 3 \\ 8 - 6 \\ -10 + 9 \end{bmatrix}}{5} = \begin{bmatrix} -\frac{9}{5} \\ \frac{2}{5} \\ \frac{-1}{5} \end{bmatrix} \quad (5)$$

$$Q = \frac{2 \begin{bmatrix} 1 \\ -4 \\ 6 \end{bmatrix} - 3 \begin{bmatrix} -2 \\ 3 \\ 5 \end{bmatrix}}{2 - 3} = \frac{\begin{bmatrix} 2 + 6 \\ -8 - 9 \\ 12 - 15 \end{bmatrix}}{-1} = \begin{bmatrix} -8 \\ 17 \\ 3 \end{bmatrix} \quad (6)$$

Python Code-Plot

```
import matplotlib.pyplot as plt
from mpl_toolkits.mplot3d import Axes3D

A = (1, -2, 3)
B = (3, 4, -5)

P = (
    (2*B[0] + 3*A[0]) / 5,
    (2*B[1] + 3*A[1]) / 5,
    (2*B[2] + 3*A[2]) / 5
)

Q = (
    (2*B[0] - 3*A[0]) / (2-3),
    (2*B[1] - 3*A[1]) / (2-3),
    (2*B[2] - 3*A[2]) / (2-3)
)

print("Internal Division Point:", P)
```

Python Code-Plot

```
fig = plt.figure(figsize=(8,8))
ax = fig.add_subplot(111, projection='3d')

ax.plot([A[0], B[0]], [A[1], B[1]], [A[2], B[2]], color='blue')

def plot_point(pt, label, color):
    ax.scatter(*pt, color=color, s=60)
    ax.text(pt[0], pt[1], pt[2], f"{label}{pt}", fontsize=10)

plot_point(A, "A", "red")
plot_point(B, "B", "red")
plot_point(P, "P", "green")
plot_point(Q, "Q", "purple")

ax.set_xlabel('X-axis')
ax.set_ylabel('Y-axis')
ax.set_zlabel('Z-axis')
ax.set_title('3D Division of Line Segment')
```


Python Code-Plot

```
ax.set_xlim(-4, 4)
ax.set_ylim(-15, 5)
ax.set_zlim(-5, 19)

plt.savefig("Figs/graph.png")
plt.show()
```

Python ctypes Call

```
import ctypes

lib = ctypes.CDLL('./mat1.so')

lib.sectionFormula.argtypes = [
    ctypes.POINTER(ctypes.c_float),
    ctypes.POINTER(ctypes.c_float),
    ctypes.c_float,
    ctypes.c_float,
    ctypes.POINTER(ctypes.c_float)
]
```

Python ctypes Call

```
lib.sectionFormula.restype = None

lib.sectionFormulaExternal.argtypes = [
    ctypes.POINTER(ctypes.c_float),
    ctypes.POINTER(ctypes.c_float),
    ctypes.c_float,
    ctypes.c_float,
    ctypes.POINTER(ctypes.c_float)
]

lib.sectionFormulaExternal.restype = None

p1 = (ctypes.c_float * 3)(1.0, -2.0, 3.0)
p2 = (ctypes.c_float * 3)(3.0, 4.0, -5.0)

res_internal = (ctypes.c_float * 3)()
res_external = (ctypes.c_float * 3)()

m = 2.0
```

Python ctypes Call

```
1 lib.sectionFormula(p1, p2, m, n, res_internal)
2 lib.sectionFormulaExternal(p1, p2, m, n, res_external)
3
4 print("Internal division (2:3): [{:.2f}, {:.2f}, {:.2f}]"
5       .format(
6         res_internal[0], res_internal[1], res_internal[2]
7       ))
8
9 print("External division (2:3): [{:.2f}, {:.2f}, {:.2f}]"
10      .format(
11        res_external[0], res_external[1], res_external[2]
12      ))
```

```
void sectionFormula(float p1[3], float p2[3], float m, float n,
float res[3]) {
    res[0] = (m * p2[0] + n * p1[0]) / (m + n);
    res[1] = (m * p2[1] + n * p1[1]) / (m + n);
    res[2] = (m * p2[2] + n * p1[2]) / (m + n);
}

void sectionFormulaExternal(float p1[3], float p2[3], float m,
float n, float res[3]) {
    res[0] = (m * p2[0] - n * p1[0]) / (m - n);
    res[1] = (m * p2[1] - n * p1[1]) / (m - n);
    res[2] = (m * p2[2] - n * p1[2]) / (m - n);
}
```

3D Division of Line Segment

