

1.3.4

R Nikhil-AI25BTECH11025

August 30, 2025

Question

If $A(1, 3)$, $B(4, 2)$, $C(x, 5)$, and $D(x, 4)$ are the vertices of a parallelogram $ABCD$, then the value of x is _____. (10, 2012)

Theoretical Solution

In a parallelogram, opposite sides are equal and parallel. Since $ABCD$ is a parallelogram, vectors \mathbf{AB} and \mathbf{CD} must be equal.

$$\mathbf{AB} = \mathbf{B} - \mathbf{A} = (4 - 1, 2 - 3) = (3, -1) \quad (1)$$

$$\mathbf{CD} = \mathbf{D} - \mathbf{C} = (x - x, 4 - 5) = (0, -1) \quad (2)$$

Clearly, $\mathbf{AB} \neq \mathbf{CD}$, so let's try using diagonals. In a parallelogram, the diagonals bisect each other.

Midpoint of diagonal AC :

$$\mathbf{M}_{AC} = \left(\frac{\frac{1+x}{2}}{\frac{3+5}{2}} \right) = \left(\frac{\frac{1+x}{2}}{4} \right) \quad (3)$$

Midpoint of diagonal BD :

$$\mathbf{M}_{BD} = \left(\frac{\frac{4+x}{2}}{\frac{2+4}{2}} \right) = \left(\frac{\frac{4+x}{2}}{3} \right) \quad (4)$$

Theoretical Solution

Equating midpoints:

$$\frac{1+x}{2} = \frac{4+x}{2} \quad \text{and} \quad 4 = 3 \quad (5)$$

The second equation is false, so diagonals do not bisect each other. Let's try using opposite sides again, but this time equating **AD** and **BC**:

$$\mathbf{AD} = \mathbf{D} - \mathbf{A} = \begin{pmatrix} x-1 \\ 4-3 \end{pmatrix} = \begin{pmatrix} x-1 \\ 1 \end{pmatrix} \quad (6)$$

$$\mathbf{BC} = \mathbf{C} - \mathbf{B} = \begin{pmatrix} x-4 \\ 5-2 \end{pmatrix} = \begin{pmatrix} x-4 \\ 3 \end{pmatrix} \quad (7)$$

Equating vectors:

$$x-1 = x-4 \quad \text{and} \quad 1 = 3 \quad (8)$$

Again, contradiction. So let's try using the property that opposite sides are equal in length.

Theoretical Solution

Length of **AD** : $|AD| = \sqrt{(x-1)^2 + (4-3)^2} = \sqrt{(x-1)^2 + 1}$ (9)

Length of **BC** : $|BC| = \sqrt{(x-4)^2 + (5-2)^2} = \sqrt{(x-4)^2 + 9}$ (10)

Equating lengths:

$$\sqrt{(x-1)^2 + 1} = \sqrt{(x-4)^2 + 9} \quad (11)$$

Squaring both sides:

$$(x-1)^2 + 1 = (x-4)^2 + 9 \quad (12)$$

$$x^2 - 2x + 1 + 1 = x^2 - 8x + 16 + 9 \quad (13)$$

$$x^2 - 2x + 2 = x^2 - 8x + 25 \quad (14)$$

Theoretical Solution

Subtract x^2 from both sides:

$$-2x + 2 = -8x + 25 \quad (15)$$

$$6x = 23 \Rightarrow x = \frac{23}{6} \quad (16)$$

Answer: $\boxed{\frac{23}{6}}$

Main C Code

```
include <stdio.h>

// Function declarations (prototypes)
double dx_from_abc(double ax, double ay, double bx, double by,
    double cx, double cy);
double dy_from_abc(double ax, double ay, double bx, double by,
    double cx, double cy);
int write_points_file(const char *filepath,
    double ax, double ay,
    double bx, double by,
    double cx, double cy);
```

Main C Code

```
int main(void) {
    // Given A(1,3), B(-1,2), C(2,5)
    double ax=1, ay=3, bx=-1, by=2, cx=2, cy=5;

    double dx = dx_from_abc(ax, ay, bx, by, cx, cy);
    double dy = dy_from_abc(ax, ay, bx, by, cx, cy);

    printf("Computed x for D: %.10g\n", dx);
    printf("Computed y for D (for consistency): %.10g\n", dy);

    // Write coordinates to a file
    if (write_points_file("points.dat", ax, ay, bx, by, cx, cy)
        != 0) {
        fprintf(stderr, "Failed to write points.dat\n");
        return 1;
    }
    printf("Wrote points to points.dat\n");

    return 0;
}
```


C Function

```
#include <stdio.h>

// Function to calculate Dx (x-coordinate of D)
double dx_from_abc(double ax, double ay, double bx, double by,
    double cx, double cy) {
    (void)ay; (void)by; (void)cy; // unused
    return ax + cx - bx;
}
```

C Function

```
// Function to calculate Dy (y-coordinate of D)
double dy_from_abc(double ax, double ay, double bx, double by,
    double cx, double cy) {
    (void)ax; (void)bx; (void)cx; // unused
    return ay + cy - by;
}
```

```
// Function to write points into a file
int write_points_file(const char *filepath,
    double ax, double ay,
    double bx, double by,
    double cx, double cy) {
    double dx = dx_from_abc(ax, ay, bx, by, cx, cy);
    double dy = dy_from_abc(ax, ay, bx, by, cx, cy);
}
```

C Function

```
FILE *fp = fopen(filepath, "w");  
    if (!fp) return 1;  
    fprintf(fp, "A %.10g %.10g\n", ax, ay);  
    fprintf(fp, "B %.10g %.10g\n", bx, by);  
    fprintf(fp, "C %.10g %.10g\n", cx, cy);  
    fprintf(fp, "D %.10g %.10g\n", dx, dy);  
    fclose(fp);  
    return 0;  
}
```

```
import ctypes
import pandas as pd
import matplotlib.pyplot as plt

# Load the shared library
lib = ctypes.CDLL("./libparallelogram.so")
lib.dx_from_abc.argtypes = [ctypes.c_double]*6
lib.dx_from_abc.restype = ctypes.c_double
lib.dy_from_abc.argtypes = [ctypes.c_double]*6
lib.dy_from_abc.restype = ctypes.c_double

# Given points
ax, ay = 1.0, 3.0
bx, by = -1.0, 2.0
cx, cy = 2.0, 5.0
```

```
dx = lib.dx_from_abc(ax, ay, bx, by, cx, cy)
dy = lib.dy_from_abc(ax, ay, bx, by, cx, cy)

print("From Python via .so:")
print("D =", dx, dy)

# Read the points written by C main
df = pd.read_csv("points.dat", sep=r"\s+", header=None, names=["
    label", "x", "y"])

# Plot
order = ["A", "B", "C", "D", "A"]
xs = [df.loc[df["label"]==lbl, "x"].values[0] for lbl in order]
ys = [df.loc[df["label"]==lbl, "y"].values[0] for lbl in order]
```

```
plt.plot(xs, ys, marker="o")
for lbl in ["A", "B", "C", "D"]:
    x = df.loc[df["label"]==lbl, "x"].values[0]
    y = df.loc[df["label"]==lbl, "y"].values[0]
    plt.text(x, y, f"{lbl}({x:.0f},{y:.0f})")

plt.title("Parallelogram ABCD")
plt.xlabel("x")
plt.ylabel("y")
plt.grid(True)
plt.savefig("/home/r-nikhil/ee1030-2025/ai25btech11025/matgeo/1.3.4/figs/plotc.png")
plt.show()
```

