Get Expired Historical Candle Data Plus

GET

```
/expired-instruments/historical-candle/:expired_instrument_key/:interval/:to_date/:from_date
```

This API extends the functionality of the existing Get Historical Candle Data API by allowing users to query data for expired contracts.

This API is particularly useful for traders and analysts who need to analyze past performance and trends of expired contracts.

It provides historical Open, High, Low, Close (OHLC) data for expired contracts, available across multiple time intervals including: `1minute`, `3minute`, `5minute`, `15minute`, `30minute` and `day`.

Request

```
curl -X 'GET' 'https://api.upstox.com/v2/expired-instruments/historical-candle/NSE_FO%7CNIFTY22D0117800CE/day/2022-11-30/2022-11-01'
--header 'Content-Type: application/json'
--header 'Accept: application/json'
--header 'Authorization: Bearer {your_access_token}'
```

For additional samples in various languages, please refer to the Sample code section on this page.

Path Parameters

expired_instrument_key

REQUIRED

Required

TYPE

`string`

DESCRIPTION

The unique identifier for the expired financial instrument for which historical data is being queried. This key is combination of normal instrument key and expiry date. The expired_instrument_key key must match the regex pattern specified in the Field Pattern Appendix.

interval

REQUIRED

Required

TYPE

`string`

DESCRIPTION

Specifies the time frame of the candles.
Possible values: `1minute`, `3minute`, `5minute`, `15minute`, `30minute`, `day`.

`to_date`

REQUIRED

Required

TYPE

`string`

DESCRIPTION

The ending date (inclusive) for the historical data range. Format: `YYYY-MM-DD`.

`from_date`

REQUIRED

Required

TYPE

`string`

DESCRIPTION

The starting date for the historical data range. Format: `YYYY-MM-DD`.

Responses

200 4XX

Response Body


```
"candles": [
  [
    "2022-11-30T00:00:00+05:30",
    125.35,
    126.8,
    122.1,
    123.45,
    1542678,
    184632
  ],
  [
    "2022-11-29T00:00:00+05:30",
```

```
        123.33,
        1876543,
        195732
      ]
    ]
  }
}
```

status

TYPE

`string`

DESCRIPTION

A string indicating the outcome of the request. Typically `success` for successful operations.

data

TYPE

`object`

DESCRIPTION

Contains OHLC values for expired contracts across various timeframes.

data.candles

TYPE

`array[]`

DESCRIPTION

Array of candle data, each presented as an array with sequential elements representing trading activity.

data.candle[0]

TYPE

`number`

DESCRIPTION

`Timestamp`: Indicating the start time of the candle's timeframe.

data.candle[1]

TYPE

`number`

DESCRIPTION

`Open`: The opening price of the asset for the given timeframe.

data.candle[2]

TYPE

`number`

DESCRIPTION

`High`: The highest price at which the asset traded during the timeframe.

data.candle[3]

TYPE

`number`

DESCRIPTION

`Low`: The lowest price at which the asset traded during the timeframe.

data.candle[4]

TYPE

`number`

DESCRIPTION

`Close`: The closing price of the asset for the given timeframe.

data.candle[5]

TYPE

`number`

DESCRIPTION

`Volume`: The total amount of the asset that was traded during the timeframe.

data.candle[6]

TYPE

`number`

DESCRIPTION

`Open Interest`: The total number of outstanding derivative contracts, such as options or futures.

Sample Code

Get Historical Candle Data for Expired Instruments

Curl | Python | Node.js | Java | PHP | Python SDK | Node.js SDK | Java SDK

```python
import requests

url = 'https://api.upstox.com/v2/expired-instruments/historical-candle/NSE_FO|73507|24-04-2025/30minute/2025-04-24/2020-02-24'
headers = {
    'Content-Type': 'application/json',
    'Accept': 'application/json',
    'Authorization': 'Bearer {your_access_token}'
}

response = requests.get(url, headers=headers)
```

```python
# Check the response status
if response.status_code == 200:
    # Do something with the response data (e.g., print it)
    print(response.json())
else:
    # Print an error message if the request was not successful
    print(f"Error: {response.status_code} - {response.text}")
```

NOTE

- Before using this API, utilize the Get Expired Option Contracts API or Get Expired Future Contracts API to obtain the `expired_instrument_key` for the expired contracts This key, required as a path parameter, is a combination of the standard instrument key and the expiry date returned by the previously mentioned APIs.
- For Open, High, Low, Close (OHLC) data of an active contracts, use the Historical Candle Data API.