

Aarya Arban

S11-07

Aim: To implement Multithreading

Code:

```
class Hello implements Runnable{
    public void run()
    {
        for(int i=0; i<5; i++)
        {
            System.out.println("hello");
            try{
                Thread.sleep(500);
            }catch(Exception e){
            };
        }
    }
}

class Hi implements Runnable{
    public void run()
    {
        for(int i=0; i<5; i++)
        {
            System.out.println("hi");
            try{
                Thread.sleep(500);
            }
            catch(Exception e){
            };
        }
    }
}
```

```
}  
  
class MultithreadingDemo  
{  
    public static void main(String []args)  
    {  
        Hi obj1 = new Hi();  
        Hello obj2 = new Hello();  
        Thread t1 = new Thread(obj1);  
        Thread t2 = new Thread(obj2);  
        t1.start();  
        t2.start();  
        System.out.println(t1.isAlive());  
        System.out.println(t2.isAlive());  
        try{  
            t1.join();  
        }  
        catch(Exception e){  
        };  
        try{  
            t2.join();  
        }catch(Exception e){  
        };  
        System.out.println(t1.isAlive());  
        System.out.println(t2.isAlive());  
        System.out.println("Bye");  
    }  
}
```

Output:

```
hi  
true  
true
```

hello

hi

hello

hi

hello

hi

hello

hi

hello

false

false

Bye