

Aarya Arban

S11 – 07

Aim: Insert Records to all the tables

Input:

Table 1:

```
mysql> insert into client_master_7 (
```

```
-> Client_no,Name,City,State,Pincode,Bal_due)
```

```
-> values('COOOO1','Ivan Bayross','Bombay','Maharashtra',400054,15000);
```

Query OK, 1 row affected (0.04 sec)

```
mysql> insert into client_master_7 (
```

```
-> Client_no,Name,City,State,Pincode,Bal_due)
```

```
-> values('COOOO2','Vandana Saitwal','Madras','Tamil Nadu',780001,0);
```

Query OK, 1 row affected (0.07 sec)

```
mysql> insert into client_master_7 (
```

```
-> Client_no,Name,City,State,Pincode,Bal_due)
```

```
-> values('COOOO3','Pramada Jaguste','Bombay','Maharashtra',400057,5000);
```

Query OK, 1 row affected (0.04 sec)

```
mysql> insert into client_master_7 (
```

```
-> Client_no,Name,City,State,Pincode,Bal_due)
```

```
-> values('COOOO4','Basu Navindgi','Bombay','Maharashtra',400056,0);
```

Query OK, 1 row affected (0.09 sec)

```
mysql> insert into client_master_7 (
```

```
-> Client_no,Name,City,State,Pincode,Bal_due)
```

```
-> values('COOOO5','Ravi Sreedharan','Delhi',100001,2000);
```

ERROR 1136 (21S01): Column count doesn't match value count at row 1

```
mysql> insert into client_master_7 (  
-> Client_no,Name,City,State,Pincode,Bal_due)  
-> values('COOOO5','Ravi Sreedharan','Delhi',' ',100001,2000);  
Query OK, 1 row affected (0.08 sec)
```

```
mysql> insert into client_master_7 (  
-> Client_no,Name,City,State,Pincode,Bal_due)  
-> values('COOOO6','Rukmini','Bombay','Maharashtra',400050,15000);  
Query OK, 1 row affected (0.06 sec)
```

Table 2:

```
mysql> insert into product_master_7  
-> values('POOOO1','1.44 Floppies',5,'Piece',100,20,525,500);  
Query OK, 1 row affected (0.03 sec)
```

```
mysql> insert into product_master_7  
-> values('PO3453','Monitors',6,'Piece',10,3,12000,11280);  
Query OK, 1 row affected (0.05 sec)
```

```
mysql> insert into product_master_7  
-> values('PO6734','Mouse',5,'Piece',20,5,1050,1000);  
Query OK, 1 row affected (0.03 sec)
```

```
mysql> insert into product_master_7  
-> values('PO7865','1.22 Floppies',5,'Piece',100,20,525,500);  
Query OK, 1 row affected (0.02 sec)
```

```
mysql> insert into product_master_7  
-> values('PO7868','Keyboards',2,'Piece',10,3,3150,3050);  
Query OK, 1 row affected (0.04 sec)
```

```
mysql> insert into product_master_7
```

```
-> values('PO7885','CD Drive',2.5,'Piece',10,3,5250,5100);
```

Query OK, 1 row affected (0.05 sec)

```
mysql> insert into product_master_7
```

```
-> values('PO7965','HDD',4,'Piece',10,3,8400,8000);
```

Query OK, 1 row affected (0.03 sec)

```
mysql> insert into product_master_7
```

```
-> values('PO7975','1.44 Drive',5,'Piece',10,3,1050,1000);
```

Query OK, 1 row affected (0.07 sec)

```
mysql> insert into product_master_7
```

```
-> values('PO8865','1.22 Drive',5,'Piece',2,3,1050,1000);;
```

Query OK, 1 row affected (0.04 sec)

Table 3:

```
insert into salesman_master_7 values('S00001', 'Kiran', 'A/14', 'Worli', 'Bombay', '400002',  
'MAH', 3000,  
100, 50,'Good');
```

```
insert into salesman_master_7 values('S00002', 'Manish', '65', 'Nariman', 'Bombay',  
'400001',  
'MAH', 3000, 200, 100,'Good');
```

```
insert into salesman_master_7 values('S00003', 'Ravi', 'P-7', 'Bandra', 'Bombay', '400032',  
'MAH',  
3000, 200, 100,'Good');
```

```
insert into salesman_master_7 values('S00004', 'Ashish', 'A/5', 'Juhu', 'Bombay', '400044',  
'MAH', 3000,  
200, 150,'Good');
```

Table 4:

```
mysql> insert into sales_order_7
```

```
(S_order_no,S_order_date,Client_no,Salesman_no,Dely_type,Billed_yn,Dely_date,Order_status)
```

```
-> values('O19001','1996-01-12','COOOO1','S00001','F','N','1996-01-20','IP');
```

Query OK, 1 row affected (0.03 sec)

```
mysql> insert into
```

```
sales_order_7(S_order_no,S_order_date,Client_no,Salesman_no,Dely_type,Billed_yn,Dely_
date,Order_status)
```

```
-> values('O19002','1996-01-25','COOOO2','S00002','P','N','1996-01-27','C');
```

Query OK, 1 row affected (0.07 sec)

```
mysql> insert into
```

```
sales_order_7(S_order_no,S_order_date,Client_no,Salesman_no,Dely_type,Billed_yn,Dely_
date,Order_status)
```

```
-> values('O46865','1996-02-18','COOOO3','S00003','F','Y','1996-02-20','F');
```

Query OK, 1 row affected (0.03 sec)

```
mysql> insert into
```

```
sales_order_7(S_order_no,S_order_date,Client_no,Salesman_no,Dely_type,Billed_yn,Dely_
date,Order_status)
```

```
-> values('O19003','1996-04-03','COOOO1','S00001','F','Y','1996-04-07','F');
```

Query OK, 1 row affected (0.04 sec)

```
mysql> insert into
```

```
sales_order_7(S_order_no,S_order_date,Client_no,Salesman_no,Dely_type,Billed_yn,Dely_
date,Order_status)
```

```
-> values('O46866','1996-05-20','COOOO4','S00002','P','N','1996-05-22','C');
```

Query OK, 1 row affected (0.01 sec)

```
mysql> insert into
```

```
sales_order_7(S_order_no,S_order_date,Client_no,Salesman_no,Dely_type,Billed_yn,Dely_
date,Order_status)
```

```
-> values('O10008','1996-05-24','COOOO5','S00004','F','N','1996-05-26','IP');
```

Query OK, 1 row affected (0.03 sec)

Table 5:

```
mysql> insert into sales_order_details_7
```

```
-> values ('O19001', 'POOOO1', 4,4,525);
```

Query OK, 1 row affected (0.03 sec)

```
mysql> insert into sales_order_details_7
```

```
-> values ('O19001', 'PO7965', 2,1,8400);
```

Query OK, 1 row affected (0.03 sec)

```
mysql> insert into sales_order_details_7
```

```
-> values ('O19001', 'PO7885', 2,1,5250);
```

Query OK, 1 row affected (0.04 sec)

```
mysql> insert into sales_order_details_7
```

```
-> values ('O19002', 'POOOO1', 10,0,525);
```

Query OK, 1 row affected (0.04 sec)

```
mysql> insert into sales_order_details_7
```

```
-> values ('O46865', 'PO7868', 3,3,3150);
```

Query OK, 1 row affected (0.01 sec)

```
mysql> insert into sales_order_details_7
```

```
-> values ('O46865', 'PO7885', 3,1,5250);
```

Query OK, 1 row affected (0.02 sec)

```
mysql> insert into sales_order_details_7
```

```
-> values ('O46865', 'POOOO1', 10,10,525);
```

Query OK, 1 row affected (0.01 sec)

```
mysql> insert into sales_order_details_7
-> values ('O46865', 'PO3453', 4,4,1050);
Query OK, 1 row affected (0.02 sec)
```

```
mysql> insert into sales_order_details_7
-> values ('O19003', 'PO3453', 2,2,1050);
Query OK, 1 row affected (0.02 sec)
```

```
mysql> insert into sales_order_details_7
-> values ('O19003', 'PO6734', 1,1,12000);
Query OK, 1 row affected (0.01 sec)
```

```
mysql> insert into sales_order_details_7
-> values ('O46866', 'PO7965', 1,0,8400);
Query OK, 1 row affected (0.01 sec)
```

```
mysql> insert into sales_order_details_7
-> values ('O46866', 'PO7975', 1,0,1050);
Query OK, 1 row affected (0.02 sec)
```

```
mysql> insert into sales_order_details_7
-> values ('O10008', 'POOOO1', 10,5,525);
Query OK, 1 row affected (0.11 sec)
```

```
mysql> insert into sales_order_details_7
-> values ('O10008', 'PO7975', 5,3,1050);
Query OK, 1 row affected (0.03 sec)
```

Table 6:

```
mysql> insert into Challan_Header_7
```

```
-> values ('CH9001', 'O19001', '1995-12-12', 'Y');
```

Query OK, 1 row affected (0.06 sec)

```
mysql> insert into Challan_Header_7
```

```
-> values ('CH6865', 'O46865', '1995-11-12', 'Y');
```

Query OK, 1 row affected (0.01 sec)

```
mysql> insert into Challan_Header_7
```

```
-> values ('CH3965', 'O10008', '1995-11-12', 'Y');
```

Query OK, 1 row affected (0.04 sec)

Table 7:

```
mysql> insert into Challan_details_7
```

```
-> values('CH9001', 'POOOO1', 4);
```

Query OK, 1 row affected (0.04 sec)

```
mysql> insert into Challan_details_7
```

```
-> values('CH9001', 'PO7965', 1);
```

Query OK, 1 row affected (0.04 sec)

```
mysql> insert into Challan_details_7
```

```
-> values('CH6865', 'PO7868', 3);
```

Query OK, 1 row affected (0.01 sec)

```
mysql> insert into Challan_details_7
```

```
-> values('CH6865', 'POOOO1', 10);
```

Query OK, 1 row affected (0.02 sec)

```
mysql> insert into Challan_details_7
```

```
-> values('CH3965', 'POOOO1', 5);
```

Query OK, 1 row affected (0.01 sec)

```
mysql> insert into Challan_details_7
```

```
-> values('CH3965', 'PO7975', 2);
```

Query OK, 1 row affected (0.01 sec)

Output:

Table 1:

```
mysql> select *from client_master_7;
```

Client_no	Name	Address1	Address2	City	State	Pincode	Bal_due
COOOO1	Ivan Bayross	NULL	NULL	Bombay	Maharashtra	400054	15000.00
COOOO2	Vandana Saitwal	NULL	NULL	Madras	Tamil Nadu	780001	0.00
COOOO3	Pramada Jaguste	NULL	NULL	Bombay	Maharashtra	400057	5000.00
COOOO4	Basu Navindgi	NULL	NULL	Bombay	Maharashtra	400056	0.00
COOOO5	Ravi Sreedharan	NULL	NULL	Delhi		100001	2000.00
COOOO6	Rukmini	NULL	NULL	Bombay	Maharashtra	400050	15000.00

6 rows in set (0.00 sec)

Table 2:

```
mysql> select *from product_master_7;
```

Product_no	Description	Profit_percent	Unit_measure	Qty_on_hand	Reorder_lvl	Sell_price	Cost_price
------------	-------------	----------------	--------------	-------------	-------------	------------	------------

PO3453	Monitors		6.00	Piece		10		3		12000.00		11280.00	
PO6734	Mouse		5.00	Piece		20		5		1050.00		1000.00	
PO7865	1.22 Floppies		5.00	Piece		100		20		525.00		500.00	
PO7868	Keyboards		2.00	Piece		10		3		3150.00		3050.00	
PO7885	CD Drive		2.50	Piece		10		3		5250.00		5100.00	
PO7965	HDD		4.00	Piece		10		3		8400.00		8000.00	
PO7975	1.44 Drive		5.00	Piece		10		3		1050.00		1000.00	
PO8865	1.22 Drive		5.00	Piece		2		3		1050.00		1000.00	
PO0001	1.44 Floppies		5.00	Piece		100		20		525.00		500.00	

+-----+-----+-----+-----+-----+-----+-----+-----+

9 rows in set (0.00 sec)

Table 3:

mysql> select *from salesman_master_7;

Salesman_no	Salesman_name	Address1	Address2	City	Pincode	State	Sal_amt	Tgt_to_get	Ytd_sales	Remarks	
S00001	Kiran	A/14	Worli	Bombay	400002	MAH	3000.00	100.00	50.00	Good	
S00002	Manish	65	Nariman	Bombay	400001	MAH	3000.00	200.00	100.00	Good	
S00003	Ravi	P-7	Bandra	Bombay	400032	MAH	3000.00	200.00	100.00	Good	

S00004	Ashish	A/5	Juhu	Bombay	400044	MAH	3000.00	
200.00	150.00	Good						

```

+-----+-----+-----+-----+-----+-----+-----+-----+-----+
+-----+

```

4 rows in set (0.00 sec)

Table 4:

```
mysql> select *from sales_order_7;
```

```

+-----+-----+-----+-----+-----+-----+-----+-----+-----+
--+

```

S_order_no	S_order_date	Client_no	Dely_addr	Salesman_no	Dely_type	
Billed_yn	Dely_date	Order_status				

```

+-----+-----+-----+-----+-----+-----+-----+-----+-----+
--+

```

O10008	1996-05-24	COOOO5	NULL	S00004	F	N	1996-05-26
IP							

O19001	1996-01-12	COOOO1	NULL	S00001	F	N	1996-01-20
IP							

O19002	1996-01-25	COOOO2	NULL	S00002	P	N	1996-01-27
C							

O19003	1996-04-03	COOOO1	NULL	S00001	F	Y	1996-04-07
F							

O46865	1996-02-18	COOOO3	NULL	S00003	F	Y	1996-02-20
F							

O46866	1996-05-20	COOOO4	NULL	S00002	P	N	1996-05-22
C							

```

+-----+-----+-----+-----+-----+-----+-----+-----+-----+
--+

```

6 rows in set (0.00 sec)

Table 5:

```
mysql> select *from sales_order_details_7;
```

```

+-----+-----+-----+-----+-----+

```

S_order_no	Product_no	Qty_ordered	Qty_disp	Product_rate	
------------	------------	-------------	----------	--------------	--

```

+-----+-----+-----+-----+-----+

```

O10008	PO7975		5		3		1050.00	
O10008	PO0001		10		5		525.00	
O19001	PO7885		2		1		5250.00	
O19001	PO7965		2		1		8400.00	
O19001	PO0001		4		4		525.00	
O19002	PO0001		10		0		525.00	
O19003	PO3453		2		2		1050.00	
O19003	PO6734		1		1		12000.00	
O46865	PO3453		4		4		1050.00	
O46865	PO7868		3		3		3150.00	
O46865	PO7885		3		1		5250.00	
O46865	PO0001		10		10		525.00	
O46866	PO7965		1		0		8400.00	
O46866	PO7975		1		0		1050.00	

```
+-----+-----+-----+-----+-----+
```

14 rows in set (0.00 sec)

Table 6:

```
mysql> select *from Challan_Header_7;
```

Challan_no	S_order_no	Challan_date	Billed_yn	
CH3965	O10008	1995-11-12	Y	
CH6865	O46865	1995-11-12	Y	
CH9001	O19001	1995-12-12	Y	

```
+-----+-----+-----+-----+-----+
```

3 rows in set (0.00 sec)

Table 7:

```
mysql> select *from Challan_details_7;
```

```
+-----+-----+-----+
```

Challan_no	Product_no	Qty_disp
------------	------------	----------

CH9001	PO7965	1
CH3965	PO7975	2
CH6865	PO7868	3
CH9001	POOOO1	4
CH3965	POOOO1	5
CH6865	POOOO1	10

6 rows in set (0.00 sec)