

Aarya Arban

S11 – 07

Aim: Write PL/SQL code to create function and procedure

Queries:

```
mysql> create procedure my_pro11(OUT client_no int)
```

```
-> begin
```

```
-> select COUNT(*) INTO client_no FROM client_master_7;
```

```
-> end;
```

```
-> &&
```

Query OK, 0 rows affected (0.07 sec)

```
mysql> call my_pro(2);
```

```
-> &&
```

```
+-----+-----+-----+-----+-----+-----+-----+-----+
| client_no | name      | address1 | address2 | city  | state  | pincode | bal_due |
+-----+-----+-----+-----+-----+-----+-----+-----+
| C00001    | Vandana Saitwal | NULL    | NULL     | Madras | Tamil Nadu | 780001 | 0.00 |
| C00002    | Vandana Saitwal | NULL    | NULL     | Madras | Tamil Nadu | 780001 | 0.00 |
```

```
mysql> call my_pro11(@a);
```

```
-> &&
```

Query OK, 1 row affected (0.03 sec)

```
mysql> select @a;
```

```
-> &&
```

```
+-----+
```

```
| @a |
```

```
+-----+
```

```
| 6 |
```

```
+-----+
```

```
mysql> delimiter $$
```

```
mysql> create function proprice(sell_price double)RETURNS varchar(20)
```

```
-> DETERMINISTIC
```

```
-> BEGIN
```

```
-> DECLARE lvl varchar(20);
```

```
-> IF sell_price<1000 THEN
```

```
-> SET lvl='CHEAP';
```

```
-> ELSEIF sell_price>3000 THEN
```

```
-> SET lvl='EXPENSIVE';
```

```
-> END IF;
```

```
-> RETURN(lvl);
```

```
-> END;
```

```
-> $$
```

Query OK, 0 rows affected (0.06 sec)

```
mysql> select product_no,proprice(sell_price) from product_master_7;
```

```
-> $$
```

```
+-----+-----+
```

```
| product_no | proprice(sell_price) |
```

```
+-----+-----+
```

```
| PO3453    | EXPENSIVE            |
```

```
| PO6734    | NULL                 |
```

```
| PO7865    | CHEAP                |
```

```
| PO7868    | EXPENSIVE            |
```

```
| PO7885    | EXPENSIVE            |
```

```
| PO7965    | EXPENSIVE            |
```

```
| PO7975    | NULL                 |
```

```
| PO8865    | NULL                 |
```

```
| PO0001    | CHEAP                |
```

```
+-----+-----+
```

9 rows in set (0.02 sec)

```
mysql> select product_no,proprice(sell_price) from product_master_7;
```

```
-> $$
```

```
+-----+-----+
| product_no | proprice(sell_price) |
+-----+-----+
| PO3453    | EXPENSIVE           |
| PO6734    | NULL                |
| PO7865    | CHEAP               |
| PO7868    | EXPENSIVE           |
| PO7885    | EXPENSIVE           |
| PO7965    | EXPENSIVE           |
| PO7975    | NULL                |
| PO8865    | NULL                |
| POOOO1    | CHEAP               |
+-----+-----+
```

```
9 rows in set (0.02 sec)
```