

Introduction to Quantum Key Distribution

Matthias Christandl

Fakultät für Physik
Ludwig-Maximilians-Universität München

January 2010



- Introduction
- Quantum Key Distribution
- Security Proof

Introduction

- What is information?
 - A mathematical concept describing "knowledge".
Basic unit is the bit 0 / 1.

- A physical concept $0 \hat{=}$  and $1 \hat{=}$ 

Introduction


- What is information?
 - A mathematical concept describing "knowledge".
Basic unit is the bit 0 / 1.
 - A physical concept $0 \hat{=}$  and $1 \hat{=}$ 
- The world is not made up of light switches, the world is made up of atoms and photons
- Atoms and photons are described by quantum mechanics
- The spin of an atom describes the information we have

about it



Introduction

- spin- $\frac{1}{2}$ system: points on the sphere




$$\begin{pmatrix} \cos \theta \\ e^{i\varphi} \sin \theta \end{pmatrix} = \cos \theta |\uparrow\rangle + e^{i\varphi} \sin \theta |\downarrow\rangle$$

- unit of information is the quantum bit or "qubit"


Introduction

- spin- $\frac{1}{2}$ system: points on the sphere




$$\begin{pmatrix} \cos \theta \\ e^{i\varphi} \sin \theta \end{pmatrix} = \cos \theta |\uparrow\rangle + e^{i\varphi} \sin \theta |\downarrow\rangle$$

- unit of information is the quantum bit or "qubit"
- we can manipulate and transmit qubits




ion trap



optical fibre

Quantum Information Science



Quantum Key Distribution

- Alice und Bob want to communicate in secrecy, but their phone is tapped.




Quantum Key Distribution

- Alice und Bob want to communicate in secrecy, but their phone is tapped.



- If they share key (string of secret random numbers),




- cipher is random and message secure (Vernam, 1926)

Quantum Key Distribution

- Alice und Bob want to communicate in secrecy, but their phone is tapped.



- If they share key (string of secret random numbers),



- cipher is random and message secure (Vernam, 1926)

Quantum Key Distribution

- key is as long as the message

Shannon (1949): this is optimal ☹

secret communication $\hat{=}$ key distribution

Quantum Key Distribution

- key is as long as the message
Shannon (1949): this is optimal ☹
secret communication $\hat{=}$ key distribution
- possible key distribution schemes:

Quantum Key Distribution

- key is as long as the message
Shannon (1949): this is optimal ☹
secret communication $\hat{=}$ key distribution
- possible key distribution schemes:
 - Alice and Bob meet \Rightarrow impractical

Quantum Key Distribution

- key is as long as the message
Shannon (1949): this is optimal ☹
secret communication $\hat{=}$ key distribution
- possible key distribution schemes:
 - Alice and Bob meet \Rightarrow impractical
 - Weaker level of security
 - assumptions on speed of Eve's computer (public key cryptography)
 - assumptions on size of Eve's harddrive (bounded storage model)

Quantum Key Distribution

- key is as long as the message
Shannon (1949): this is optimal ☹
secret communication $\hat{=}$ key distribution
- possible key distribution schemes:
 - Alice and Bob meet \Rightarrow impractical
 - Weaker level of security
 - assumptions on speed of Eve's computer (public key cryptography)
 - assumptions on size of Eve's harddrive (bounded storage model)
 - Use quantum mechanical effects (Bennett & Brassard 1984, Ekert 1991)

Quantum Key Distribution

prepare & measure (Wiesner 1970's, Bennett & Brassard 1984)



Quantum Key Distribution

prepare & measure (Wiesner 1970's, Bennett & Brassard 1984)




Security guaranteed by uncertainty principle

- Alice sends eigenstates of σ_z or σ_x .
- Bob measures observable σ_z or σ_x .
- They tell each other the observable, but not the result.
- They should obtain the same result when they used the same observable \Rightarrow **key**
- If Eve measures in the wrong observable, they have an error with probability $\frac{1}{2}$, since $[\sigma_z, \sigma_x] \neq 0$.


Quantum Key Distribution

entanglement-based (Ekert 1991)



Quantum Key Distribution

entanglement-based (Ekert 1991)



Security guaranteed by monogamy of entanglement

- Alice and Bob check (Bell inequality):

$$|\psi\rangle_{ABE} \stackrel{?}{=} \frac{1}{\sqrt{2}}(|0\rangle_A|0\rangle_B + |1\rangle_A|1\rangle_B)|\phi\rangle_E.$$

- If YES: Eve does not know their measurement results.
Results are random \Rightarrow **key**
- If NO: they abort the protocol.

Quantum Key Distribution

- Entangled state of two qubits $\frac{1}{\sqrt{2}}(|0\rangle_A|0\rangle_B + |1\rangle_A|1\rangle_B)$

Quantum Key Distribution

- Entangled state of two qubits $\frac{1}{\sqrt{2}}(|0\rangle_A|0\rangle_B + |1\rangle_A|1\rangle_B)$
- New basis

$$|+\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) \quad |-\rangle = \frac{1}{\sqrt{2}}(|0\rangle - |1\rangle)$$

- easy calculation

$$\frac{1}{\sqrt{2}}(|0\rangle_A|0\rangle_B + |1\rangle_A|1\rangle_B) = \frac{1}{\sqrt{2}}(|+\rangle_A|+\rangle_B + |-\rangle_A|-\rangle_B)$$

Quantum Key Distribution

- Entangled state of two qubits $\frac{1}{\sqrt{2}}(|0\rangle_A|0\rangle_B + |1\rangle_A|1\rangle_B)$
- New basis

$$|+\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) \quad |-\rangle = \frac{1}{\sqrt{2}}(|0\rangle - |1\rangle)$$

- easy calculation

$$\frac{1}{\sqrt{2}}(|0\rangle_A|0\rangle_B + |1\rangle_A|1\rangle_B) = \frac{1}{\sqrt{2}}(|+\rangle_A|+\rangle_B + |-\rangle_A|-\rangle_B)$$

- If Alice and Bob measure observable $\sigma_z \Rightarrow$ same result
- If Alice and Bob measure observable $\sigma_x \Rightarrow$ same result

Quantum Key Distribution

- Entangled state of two qubits $\frac{1}{\sqrt{2}}(|0\rangle_A|0\rangle_B + |1\rangle_A|1\rangle_B)$
- New basis

$$|+\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) \quad |-\rangle = \frac{1}{\sqrt{2}}(|0\rangle - |1\rangle)$$

- easy calculation

$$\frac{1}{\sqrt{2}}(|0\rangle_A|0\rangle_B + |1\rangle_A|1\rangle_B) = \frac{1}{\sqrt{2}}(|+\rangle_A|+\rangle_B + |-\rangle_A|-\rangle_B)$$

- If Alice and Bob measure observable $\sigma_z \Rightarrow$ same result
- If Alice and Bob measure observable $\sigma_x \Rightarrow$ same result
- Converse is true, too:
 - same measurement result \Rightarrow they have state $\frac{1}{\sqrt{2}}(|0\rangle_A|0\rangle_B + |1\rangle_A|1\rangle_B)$
 - Alice and Bob can test whether or not they have the state $\frac{1}{\sqrt{2}}(|0\rangle_A|0\rangle_B + |1\rangle_A|1\rangle_B)$!

Quantum Key Distribution

- Assume that Alice and Bob have the state
$$|\phi\rangle_{AB} = \frac{1}{\sqrt{2}}(|0\rangle_A|0\rangle_B + |1\rangle_A|1\rangle_B)$$
and measure in the same basis.
- Can someone else guess the result?

Quantum Key Distribution

- Assume that Alice and Bob have the state

$$|\phi\rangle_{AB} = \frac{1}{\sqrt{2}}(|0\rangle_A|0\rangle_B + |1\rangle_A|1\rangle_B)$$

and measure in the same basis.

- Can someone else guess the result?
- No! The measurement result is secure!**
 - Total state of Alice, Bob and Eve

$$|\psi\rangle_{ABE} = |\phi\rangle_{AB} \otimes |\phi\rangle_E,$$

- because Alice and Bob have a pure state
- Eve is not at all correlated with Alice and Bob!
- Monogamy of entanglement
- Try: $|\psi\rangle_{ABE} = \frac{1}{\sqrt{2}}(|0\rangle_A|0\rangle_B|0\rangle_E + |1\rangle_A|1\rangle_B|1\rangle_E)$

$$\rho_{AB} = \frac{1}{2}(|0\rangle_A|0\rangle_B\langle 0|_A\langle 0|_B + |1\rangle_A|1\rangle_B\langle 1|_A\langle 1|_B)$$

different from


$$|\phi\rangle\langle\phi|_{AB} = \frac{1}{2}(|0\rangle_A|0\rangle_B\langle 0|_A\langle 0|_B +$$

$$|1\rangle_A|1\rangle_B\langle 0|_A\langle 0|_B + |0\rangle_A|0\rangle_B\langle 1|_A\langle 1|_B + |1\rangle_A|1\rangle_B\langle 1|_A\langle 1|_B)$$

Quantum Key Distribution

The Quantum Key Distribution Protocol


Distribution



Quantum Key Distribution

The Quantum Key Distribution Protocol

Distribution



Quantum Key Distribution

The Quantum Key Distribution Protocol

Distribution





Quantum Key Distribution

The Quantum Key Distribution Protocol

Distribution



Measurement with σ_x or σ_z




Quantum Key Distribution

The Quantum Key Distribution Protocol


Distribution



Measurement with σ_x or σ_z



Error-free? $|\phi\rangle_{AB} \stackrel{?}{=} \frac{1}{\sqrt{2}}(|0\rangle_A|0\rangle_B + |1\rangle_A|1\rangle_B)$





Quantum Key Distribution

The Quantum Key Distribution Protocol


Distribution



Measurement with σ_x or σ_z



Error-free? $|\phi\rangle_{AB} \stackrel{?}{=} \frac{1}{\sqrt{2}}(|0\rangle_A|0\rangle_B + |1\rangle_A|1\rangle_B)$



If YES: **key**. If NO: no key

Quantum Key Distribution

- entanglement \Rightarrow key
- key \Rightarrow perfectly secure communication
- not possible with classical physics
- future (quantum) technology!



Security Proof

The Quantum Key Distribution Protocol


Distribution



Measurement with σ_x or σ_z



Error-free? $|\phi\rangle_{AB} \stackrel{?}{=} \frac{1}{\sqrt{2}}(|0\rangle_A|0\rangle_B + |1\rangle_A|1\rangle_B)$



If YES: **key**. If NO: no key

Security Proof

- Honest Eve would distribute

$$|\Psi\rangle_{ABC}^n = |\psi\rangle_{ABE}^{\otimes n} \quad \text{bits are independent}$$

$$|\psi\rangle_{ABE} = |\phi\rangle_{AB} \otimes |\phi\rangle_E \quad \text{Eve knows nothing}$$

$$|\phi\rangle_{AB} = \frac{1}{\sqrt{2}}(|0\rangle_A|0\rangle_B + |1\rangle_A|1\rangle_B) \quad \text{bits are random}$$

- Alice and Bob need to test whether Eve is honest or not.

Security Proof

- If Eve sends states of the form $|\Psi\rangle_{ABC}^n = |\psi\rangle_{ABE}^{\otimes n}$
- Alice and Bob test (on a subset): Are the pairs of the form $|\phi\rangle_{AB} = \frac{1}{\sqrt{2}}(|0\rangle_A|0\rangle_B + |1\rangle_A|1\rangle_B)$
i.e. is the data error-free ?
- If YES, standard statistical analysis implies
 - (almost) all remaining triples are of the form $|\phi\rangle_{AB} \otimes |\phi\rangle_E$
 \Rightarrow resulting bits are (almost) identical and random
 \Rightarrow Eve has (almost) no information about bits
 - Alice and Bob perform error correction
 - Alice and Bob delete a few random bits \Rightarrow
Eve has **no** information about remaining bits
(privacy amplification)
 \Rightarrow **key**
- If NO, abort the protocol


Security Proof

The Protocol


Distribution $|\Psi\rangle_{ABC}^n = |\psi\rangle_{ABE}^{\otimes n}$



Measurement



Error Estimation



$$|\phi\rangle_{AB} \stackrel{?}{=} \frac{1}{\sqrt{2}}(|0\rangle_A|0\rangle_B + |1\rangle_A|1\rangle_B)$$


NO: Abort protocol

YES:




Security Proof

- Proof works as long as $|\Psi\rangle_{ABC}^n = |\psi\rangle_{ABE}^{\otimes n}$.




- But why should Eve prepare such a state?
Why not the following?



Security Proof

De Finetti Theorem (Diaconis and Freedman, 1980)

Drawing balls from an urn with or without replacement results in almost the same probability distribution.



If k are drawn out of n , then

$$\|P^k - \sum_i p_i Q_i^{\times k}\|_1 \leq \text{const} \frac{k}{n}.$$

Security Proof

Quantum generalisations have been obtained by Størmer, Hudson & Moody, and Werner et al.. ($n = \infty$)

Quantum De Finetti Theorem

Ch., König, Mitchison, Renner, Comm. Math. Phys. 273, 473498 (2007)

Let ρ^n be a permutation-invariant state $\pi \rho \pi^{-1} = \rho$, then

$$\|\rho^k - \sum_i p_i \sigma_i^{\otimes k}\|_1 \leq \text{const} \frac{k}{n}$$

- $\text{const} = 4d^2$
- d dependence is necessary
- classically, k^2/n bound exists

Security Proof


Proof sketch

- reduce problem to the Bosonic case $\pi\rho = \rho$, for all $\pi \in S_n$
- ρ lives on $\text{Sym}^n(\mathbb{C}^d) \subset \text{Sym}^k(\mathbb{C}^d) \otimes \text{Sym}^{n-k}(\mathbb{C}^d)$
- measurement with $SU(d)$ coherent states
 $|\phi\rangle^{\otimes n} = |\phi\rangle^{\otimes k} \otimes |\phi\rangle^{\otimes n-k}$
- post-measurement on k particles: $\rho_{\text{post}}^k = \int \mu(\phi) |\phi\rangle\langle\phi|^{\otimes k}$
- gentle measurement $\rho^k \approx \rho_{\text{post}}^k$ (error k/n).

generalises to arbitrary irreducible representations of $SU(d)$.

Security Proof

- Alice and Bob select a random sample of pairs (after pairs have been distributed!)



- ⇒ can use proof from before (tensor product)
- ⇒ proof of the security of Quantum Key Distribution!

Security Proof

- Closer look: deviation from perfect key (due to quantum de Finetti theorem)

$$\epsilon \approx k/n$$

- n : number of pairs that Eve distributed
- k : number of bits of key

Security Proof

- Closer look: deviation from perfect key (due to quantum de Finetti theorem)

$$\epsilon \approx k/n$$

- n : number of pairs that Eve distributed
- k : number of bits of key
- key rate $r \approx k/n \approx \epsilon \approx 0 \Rightarrow$ not good enough
- need replacement for de Finetti theorem
- Renner's exp. de Finetti theorem, involved, non-optimal

Security Proof

Post-selection Technique

Ch., König, Renner, Phys. Rev. Lett. 102, 020504 (2009)

- Idea: Compare actual protocol with an ideal protocol (which produces perfect key)
- Theorem about permutation-covariant maps, rather than permutation-invariant states.

Security Proof

Post-selection Technique

Ch., König, Renner, Phys. Rev. Lett. 102, 020504 (2009)

- Idea: Compare actual protocol with an ideal protocol (which produces perfect key)
- Theorem about permutation-covariant maps, rather than permutation-invariant states.
- In QKD:
 - $r \approx k/n \approx 1 - \delta$ and $\epsilon \approx \exp(-\delta^2 n)$
 - optimal parameters
 - relevant in current experiments (since $n \approx 10^5$)
 - Eve's best attack $|\Psi_{ABE}^n\rangle = |\psi_{ABE}\rangle^{\otimes n}$
 - conceptual and technical simplification of security proofs
- Other applications: Quantum Reverse Shannon Theorem

Berta, Ch. and Renner, arXiv:0912.3805

