

Experiment :11

Name- Aaryan Singh

UID-23BCC70008

Part A: Prevent Duplicate Enrollments Using Locking Description:

Simulate concurrent users attempting to enroll students in courses. Implement a mechanism that prevents two users from enrolling the same student into the same course simultaneously by using transactions and unique constraints.

Input Format:

- Table StudentEnrollments with columns:
 - `enrollment_id` (INT, Primary Key)
 - `student_name` (VARCHAR(100))
 - `course_id` (VARCHAR(10))
 - `enrollment_date` (DATE)

Output Format:

Only one user should be able to insert the record successfully for a given `(student_name, course_id)` pair.

Constraints:

- Each student can enroll in a course only once.
- The pair `(student_name, course_id)` must be unique.
- Use transactions to handle concurrent access.

Sample Input:

enrollment_id	student_name	course_id	enrollment_date
1	Ashish	CSE101	2024-07-01
2	Smaran	CSE102	2024-07-01
3	Vaibhav	CSE101	2024-07-01

Sample Output: If two users try to enroll `'Ashish'` in `'CSE101'`, only the first will succeed; the second will get a constraint violation.

Query:

```
CREATE TABLE IF NOT EXISTS StudentEnrollments (  
  enrollment_id INT PRIMARY KEY,  student_name  
  VARCHAR(100),  course_id VARCHAR(10),  
  enrollment_date DATE,  
  UNIQUE(student_name, course_id)  
);  
  
INSERT INTO StudentEnrollments (enrollment_id, student_name, course_id,  
  enrollment_date)  
VALUES  
(1, 'Ashish', 'CSE101', '2024-07-01'),  
(2, 'Smaran', 'CSE102', '2024-07-01'),  
(3, 'Vaibhav', 'CSE101', '2024-07-01')  
ON DUPLICATE KEY UPDATE enrollment_id = enrollment_id;  
  
START TRANSACTION;  
  
SELECT * FROM StudentEnrollments  
WHERE student_name = 'Ashish' AND course_id = 'CSE101'  
FOR UPDATE;  
  
INSERT INTO StudentEnrollments (enrollment_id, student_name, course_id,  
  enrollment_date)  
SELECT 4, 'Ashish', 'CSE101', '2024-07-02'  
WHERE NOT EXISTS (  
  SELECT 1 FROM StudentEnrollments  
  WHERE student_name = 'Ashish' AND course_id = 'CSE101'  
);  
  
COMMIT;
```

Output:

queries.sql

+

AI NEW MySQL RUN

1- CREATE TABLE IF NOT EXISTS StudentEnrollments (
2- enrollment_id INT PRIMARY KEY,
3- student_name VARCHAR(100),
4- course_id VARCHAR(10),
5- enrollment_date DATE,
6- UNIQUE(student_name, course_id)
7-);
8-
9- INSERT INTO StudentEnrollments (enrollment_id, student_name, course_id, enrollment_date)
10- VALUES
11- (1, 'Ashish', 'CSE101', '2024-07-01'),
12- (2, 'Smaran', 'CSE102', '2024-07-01'),
13- (3, 'Vaibhav', 'CSE101', '2024-07-01')
14- ON DUPLICATE KEY UPDATE enrollment_id = enrollment_id;
15-
16- START TRANSACTION;
17-
18- SELECT * FROM StudentEnrollments
19- WHERE student_name = 'Ashish' AND course_id = 'CSE101'
20- FOR UPDATE;
21-
22- INSERT INTO StudentEnrollments (enrollment_id, student_name, course_id, enrollment_date)
23- SELECT 4, 'Ashish', 'CSE101', '2024-07-02'
24- WHERE NOT EXISTS (
25- SELECT 1 FROM StudentEnrollments
26- WHERE student_name = 'Ashish' AND course_id = 'CSE101'
27-);
28-
29- COMMIT;
30-

STDIN

Input for the program (Optional)

Output:

enrollment_id	student_name	course_id	enrollment_date
1	Ashish	CSE101	2024-07-01

Part B: Use SELECT FOR UPDATE to Lock Student Record

Description:

Use row-level locking via `SELECT FOR UPDATE` to prevent conflicts. Simulate a situation where a student is being verified before enrollment and locked until confirmation, preventing other users from updating it simultaneously.

Input Format:

- Same table: StudentEnrollments

Output Format:

The selected row will be locked until the transaction is committed or rolled back. Other users trying to access that row will be blocked.

Constraints:

- Use `START TRANSACTION` and `SELECT FOR UPDATE`.
- Locking should block conflicting transactions on the same record.

Sample Input:

Simulation Steps (Using Row-Level Locking with `SELECT FOR UPDATE`) User

A:

1. Start a transaction.
2. Use a `SELECT FOR UPDATE` query to lock the specific row where:
 - Student name is `'Ashish'`
 - Course ID is `'CSE101'`
3. Keep the transaction open (do not commit or rollback yet).

This locks the row so that no one else can update it until User A finishes.

User B (while User A's transaction is still open):

1. Try to update the same row (`student_name = 'Ashish'` and `course_id = 'CSE101'`).

This update will be blocked (it will wait) because the row is locked by User A.

Sample Output:

User B will be blocked until User A finishes the transaction.

Query:

```
CREATE TABLE IF NOT EXISTS StudentEnrollments (  
  enrollment_id INT PRIMARY KEY,  student_name  
  VARCHAR(100),  course_id VARCHAR(10),  
  enrollment_date DATE,  
  UNIQUE(student_name, course_id)  
);
```

```
INSERT INTO StudentEnrollments (enrollment_id, student_name, course_id,  
enrollment_date)  
VALUES  
(1, 'Ashish', 'CSE101', '2024-07-01'),  
(2, 'Smaran', 'CSE102', '2024-07-01'),  
(3, 'Vaibhav', 'CSE101', '2024-07-01')  
ON DUPLICATE KEY UPDATE enrollment_id = enrollment_id;
```

```
START TRANSACTION;
```

```
SELECT *  
FROM StudentEnrollments  
WHERE student_name = 'Ashish' AND course_id = 'CSE101'  
FOR UPDATE;
```

```
UPDATE StudentEnrollments  
SET enrollment_date = '2024-08-01'  
WHERE student_name = 'Ashish' AND course_id = 'CSE101';
```

```
COMMIT;
```

Output:



The screenshot shows a MySQL query editor with a SQL script on the left and the output on the right. The SQL script includes creating a table, inserting data, starting a transaction, locking a row for update, updating the date, and committing. The output shows a table with one row for Ashish's enrollment, where the date has been updated from 2024-07-01 to 2024-08-01.

```
1 CREATE TABLE IF NOT EXISTS StudentEnrollments (  
2   enrollment_id INT PRIMARY KEY,  
3   student_name VARCHAR(100),  
4   course_id VARCHAR(10),  
5   enrollment_date DATE,  
6   UNIQUE(student_name, course_id)  
7 );  
8  
9 INSERT INTO StudentEnrollments (enrollment_id, student_name, course_id, enrollment_date)  
10 VALUES  
11 (1, 'Ashish', 'CSE101', '2024-07-01'),  
12 (2, 'Smaran', 'CSE102', '2024-07-01'),  
13 (3, 'Vaibhav', 'CSE101', '2024-07-01')  
14 ON DUPLICATE KEY UPDATE enrollment_id = enrollment_id;  
15  
16 START TRANSACTION;  
17  
18 SELECT *  
19 FROM StudentEnrollments  
20 WHERE student_name = 'Ashish' AND course_id = 'CSE101'  
21 FOR UPDATE;  
22  
23 UPDATE StudentEnrollments  
24 SET enrollment_date = '2024-08-01'  
25 WHERE student_name = 'Ashish' AND course_id = 'CSE101';  
26  
27 COMMIT;
```

Output:

enrollment_id	student_name	course_id	enrollment_date
1	Ashish	CSE101	2024-08-01

Part C: Demonstrate Locking Preserving Consistency in Concurrent Transactions Description:

Demonstrate how locking preserves data consistency when multiple users attempt concurrent updates. Show how update conflicts are avoided when row-level locks are used appropriately in transactions.

Input Format:

Same StudentEnrollments table as above.

Output Format:

Conflicting operations are serialized due to locking, and data remains consistent without corruption or duplication.

Constraints:

- Each user must use transactions with locking.
- Show that without locking, both users could overwrite each other's changes.

Sample Input:

enrollment_id	student_name	course_id	enrollment_date
1	Ashish	CSE101	2024-07-01

Sample Output:

After both users run their updates one after the other, only the last committed update is reflected — no race condition or inconsistent data.

Output:

The screenshot shows a MySQL query editor with a SQL script on the left and its output on the right. The script creates a table, inserts a row, and then performs two updates on the same row within a transaction. The output shows the final state of the table after the transaction is committed.

```
1 CREATE TABLE IF NOT EXISTS StudentEnrollments (
2   enrollment_id INT PRIMARY KEY,
3   student_name VARCHAR(100),
4   course_id VARCHAR(10),
5   enrollment_date DATE,
6   UNIQUE(student_name, course_id)
7 );
8
9 INSERT INTO StudentEnrollments (enrollment_id, student_name, course_id, enrollment_date)
10 VALUES
11 (1, 'Ashish', 'CSE101', '2024-07-01');
12 ON DUPLICATE KEY UPDATE enrollment_id = enrollment_id;
13
14 START TRANSACTION;
15
16 SELECT *
17 FROM StudentEnrollments
18 WHERE student_name = 'Ashish' AND course_id = 'CSE101'
19 FOR UPDATE;
20
21 UPDATE StudentEnrollments
22 SET enrollment_date = '2024-07-15'
23 WHERE student_name = 'Ashish' AND course_id = 'CSE101';
24
25 COMMIT;
```

Output:

enrollment_id	student_name	course_id	enrollment_date
1	Ashish	CSE101	2024-07-01