

AutoML: Dynamic Configuration & Learning

Learning to Learn: Supervised

Bernd Bischl Frank Hutter Lars Kotthoff
Marius Lindauer Joaquin Vanschoren

Learning to Learn

Idea

- Learn algorithms directly, e.g., how to search in the weight space
- First idea: learn weight updates of a neural network

Learning to Learn

Idea

- Learn algorithms directly, e.g., how to search in the weight space
- First idea: learn weight updates of a neural network

Learning to learn by gradient descent by gradient descent

[Andrychowicz et al. 2016]

Weight updates (note: θ denote DNN weights):

$$\theta^{(t+1)} = \theta^{(t)} - \alpha^{(t)} \nabla f(\theta^{(t)})$$

Learning to Learn

Idea

- Learn algorithms directly, e.g., how to search in the weight space
- First idea: learn weight updates of a neural network

Learning to learn by gradient descent by gradient descent

[Andrychowicz et al. 2016]

Weight updates (note: θ denote DNN weights):

$$\theta^{(t+1)} = \theta^{(t)} - \alpha^{(t)} \nabla f(\theta^{(t)})$$

Even more general:

$$\theta^{(t+1)} = \theta^{(t)} + g^{(t)}(\nabla f(\theta^{(t)}), \phi)$$

where g is the optimizer and ϕ are the parameters of the optimizer g .

Learning to Learn

Idea

- Learn algorithms directly, e.g., how to search in the weight space
- First idea: learn weight updates of a neural network

Learning to learn by gradient descent by gradient descent

[Andrychowicz et al. 2016]

Weight updates (note: θ denote DNN weights):

$$\theta^{(t+1)} = \theta^{(t)} - \alpha^{(t)} \nabla f(\theta^{(t)})$$

Even more general:

$$\theta^{(t+1)} = \theta^{(t)} + g^{(t)}(\nabla f(\theta^{(t)}), \phi)$$

where g is the optimizer and ϕ are the parameters of the optimizer g .

\rightsquigarrow Goal: Optimize f wrt θ by learning g (resp. ϕ)

Learning to Learn: Objective [Andrychowicz et al. 2016]

$$L(\phi) = \mathbb{E} [f(\theta^*(f, \phi))]$$

where L is a loss function and $\theta^*(f, \phi)$ are the optimized weights θ^* by using the optimizer parameterized with ϕ on function f .

Learning to Learn: Objective [Andrychowicz et al. 2016]

$$L(\phi) = \mathbb{E} [f(\theta^*(f, \phi))]$$

where L is a loss function and $\theta^*(f, \phi)$ are the optimized weights θ^* by using the optimizer parameterized with ϕ on function f .

$$L(\phi) = \mathbb{E} \left[\sum_{t=1}^T w^{(t)} f(\theta^{(t)}) \right]$$

Learning to Learn: Objective [Andrychowicz et al. 2016]

$$L(\phi) = \mathbb{E} [f(\theta^*(f, \phi))]$$

where L is a loss function and $\theta^*(f, \phi)$ are the optimized weights θ^* by using the optimizer parameterized with ϕ on function f .

$$L(\phi) = \mathbb{E} \left[\sum_{t=1}^T w^{(t)} f(\theta^{(t)}) \right]$$

where w_t are arbitrary weights associated with each time step and

Learning to Learn: Objective [Andrychowicz et al. 2016]

$$L(\phi) = \mathbb{E} [f(\theta^*(f, \phi))]$$

where L is a loss function and $\theta^*(f, \phi)$ are the optimized weights θ^* by using the optimizer parameterized with ϕ on function f .

$$L(\phi) = \mathbb{E} \left[\sum_{t=1}^T w^{(t)} f(\theta^{(t)}) \right]$$

where w_t are arbitrary weights associated with each time step and

$$\begin{aligned} \theta^{(t+1)} &= \theta^{(t)} + g^{(t)} \\ \begin{pmatrix} g^{(t)} \\ h^{(t+1)} \end{pmatrix} &= m(\nabla_{\theta} f(\theta^{(t)}), h^{(t)}, \phi) \end{aligned}$$

Learning to Learn: Objective [Andrychowicz et al. 2016]

$$L(\phi) = \mathbb{E} [f(\theta^*(f, \phi))]$$

where L is a loss function and $\theta^*(f, \phi)$ are the optimized weights θ^* by using the optimizer parameterized with ϕ on function f .

$$L(\phi) = \mathbb{E} \left[\sum_{t=1}^T w^{(t)} f(\theta^{(t)}) \right]$$

where w_t are arbitrary weights associated with each time step and

$$\begin{aligned} \theta^{(t+1)} &= \theta^{(t)} + g^{(t)} \\ \begin{pmatrix} g^{(t)} \\ h^{(t+1)} \end{pmatrix} &= m(\nabla_{\theta} f(\theta^{(t)}), h^{(t)}, \phi) \end{aligned}$$

\rightsquigarrow Goal: Learn m via ϕ by using gradient descent by optimizing L

Learning to Learn: Objective [Andrychowicz et al. 2016]

$$L(\phi) = \mathbb{E} [f(\theta^*(f, \phi))]$$

where L is a loss function and $\theta^*(f, \phi)$ are the optimized weights θ^* by using the optimizer parameterized with ϕ on function f .

$$L(\phi) = \mathbb{E} \left[\sum_{t=1}^T w^{(t)} f(\theta^{(t)}) \right]$$

where w_t are arbitrary weights associated with each time step and

$$\begin{aligned} \theta^{(t+1)} &= \theta^{(t)} + g^{(t)} \\ \begin{pmatrix} g^{(t)} \\ h^{(t+1)} \end{pmatrix} &= m(\nabla_{\theta} f(\theta^{(t)}), h^{(t)}, \phi) \end{aligned}$$


↪ Goal: Learn m via ϕ by using gradient descent by optimizing L

↪ “Learning to learn gradient descent by gradient descent”


Learning to Learn: LSTM approach [Andrychowicz et al. 2016]

Optimizee Target network to be trained

Optimizer LSTM with hidden state h_t that predicts weight updates g_t




Learning to Learn: Coordinatewise LSTM optimizer [Andrychowicz et al. 2016]




- One LSTM for each coordinate (i.e., weight)
- All LSTMs have shared parameters ϕ
- Each coordinate has its own separate hidden state

Learning to Learn: Coordinatewise LSTM optimizer [Andrychowicz et al. 2016]




- One LSTM for each coordinate (i.e., weight)
 - All LSTMs have shared parameters ϕ
 - Each coordinate has its own separate hidden state
- ~> We can train the LSTM on k weights and apply it larger DNNs with k' weights, where $k \leq k'$

Learning to Learn with LSTM: Results [Andrychowicz et al. 2016]



Learning to Learn with LSTM: Results [Andrychowicz et al. 2016]


Changing the original architecture of the DNN:



↪ learnt optimizer is robust against some architectural changes

Learning to Learn with LSTM: Results [Andrychowicz et al. 2016]

Changing the activation function to ReLU:



↪ fails on other activation functions

Black Box Optimization Setting

$$\mathbf{x}^* \in \arg \min_{\mathbf{x} \in \mathcal{X}} f(\mathbf{x})$$

- 1 Given the current state of knowledge $h^{(t)}$ propose a query point $\mathbf{x}^{(t)}$
- 2 Observe the response $y^{(t)}$
- 3 Update any internal statistics to produce $h^{(t+1)}$

Learning Black Box Optimization

Essentially, a similar idea as before:

$$\begin{aligned} h^{(t)}, \mathbf{x}^{(t)} &= \text{RNN}_{\phi}(h^{(t-1)}, \mathbf{x}^{(t-1)}, y^{(t)}) \\ y^{(t)} &\sim p(y|\mathbf{x}^{(t)}) \end{aligned}$$

- Using recurrent neural network (RNN) to predict next x_t .
- $h^{(t)}$ is the internal hidden state

- Sum loss: Provides more information than final loss

$$L_{\text{sum}}(\phi) = \mathbb{E}_{f, y^{(1:T-1)}} \left[\sum_{t=1}^T f(\mathbf{x}^{(t)}) \right]$$

Learning Black-box Optimization: Loss Functions [Chen et al. 2017]

- Sum loss: Provides more information than final loss

$$L_{\text{sum}}(\phi) = \mathbb{E}_{f, y^{(1:T-1)}} \left[\sum_{t=1}^T f(\mathbf{x}^{(t)}) \right]$$

- EI loss: Try to learn behavior of Bayesian optimizer based on expected improvement (EI)
 - ▶ requires model (e.g., GP)

$$L_{\text{EI}}(\phi) = -\mathbb{E}_{f, y^{(1:T-1)}} \left[\sum_{t=1}^T \text{EI}(\mathbf{x}^{(t)} | y^{(1:t-1)}) \right]$$

Learning Black-box Optimization: Loss Functions [Chen et al. 2017]

- Sum loss: Provides more information than final loss

$$L_{\text{sum}}(\phi) = \mathbb{E}_{f,y^{(1:T-1)}} \left[\sum_{t=1}^T f(\mathbf{x}^{(t)}) \right]$$


- El loss: Try to learn behavior of Bayesian optimizer based on expected improvement (EI)
 - ▶ requires model (e.g., GP)

$$L_{\text{EI}}(\phi) = -\mathbb{E}_{f,y^{(1:T-1)}} \left[\sum_{t=1}^T \text{EI}(\mathbf{x}^{(t)} | y^{(1:t-1)}) \right]$$

- Observed Improvement Loss:


$$L_{\text{OI}}(\phi) = \mathbb{E}_{f,y^{(1:T-1)}} \left[\sum_{t=1}^T \min \left\{ f(\mathbf{x}^{(t)}) - \min_{i < t} (f(\mathbf{x}^{(i)})), 0 \right\} \right]$$

Learning Black-box Optimization: Results [Chen et al. 2017]



- Hartmann3 is an artificial function with 3 dimensions

Learning Black-box Optimization: Results [Chen et al. 2017]



- Hartmann3 is an artificial function with 3 dimensions

↪ L_{OI} and L_{EI} perform best

↪ L_{OI} easier to compute than L_{EI}
because we need a predictive model to compute EI