

AutoML: Meta-Learning

Introduction

Bernd Bischl Frank Hutter Lars Kotthoff
Marius Lindauer Joaquin Vanschoren

Intro: humans can easily learn from a single example

thanks to years of learning (and eons of evolution)

Canna Indica 'Picasso'



train


later
→

?




test

Can a computer learn from a single example?



Can a computer learn from a single example?




That won't work :) Humans also don't start from scratch.

Transfer learning?

Target task



Source task



ImageNet
(14 million images)

↓ **Pretrain**

→ **Finetune**



e.g. ResNet50
(23 million trainable parameters)


→ **Canna
Indica
'Picasso'**

Transfer learning?

Target task



Source task



ImageNet
(14 million images)

↓ **Pretrain**

→ **Finetune**



e.g. ResNet50
(23 million trainable parameters)


→ **Canna
Indica
'Picasso'**

A single source task (e.g. ImageNet) may not generalize well to the test task.

Meta-learning

Learn over a series (or distribution) of many different tasks/episodes


Inductive bias: learn *assumptions* that you can transfer to new tasks
Prepare yourself to learn new things faster



Meta-learning

Learn over a series (or distribution) of many different tasks/episodes

Inductive bias: learn **assumptions** that you can transfer to new tasks
Prepare yourself to learn new things faster




Useful in many real-life situations: rare events, test-time constraints, data collection costs, privacy issues,...

Inspired by human learning

We don't transfer from a single source task, we learn across many, many tasks
We have a 'drive' to explore new, challenging, but doable, fun tasks


year 1



year 2



year 3




year 4



Human-like Learning***

humans learn across tasks: less trial-and-error, less data, less compute
new tasks should be related to experience (doable, fun, interesting?)



key aspects of fast learning: compositionality, causality, learning to learn

Inductive bias (in language)

which assumptions do we make?




Training




 dax


 zup

 lug

 wif

   lug blicket wif

   wif blicket dax

  lug kiki wif

  wif kiki dax

Test

dax blicket zup?

wif blicket dax kiki lug?

Inductive bias (in language)

which assumptions do we make?




Training


 dax


 zup



 lug

 wif




   lug blicket wif

   wif blicket dax

  lug kiki wif

  wif kiki dax

Test

   dax blicket zup?

wif blicket dax kiki lug?

Inductive bias (in language)

which assumptions do we make?




Training




 dax



 zup

 lug

 wif




   lug blicket wif

   wif blicket dax

  lug kiki wif

  wif kiki dax

Test

   dax blicket zup?

    wif blicket dax kiki lug?

Inductive bias (in language)

which assumptions do we make?




Training

 dax

 zup



 lug

 wif




   lug blicket wif

   wif blicket dax

  lug kiki wif

  wif kiki dax

Test

   dax blicket zup?

    wif blicket dax kiki lug?

Common mistakes



one-to-one bias:
assume that every word is one color

Inductive bias (in language)




which assumptions do we make?





Training

 dax
 zup
 lug
 wif




   lug blicket wif
   wif blicket dax
  lug kiki wif
  wif kiki dax





Test

   dax blicket zup?

    wif blicket dax kiki lug?

Common mistakes

   one-to-one bias:
assume that every word is one color

    concatenation bias:
assume that order is always left-to-right

What if there is no training data?

we can still solve problems by making assumptions

Item pool



Test

zup?

zup zup?

dax zup?

zup tufa?

zup wif zup?

zup wif blicket?

blicket wif zup?

What if there is no training data?

we can still solve problems by making assumptions

Item pool



Test



zup?

zup zup?

dax zup?

zup tufa?

zup wif zup?

zup wif blicket?

blicket wif zup?


What if there is no training data?

we can still solve problems by making assumptions

Item pool



Test



zup?



zup zup?

dax zup?

zup tufa?

zup wif zup?

zup wif blicket?

blicket wif zup?

What if there is no training data?

we can still solve problems by making assumptions

Item pool



Test

-  zup?
-   zup zup?
-   dax zup?
- zup tufa?
- zup wif zup?
- zup wif blicket?
- blicket wif zup?

What if there is no training data?

we can still solve problems by making assumptions

Item pool



Test

-  zup?
-   zup zup?
-   dax zup?
-   zup tufa?
- zup wif zup?
- zup wif blicket?
- blicket wif zup?

What if there is no training data?

we can still solve problems by making assumptions

Item pool



Test

-  zup?
-   zup zup?
-   dax zup?
-   zup tufa?
-    zup wif zup?
- zup wif blicket?
- blicket wif zup?

What if there is no training data?

we can still solve problems by making assumptions

Item pool



Test

- zup?
- zup zup?
- dax zup?
- zup tufa?
- zup wif zup?
- zup wif blicket?
- blicket wif zup?

What if there is no training data?

we can still solve problems by making assumptions

Item pool



Test

-  zup?
-   zup zup?
-   dax zup?
-   zup tufa?
-    zup wif zup?
-    zup wif blicket?
-    blicket wif zup?

What if there is no training data?

we can still solve problems by making assumptions

Item pool



Test



Commonly used assumptions:



one-to-one bias:

assume that every word is one color
(and not a function or something else)

What if there is no training data?

we can still solve problems by making assumptions


Item pool



Test




Commonly used assumptions:



one-to-one bias:

assume that every word is one color
(and not a function or something else)



concatenation bias:

assume that order is always left-to-right

What if there is no training data?

we can still solve problems by making assumptions


Item pool



Test




Commonly used assumptions:



one-to-one bias:

assume that every word is one color
(and not a function or something else)



concatenation bias:

assume that order is always left-to-right



mutual exclusivity:

if object has a name, it doesn't need
another name

What if there is no training data?

we can still solve problems by making assumptions


Item pool



Test




Commonly used assumptions:



one-to-one bias:

assume that every word is one color
(and not a function or something else)



concatenation bias:

assume that order is always left-to-right



mutual exclusivity:

if object has a name, it doesn't need
another name

Humans *assume* that words have consistent meanings and follow input/output constraints

What if there is no training data?

we can still solve problems by making assumptions


Item pool



Test




Commonly used assumptions:



one-to-one bias:

assume that every word is one color
(and not a function or something else)



concatenation bias:

assume that order is always left-to-right



mutual exclusivity:


if object has a name, it doesn't need
another name

Humans *assume* that words have consistent meanings and follow input/output constraints

These assumptions (inductive biases) are necessary for learning quickly


Meta-learning inductive biases

Capture *useful assumptions* from the data - that can often not be easily expressed



Meta-learning goal

learn *minimal* inductive biases from prior tasks instead of constructing manual ones
should still generalize well (otherwise you meta-overfit)



Inductive bias: any assumptions added to training data to learn more effectively. E.g:

- Instead of **general model architectures**, **learn better architectures (and hyperparameters)**
- Instead of **starting from random weights**, **learn good initial weights**
- Instead of **standard loss/reward function**, **learn a better loss/reward function**

What can we learn to learn?

3 pillars

