

AutoML: Beyond AutoML

Per-Instance Algorithm Configuration

Bernd Bischl Frank Hutter Lars Kotthoff
Marius Lindauer Joaquin Vanschoren

Homogeneous vs. Heterogeneous Instances

Assumption of AC: Homogeneous Instance Distribution

- Algorithm configuration tools assume that the [instance distribution is homogeneous](#) (see video on "Best Practices for AC")
- Important because
 - ▶ there is a well-performing configuration for all (or most) instances
 - ▶ the racing algorithm can make educated decisions on subsets

Homogeneous vs. Heterogeneous Instances

Assumption of AC: Homogeneous Instance Distribution

- Algorithm configuration tools assume that the [instance distribution is homogeneous](#) (see video on "Best Practices for AC")
- Important because
 - ▶ there is a well-performing configuration for all (or most) instances
 - ▶ the racing algorithm can make educated decisions on subsets

Violated assumption of AC: Heterogeneous Instance Distribution

- The racing algorithm will make inconsistent (or even wrong) decisions
- There is no single well-performing configuration for all instances

Homogeneous vs. Heterogeneous Instances

Assumption of AC: Homogeneous Instance Distribution

- Algorithm configuration tools assume that the [instance distribution is homogeneous](#) (see video on "Best Practices for AC")
- Important because
 - ▶ there is a well-performing configuration for all (or most) instances
 - ▶ the racing algorithm can make educated decisions on subsets

Violated assumption of AC: Heterogeneous Instance Distribution

- The racing algorithm will make inconsistent (or even wrong) decisions
- There is no single well-performing configuration for all instances

⇒ What should we do with heterogeneous instance distributions?

Why are systems for heterogeneous instance distributions important?

- ① We cannot guarantee homogeneity in practice
 - ① Instances might get larger and harder
 - ② The underlying task or business case might change


Why are systems for heterogeneous instance distributions important?

- ① We cannot guarantee homogeneity in practice
 - ① Instances might get larger and harder
 - ② The underlying task or business case might change
- ② We don't want to do algorithm configuration always from scratch


Why are systems for heterogeneous instance distributions important?

- ① We cannot guarantee homogeneity in practice
 - ① Instances might get larger and harder
 - ② The underlying task or business case might change
- ② We don't want to do algorithm configuration always from scratch
- ③ An adaptive configuration system would be the holy grail
 - ~> hard to achieve

PIAC: Per-Instance Algorithm Configuration



PIAC: Per-Instance Algorithm Configuration



- You can use whichever kind of algorithm selection (wizard) you want
- **Challenge:** Building a portfolio
- **Use case:** Instances are heterogeneous

PIAC: Manual Expert Approach

Basic Assumption

Heterogeneous instance set can be divided into homogeneous subsets

PIAC: Manual Expert Approach

Basic Assumption

Heterogeneous instance set can be divided into homogeneous subsets

Manual Expert

- An expert knows the homogeneous subsets (e.g., origin of instances)
- Determine a well-performing configuration on each subset
→ portfolio of configurations
- Use Algorithm Selection to select a well-performing configuration on each instance

Idea

Training:

- 1 Cluster instances into homogeneous subsets
(using g -means in the instance feature space)
- 2 Apply algorithm configuration (here GGA) on each instance set

Instance-Specific Algorithm Configuration: ISAC [Kadioglu et al. 2010]


Idea

Training:

- 1 Cluster instances into homogeneous subsets (using g -means in the instance feature space)
- 2 Apply algorithm configuration (here GGA) on each instance set

Test:

- 1 Determine the nearest cluster (k -NN with $k = 1$) in feature space
- 2 Apply optimized configuration of this cluster



Idea

- Iteratively add configurations to a portfolio \mathbf{P} , start with $\mathbf{P} = \emptyset$
- In each iteration, determine configuration that is complementary to \mathbf{P}
 - ↪ Maximize marginal contribution to \mathbf{P}

Idea

- Iteratively add configurations to a portfolio \mathbf{P} , start with $\mathbf{P} = \emptyset$
- In each iteration, determine configuration that is complementary to \mathbf{P}
 - ↪ Maximize marginal contribution to \mathbf{P}

Marginal contribution of a configuration λ to a portfolio \mathbf{P} :


$$c(\mathbf{P}) - c(\mathbf{P} \cup \{\lambda\})$$

Idea

- Iteratively add configurations to a portfolio \mathbf{P} , start with $\mathbf{P} = \emptyset$
- In each iteration, determine configuration that is complementary to \mathbf{P}
 - ↪ Maximize marginal contribution to \mathbf{P}

Marginal contribution of a configuration λ to a portfolio \mathbf{P} :

$$c(\mathbf{P}) - c(\mathbf{P} \cup \{\lambda\})$$




Idea

- Iteratively add configurations to a portfolio \mathbf{P} , start with $\mathbf{P} = \emptyset$
- In each iteration, determine configuration that is complementary to \mathbf{P}
 - ↪ Maximize marginal contribution to \mathbf{P}

Marginal contribution of a configuration λ to a portfolio \mathbf{P} :

$$c(\mathbf{P}) - c(\mathbf{P} \cup \{\lambda\})$$




Idea

- Iteratively add configurations to a portfolio \mathbf{P} , start with $\mathbf{P} = \emptyset$
- In each iteration, determine configuration that is complementary to \mathbf{P}
 - ↪ Maximize marginal contribution to \mathbf{P}

Marginal contribution of a configuration λ to a portfolio \mathbf{P} :

$$c(\mathbf{P}) - c(\mathbf{P} \cup \{\lambda\})$$




Idea


- Iteratively add configurations to a portfolio \mathbf{P} , start with $\mathbf{P} = \emptyset$
- In each iteration, determine configuration that is complementary to \mathbf{P}
 - ↪ Maximize marginal contribution to \mathbf{P}

Marginal contribution of a configuration λ to a portfolio \mathbf{P} :


$$c(\mathbf{P}) - c(\mathbf{P} \cup \{\lambda\})$$




Heterogeneous example




Heterogeneous example




Heterogeneous example



Heterogeneous example




Hydra: Iteration 1




Search initial well performing configuration. Add λ_0 to \mathbf{P}

Hydra: Iteration 1




Hydra: Iteration 2



Search well performing configuration complementary to \mathbf{P} .
Add λ_1 to \mathbf{P} .

Hydra: Iteration 2



Idea

- Optimize a schedule of configurations with algorithm configuration

Idea

- Optimize a schedule of configurations with algorithm configuration

Approach

- Iteratively add a configuration with a time slot t to a schedule $\mathcal{S} \oplus \langle \lambda, t \rangle$

Idea

- Optimize a schedule of configurations with algorithm configuration

Approach

- Iteratively add a configuration with a time slot t to a schedule $\mathcal{S} \oplus \langle \lambda, t \rangle$
- In each iteration, only optimize on instances not solved so far
- The time slot is a further parameter in the configuration space

Idea

- Optimize a schedule of configurations with algorithm configuration

Approach

- Iteratively add a configuration with a time slot t to a schedule $\mathcal{S} \oplus \langle \lambda, t \rangle$
- In each iteration, only optimize on instances not solved so far
- The time slot is a further parameter in the configuration space
- Optimize marginal contribution per time spent:

$$\frac{c(\mathcal{S}) - c(\mathcal{S} \oplus \langle \lambda, t \rangle)}{t}$$

Submodularity

Observation

- Performance metrics of Hydra and Cedalion are submodular
 - ▶ Family of functions
 - ▶ Adding an element to a set reduces the function value
 - ▶ Diminishing returns: decrease of the value reduction over time

Submodularity

Observation

- Performance metrics of Hydra and Cedalion are submodular
 - ▶ Family of functions
 - ▶ Adding an element to a set reduces the function value
 - ▶ Diminishing returns: decrease of the value reduction over time

Definition (Submodularity of f)

For every $X, Y \subseteq Z$ with $X \subseteq Y$ and every $x \in Z - Y$ we have that

$$f(X \cup \{x\}) - f(X) \geq f(Y \cup \{x\}) - f(Y)$$

Submodularity

Observation

- Performance metrics of Hydra and Cedalion are submodular
 - ▶ Family of functions
 - ▶ Adding an element to a set reduces the function value
 - ▶ Diminishing returns: decrease of the value reduction over time

Definition (Submodularity of f)

For every $X, Y \subseteq Z$ with $X \subseteq Y$ and every $x \in Z - Y$ we have that

$$f(X \cup \{x\}) - f(X) \geq f(Y \cup \{x\}) - f(Y)$$

Advantage

We can bound the error of the portfolio/schedule:

At most away from optimum by factor of 0.63 (see [Streeter & Golovin '08])

Dynamic Instance Grouping [Liu et al. 2019]

Idea

- Similar to ISAC: group instances into clusters
- Similar to Hydra: refine clusters and configurations over several iterations

Dynamic Instance Grouping [Liu et al. 2019]

Idea

- Similar to ISAC: group instances into clusters
- Similar to Hydra: refine clusters and configurations over several iterations

Main Idea

- 1 Group instances randomly into clusters
- 2 run AC on each cluster
- 3 Update clusters based on performance (estimates)
- 4 Go to 2. if budget is not empty
- 5 Consider all configurations ever found to create final portfolio

Dynamic Instance Grouping [Liu et al. 2019]

Idea

- Similar to ISAC: group instances into clusters
- Similar to Hydra: refine clusters and configurations over several iterations

Main Idea

- 1 Group instances randomly into clusters
 - 2 run AC on each cluster
 - 3 Update clusters based on performance (estimates)
 - 4 Go to 2. if budget is not empty
 - 5 Consider all configurations ever found to create final portfolio
- increase the configuration budget in each iteration
 - ▶ first clusterings will have a poor quality → small configuration time
 - ▶ later clusterings will be better → more configuration time