# AutoML: Neural Architecture Search (NAS)

NASLib: A Modular and Extensible NAS Library

Bernd Bischl <u>Frank Hutter</u> Lars Kotthoff Marius Lindauer Joaquin Vanschoren

- Allow fair comparisons without confounding factors, which could be due to
  - Different codebases
  - Different search and evaluation pipelines
  - Different hyperparameter settings
  - Other confounding factors, e.g., library versions, GPU types, etc.

- Allow fair comparisons without confounding factors, which could be due to
  - Different codebases
  - Different search and evaluation pipelines
  - Different hyperparameter settings
  - Other confounding factors, e.g., library versions, GPU types, etc.
- Modularize different components of NAS optimizers to allow combining them

- Allow fair comparisons without confounding factors, which could be due to
  - Different codebases
  - Different search and evaluation pipelines
  - Different hyperparameter settings
  - Other confounding factors, e.g., library versions, GPU types, etc.
- Modularize different components of NAS optimizers to allow combining them
- Offer researchers a convenient way of prototyping new NAS methods

- Allow fair comparisons without confounding factors, which could be due to
  - Different codebases
  - Different search and evaluation pipelines
  - Different hyperparameter settings
  - Other confounding factors, e.g., library versions, GPU types, etc.
- Modularize different components of NAS optimizers to allow combining them
- Offer researchers a convenient way of prototyping new NAS methods
- Offer users reliable implementations of NAS methods
  - ► Facilitate the use of NAS for new search spaces
  - Develop a robust true AutoML framework

- NASLib implements a broad range of NAS optimizers
  - ▶ Blackbox NAS methods, e.g., Regularized Evolution
  - One-shot NAS methods, e.g., DARTS

- NASLib implements a broad range of NAS optimizers
  - ▶ Blackbox NAS methods, e.g., Regularized Evolution
  - ► One-shot NAS methods, e.g., DARTS
- The optimizers are modularized
  - ▶ This allows to switch from, e.g., DARTS to GDAS or PC-DARTS by just one method call

- NASLib implements a broad range of NAS optimizers
  - ▶ Blackbox NAS methods, e.g., Regularized Evolution
  - One-shot NAS methods, e.g., DARTS
- The optimizers are modularized
  - ▶ This allows to switch from, e.g., DARTS to GDAS or PC-DARTS by just one method call
- The evaluators are agnostic to the origin of an architecture
  - ▶ The final architecture is run using exactly the same object to evaluate on the test set

- NASLib implements a broad range of NAS optimizers
  - ▶ Blackbox NAS methods, e.g., Regularized Evolution
  - One-shot NAS methods, e.g., DARTS
- The optimizers are modularized
  - ▶ This allows to switch from, e.g., DARTS to GDAS or PC-DARTS by just one method call
- The evaluators are agnostic to the origin of an architecture
  - ▶ The final architecture is run using exactly the same object to evaluate on the test set
- NASLib's main building block is the graph object represented as a NetworkX <sup>1</sup> graph
  - Easily manipulate the graph by adding/removing nodes/edges
  - Hide complexity of dealing with the PyTorch computational graph
  - Easy high-level way of creating complex structures, e.g., hierarchical search spaces


<sup>&</sup>lt;sup>1</sup>https://networkx.github.io/

- The optimizers are agnostic to the search space they are running on
  - ► This facilitates their use for new types of search spaces

- The optimizers are agnostic to the search space they are running on
  - ▶ This facilitates their use for new types of search spaces
- An optimizer takes the search space as a NetworkX object and builds the PyTorch computational graph




- The optimizers are agnostic to the search space they are running on
  - ► This facilitates their use for new types of search spaces
- An optimizer takes the search space as a NetworkX object and builds the PyTorch computational graph



- Depending on the optimizer, each operation choice in the NetworkX object becomes:
  - a MixedOp for one-shot NAS optimizers, e.g. DARTS
  - a CategoricalOp for black-box optimizers, e.g. Regularized Evolution

### NASLib: Overview



### Tabular benchmarks for one-shot NAS

- NAS-Bench-101 [Ying et al. 2019] is not directly compatible with one-shot NAS methods
  - ▶ Mainly due to the constraint of at most 9 edges in the cell

### Tabular benchmarks for one-shot NAS


- NAS-Bench-101 [Ying et al. 2019] is not directly compatible with one-shot NAS methods
  - ▶ Mainly due to the constraint of at most 9 edges in the cell
- NAS-Bench-1Shot1 [Zela et al. 2020]
  - 3 sub-spaces of NAS-Bench-101 that are compatible with one-shot methods
    - ★ 6240, 29160, and 363648 architectures, respectively
  - Currently the largest one-shot NAS tabular benchmark

### Tabular benchmarks for one-shot NAS

- NAS-Bench-101 [Ying et al. 2019] is not directly compatible with one-shot NAS methods
  - ▶ Mainly due to the constraint of at most 9 edges in the cell
- NAS-Bench-1Shot1 [Zela et al. 2020]
  - 3 sub-spaces of NAS-Bench-101 that are compatible with one-shot methods
    - ★ 6240, 29160, and 363648 architectures, respectively
  - Currently the largest one-shot NAS tabular benchmark
- NAS-Bench-201 [Dong and Yang. 2020]
  - Much smaller than NAS-Bench-101 and largest NAS-Bench-1Shot1 subspace
    - ★ 15 625 architectures
  - Every architecture in the search space evaluated on 3 image classification datasets


# NASLib case study: Results on NAS-Bench-201


 NAS-Bench-201 is already integrated in NASLib and we can run any one-shot optimizer on it



# NASLib case study: Results on NAS-Bench-201


- NAS-Bench-201 is already integrated in NASLib and we can run any one-shot optimizer on it
- We can also combine random perturbations [Chen and Hsieh, 2020] with any one-shot optimizer





# NASLib case study: Results on NAS-Bench-201

- NAS-Bench-201 is already integrated in NASLib and we can run any one-shot optimizer on it
- We can also combine random perturbations [Chen and Hsieh, 2020] with any one-shot optimizer
- We can also evaluate black-box optimizers cheaply with a tabular benchmark



#### Room for many interesting projects and theses

- Applications of NAS to your problem of interest, with interesting search spaces
  - ▶ NASLib is the first library that separates the NAS method from the search spaces
    - ★ Therefore, no changes are required in the NAS methods
    - ★ This should make new applications much easier

### Room for many interesting projects and theses

- Applications of NAS to your problem of interest, with interesting search spaces
  - ▶ NASLib is the first library that separates the NAS method from the search spaces
    - ★ Therefore, no changes are required in the NAS methods
    - ★ This should make new applications much easier
- Studying hierarchical search spaces in detail

### Room for many interesting projects and theses

- Applications of NAS to your problem of interest, with interesting search spaces
  - ▶ NASLib is the first library that separates the NAS method from the search spaces
    - ★ Therefore, no changes are required in the NAS methods
    - \* This should make new applications much easier
- Studying hierarchical search spaces in detail
- Combining different components of existing NAS methods
  - ▶ So far, it has been very hard on a code level to mix and match components
  - ▶ It ought to be possible to design the world's best NAS method by combining the right components

#### Room for many interesting projects and theses

- Applications of NAS to your problem of interest, with interesting search spaces
  - NASLib is the first library that separates the NAS method from the search spaces
    - ★ Therefore, no changes are required in the NAS methods
    - \* This should make new applications much easier
- Studying hierarchical search spaces in detail
- Combining different components of existing NAS methods
  - ▶ So far, it has been very hard on a code level to mix and match components
  - ▶ It ought to be possible to design the world's best NAS method by combining the right components

### Room for interesting Hiwi projects

Not everything is perfect yet, we can use lots of support by great programmers

# Questions to Answer for Yourself / Discuss with Friends

#### • Repetition:

What would one have to do in order to apply the methods in NASLib to a new search space?

#### • Discussion:

Is there a problem of your interest that you would you like to apply the methods in NASLib to?

#### Discussion:

Given that NASLib's modular design allows mixing and matching components of one-shot NAS methods, which of the methods we discussed might make sense to combine?

