

# AutoML: Beyond AutoML

## Per-Instance Algorithm Configuration

Bernd Bischl   Frank Hutter   Lars Kotthoff  
Marius Lindauer   Joaquin Vanschoren

# Homogeneous vs. Heterogeneous Instances

## Assumption of AC: Homogeneous Instance Distribution

- Algorithm configuration tools assume that the [instance distribution is homogeneous](#) (see video on "Best Practices for AC")
- Important because
  - ▶ there is a well-performing configuration for all (or most) instances
  - ▶ the racing algorithm can make educated decisions on subsets

# Homogeneous vs. Heterogeneous Instances

## Assumption of AC: Homogeneous Instance Distribution

- Algorithm configuration tools assume that the [instance distribution is homogeneous](#) (see video on "Best Practices for AC")
- Important because
  - ▶ there is a well-performing configuration for all (or most) instances
  - ▶ the racing algorithm can make educated decisions on subsets

## Violated assumption of AC: Heterogeneous Instance Distribution

- The racing algorithm will make inconsistent (or even wrong) decisions
- There is no single well-performing configuration for all instances

# Homogeneous vs. Heterogeneous Instances

## Assumption of AC: Homogeneous Instance Distribution

- Algorithm configuration tools assume that the **instance distribution is homogeneous** (see video on "Best Practices for AC")
- Important because
  - ▶ there is a well-performing configuration for all (or most) instances
  - ▶ the racing algorithm can make educated decisions on subsets

## Violated assumption of AC: Heterogeneous Instance Distribution

- The racing algorithm will make inconsistent (or even wrong) decisions
- There is no single well-performing configuration for all instances

⇒ What should we do with heterogeneous instance distributions?

# Why are systems for heterogeneous instance distributions important?

- ① We cannot guarantee homogeneity in practice
  - ① Instances might get larger and harder
  - ② The underlying task or business case might change


# Why are systems for heterogeneous instance distributions important?

- ① We cannot guarantee homogeneity in practice
  - ① Instances might get larger and harder
  - ② The underlying task or business case might change
- ② We don't want to do algorithm configuration always from scratch

# Why are systems for heterogeneous instance distributions important?


- ① We cannot guarantee homogeneity in practice
  - ① Instances might get larger and harder
  - ② The underlying task or business case might change
- ② We don't want to do algorithm configuration always from scratch
- ③ An adaptive configuration system would be the holy grail
  - hard to achieve

# PIAC: Per-Instance Algorithm Configuration





# PIAC: Per-Instance Algorithm Configuration



- You can use whichever kind of algorithm selection (wizard) you want
- **Challenge:** Building a portfolio
- **Use case:** Instances are heterogeneous

# PIAC: Manual Expert Approach

## Basic Assumption

Heterogeneous instance set can be divided into homogeneous subsets

# PIAC: Manual Expert Approach

## Basic Assumption

Heterogeneous instance set can be divided into homogeneous subsets

## Manual Expert

- An expert knows the homogeneous subsets (e.g., origin of instances)
- Determine a well-performing configuration on each subset  
→ portfolio of configurations
- Use Algorithm Selection to select a well-performing configuration on each instance

## Idea

### Training:

- 1 Cluster instances into homogeneous subsets  
(using  $g$ -means in the instance feature space)
- 2 Apply algorithm configuration (here GGA) on each instance set

# Instance-Specific Algorithm Configuration: ISAC [Kadioglu et al. 2010]


## Idea

Training:

- 1 Cluster instances into homogeneous subsets (using  $g$ -means in the instance feature space)
- 2 Apply algorithm configuration (here GGA) on each instance set

Test:

- 1 Determine the nearest cluster ( $k$ -NN with  $k = 1$ ) in feature space
- 2 Apply optimized configuration of this cluster



## Idea

- Iteratively add configurations to a portfolio  $\mathbf{P}$ , start with  $\mathbf{P} = \emptyset$
- In each iteration, determine configuration that is complementary to  $\mathbf{P}$ 
  - ↪ Maximize marginal contribution to  $\mathbf{P}$

## Idea

- Iteratively add configurations to a portfolio  $\mathbf{P}$ , start with  $\mathbf{P} = \emptyset$
- In each iteration, determine configuration that is complementary to  $\mathbf{P}$ 
  - ↪ Maximize marginal contribution to  $\mathbf{P}$

Marginal contribution of a configuration  $\lambda$  to a portfolio  $\mathbf{P}$ :


$$c(\mathbf{P}) - c(\mathbf{P} \cup \{\lambda\})$$

## Idea

- Iteratively add configurations to a portfolio  $\mathbf{P}$ , start with  $\mathbf{P} = \emptyset$
- In each iteration, determine configuration that is complementary to  $\mathbf{P}$ 
  - ↪ Maximize marginal contribution to  $\mathbf{P}$

Marginal contribution of a configuration  $\lambda$  to a portfolio  $\mathbf{P}$ :

$$c(\mathbf{P}) - c(\mathbf{P} \cup \{\lambda\})$$






## Idea

- Iteratively add configurations to a portfolio  $\mathbf{P}$ , start with  $\mathbf{P} = \emptyset$
- In each iteration, determine configuration that is complementary to  $\mathbf{P}$ 
  - ↪ Maximize marginal contribution to  $\mathbf{P}$

Marginal contribution of a configuration  $\lambda$  to a portfolio  $\mathbf{P}$ :

$$c(\mathbf{P}) - c(\mathbf{P} \cup \{\lambda\})$$




## Idea

- Iteratively add configurations to a portfolio  $\mathbf{P}$ , start with  $\mathbf{P} = \emptyset$
- In each iteration, determine configuration that is complementary to  $\mathbf{P}$ 
  - ↪ Maximize marginal contribution to  $\mathbf{P}$

Marginal contribution of a configuration  $\lambda$  to a portfolio  $\mathbf{P}$ :

$$c(\mathbf{P}) - c(\mathbf{P} \cup \{\lambda\})$$




## Idea


- Iteratively add configurations to a portfolio  $\mathbf{P}$ , start with  $\mathbf{P} = \emptyset$
- In each iteration, determine configuration that is complementary to  $\mathbf{P}$ 
  - ↪ Maximize marginal contribution to  $\mathbf{P}$

Marginal contribution of a configuration  $\lambda$  to a portfolio  $\mathbf{P}$ :


$$c(\mathbf{P}) - c(\mathbf{P} \cup \{\lambda\})$$




# Heterogeneous example




# Heterogeneous example




# Heterogeneous example



# Heterogeneous example




## Hydra: Iteration 1




Search initial well performing configuration. Add  $\lambda_0$  to  $\mathbf{P}$



# Hydra: Iteration 1




## Hydra: Iteration 2



Search well performing configuration complementary to  $\mathbf{P}$ .  
Add  $\lambda_1$  to  $\mathbf{P}$ .

## Hydra: Iteration 2



## Idea

- Optimize a schedule of configurations with algorithm configuration

## Idea

- Optimize a schedule of configurations with algorithm configuration

## Approach

- Iteratively add a configuration with a time slot  $t$  to a schedule  $\mathcal{S} \oplus \langle \lambda, t \rangle$

## Idea

- Optimize a schedule of configurations with algorithm configuration

## Approach

- Iteratively add a configuration with a time slot  $t$  to a schedule  $\mathcal{S} \oplus \langle \lambda, t \rangle$
- In each iteration, only optimize on instances not solved so far
- The time slot is a further parameter in the configuration space

## Idea

- Optimize a schedule of configurations with algorithm configuration

## Approach

- Iteratively add a configuration with a time slot  $t$  to a schedule  $\mathcal{S} \oplus \langle \lambda, t \rangle$
- In each iteration, only optimize on instances not solved so far
- The time slot is a further parameter in the configuration space
- Optimize marginal contribution per time spent:

$$\frac{c(\mathcal{S}) - c(\mathcal{S} \oplus \langle \lambda, t \rangle)}{t}$$

# Submodularity

## Observation

- Performance metrics of Hydra and Cedalion are submodular
  - ▶ Family of functions
  - ▶ Adding an element to a set reduces the function value
  - ▶ Diminishing returns: decrease of the value reduction over time



# Submodularity

## Observation

- Performance metrics of Hydra and Cedalion are submodular
  - ▶ Family of functions
  - ▶ Adding an element to a set reduces the function value
  - ▶ Diminishing returns: decrease of the value reduction over time

## Definition (Submodularity of $f$ )

For every  $X, Y \subseteq Z$  with  $X \subseteq Y$  and every  $x \in Z - Y$  we have that

$$f(X \cup \{x\}) - f(X) \geq f(Y \cup \{x\}) - f(Y)$$

# Submodularity

## Observation

- Performance metrics of Hydra and Cedalion are submodular
  - ▶ Family of functions
  - ▶ Adding an element to a set reduces the function value
  - ▶ Diminishing returns: decrease of the value reduction over time

## Definition (Submodularity of $f$ )

For every  $X, Y \subseteq Z$  with  $X \subseteq Y$  and every  $x \in Z - Y$  we have that

$$f(X \cup \{x\}) - f(X) \geq f(Y \cup \{x\}) - f(Y)$$

## Advantage

We can bound the error of the portfolio/schedule:

At most away from optimum by factor of 0.63 (see [Streeter and Golovin. 2008])

# Dynamic Instance Grouping [Liu et al. 2018]

## Idea

- Similar to ISAC: group instances into clusters
- Similar to Hydra: refine clusters and configurations over several iterations

# Dynamic Instance Grouping [Liu et al. 2018]

## Idea

- Similar to ISAC: group instances into clusters
- Similar to Hydra: refine clusters and configurations over several iterations

## Main Idea

- 1 Group instances randomly into clusters
- 2 run AC on each cluster
- 3 Update clusters based on performance (estimates)
- 4 Go to 2. if budget is not empty
- 5 Consider all configurations ever found to create final portfolio

# Dynamic Instance Grouping [Liu et al. 2018]

## Idea

- Similar to ISAC: group instances into clusters
- Similar to Hydra: refine clusters and configurations over several iterations

## Main Idea

- 1 Group instances randomly into clusters
  - 2 run AC on each cluster
  - 3 Update clusters based on performance (estimates)
  - 4 Go to 2. if budget is not empty
  - 5 Consider all configurations ever found to create final portfolio
- increase the configuration budget in each iteration
    - ▶ first clusterings will have a poor quality → small configuration time
    - ▶ later clusterings will be better → more configuration time