

Developer's Manual

Troubleshooting & Prerequisites

This software setup has been tested in the KCL lab and should be working. This project requires Nix with flakes and nix-command enabled.

If you encounter a "command not found" or "experimental feature" error, you can bypass local configuration issues by appending the experimental flags directly to the commands:

```
nix --extra-experimental-features 'nix-command flakes' run .#run
```

Installation: If Nix is not installed, follow the official instructions at nixos.org or run:

```
curl -L https://nixos.org/nix/install | sh
```

If Selenium testing breaks, please install Google Chrome. Keep the chrome drivers updated as well. Remember, if you are using WSL with Windows, you must have Google Chrome installed inside your WSL setup.

When logging in as a player after seeding an account, it is highly recommended that you start a new game. You can continue the game currently seeded, but it won't provide the best experience.

Installation guide

1. Download the .zip file.
2. Unzip the .zip inside a folder or place on your computer.
3. Double-click into the folder you just unzipped.
4. Right click on an empty space, and run a terminal.
5. In the terminal, do
`nix run .#init`
6. Afterward do
`nix run .#run`
7. In the terminal, it should say "Starting development server at <http://127.0.0.1:<port>/>". Please CTRL+LMB on that link to open the local website.
8. You can CTRL+C whilst in the terminal to shut the server down. Go back to step 6 if you'd like to run the server again.
9. To run tests, do
`nix run .#tests`
10. After running tests, you will see the amount of tests passed in the terminal. To find the coverage, please open the index.html file on a browser, which can be found in ~/htmlcov
11. (Optional) You can also seed by doing
`nix run .#seed`

12. (Optional) You can also unseed by doing
nix run .#unseed