



## TROUBLESHOOTING STEPS FOR MERCHANTS- APN'S SETTINGS

### ANDROID PHONES-

- Do you see any **signal bars**, or is there an **"X"** where the signal should be?
- Are there any messages at the top of the screen, such as **"No Service"** or **"Emergency Calls Only"**?
- Is the mobile data turned on?
- Do you know if your Android phone is compatible with AT&T or unlocked for use with other carriers?

If the customer does not know if the Android phone is AT&T-compatible or unlocked, we can continue with the APN setup, **but we cannot guarantee it will work.**

### General Steps:

- Go to settings.
- Tap on the network and Internet.
- Tap on Mobile networks.
- Click on advance.
- Look and click on APN or Access Point Name.
- Click on the three little dots in the upper right corner and click on reset to default.
- Tap on the plus sign (+) in the upper right corner.

The customer must edit only the first 2 options in the following way:

Name: ereseller

APN: ereseller

- Then click on the 3 little dots and select Save
- Please highlight the circle next to "ereseller"
- Lastly, the customer can reboot the device.

## IMPORTANT! !!

If the Issue persists after adding the name and APN as "ereseller", you MUST set all these fields on the APN settings.

|                     |                                                                     |
|---------------------|---------------------------------------------------------------------|
| Name                | ereseller                                                           |
| APN                 | ereseller                                                           |
| Proxy               | Not set                                                             |
| Port                | Not set                                                             |
| Username            | Not set                                                             |
| Password            | Not set                                                             |
| Server              | Not set                                                             |
| MMSC                | <a href="http://mmsc.mobile.att.net">http://mmsc.mobile.att.net</a> |
| MMS proxy           | proxy.mobile.att.net                                                |
| MMS port            | 80                                                                  |
| MCC                 | 310                                                                 |
| MNC                 | 280                                                                 |
| Authentication type | Not set                                                             |
| APN type            | default,mms,supl,hipri                                              |
| APN protocol        | IPv4 /IPv6                                                          |
| Bearer              | Unspecified                                                         |
| MVNO Operator type  | GID                                                                 |
| MVNO Operator Value | 20FF                                                                |

**Note: After saving the APN, REBOOT THE DEVICE and test the Service**

## IPHONE TROUBLESHOOTING SETTINGS

1. Confirm that the phone is not network/carrier locked.
2. Toggle the device into airplane mode and wait 30 seconds. Then toggle airplane mode back off.
3. Confirm that there are no software updates available. Settings > General > Software Update – If any are available, download over Wi-Fi. iOS devices must be able to support iOS 17.0 or newer
4. If the iOS firmware has been updated to 17.0 (minimum supported), and data is still not working. (The user may potentially find a carrier update under Settings> General)
5. Check to ensure that data is turned on. Settings > Cellular > make sure cellular data is enabled
6. Further check that data is enabled. Settings > Cellular > Cellular data options – Make sure 4G/5G and VoLTE are enabled
7. Remove the SIM card from the device and then replace it into the device.
8. Reset Network Settings – Remove SIM card, go to Settings > General > Reset iPhone > Reset Network Settings. Once the phone fully restarts, add the SIM card back in.