Company Name	LoremIpsum	Project Title	Fossee
Group/Team Name	LoremIpsum	Subtitle	
Designer	LoremIpsum	Job Number	123
Date	18 /05 /2020	Client	LoremIpsum

1 Input Parameters

Module			Beam Coverplate Weld Connection	
MainModule			Moment Connection	
Moment(kNm)*			10.0	
Shear(kN)*			10.0	
Axial (kN) *			10.0	
Section				
	Beam Section *		NPB 270x135x30.7	
	Material *		E 250 (Fe 410 W)A	
	Ultimate strength, fu (MPa)		410	
	Yield Strength , fy (MPa)		250	
	Mass	30.73	Iz(mm4)	49173000.0
	Area(mm2) - A	3910.0	Iy(mm4)	3574200.0
	D(mm)	267.0	rz(mm)	112.10000000000001
	B(mm)	135.0	ry(mm)	30.2
	t(mm)	5.5	Zz(mm3)	368340.0
	T(mm)	8.7	Zy(mm3)	52950.0
	FlangeSlope	90	Zpz(mm3)	412490.0
	R1(mm)	1.5	Zpy(mm3)	52950.0
	R2(mm)	0.0		
Weld Details				
Weld Type			Fillet	
Type of weld fabrication			Shop Weld	
Material grade overwrite (MPa) Fu			410.0	

Company Name	LoremIpsum	Project Title	Fossee
Group/Team Name	LoremIpsum	Subtitle	
Designer	LoremIpsum	Job Number	123
Date	18 /05 /2020	Client	LoremIpsum

2 Design Checks

2.1 Member Capacity

Check	Required	Provided	Remarks
Axial Capacity Ac (kN)		$Ac = \frac{A * f_y}{\gamma_{m0} * 1000}$ $= \frac{3910.0 * 250}{1.1 * 1000}$ $= 888.64$	
Shear Capacity Sc (kN)		$S_c = \frac{A_v * f_y}{\sqrt{3} * \gamma_{mo} * 1000}$ $= \frac{249.6 * 5.5 * 250}{\sqrt{3} * 1.1 * 1000}$ $= 180.13327999999998$	
Plastic Moment Capacity Pmc (kNm)		$Pmc = \frac{\beta_b * Z_p * fy}{\gamma_{mo} * 1000000}$ $= \frac{1 * 85663 * 250}{1.1 * 1000000}$ $= 19.47$	
Moment Deformation Criteria Mdc (kNm)		$Mdc = \frac{1.5 * Z_e * fy}{1.1}$ $= \frac{1.5 * 368340.0 * 250}{1.1}$ $= 125.57$	
Moment Capacity Mc (kNm)		$M_c = min(Pmc, Mdc)$ $= min(19.47, 125.57)$ $= 19.47$	

Company Name	LoremIpsum	Project Title	Fossee
Group/Team Name	LoremIpsum	Subtitle	
Designer	LoremIpsum	Job Number	123
Date	18 /05 /2020	Client	LoremIpsum

2.2 Load Consideration

Check	Required	Provided	Remarks
Axial Load Au (kN)	$Ac_{min} = 0.3 * A_c$ $= 0.3 * 888.64$ $= 266.59$	$Au = max(A, Ac_{min})$ $= max(10.0, 266.59)$ $= 266.59$	Pass
Shear Load Vu (kN)	$Sc_{min} = 0.6 * A_c$ $= 0.6 * 180.13$ $= 108.08$	$Vu = max(V, Vc_{min})$ $= max(10.0, 108.08)$ $= 108.08$	Pass
Moment Load Mu (kNm)	$Mc_{min} = 0.5 * M_c$ $= 0.5 * 19.47$ $= 9.73$	$Mu = max(M, Mc_{min})$ $= max(10.0, 9.73)$ $= 10.0$	Pass
Forces Carried by Web		$A_w = Axial\ force\ in\ web$ $= \frac{(D - 2 * T) * t * Au}{A}$ $= \frac{(267.0 - 2 * 8.7) * 5.5 * 266.59}{3910.0}$ $= 93.6$ $M_w = Moment\ in\ web$ $= \frac{Z_w * Mu}{Z}$ $= \frac{85663 * 10.0}{412490.0}$ $= 2.08$	
Forces Carried by Flange		$A_f = Axial\ force\ in\ flange$ $= \frac{Au * B * T}{A}$ $= \frac{266.59 * 135.0 * 8.7}{3910.0}$ $= 80.08$ $M_f = Moment\ in\ flange$ $= Mu - M_w$ $= 10.0 - 2.08$ $= 7.92$ $F_f = flange\ force$ $= \frac{M_f * 1000}{D - T} + A_f$ $= \frac{7.92}{267.0 - 8.7} + 80.08$ $= 110.75$	

Company Name	LoremIpsum	Project Title	Fossee
Group/Team Name	LoremIpsum	Subtitle	
Designer	LoremIpsum	Job Number	123
Date	18 /05 /2020	Client	LoremIpsum

2.3 Weld Design Checks

Check	Required	Provided	Remarks
Min Weld Size (mm)	$Thickness\ of\ Thicker\ part$ $= max(8.7, 14.0)$ $= 14.0$ $IS800:2007\ cl.10.5.2.3\ Table21,$ $t_{w_{min}} = 5$	7	Pass
Max Weld Size (mm)	$Thickness\ of\ Thinner\ part$ $= Min(8.7, 14.0) = 8.7$ $t_{w_{max}} = 8.7$	7	Pass
Flange Weld Strength (N/mm)	$Stress = \frac{F_f * 1000}{F_{rl}}$ $= \frac{110.75 * 1000}{391}$ $= 283.2588987614436$	927.92	Pass

Company Name	LoremIpsum	Project Title	Fossee
Group/Team Name	LoremIpsum	Subtitle	
Designer	LoremIpsum	Job Number	123
Date	18 /05 /2020	Client	LoremIpsum

2.4 Flange Plate Check

Check	Required	Provided	Remarks
Min. Plate Height (mm)	50	$b_{fp} = B - 2 * sp$ $= 135.0 - 2 * 15$ $= 105$	Pass
Max. Plate Height (mm)	$b_{fp} = B - 2 * sp$ $= 135.0 - 2 * 15$ $= 105$	105	Pass
Min. Plate Length (mm)	105	$l_{fp} = [2 * (l_w + 2 * s) + g]$ $= [2 * (1502 * 7) + 10.0]$ $= 340$	Pass

Company Name	LoremIpsum	Project Title	Fossee
Group/Team Name	LoremIpsum	Subtitle	
Designer	LoremIpsum	Job Number	123
Date	18 /05 /2020	Client	LoremIpsum

3 3D View

Figure 1: 3D View