Company Name	LoremIpsum	Project Title	Fossee
Group/Team Name	LoremIpsum	Subtitle	
Designer	LoremIpsum	Job Number	123
Date	18 /05 /2020	Client	LoremIpsum

# 1 Input Parameters

Modu	ıle		Beam	Coverplate Weld Connection
MainMo	MainModule		Moment Connection	
Moment(l	(Nm)*			100.0
Shear(k	:N)*			10.0
Axial (k	N) *			10.0
	Section			
	Beam S	ection *		MB 600
	Mate	rial *		E 250 (Fe 410 W)A
т Ү	Ultimate stren	igth, fu (MPa)		410
	Yield Strengt	th , fy (MPa)		250
$(B-t)$ $\alpha$	Mass	121.0	Iz(mm4)	902480000.0
4 t	Area(mm2) -	15419.9999999	9 <b>99%</b> m4)	24790000.0
ZZ D	A			
	D(mm)	600.0	rz(mm)	242.0
R <sub>1</sub>	B(mm)	210.0	ry(mm)	40.0999999999994
В	t(mm)	12.0	Zz(mm3)	3008300.0
P V	T(mm)	20.3	Zy(mm3)	236000.0
	FlangeSlope	98	Zpz(mm3)	3454600.0
	R1(mm)	20.0	Zpy(mm3)	236000.0
	R2(mm)	10.0		
		Weld Details		
Weld Type Type of weld fabrication			Fillet	
		Shop Weld		
Material grade over	write (MPa) Fu			410.0

Company Name	LoremIpsum	Project Title	Fossee
Group/Team Name	LoremIpsum	Subtitle	
Designer	LoremIpsum	Job Number	123
Date	18 /05 /2020	Client	LoremIpsum

## 2 Design Checks

### 2.1 Member Capacity

Check	Required	Provided	Remarks
Axial Capacity Ac (kN)		$Ac = \frac{A * f_y}{\gamma_{m0} * 1000}$ $= \frac{15419.99999999998 * 250}{1.1 * 1000}$ $= 3504.55$	
Shear Capacity Sc (kN)		$S_c = \frac{A_v * f_y}{\sqrt{3} * \gamma_{mo} * 1000}$ $= \frac{559.4 * 12.0 * 250}{\sqrt{3} * 1.1 * 1000}$ $= 880.82657$	
Plastic Moment Capacity Pmc (kNm)		$Pmc = \frac{\beta_b * Z_p * fy}{\gamma_{mo} * 1000000}$ $= \frac{1 * 938785 * 250}{1.1 * 1000000}$ $= 213.36$	
Moment Deformation Criteria Mdc (kNm)		$Mdc = \frac{1.5 * Z_e * fy}{1.1}$ $= \frac{1.5 * 3008300.0 * 250}{1.1}$ $= 1025.56$	
Moment Capacity Mc (kNm)		$M_c = min(Pmc, Mdc)$ = $min(213.36, 1025.56)$ = $213.36$	

Company Name	LoremIpsum	Project Title	Fossee
Group/Team Name	LoremIpsum	Subtitle	
Designer	LoremIpsum	Job Number	123
Date	18 /05 /2020	Client	LoremIpsum

#### 2.2 Load Consideration

Check	Required	Provided	Remarks
	$Ac_{min} = 0.3 * A_c$	$Au = max(A, Ac_{min})$	
Axial Load Au (kN)	= 0.3 * 3504.55	= max(10.0, 1051.36)	Pass
	= 1051.36	= 1051.36	
	$Sc_{min} = 0.6 * A_c$	$Vu = max(V, Vc_{min})$	
Shear Load Vu (kN)	= 0.6 * 880.83	= max(10.0, 528.5)	Pass
	= 528.5	= 528.5	
	$Mc_{min} = 0.5 * M_c$	$Mu = max(M, Mc_{min})$	
Moment Load Mu (kNm)	= 0.5 * 213.36	= max(100.0, 106.68)	Pass
	= 106.68	= 106.68	
		$A_w = Axial \ force \ in \ web$	
		$= \frac{(D-2*T)*t*Au}{\Delta}$	
			100
		$= \frac{(600.0 - 2 * 20.3) * 12.0 * 105}{15410.0000000000000000000000000000000000$	1.36
		$ \begin{array}{r} - \\ 15419.9999999999999999999999999999999999$	
Forces Carried by Web		$M_w = Moment \ in \ web$	
		$=\frac{Z_w*Mu}{Z}$	
		$= \frac{938785 * 106.68}{3454600.0}$	
		= 28.99	
		$A_f = Axial \ force \ in \ flange$	
		$= \frac{Au * B * T}{A}$	
		$= \frac{1051.36 * 210.0 * 20.3}{15419.999999999998}$	
		= 290.66	
		$M_f = Moment \ in \ flange$	
		$= Mu - M_w$	
Forces Carried by Flange		= 106.68 - 28.99	
		= 77.69	
		$F_f = flange\ force$	
		$= \frac{M_f * 1000}{D - T} + A_f$	
		$=\frac{77.69}{600.0-20.3}+290.66$	
		=424.68	

Company Name	LoremIpsum	Project Title	Fossee
Group/Team Name	LoremIpsum	Subtitle	
Designer	LoremIpsum	Job Number	123
Date	18 /05 /2020	Client	LoremIpsum

#### 2.3 Weld Design Checks

Check	Required	Provided	Remarks
	Thickness of Thicker part $= max(20.3, 28.0)$		
Min Weld Size (mm)	$ = 28.0  IS800 : 2007 cl.10.5.2.3 Table 21,  tw_{min} = 6 $	16	Pass
Max Weld Size (mm)	$Thickness of Thinner part$ $= Min(20.3, 28.0) = 20.3$ $t_{w_{max}} = 20.3$	16	Pass
Flange Weld Strength (N/mm)	$Stress = \frac{F_f * 1000}{F_{rl}}$ $= \frac{424.68 * 1000}{540}$ $= 786.437897319835$	2120.95	Pass

Company Name	LoremIpsum	Project Title	Fossee
Group/Team Name	LoremIpsum	Subtitle	
Designer	LoremIpsum	Job Number	123
Date	18 /05 /2020	Client	LoremIpsum

#### 2.4 Flange Plate Check

Check	Required	Provided	Remarks
Min. Plate Height (mm)	50	$b_{fp} = B - 2 * sp$ $= 210.0 - 2 * 21$ $= 165$	Pass
Max. Plate Height (mm)	$b_{fp} = B - 2 * sp$ = 210.0 - 2 * 21 = 165	165	Pass
Min. Plate Length (mm)	165	$l_{fp} = [2 * (l_w + 2 * s) + g]$ $= [2 * (2052 * 16) + 10.0]$ $= 480$	Pass

Company Name	LoremIpsum	Project Title	Fossee
Group/Team Name	LoremIpsum	Subtitle	
Designer	LoremIpsum	Job Number	123
Date	18 /05 /2020	Client	LoremIpsum

### 3 3D View



Figure 1: 3D View