

# FLOATING SUCTION UNITS

Precision-engineered for purity, TheGAW FSUs redefine clean fluid extraction in every drop.

TheGAW's Floating Suction Units ensure efficient, contaminant-free fluid extraction from storage tanks. Designed to handle sludge and debris, they deliver clean results for both underground and above-ground tanks with unmatched versatility.

## KEY FEATURES & BENEFITS


- Materials: SS, CS, & Aluminum
- Floating Pontoon: Suspension
- Suction Height: Displayable
- Roof Integration: Internal/External
- Conflict Prevention: Special supports
- Sizes: 2"-18"
- Maintenance: Low, lubricated joints
- Customization: Tailored FSUs
- Warranty: 2 years

## TECHNICAL SPECIFICATION

Model	Diameter (inches)	Flow Rate (m³/h)	Pressure (Bar)	Material	Weight (kg)
TGFS2	2"	80	8	Stainless Steel	25
TGFS4	4"	100	10	Carbon Steel	40
TGFS6	6"	150	15	Aluminum	60
TGFS8	8"	200	12	Stainless Steel, Duplex	80
TGFS10	10"	300	10	Stainless Steel, Carbon	120

## Custom FSU Achievement

TheGAW's team has meticulously engineered five customized FSU units for a 30-meter tank, delivering them on an expedited timeline and ensuring quality with a comprehensive two-year warranty.



“TheGAW delivers innovative and cost-effective solutions, offering single and double-joint suction units tailored to meet diverse application requirements.”

Certificates & Standards

