



CATEGORY: BOLTING SOLUTIONS







## **KEY FEATURES OF APPT SERIES**

- Single-Acting, high performance tensioner pump.
- Accurately adjust output pressure in the range of 10,000~43,500 psi
- Easy to be connected with quick releasing couplings
- · Convenient to carry with a compact design
- Pressure up to 10,000 Psi / 700 bar, based on industrial applications.
- Compact automatic three stage flow, can start in high pressure.
- The high efficiency cooling system makes the pump suitable in extreme environments.

## **TECHNICAL SPECIFICATIONS**

MODEL	ATEP-20E	ATEP-20P
DRIVE MECHANISM	Electric	Pneumatic
MAX OUTPUT PRESSURE	2000 Bar	2000 Bar
TANK CAPACITY	5.5L	6L
FLOW(LOW-HIGH)	5.5-0.45L/min	5.5-0.45L/min
POWER	1.1KW	3KW
AIR IN	-	4 - 8 Bar
POWER SOURCE	220V/115V/250V	-
OUTPUT PORT	2x1/4" BSP	2x1/4" BSP
DIMENSIONS(mm)	419x292x434	419x267x434
WEIGHT(Kgs)	28	26

## **ADITIONAL ACCESSORIES**

- · High Pressure Hydraulic Hoses
- Quick Couplers
- · Pressure Gauges
- FRL
- Air Hose