

See discussions, stats, and author profiles for this publication at: <https://www.researchgate.net/publication/340599248>

# SKIN DISEASE RECOGNITION METHOD BASED ON IMAGE COLOR AND NEURAL NETWORK

Article · April 2020

CITATIONS

0

READS

229

1 author:



[Pravin Kshirsagar](#)

Avn Insitute of Engineering and Technology

75 PUBLICATIONS 156 CITATIONS

[SEE PROFILE](#)

Some of the authors of this publication are also working on these related projects:



A Novel Probabilistic-PSO Based Learning Algorithm for Optimization of Neural Networks for Benchmark Problems [View project](#)



Hybrid Heuristic Optimization for Benchmark Datasets [View project](#)

## SKIN DISEASE RECOGNITION METHOD BASED ON IMAGE COLOR AND NEURAL NETWORK

1.GUDURU DIVYA,2. DR.PRAVIN KSHIRSAGAR,3. NELIKANTI SREEJA, 4. KUKUDALA JHANSI,3&4.UG SCHOLAR,2. PROFESSOR& HEAD - ECE

DEPARTMENT OF ECE, AVN INSTITUTE OF ENGINEERING AND TECHNOLOGY, KOHEDA ROAD, IBRAHIMPATNAM(M), R.R.DIST-501510, HYDERABAD

### ABSTARCT:

Skin diseases have a serious impact on people's life and health. Current research proposes an efficient approach to identify singular type of skin diseases. It is necessary to develop automatic methods in order to increase the accuracy of diagnosis for multitype skin diseases. In this paper, three type skin diseases such as herpes, dermatitis, and psoriasis skin disease could be identified by a new recognition method. Initially, skin images were preprocessed to remove noise and irrelevant background by filtering and transformation.a deep neural network based ensemble method is experimented for automatic identification of skin disease from dermoscopic images.

### INTRODUCTION:

Composed of epidermis, dermis, and subcutaneous tissues, skin is the largest organ of human body, containing blood vessels, lymphatic vessels, nerves, and

muscles, which can perspire, perceive the external temperature, and protect the body. Covering the entire body, the skin can protect multiple tissues and organs in the body from external invasions including artificial skin damage, chemical damage, adventitious viruses, and individuals' immune system. Besides, skin can also avoid the loss of lipids together with water within epidermis and dermis so that skin barrier function can be stabilized [1]. In spite of defense and barrier function, skin is not indestructible in that skin tends to be constantly influenced by a variety of external and genetic factors. Currently, there are three main types of skin diseases appearing in human body, including viral skin diseases, fungal skin diseases, and allergic skin disease. Despite the fact that these types of skin diseases can be cured at present, these diseases indeed have brought trouble to patients' life. Nowadays, the majority of conclusions on the patients' existing symptoms are drawn mainly based on doctors' years of

experience or their own subjective judgments, which may lead to misjudgments and consequently delay the treatment of these. Therefore, it is of great theoretical significance and practical value to study how to extract symptoms of diverse skin diseases on the basis of modern science and technology. Under this circumstance, effective and accurate identification of the types of skin diseases can be achieved to prescribe treatment according to patients' symptoms [2]. Over the past few years, the image processing technique has achieved rapid development in medicine. Some equipment based on digital image technology has also been widely applied to people's everyday life, for instance, computed tomography (CT), digital subtraction angiography (DSA), and magnetic resonance imaging (MRI). Deeper research on this direction has been carried out by scholars all over the world. For example, the skin disease varicella was detected by Oyola and Arroyo [3] through image processing technique's color transformation, equalization as well as edge detection, and the image of varicella was eventually collected and classified through Hough transform. The final empirical results demonstrated that a better diagnosis was received in terms of detection on varicella, and preliminary test was also conducted on varicella and herpes zoster on that basis. Chung and Sapiro [4]

put forward a method to detect the image of skin lesions based on partial differential equation (PDE), with which a contour model of skin lesions was extracted on the basis of its morphological filtering through PDE. The classification of pigmented skin lesions with unaided eye is challenging, even for the highly experienced dermatologists. So, dermoscopy is used for visual inspection of the skin lesions in a better way. This device can magnify the inspected regions as well as eliminates the surface reflection of the skin which leads to improve the diagnostic accuracy. But in several occasions using dermatoscope a trained experts also fail to make correct prediction [1], [2]. Hence, several computer assisted automated approaches are proposed to analysis dermoscopy images [3]–[5]. The identification of skin disease from dermoscopy images are treated as an image classification problem. The tradition approach of image classification needs robust feature representation which are feed to the classifier for training. So, inspired by the medical diagnostic procedure several color, texture and shape features are used to characterize the skin lesion. However, it is very much difficult to develop robust feature representation to deal with the dermoscopy images obtained from different acquisition devices and captured in diverse illumination conditions [3]. This

draws the computer vision researchers to use deep convolutional neural networks. The convolutional neural network (CNN) [16][17][18][19][20] binds the feature extraction, feature selection and classification modules into a single unit. It can automatically extract discriminating features from the labelled images [6]. Hence, CNN produces unimaginable performance in several image classification problems. But the limitation of CNN is that it is data hungry [26][27][28][29][30]. So, to get rid of that, transfer learning is used [7]. The transfer learning approach is nothing but tricky initialization of the network weights. In transfer learning scheme, the network weights are initialized with the learnt weights of a CNN trained on another dataset [21][22][23][24][25]. Generally, a CNN trained on the imagenet classification challenge is used for that purpose. In this paper, ensemble of deep convolutional neural networks are used to classify the dermoscopy images into one of the seven disease classes- Melanoma, Melanocytic nevus, Basal cell carcinoma, Actinic keratosis, Benign keratosis, Dermatofibroma and Vascular lesion. We fine-tune three popular deep learning architectures namely- ResNet50 [8], DenseNet121 [9] and MobileNet-50 [10]. to predict the disease class. Finally, a majority-voting is applied on the basis of

the predicted class probability maps obtained from the trained classification networks.

## **DATASET**

In this research, the challenge dataset produced for the workshop ISIC 2018: Skin Lesion Analysis Towards Melanoma Detection<sup>1</sup> is used [11], [12]. In training set, there are a total of 10015 skin lesion images from seven skin diseases- Melanoma (1113), Melanocytic nevus (6705), Basal cell carcinoma (514), Actinic keratosis (327), Benign keratosis (1099), Dermatofibroma (115) and Vascular (142). The validation dataset consists of 193 images. Sample images from all seven lesion

## **EXISTING SYSTEM:**

- Skin tone is often combined with other cues like texture and edge features. This is achieved by breaking down the image into individual pixels and classifying them into skin colored and non-skin colored [1]. One simple method is to check if each skin pixel falls into a defined color range or values in some coordinates of a color space. There are many skin color spaces like

RGB, HSV, YCbCr, YIQ, YUV, etc. that are used for skin color segmentation


- K -means A clustering method for grouping similar data, that is popular for cluster analysis in data mining .K-means clustering[2] aims to partition observations on different categories. The problem occurs if the dataset is very large, complex and computational of clustering is difficult. So, the proposed method directly uses an ensemble of neural network models [10]where clustering is not used for better efficiency
- Image gradient The edge detector[15][26][27][28][29][30] in most of image processing models uses an image gradient algorithm for edge detection.Using Image Gradient algorithm various points are not detected accurately. Differentiating the background pixels and foreground pixels will not be that much accurate. For example, differentiating the skin and the background will be not accurate. This is the major disadvantage of using image gradient algorithm[3]. The proposed approach overcomes this issue. In the proposed system the

features are extracted first various values differentiate the background and foreground pixels.

- RGB color algorithm Unique features from the medical image are taken and are segmented using Histogram algorithm. The diseases are classified based on the Histogram values[4] and tolerance level value of the image. We taking into consideration of mean values[4] of images RGB(RED, GREEN, BLUE). The values are calculated and the background of the images is considered to be black. This is not applicable for all images where the error in mean values may occur and the background of the image may not be black always. The proposed model does not take mean values and the features are not extracted based on the histogram. So the possibility of the wrong classification of the image is avoided.

**PROPOSED METHODOLOGY** In this paper, we used ensemble of three trained convolutional neural networks to identify the skin lesion. Ensemble learning is nothing but aggregation of predicted scores obtained from different classifiers. It is used for combining multiple weak

classifiers to develop a stronger classifier. The individual classifiers can be constructed in several ways such as (a) using different classification algorithms [31][32][33][34][35][36], (b) training same classifier with different hyperparameters (c) using different training sets. In this paper, we used three state-of the art convolutional neural network models namely ResNet50 [8], DenseNet121 [9] and MobileNet [10]. The success of these networks in image net classification challenge motivate us for choosing them. The training dataset suffers from data imbalance. We tackle this problem by back propagating the weighted loss from the loss layer. For classifier model construction, we fine-tuned the pre-trained weights of these models separately. Finally, the average predicted class probabilities obtained from these trained networks are used to decide the class label of the test image. Thus an input image is classified into one of the specified lesion classes.



## RESULTS:




Fig (1)




Fig (2)







Fig (3)




Fig(4)




Fig(5)



Fig(6)



Fig(7)



Fig(8)

Fig(1)-fig(7) Training and Testing iteration Values Of an Data Set, Fig(8) Skin Disease Detection

## CONCLUSION:

We used 10% of the training images as validation images. The validation images are used for deciding the training hyper parameters. Before fine-tuning a pre-trained model, firstly the last layer (softmax classification layer) is removed and then the number of node in last layer is set to 7 (as we are dealing with 7 class classification problem). Firstly, except the the last layer all other layers are freed and the network is trained with a learning



rate of 0.01, for 10 epochs with early stopping having a patience of 5 (i.e., if there is no improvement in validation loss after 5 epochs the backpropagation algorithm automatically terminates). After that, all layers are unfreezed and fine-tuned with a learning rate of 0.001 for 100 epochs. This time we used early stopping having a patience of 10. Horizontal and vertical flipping is used for augmentation. The performance of the developed classifiers are scored using a normalized multi-class accuracy metric (balanced across categories). This scoring is obtained from the online portal of the challenge

## REFERENCES

- [1] K. H., P. H., W. K., and B. M., "Diagnostic accuracy of dermoscopy," *The Lancet Oncology*, vol. 3, no. 3, pp. 159–165, 2002.
- [2] M. Vestergaard, H. P. Macaskill, P. and, and S. Menzies, "Dermoscopy compared with naked eye examination for the diagnosis of primary melanoma: a meta-analysis of studies performed in a clinical setting," *Br J Dermatol*, vol. 159, pp. 669–676, 2008.
- [3] C. Barata, M. E. Celebi, and J. S. Marques, "Improving dermoscopy image classification using color constancy," *IEEE journal of biomedical and health informatics*, vol. 19, no. 3, pp. 1146–1152, 2015.
- [4] F. E. S. Alencar, D. C. Lopes, and F. M. M. Neto, "Development of a system classification of images dermoscopic for mobile devices," *IEEE Latin America Transactions*, vol. 14, no. 1, pp. 325–330, Jan 2016.
- [5] N. C. F. Codella, Q. B. Nguyen, S. Pankanti, D. A. Gutman, B. Helba, A. C. Halpern, and J. R. Smith, "Deep learning ensembles for melanoma recognition in dermoscopy images," *IBM Journal of Research and Development*, vol. 61, no. 4/5, pp. 5:1–5:15, July 2017.
- [6] A. Krizhevsky, I. Sutskever, and G. E. Hinton, "Imagenet classification with deep convolutional neural networks," in *Advances in neural information processing systems*, 2012, pp. 1097–1105.
- [7] A. Pal, A. Chaturvedi, U. Garain, A. Chandra, and R. Chatterjee, "Severity grading of psoriatic plaques using deep cnn based multi-task learning," in *2016 23rd International Conference on Pattern Recognition (ICPR)*, Dec 2016, pp. 1478–1483.
- [8] K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," in *Proceedings of the IEEE*



conference on computer vision and pattern recognition, 2016, pp. 770–778.

[9] G. Huang, Z. Liu, L. Van Der Maaten, and K. Q. Weinberger, “Densely connected convolutional networks.” in CVPR, vol. 1, no. 2, 2017, p. 3.

[10] A. G. Howard, M. Zhu, B. Chen, D. Kalenichenko, W. Wang, T. Weyand, M. Andreetto, and H. Adam, “Mobilenets: Efficient convolutional neural networks for mobile vision applications,” arXiv preprint arXiv:1704.04861, 2017.

[11] Bhuvaneswari Amma N.G., “Cardiovascular Disease Prediction System using Genetic Algorithm and Neural Network”, International Conference on Computing, Communication and Applications .IEEE-2012.

[12] Nilakshi P. Waghulde, Nilima P. Patil, “Genetic Neural Approach for Heart Disease Prediction”, International Journal of Advanced Computer Research Volume-4 Number-3 Issue-16 September-2014.

[13] Warsuzarina Mat Jubadi, Siti FaridatulAisyahMohdSahak, “Heartbeat Monitoring Alert via SMS” 2009 IEEE Symposium on Industrial

Electronics and Applications (ISIEA 2009), October 4-6, 2009, Kuala Lumpur, Malaysia.

[14] Purnima, Puneet Singh, “Zigbee and GSM Based Patient Health Monitoring System”, International Conference on Electronics and Communication System (IECS -2014).

[15] Nisha singh, Sr. Asst. Prof. Ravi Mishra, “Microcontroller Based Wireless Temperature and Heart Beat ReadOut”, IOSR Journal of Engineering (IOSRJEN), (Jan. 2013), PP 01 -06.

[16]. Dr.SudhirAkojwar, Pravin Kshirsagar, “A Novel Probabilistic-PSO Based Learning Algorithm for Optimization of Neural Networks for Benchmark Problems”, WSEAS International conference on Neural Network-2016, Rome, Italy

[17]. Dr. Sudhir Akojwar, Pravin Kshirsagar, “Performance Evolution of Optimization Techniques for Mathematical Benchmark Functions”, WSEAS International conference on Neural Network-2016, Rome ,Italy(Published in International Journal of Computer)

[18].Pravin Kshirsagar, Dr. Sudhir Akojwar, “A hybridized neural network and optimization algorithms for prediction & classification of neurological disorders”,

Int. Journal of Biomedical Engineering and Technology, Vol. 28, No. 4, 2018.

[19] Pravin Kshirsagar, Dr. Sudhir Akojwar, "Hybrid Heuristic Optimization for Benchmark Datasets", International Journal of Computer Application, Volume 146-No, 7, July 2016

[20]. Pravin Kshirsagar, Dr. Sudhir Akojwar, "Classification Human Motion using EEG Signals", International Journal of Computer Application, Volume 146-No, 7, July 2016

[21]. Pravin Kshirsagar, Dr. Sudhir Akojwar, "Classification & Detection of Neurological Disorders using ICA & AR as Feature Extractor", International Journal Series in Engineering Science (**IJSSES**), Volume 1, Issue 1, 2015.

[22]. Pravin Kshirsagar, Dr. Sudhir Akojwar, "Novel Approach for Classification and Prediction of Non Linear Chaotic Databases", International IEEE Conference on Electrical, Electronics, and Optimization Techniques (ICEEOT) – 2016.

[23] Pravin Kshirsagar, Dr. Sudhir Akojwar, "Prediction of Neurological Disorders using PSO with GRNN", IEEE SCOPES International Conference, 2016

[24] Pravin Kshirsagar, Dr. Sudhir Akojwar, "Classification and Prediction of Epilepsy using FFBNPNN with PSO", IEEE International Conference on Communication Networks, 2015

[25] Pravin Kshirsagar, Dr. Sudhir Akojwar, "Chaotic Time Series Prediction using correlation Dimension and Adaptive Neuro-Fuzzy Inference System International Journal of Engineering Research and General Science Volume 3, Issue 5, September-October, 2015, ISSN 2091-2730.

[26] Pravin Kshirsagar, Dr. Sudhir Akojwar, "Hybrid Model for Classification and Detection of Neurological Disorders", International Journal of Advanced Research in Computer and Communication Engineering Vol. 4, Issue 7, July 2015.

[27] Pravin Kshirsagar, Dr. Sudhir Akojwar, "Detection of Neurological Disorders Using Soft Computing Technique", International Journal of Advanced Research in Electronics and Communication Engineering (IJARECE) Volume 4, Issue 7, July 2015

[28] Dr. Sudhir Akojwar, Pravin Kshirsagar, Vijetalaxmi Pai "Feature Extraction of EEG Signals using Wavelet and Principal Component analysis", National Conference on Research Trends In Electronics, Computer Science & Information Technology and Doctoral Research Meet, Feb 21st & 22nd, 2014

[29] Pravin Kshirsagar, Nagaraj Balakrishnan & Arpit Deepak Yadav, "Modelling of optimised neural network for classification and prediction of benchmark datasets," Computer Methods in

Biomechanics and Biomedical Engineering:  
Imaging & Visualization, DOI:  
10.1080/21681163.2019.1711457,2020

[31] Pravin Kshirsagar, Dr. Sudhir Akojwar(2017), “Classification of ECG-Signals using Artificial Neural Networks”, Research Gate.

[32. Pravin Kshirsagar, AmbarishSalodkar, Roshan Bhaiswar,” Iris Recognition Using Stationary Wavelet Transform and Artificial Neural Network”, International Journal of Engineering and Innovative Technology (IJEIT) Volume 1, Issue 3, March 2012.

[33] Anil N Rakhonde, Pravin RK Shirsagar, Swagat M Marve, “Diabetes Retinopathy Disease Detection using Convolution Neural Network”, Test Engineering and Management, January-February 2020 ISSN: 0193-4120, Vol. 81, Page No. 4431 – 4434.

[34] PravinR Kshirsagar, Anil N Rakhonde, Pranav Chippalkatti,” MRI IMAGE BASED BRAIN TUMOR DETECTION USING MACHINE LEARNING”, Test Engineering and Management, January-February 2020 ISSN: 0193-4120, Vol. 81, Page No. 3672 – 3680.

[35]Pravin R. Kshirsagar, Pranav P. Chippalkatti ,Swagat M. Karve,”Optimum Spread for Generalized Regression Neural Network using Particle Swarm Intelligence”,Jour of Adv Research in Dynamical & Control Systems, Vol. 10, 09-Special Issue,Pp. 170-179, 2018.

[36] Pravin R. Kshirsagar, Pranav P. Chippalkatti ,Swagat M. Karve,”Performance Optimization of Neural Network using GA Incorporated PSO”,Jour of Adv Research in Dynamical & Control Systems, Vol. 10, 09-Special Issue, Pp.156-169,2018.