EIGRP:


Activities
PacketTracer
Feb 6 12:04 PM
Cisco Packet Tracer - /home/administrator/Downloads/csg124-02-EIGRP-configuration-practice-topology-configured.pkt
File Edit Options View Tools Extensions Window Help
Logical
Physical
PC0
Physical Config Desktop Programming Attributes
Command Prompt
Cisco Packet Tracer PC Command Line 1.0
C:\>ping 20.0.0.2
Pinging 20.0.0.2 with 32 bytes of data:
Request timed out.
Reply from 20.0.0.2: bytes=32 time=1ms TTL=124
Reply from 20.0.0.2: bytes=32 time<1ms TTL=124
Reply from 20.0.0.2: bytes=32 time<1ms TTL=124
Ping statistics for 20.0.0.2:
Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
Approximate round trip times in milli-seconds:
Minimum = 0ms, Maximum = 1ms, Average = 0ms
C:\>tracert 20.0.0.2
Tracing route to 20.0.0.2 over a maximum of 30 hops:
1 0 ms 0 ms 0 ms 10.0.0.1
2 0 ms 0 ms 0 ms 192.168.1.2
3 0 ms 0 ms 0 ms 192.168.1.6
4 0 ms 0 ms 0 ms 192.168.1.10
5 0 ms 0 ms 0 ms 20.0.0.2
Trace complete.
C:\>
Top
New
Delete
Toggle PDU List Window
ISR4331

OSPF:


Activities
PacketTracer
Feb 6 12:35 PM
Cisco Packet Tracer - /home/administrator/Downloads/packet-tracer-lab-with-ospf-configuration.pkt
File Edit Options View Tools Extensions Window Help
Logical
Physical
PC0
Physical Config Desktop Programming Attributes
Command Prompt
Cisco Packet Tracer PC Command Line 1.0
C:\>ping 50.0.0.2
Pinging 50.0.0.2 with 32 bytes of data:
Request timed out.
Reply from 50.0.0.2: bytes=32 time<1ms TTL=125
Reply from 50.0.0.2: bytes=32 time<1ms TTL=125
Reply from 50.0.0.2: bytes=32 time<1ms TTL=125
Ping statistics for 50.0.0.2:
Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
Approximate round trip times in milli-seconds:
Minimum = 0ms, Maximum = 0ms, Average = 0ms
C:\>tracert 50.0.0.2
Tracing route to 50.0.0.2 over a maximum of 30 hops:
1 0 ms 0 ms 0 ms 10.0.0.1
2 0 ms 0 ms 0 ms 20.0.0.2
3 0 ms 1 ms 0 ms 40.0.0.2
4 0 ms 0 ms 0 ms 50.0.0.2
Trace complete.
C:\>
Top
Scenario 0
New
Delete
Toggle PDU List Window
ISR4331

Configuration of WLAN using static IP addressing:



Configuration of WLAN using DHCP and MAC filtering: