

# Control Systems

G V V Sharma\*

CONTENTS		9	Phase Margin	3
<b>1</b>	<b>Signal Flow Graph</b>	1	<b>10</b>	<b>Oscillator</b>
1.1	Mason's Gain Formula . . .	1	10.1	Introduction . . . . .
1.2	Matrix Formula . . . . .	1	10.2	Example . . . . .
<b>2</b>	<b>Bode Plot</b>	1	<i>Abstract</i> —This manual is an introduction to control systems based on GATE problems. Links to sample Python codes are available in the text.	
2.1	Introduction . . . . .	1	Download python codes using	
2.2	Example . . . . .	1	svn co https://github.com/gadepall/school/trunk/control/codes	
<b>3</b>	<b>Second order System</b>	1		
3.1	Damping . . . . .	1		
3.2	Example . . . . .	1		
3.3	Settling Time . . . . .	1		
<b>4</b>	<b>Routh Hurwitz Criterion</b>	3		
4.1	Routh Array . . . . .	3	1 SIGNAL FLOW GRAPH	
4.2	Marginal Stability . . . . .	3	1.1 Mason's Gain Formula	
4.3	Stability . . . . .	3	1.2 Matrix Formula	
4.4	Example . . . . .	3	2 BODE PLOT	
<b>5</b>	<b>State-Space Model</b>	3	2.1 Introduction	
5.1	Controllability and Observability . . . . .	3	2.2 Example	
5.2	Second Order System . . . . .	3	3 SECOND ORDER SYSTEM	
5.3	Example . . . . .	3	3.1 Damping	
5.4	Example . . . . .	3	3.2 Example	
5.5	Example . . . . .	3	3.3 Settling Time	
<b>6</b>	<b>Nyquist Plot</b>	3	3.3.1. Find the closed loop transfer function for the system in Fig. given that	
6.1	Introduction . . . . .	3		
6.2	Example . . . . .	3		
<b>7</b>	<b>Compensators</b>	3	$G(s) = \frac{1}{s^2 + 2s} \quad (3.3.1.1)$	
7.1	Phase Lead . . . . .	3		
7.2	Example . . . . .	3		
<b>8</b>	<b>Gain Margin</b>	3		
8.1	Introduction . . . . .	3		
8.2	Example . . . . .	3		

\*The author is with the Department of Electrical Engineering, Indian Institute of Technology, Hyderabad 502285 India e-mail: gadepall@iith.ac.in. All content in this manual is released under GNU GPL. Free and open source.




Fig. 3.3.1

**Solution:** The closed loop transfer function is

$$H(s) = \frac{kG(s)}{1 + kG(s)} \quad (3.3.1.2)$$

$$= \frac{k}{s^2 + 2s + k} \quad (3.3.1.3)$$

after substituting from (3.3.1.1).

3.3.2. Find the step response of the system.

**Solution:** The characteristics of the poles of transfer function describes the property of the transfer function.

Calculating poles :

$$s^2 + 2s + k = 0 \quad (3.3.2.1)$$

$$s = \frac{-2 \pm \sqrt{(-2)^2 - 4(1)(k)}}{2(1)} \quad (3.3.2.2)$$

$$s = -1 \pm \sqrt{1 - k} \quad (3.3.2.3)$$

Calculating step response for a general damping system (3.3.1.3) :

$$X(s) = \frac{1}{s} \quad (3.3.2.4)$$

$$Y(s) = H(s)X(s) \quad (3.3.2.5)$$

$$= \frac{k}{s^2 + 2s + k} \frac{1}{s} \quad (3.3.2.6)$$

$$\begin{aligned} y(t) &= u(t) + \frac{k}{(2\sqrt{1-k})(-1 + \sqrt{1-k})} e^{(-1+\sqrt{1-k})t} u(t) \\ &+ \frac{k}{(2\sqrt{1-k})(1 + \sqrt{1-k})} e^{(-1-\sqrt{1-k})t} u(t) \end{aligned} \quad (3.3.2.7)$$

Over Damped System:

For the closed loop transfer function (3.3.1.3) to be Over damped system, poles should be Real and Distinct, this happens when  $k$  is less than 1.

Under Damped System:

For the closed loop transfer function (3.3.1.3) to be Under damped system, poles should be Complex and Conjugate, this happens when  $k$  is greater than 1.

Critical Damped System:

For the closed loop transfer function (3.3.1.3) to be Critical damped system, poles should be Real at same location, this happens when  $k$  is 1.

3.3.3. Find steady state response using the final value theorem.

**Solution:**

$$\lim_{t \rightarrow \infty} y(t) = \lim_{s \rightarrow 0} sY(s) \quad (3.3.3.1)$$

$$= \lim_{s \rightarrow 0} s \frac{k}{s^2 + 2s + k} \frac{1}{s} \quad (3.3.3.2)$$

$$= \lim_{s \rightarrow 0} \frac{k}{s^2 + 2s + k} \quad (3.3.3.3)$$

$$= \frac{k}{k} = 1 \quad (3.3.3.4)$$

3.3.4. Find the settling time in terms of 'k' .

**Solution:**

$$0.98 < y(t) < 1.02 \quad (3.3.4.1)$$

$$\begin{aligned} 0.98 < u(t) + \frac{k}{(2\sqrt{1-k})(-1 + \sqrt{1-k})} e^{(-1+\sqrt{1-k})t} u(t) \\ + \frac{k}{(2\sqrt{1-k})(1 + \sqrt{1-k})} e^{(-1-\sqrt{1-k})t} u(t) < 1.02 \end{aligned} \quad (3.3.4.2)$$

On further simplifying (3.3.4.2)

$$\begin{aligned} -0.02 < \frac{-1}{\sqrt{1-k}} e^{-t} \left[ \sinh(\sqrt{1-k})t + \sqrt{1-k} \cosh(\sqrt{1-k})t \right] < 0.02 \end{aligned} \quad (3.3.4.3)$$

## 4 ROUTH HURWITZ CRITERION

### *4.1 Routh Array*

### *4.2 Marginal Stability*

### *4.3 Stability*

### *4.4 Example*

## 5 STATE-SPACE MODEL

### *5.1 Controllability and Observability*

### *5.2 Second Order System*

### *5.3 Example*

### *5.4 Example*

### *5.5 Example*

## 6 NYQUIST PLOT

### *6.1 Introduction*

### *6.2 Example*

## 7 COMPENSATORS

### *7.1 Phase Lead*

### *7.2 Example*

## 8 GAIN MARGIN

### *8.1 Introduction*

### *8.2 Example*

## 9 PHASE MARGIN

## 10 OSCILLATOR

### *10.1 Introduction*

### *10.2 Example*