

```
In [1]: import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import itertools
```

```
In [3]: models = ['Model 1', 'Model 2', 'Model 3', 'Model 4']

# Labeled Classes
labels=[0,1,2]

# Class Names
# Setosa = 0, Versicolor = 1, Virginica = 2
classes = ['Setosa', 'Versicolor', 'Virginica']


df = pd.read_csv(r'C:\Users\309962\Desktop\IrisSample.csv')
```

```
In [4]: df.head(15)
```

Out[4]:


	sepal_length	sepal_width	petal_length	petal_width	class	NumericClass	Model1_Prediction
0	5.8	4.0	1.2	0.2	Iris-setosa	0	(
1	5.7	4.4	1.3	0.4	Iris-setosa	0	.
2	5.1	3.4	1.5	0.2	Iris-setosa	0	(
3	5.4	3.9	1.7	0.4	Iris-setosa	0	(
4	4.3	3.0	1.1	0.1	Iris-setosa	0	.
5	4.9	2.4	3.3	1.0	Iris-versicolor	1	.
6	5.9	3.0	4.2	1.5	Iris-versicolor	1	.
7	6.6	3.0	4.4	1.4	Iris-versicolor	1	;
8	5.0	2.3	3.3	1.0	Iris-versicolor	1	.
9	6.2	2.9	4.3	1.3	Iris-versicolor	1	.
10	5.8	2.7	5.1	1.9	Iris-virginica	2	.
11	7.2	3.6	6.1	2.5	Iris-virginica	2	.
12	6.4	3.2	5.3	2.3	Iris-virginica	2	;
13	7.4	2.8	6.1	1.9	Iris-virginica	2	;
14	6.1	2.6	5.6	1.4	Iris-virginica	2	;

```
In [5]: plt.figure()  
plt.scatter(df.index,df['NumericClass'],label='Actual')  
plt.legend(loc=4)  
plt.yticks([0,1,2])  
plt.xlabel('Sample')  
plt.ylabel('Class')  
plt.show()
```



In [6]:





```
# Compare performance of Actual and Model 1 Prediction
plt.figure()
plt.scatter(df.index,df['NumericClass'],label='Actual')
plt.scatter(df.index,df['Model1_Prediction'],label='Model 1',marker='^')
plt.legend(loc=4)
plt.yticks([0,1,2])
plt.xlabel('Sample')
plt.ylabel('Class')
plt.show()
```



```
In [7]: plt.figure(figsize=(10,10))

for idx, model in enumerate(models):
    plt.subplot(2,2,idx+1)

    plt.scatter(df.index,df['NumericClass'],label='Actual')
    plt.scatter(df.index,df[model.replace(' ','') + '_Prediction'],
                label=model,marker='^')
    plt.yticks([0,1,2])
    plt.legend(loc=4)
    plt.xlabel('Sample')
    plt.ylabel('Class')
```



```
In [8]: from sklearn.metrics import classification_report, confusion_matrix
```

```

In [9]: # Reference:
# https://scikit-learn.org/stable/auto_examples/model_selection/plot_confusion_ma
def plot_confusion_matrix(cm, classes,
                           normalize=False,
                           title='Confusion matrix',
                           cmap=plt.cm.Blues):
    """
    This function prints and plots the confusion matrix.
    Normalization can be applied by setting `normalize=True`.
    """
    if normalize:
        cm = cm.astype('float') / cm.sum(axis=1)[:, np.newaxis]
        #print("Normalized confusion matrix")
    #else:
    #    print('Confusion matrix, without normalization')

    #print(cm)

    plt.imshow(cm, interpolation='nearest', cmap=cmap)
    plt.title(title)
    plt.colorbar()
    tick_marks = np.arange(len(classes))
    plt.xticks(tick_marks, classes, rotation=45)
    plt.yticks(tick_marks, classes)

    fmt = '.2f' if normalize else 'd'
    thresh = cm.max() / 2.
    for i, j in itertools.product(range(cm.shape[0]), range(cm.shape[1])):
        plt.text(j, i, format(cm[i, j], fmt),
                 horizontalalignment="center",
                 color="white" if cm[i, j] > thresh else "black")

    plt.ylabel('True label')
    plt.xlabel('Predicted label')
    plt.tight_layout()

```

```

In [10]: # Compute confusion matrix
cnf_matrix = confusion_matrix(df['NumericClass'],
                              df['Model1_Prediction'], labels=labels)

```

```

In [11]: cnf_matrix


```

```


Out[11]: array([[3, 2, 0],
                [0, 4, 1],
                [0, 2, 3]], dtype=int64)

```

```
In [12]: # Plot confusion matrix
plt.figure()
plot_confusion_matrix(cnf_matrix, classes=classes,
                      title='Model 1 Confusion matrix - Count')
```



```
In [13]: # Plot normalized confusion matrix (ratio)
plt.figure()
plot_confusion_matrix(cnf_matrix, classes=classes,
                      title='Model 1 Confusion matrix - Fraction', normalize=True)
```







In [14]:

```
# Plot confusion matrix
# Show actual counts
for model in models:
    #print(model)
    cnf_matrix = confusion_matrix(df['NumericClass'],
                                  df[model.replace(' ', '') + '_Prediction'],
                                  labels=labels)

    np.set_printoptions(precision=2)

    # Plot non-normalized confusion matrix
    plt.figure()
    plot_confusion_matrix(cnf_matrix, classes=classes,
                          title= model + ' Confusion matrix - Count', normalize=False
```









In [15]:

```
# Compute confusion matrix
# Show Ratio
for model in models:
    #print(model)
    cnf_matrix = confusion_matrix(df['NumericClass'],
                                  df[model.replace(' ', '_') + '_Prediction'], label
                                  np.set_printoptions(precision=2)

    # Plot non-normalized confusion matrix
    plt.figure()
    plot_confusion_matrix(cnf_matrix, classes=classes,
                          title= model + ' Confusion matrix - Fraction', normalize=True
```






```
In [16]: # Using SKLearn classification report
# Micro vs Macro Average
# Reference:
# https://datascience.stackexchange.com/questions/15989/micro-average-vs-macro-a
for model in models:
    print(model)
    print(classification_report(
        df['NumericClass'],
        df[model.replace(' ', '_') + '_Prediction'],
        labels=labels,
        target_names=classes))
```

Model 1

	precision	recall	f1-score	support
Setosa	1.00	0.60	0.75	5
Versicolor	0.50	0.80	0.62	5
Virginica	0.75	0.60	0.67	5
avg / total	0.75	0.67	0.68	15

Model 2

	precision	recall	f1-score	support
Setosa	0.00	0.00	0.00	5
Versicolor	0.33	1.00	0.50	5
Virginica	0.00	0.00	0.00	5
avg / total	0.11	0.33	0.17	15

Model 3

	precision	recall	f1-score	support
Setosa	1.00	1.00	1.00	5
Versicolor	0.60	0.60	0.60	5
Virginica	0.60	0.60	0.60	5
avg / total	0.73	0.73	0.73	15

Model 4

	precision	recall	f1-score	support
Setosa	0.20	0.20	0.20	5
Versicolor	0.17	0.20	0.18	5
Virginica	0.25	0.20	0.22	5
avg / total	0.21	0.20	0.20	15

C:\ProgramData\Anaconda3\lib\site-packages\sklearn\metrics\classification.py:1135: UndefinedMetricWarning: Precision and F-score are ill-defined and being set to 0.0 in labels with no predicted samples.
'precision', 'predicted', average, warn_for)

Summary

Macro average = Treat all classes equally. Average of individual class scores

Weighted average = Take frequency of the classes into consideration.

Weighted Average is recommended if there is uneven class distribution

In this example, Weighted Average of Model 1 and Model 3 are highest.

Reference:

<https://datascience.stackexchange.com/questions/15989/micro-average-vs-macro-average-performance-in-a-multiclass-classification-settin>

<https://docs.aws.amazon.com/machine-learning/latest/dg/multiclass-classification.html>