

Assignment: Investigating an Incident - Real World

Name: Aastha Thakker

Roll No. 250103002004

Sem: 2

Subject: Network Security

Course: MSc Cyber Security

Timing & Performance

SWITCH	EXAMPLE	DESCRIPTION
-T0	nmap 192.168.1.1 -T0	Paranoid (0) Intrusion Detection System evasion
-T1	nmap 192.168.1.1 -T1	Sneaky (1) Intrusion Detection System evasion
-T2	nmap 192.168.1.1 -T2	Polite (2) slows down the scan to use less bandwidth and use less target machine resources
-T3	nmap 192.168.1.1 -T3	Normal (3) which is default speed
-T4	nmap 192.168.1.1 -T4	Aggressive (4) speeds scans; assumes you are on a reasonably fast and reliable network
-T5	nmap 192.168.1.1 -T5	Insane (5) speeds scan; assumes you are on an extraordinarily fast network

```
(aastha@kali)-[~]
$ nmap scanme.nmap.org -T4 -F
Starting Nmap 7.98 ( https://nmap.org ) at 2026-02-24 05:15 -0500
Nmap scan report for scanme.nmap.org (45.33.32.156)
Host is up (0.12s latency).
Other addresses for scanme.nmap.org (not scanned): 2600:3c01::f03c:91ff:fe18:bb2f
Not shown: 94 closed tcp ports (reset)
PORT      STATE SERVICE
22/tcp    open  ssh
80/tcp    open  http
119/tcp   filtered nntp
445/tcp   filtered microsoft-ds
2000/tcp  open  cisco-sccp
5060/tcp  open  sip

Nmap done: 1 IP address (1 host up) scanned in 6.67 seconds
```

```
(aastha@kali)-[~]
$ nmap scanme.nmap.org -T3 -F
Starting Nmap 7.98 ( https://nmap.org ) at 2026-02-24 05:15 -0500
Nmap scan report for scanme.nmap.org (45.33.32.156)
Host is up (0.047s latency).
Other addresses for scanme.nmap.org (not scanned): 2600:3c01::f03c:91ff:fe18:bb2f
Not shown: 95 filtered tcp ports (no-response)
PORT      STATE SERVICE
22/tcp    open  ssh
80/tcp    open  http
113/tcp   closed ident
2000/tcp  open  cisco-sccp
5060/tcp  open  sip

Nmap done: 1 IP address (1 host up) scanned in 3.14 seconds
```

```

(aastha@kali)-[~]
$ nmap scanme.nmap.org -T5 -F
Starting Nmap 7.98 ( https://nmap.org ) at 2026-02-24 05:15 -0500
Stats: 0:00:01 elapsed; 0 hosts completed (1 up), 1 undergoing SYN Stealth Scan
SYN Stealth Scan Timing: About 5.00% done; ETC: 05:15 (0:00:19 remaining)
Nmap scan report for scanme.nmap.org (45.33.32.156)
Host is up (0.10s latency).
Other addresses for scanme.nmap.org (not scanned): 2600:3c01::f03c:91ff:fe18:bb2f
Not shown: 95 filtered tcp ports (no-response)
PORT      STATE SERVICE
22/tcp    open  ssh
80/tcp    open  http
113/tcp   closed ident
2000/tcp  open  cisco-sccp
5060/tcp  open  sip

Nmap done: 1 IP address (1 host up) scanned in 3.86 seconds

```

Timing and Performance Switches

WITCH	EXAMPLE INPUT	DESCRIPTION
-host-timeout <time>	1s; 4m; 2h	Give up on target after this long
-min-rtt-timeout/max-rtt-timeout/initial-rtt-timeout <time>	1s; 4m; 2h	Specifies probe round trip time
-min-hostgroup/max-hostgroup <size><size>	50; 1024	Parallel host scan group sizes

-min-parallelism/max-parallelism <numprobes>	10; 1	Probe parallelization
-max-retries <tries>	3	Specify the maximum number of port scan probe retransmissions
-min-rate <number>	100	Send packets no slower than <number> per second
-max-rate <number>	100	Send packets no faster than <number> per second

```
(aastha@kali)-[~]
$ nmap scanme.nmap.org -host-timeout 5
Starting Nmap 7.98 ( https://nmap.org ) at 2026-02-24 05:17 -0500
Nmap scan report for scanme.nmap.org (45.33.32.156)
Host is up (0.073s latency).
Other addresses for scanme.nmap.org (not scanned): 2600:3c01::f03c:91ff:fe18:bb2f
Skipping host scanme.nmap.org (45.33.32.156) due to host timeout
Nmap done: 1 IP address (1 host up) scanned in 5.24 seconds
```

```
(aastha@kali)-[~]
$ nmap scanme.nmap.org -max-retries 3 -F
Starting Nmap 7.98 ( https://nmap.org ) at 2026-02-24 05:22 -0500
Nmap scan report for scanme.nmap.org (45.33.32.156)
Host is up (0.044s latency).
Other addresses for scanme.nmap.org (not scanned): 2600:3c01::f03c:91ff:fe18:bb2f
Not shown: 96 filtered tcp ports (no-response)
PORT      STATE SERVICE
22/tcp    open  ssh
80/tcp    open  http
2000/tcp  open  cisco-sccp
5060/tcp  open  sip

Nmap done: 1 IP address (1 host up) scanned in 3.35 seconds
```

```
(aastha@kali)-[~]
$ nmap scanme.nmap.org -max-rate 100 -F
Starting Nmap 7.98 ( https://nmap.org ) at 2026-02-24 05:22 -0500
Nmap scan report for scanme.nmap.org (45.33.32.156)
Host is up (0.11s latency).
Other addresses for scanme.nmap.org (not scanned): 2600:3c01::f03c:91ff:fe18:bb2f
Not shown: 95 closed tcp ports (reset)
PORT      STATE      SERVICE
22/tcp    open      ssh
80/tcp    open      http
445/tcp    filtered  microsoft-ds
2000/tcp  open      cisco-scp
5060/tcp  open      sip

Nmap done: 1 IP address (1 host up) scanned in 9.22 seconds

(aastha@kali)-[~]
$ nmap scanme.nmap.org -min-rate 100 -F
Starting Nmap 7.98 ( https://nmap.org ) at 2026-02-24 05:22 -0500
Nmap scan report for scanme.nmap.org (45.33.32.156)
Host is up (0.091s latency).
Other addresses for scanme.nmap.org (not scanned): 2600:3c01::f03c:91ff:fe18:bb2f
Not shown: 95 filtered tcp ports (no-response)
PORT      STATE      SERVICE
22/tcp    open      ssh
80/tcp    open      http
113/tcp   closed    ident
2000/tcp  open      cisco-scp
5060/tcp  open      sip

Nmap done: 1 IP address (1 host up) scanned in 3.15 seconds
```

NSE Scripts

SWITCH	EXAMPLE	DESCRIPTION
-sC	nmap 192.168.1.1 -sC	Scan with default NSE scripts. Considered useful for discovery and safe
-script default	nmap 192.168.1.1 -script default	Scan with default NSE scripts. Considered useful for discovery and safe
-script	nmap 192.168.1.1 -script=banner	Scan with a single script. Example banner

-script	nmap 192.168.1.1 -script=http*	Scan with a wildcard. Example http
-script	nmap 192.168.1.1 -script=http,banner	Scan with two scripts. Example http and banner
-script	nmap 192.168.1.1 -script "not intrusive"	Scan default, but remove intrusive scripts
-script- args	nmap -script snmp-sysdescr -script-args snmpcommunity=admin 192.168.1.1	NSE script with arguments

```
(aastha@kali)-[~]
$ nmap scanme.nmap.org -sC -F
Starting Nmap 7.98 ( https://nmap.org ) at 2026-02-24 05:34 -0500
Nmap scan report for scanme.nmap.org (45.33.32.156)
Host is up (0.12s latency).
Other addresses for scanme.nmap.org (not scanned): 2600:3c01::f03c:91ff:fe18:bb2f
Not shown: 95 closed tcp ports (reset)
PORT      STATE      SERVICE
22/tcp    open      ssh
| ssh-hostkey:
|   1024 ac:00:a0:1a:82:ff:cc:55:99:dc:67:2b:34:97:6b:75 (DSA)
|   2048 20:3d:2d:44:62:2a:b0:5a:9d:b5:b3:05:14:c2:a6:b2 (RSA)
|   256 96:02:bb:5e:57:54:1c:4e:45:2f:56:4c:4a:24:b2:57 (ECDSA)
|_  256 33:fa:91:0f:e0:e1:7b:1f:6d:05:a2:b0:f1:54:41:56 (ED25519)
80/tcp    open      http
|_ http-title: Go ahead and ScanMe!
|_ http-favicon: Nmap Project
445/tcp   filtered  microsoft-ds
2000/tcp  open      cisco-sccp
5060/tcp  open      sip

Nmap done: 1 IP address (1 host up) scanned in 18.47 seconds
```

```
(aastha@kali)-[~]
└─$ nmap scanme.nmap.org -script default -F
Starting Nmap 7.98 ( https://nmap.org ) at 2026-02-24 05:23 -0500
Nmap scan report for scanme.nmap.org (45.33.32.156)
Host is up (0.10s latency).
Other addresses for scanme.nmap.org (not scanned): 2600:3c01::f03c:91ff:fe18:bb2f
Not shown: 95 closed tcp ports (reset)
PORT      STATE SERVICE
22/tcp    open  ssh
|_ ssh-hostkey:
|   1024 ac:00:a0:1a:82:ff:cc:55:99:dc:67:2b:34:97:6b:75 (DSA)
|   2048 20:3d:2d:44:62:2a:b0:5a:9d:b5:b3:05:14:c2:a6:b2 (RSA)
|   256 96:02:bb:5e:57:54:1c:4e:45:2f:56:4c:4a:24:b2:57 (ECDSA)
|_  256 33:fa:91:0f:e0:e1:7b:1f:6d:05:a2:b0:f1:54:41:56 (ED25519)
80/tcp    open  http
|_ http-title: Go ahead and ScanMe!
|_ http-favicon: Nmap Project
445/tcp   filtered microsoft-ds
2000/tcp  open   cisco-sccp
5060/tcp  open   sip

Nmap done: 1 IP address (1 host up) scanned in 15.26 seconds
```

```
(aastha@kali)-[~]
└─$ nmap scanme.nmap.org -script=banner -F
Starting Nmap 7.98 ( https://nmap.org ) at 2026-02-24 05:24 -0500
Nmap scan report for scanme.nmap.org (45.33.32.156)
Host is up (0.052s latency).
Other addresses for scanme.nmap.org (not scanned): 2600:3c01::f03c:91ff:fe18:bb2f
Not shown: 88 filtered tcp ports (no-response)
PORT      STATE SERVICE
22/tcp    open  ssh
|_ banner: SSH-2.0-OpenSSH_6.6.1p1 Ubuntu-2ubuntu2.13
80/tcp    open  http
110/tcp   closed pop3
111/tcp   closed rpcbind
113/tcp   closed ident
199/tcp   closed smux
995/tcp   closed pop3s
2000/tcp  open   cisco-sccp
3306/tcp  closed mysql
5060/tcp  open   sip
8080/tcp  closed http-proxy
8888/tcp  closed sun-answerbook

Nmap done: 1 IP address (1 host up) scanned in 15.16 seconds
```

```
(aastha@kali)~$ nmap scanme.nmap.org -script="not intrusive" -F
Starting Nmap 7.98 ( https://nmap.org ) at 2026-02-24 05:25 -0500
No profinet devices in the subnet
Pre-scan script results:
| eap-info:
|   Available authentication methods with identity="anonymous" on interface eth0
|   unknown EAP-TTLS
|   unknown EAP-TLS
|   unknown EAP-MSCHAP-V2
|   unknown PEAP
Bug in lltd-discovery: no string output.
| targets-sniffer: Sniffed 14 address(es).
| 224.0.0.1
| 239.255.255.253
| 10.0.2.2
| 224.0.0.251
| 239.255.255.250
| 224.0.0.9
| fd17:625c:f037:2:a95:cccf:cd38:d588
| fe80::a00:27ff:fe1f:b723
| 0.0.0.0
| fe80::2cb6:e533:df1b:38af
| a00:20f::
| 224.0.0.13
| 10.0.2.3
| 224.0.23.12
Bug in broadcast-upnp-info: no string output.
| broadcast-dhcp-discover:
|   Response 1 of 1:
|     Interface: eth0
|     IP Offered: 10.0.2.16
|     Server Identifier: 10.0.2.2
|     Subnet Mask: 255.255.255.0
|     Router: 10.0.2.2
|     Domain Name Server: 10.0.2.3
|_ hostmap-robtex: *TEMPORARILY DISABLED* due to changes in Robtex's API. See https://www.robtex.com/api/
|_ http-robtex-shared-ns: *TEMPORARILY DISABLED* due to changes in Robtex's API. See https://www.robtex.com/api/
| targets-asn:
|_ targets-asn.asn is a mandatory parameter
Segmentation fault      nmap scanme.nmap.org -script="not intrusive" -F
```


Useful NSE Script Examples

COMMAND	DESCRIPTION
<code>nmap -Pn -script=http-sitemap-generator scanme.nmap.org</code>	http site map generator
<code>nmap -n -Pn -p 80 -open -sV -vvv -script banner,http-title -iR 1000</code>	Fast search for random web servers
<code>nmap -Pn -script=dns-brute domain.com</code>	Brute forces DNS hostnames guessing subdomains
<code>nmap -n -Pn -vv -O -sV -script smb-enum*,smb-ls,smb-mbenum,smb-os-discovery,smb-s*,smb-vuln*,smbv2* -vv 192.168.1.1</code>	Safe SMB scripts to run
<code>nmap -script whois* domain.com</code>	Whois query
<code>nmap -p80 -script http-unsafe-output-escaping scanme.nmap.org</code>	Detect cross site scripting vulnerabilities
<code>nmap -p80 -script http-sql-injection scanme.nmap.org</code>	Check for SQL injections

```

(aastha@kali)-[~]
└─$ nmap -Pn -script=http-sitemap-generator scanme.nmap.org -F
Starting Nmap 7.98 ( https://nmap.org ) at 2026-03-03 00:56 -0500
Nmap scan report for scanme.nmap.org (45.33.32.156)
Host is up (0.24s latency).
Other addresses for scanme.nmap.org (not scanned): 2600:3c01::f03c:91ff:fe18:bb2f
Not shown: 95 closed tcp ports (reset)
PORT      STATE      SERVICE
22/tcp    open      ssh
80/tcp    open      http
| http-sitemap-generator:
|   Directory structure:
|   /
|   Other: 1; css: 1
|   /images/
|   png: 1
|   /shared/css/
|   css: 2
|   /shared/images/
|   png: 1; svg: 1
|   /shared/js/
|   js: 1
|   Longest directory structure:
|   Depth: 2
|   Dir: /shared/images/
|   Total files found (by extension):
|_   Other: 1; css: 3; js: 1; png: 2; svg: 1
445/tcp    filtered  microsoft-ds
2000/tcp   open      cisco-sccp
5060/tcp   open      sip

Nmap done: 1 IP address (1 host up) scanned in 26.37 seconds

```

```

(aastha@kali)-[~]
└─$ nmap -Pn -script=dns-brute aasthathakker.com -F
Starting Nmap 7.98 ( https://nmap.org ) at 2026-03-03 01:01 -0500
Nmap scan report for aasthathakker.com (185.230.63.171)
Host is up (0.22s latency).
Other addresses for aasthathakker.com (not scanned): 185.230.63.107 185.230.63.186
rDNS record for 185.230.63.171: unallocated.63.wixsite.com
Not shown: 95 filtered tcp ports (no-response)
PORT      STATE      SERVICE
80/tcp    open      http
113/tcp   closed    ident
443/tcp   open      https
2000/tcp   open      cisco-sccp
5060/tcp   open      sip

Host script results:
| dns-brute:
|   DNS Brute-force hostnames:
|   en.aasthathakker.com - 34.160.37.117
|_   www.aasthathakker.com - 34.160.37.117

Nmap done: 1 IP address (1 host up) scanned in 47.00 seconds

```

```

(aastha@kali)-[~]
$ nmap -Pn -script whois* aasthathakker.com -F
Starting Nmap 7.98 ( https://nmap.org ) at 2026-03-03 01:03 -0500
Nmap scan report for aasthathakker.com (185.230.63.107)
Host is up (1.9s latency).
Other addresses for aasthathakker.com (not scanned): 185.230.63.171 185.230.63.186
rDNS record for 185.230.63.107: unallocated.63.wixsite.com
Not shown: 97 filtered tcp ports (no-response)
PORT      STATE SERVICE
113/tcp   closed ident
2000/tcp  open  cisco-sccp
5060/tcp  open  sip

Host script results:
| whois-ip: Record found at whois.ripe.net
| inetnum: 185.230.63.0 - 185.230.63.255
| netname: wix_com_inc
| country: US
| _person: Stanislav Panich
| whois-domain:
|
| Domain name record found at whois.verisign-grs.com
|   Domain Name: AASTHATHAKKER.COM\x0D
|   Registry Domain ID: 3034952651_DOMAIN_COM_VRSN\x0D
|   Registrar WHOIS Server: whois.wix.com\x0D
|   Registrar URL: http://www.wix.com\x0D
|   Updated Date: 2026-02-01T06:51:06Z\x0D
|   Creation Date: 2025-11-02T09:28:11Z\x0D
|   Registry Expiry Date: 2026-11-02T09:28:11Z\x0D
|   Registrar: Wix.com Ltd.\x0D
|   Registrar IANA ID: 3817\x0D
|   Registrar Abuse Contact Email: domain-abuse@wix.com\x0D
|   Registrar Abuse Contact Phone: +14154291173\x0D
|   Domain Status: clientTransferProhibited https://icann.org/epp#clientTransferProhibited\x0D
|   Domain Status: clientUpdateProhibited https://icann.org/epp#clientUpdateProhibited\x0D
|   Name Server: NS4.WIXDNS.NET\x0D
|   Name Server: NS5.WIXDNS.NET\x0D
|   DNSSEC: unsigned\x0D
|   URL of the ICANN Whois Inaccuracy Complaint Form: https://www.icann.org/wicf/\x0D
| >>> Last update of whois database: 2026-03-03T05:59:24Z <<<\x0D
| \x0D
| For more information on Whois status codes, please visit https://icann.org/epp\x0D
| \x0D
| NOTICE: The expiration date displayed in this record is the date the\x0D
| registrar's sponsorship of the domain name registration in the registry is\x0D
| currently set to expire. This date does not necessarily reflect the expiration\x0D
| date of the domain name registrant's agreement with the sponsoring\x0D
| registrar. Users may consult the sponsoring registrar's Whois database to\x0D
| view the registrar's reported date of expiration for this registration.\x0D
| \x0D
| TERMS OF USE: You are not authorized to access or query our Whois\x0D

```

```

(aastha@kali)-[~]
$ nmap -p80 -script http-unsafe-output-escaping aasthathakker.com
Starting Nmap 7.98 ( https://nmap.org ) at 2026-03-03 01:06 -0500
Nmap scan report for aasthathakker.com (185.230.63.107)
Host is up (0.0018s latency).
Other addresses for aasthathakker.com (not scanned): 185.230.63.171 185.230.63.186
rDNS record for 185.230.63.107: unallocated.63.wixsite.com

PORT      STATE SERVICE
80/tcp    filtered http

Nmap done: 1 IP address (1 host up) scanned in 1.00 seconds

```

```

(aastha@kali)-[~]
$ nmap -p80 -script http-sql-injection aasthathakker.com
Starting Nmap 7.98 ( https://nmap.org ) at 2026-03-03 01:09 -0500
Nmap scan report for aasthathakker.com (185.230.63.107)
Host is up (0.00046s latency).
Other addresses for aasthathakker.com (not scanned): 185.230.63.171 185.230.63.186
rDNS record for 185.230.63.107: unallocated.63.wixsite.com

PORT      STATE      SERVICE
80/tcp    filtered  http

Nmap done: 1 IP address (1 host up) scanned in 0.63 seconds

```

Firewall / IDS Evasion and Spoofing

SWITCH	EXAMPLE	DESCRIPTION
-f	nmap 192.168.1.1 -f	Requested scan (including ping scans) use tiny fragmented IP packets. Harder for packet filters
-mtu	nmap 192.168.1.1 -mtu 32	Set your own offset size
-D	nmap -D 192.168.1.101,192.168.1.102,192.168.1.103,192.168.1.23 192.168.1.1	Send scans from spoofed IPs
-D	nmap -D decoy-ip1,decoy-ip2,your-own-ip,decoy-ip3,decoy-ip4 remote-host-ip	Above example explained
-S	nmap -S www.microsoft.com www.facebook.com	Scan Facebook

		from Microsoft (-e eth0 -Pn may be required)
-g	nmap -g 53 192.168.1.1	Use given source port number
-proxies	nmap -proxies http://192.168.1.1:8080, http://192.168.1.2:8080 192.168.1.1	Relay connections through HTTP/SOCKS4 proxies
-data-length	nmap -data-length 200 192.168.1.1	Appends random data to sent packets

```
(aastha@kali)~$ nmap scanme.nmap.org -f -F
Starting Nmap 7.98 ( https://nmap.org ) at 2026-02-24 05:28 -0500
Nmap scan report for scanme.nmap.org (45.33.32.156)
Host is up (0.052s latency).
Other addresses for scanme.nmap.org (not scanned): 2600:3c01::f03c:91ff:fe18:bb2f
Not shown: 88 filtered tcp ports (no-response)
PORT      STATE SERVICE
22/tcp    open  ssh
25/tcp    closed smtp
53/tcp    closed domain
80/tcp    open  http
113/tcp   closed ident
135/tcp   closed msrpc
139/tcp   closed netbios-ssn
199/tcp   closed smux
443/tcp   closed https
2000/tcp  open  cisco-sccp
5060/tcp  open  sip
8888/tcp  closed sun-answerbook

Nmap done: 1 IP address (1 host up) scanned in 3.97 seconds
```

```
(aastha@kali)-[~]
$ nmap scanme.nmap.org -mtu 32 -F
Starting Nmap 7.98 ( https://nmap.org ) at 2026-02-24 05:28 -0500
Nmap scan report for scanme.nmap.org (45.33.32.156)
Host is up (0.046s latency).
Other addresses for scanme.nmap.org (not scanned): 2600:3c01::f03c:91ff:fe18:bb2f
Not shown: 86 filtered tcp ports (no-response)
PORT      STATE SERVICE
22/tcp    open  ssh
23/tcp    closed telnet
80/tcp    open  http
110/tcp   closed pop3
111/tcp   closed rpcbind
113/tcp   closed ident
199/tcp   closed smux
995/tcp   closed pop3s
2000/tcp  open  cisco-sccp
3389/tcp  closed ms-wbt-server
5060/tcp  open  sip
5900/tcp  closed vnc
8080/tcp  closed http-proxy
8888/tcp  closed sun-answerbook

Nmap done: 1 IP address (1 host up) scanned in 3.79 seconds
```

```
(aastha@kali)-[~]
$ nmap scanme.nmap.org -g 53 -F
Starting Nmap 7.98 ( https://nmap.org ) at 2026-02-24 05:30 -0500
Nmap scan report for scanme.nmap.org (45.33.32.156)
Host is up (0.044s latency).
Other addresses for scanme.nmap.org (not scanned): 2600:3c01::f03c:91ff:fe18:bb2f
Not shown: 96 filtered tcp ports (no-response)
PORT      STATE SERVICE
22/tcp    open  ssh
80/tcp    open  http
2000/tcp  open  cisco-sccp
5060/tcp  open  sip

Nmap done: 1 IP address (1 host up) scanned in 3.72 seconds
```

```
(aastha@kali)-[~]
└─$ nmap scanme.nmap.org -data-length 100 -F
Starting Nmap 7.98 ( https://nmap.org ) at 2026-02-24 05:40 -0500
Nmap scan report for scanme.nmap.org (45.33.32.156)
Host is up (0.070s latency).
Other addresses for scanme.nmap.org (not scanned): 2600:3c01::f03c:91ff:fe18:bb2f
Not shown: 82 closed tcp ports (reset)
PORT      STATE      SERVICE
7/tcp     filtered  echo
22/tcp    open      ssh
80/tcp    open      http
179/tcp   filtered  bgp
444/tcp   filtered  snpp
445/tcp   filtered  microsoft-ds
514/tcp   filtered  shell
631/tcp   filtered  ipp
1029/tcp  filtered  ms-lsa
1900/tcp  filtered  upnp
2000/tcp  open      cisco-sccp
3000/tcp  filtered  ppp
5060/tcp  open      sip
5190/tcp  filtered  aol
5800/tcp  filtered  vnc-http
8000/tcp  filtered  http-alt
8081/tcp  filtered  blackice-icecap
49157/tcp filtered  unknown

Nmap done: 1 IP address (1 host up) scanned in 6.69 seconds
```